Office	ate of New Mexico	Form C-103 May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources 625 N. French Dr., Hobbs, NM 88240	
1301 W. Grand Ave., Artesia, NM 88210 OIL CON	ISERVATION DIVISION	30-005-63802 5. Indicate Type of Lease
1000 Pio Brazos Pd. Aztec NM 87410	South St. Francis Dr. anta Fe, NM 87505	STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Buffalo Valley 8 State
1. Type of Well: Oil Well Gas Well Other		8. Well Number
2. Name of Operator	RECEIVED	9. OGRID Number
Gruy Petroleum Management Co.	MAR 2 4 2006	162683
3. Address of Operator PO Box 140907; Irving, TX 75014-0907	OOD-AATESIA	10. Pool name or Wildcat Buffalo Valley; Penn (Prorated Gas)
4. Well Location		Buildio vaney, remi (Frontied Gas)
Unit Letter M: 1085 feet from the South line and 1165 feet from the West line		
Section 8 Township 15S Range 28E NMPM County Chaves .		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3533' GR		
Pit or Below-grade Tank Application or Closure Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water		
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ P AND A ☐		
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB 🖂		
OTHER: OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
02-24-06 Spudded 17-1/2" hole. 02-25-06 Ran 10 jts 13-3/8" 48# H-40 STC casing to 434'. Cemented with lead of 220 sx (13.7 wt) and tail of 150 sx		
02-25-06 Ran 10 jts 13-3/8" 48# H-40 STC casing to 434'. Cemented with lead of 220 sx (13.7 wt) and tail of 150 sx (14.8 wt). Circulated 30 sx to surface. WOC 14.5 hours. Tested casing to 500 psi for 30 minutes.		
02-27-06 Reached TD of 12-1/4" hole. Ran 42 jts 9-5/8" 40# J-55 LTC casing to 1824'.		
02-28-06 Cemented with lead of 550 sx + 0.25# FLocele (11.9 wt, 2.45 yld) and tail of 200 sx (14.8 wt, 1.33 yld). Circulated 300 sx to surface. WOC 23 hours. Tested casing to 1500 psi for 30 minutes.		
Circulated 300 sx to surface. WOC 23 hours. Tested easing to 1300 psi for 30 minutes.		
English Control of the Control of th	·	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.		
SIGNATURE Valatifing	TITLE Regulatory Tec	chnician DATE March 21, 2006
Type or print name Natalie Krueger For State Use Only	email address:nkrueger@	cimarex.com Telephone No. 972-401-3111
FOR RECORDS ON	LY	MAR 2 7 2006
APPROVED BY: Conditions of Approval (if any):	TITLE	DATE