

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-015-32235
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Point Judith State Com
8. Well Number	1
9. OGRID Number	004378
10. Pool name or Wildcat	Crow Flats; Morrow, Southeast Gas

4. Well Location
Unit Letter L: 1,650 feet from the South line and 660 feet from the West line
Section 36 Township 16-S Range 28-E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,606' GL

Pit or Below-grade Tank Application ☒ or Closure ☐

Pit type steel pit Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

13 3/8", 48# csg @ 207' w/ 260 sx, circulated; 8 3/8", 32# csg @ 1,908' w/ 600 sx, circulated; 5 1/2", 17# csg @ 10,207' w/ 785 sx, TOC @ 5,000' by CBL. Perfs 10,030 - 10,052'. 2 3/8" tubing & packer @ 9,910'
Notify NMOCD 24 hrs prior to move in, and 4 hrs prior to plugs, hold daily tailgate safety meetings w/ crews. Set steel pit prior to MI

1. POOH w/ production tubing. Set CIBP @ 9,980'. Circulate hole w/ mud and pump 25 sx C cmt on CIBP.
 2. Pump 25 sx C cmt @ 8,111' Penn
 3. Pump 25 sx C cmt @ 5,644' Abo
 4. Cut & pull 5 1/2" casing from ~ 4,900' (based on stretch measurements)
 5. Pump 40 sx C cmt @ ~ 4,950' 50' inside casing stub WOC & TAG
 6. Pump 60 sx C cmt @ 1,958' shoe plug WOC & TAG
 7. Pump 35 sx C cmt @ 1,180' base of salt - WOC & TAG
 8. Pump 35 sx C cmt @ 257' surface casing shoe plug - TAG
 9. Pump 15 sx C cmt 50' to surface 60'
- Cut off wellhead & anchors, install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jim Newman TITLE Engineer, Triple N Services, Inc. DATE 03/20/06

Type or print name James F. Newman, P.E.

E-mail address: jim@triplenservices.com

Telephone No. 432.687.1994

For State Use Only

APPROVED BY: PhD Hankins

TITLE AA

DATE 3/23/06

Conditions of Approval (if any):