

Office

Energy, Minerals and Natural Resources

Revised July 18, 2013

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88201

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

PENROCK OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

RECEIVED

WELL API NO.

30-005-62145

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Mckay-Winston

8. Well Number 001

9. OGRID Number 181156

10. Pool name or Wildcat

Pecos Slope; ABO (Gas)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Scythian Ltd

3. Address of Operator

300 N Marienfeld, Suite 950, Midland, TX 79701

4. Well Location

Unit Letter C : 660 feet from the North line and 1980 feet from the West lineSection 3 Township 8S Range 26E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3766

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/23/17 - 1/24/17

1. Move 2 3/8" tubing from Isler Fee + steel pit.

2. RU WSU. PU 2 3/8" work string. Tag CIBP @ 4218'.

3. RU cementer. Circulate 10# gelled brine & spot 25 sxs cement on top of CIBP @ 4218'. WOC & tagged TOC @ 3974'

4. Pull up to 3415'. Spotted 25 sxs. WOC. Tagged TOC @ 3315'.

5. Spotted 25 sxs cement. Cement plug @ 1935'. WOC & tagged @ 1827'

6. RU wireline. Perf 2 squeeze holes @ 850'. Squeeze 50 sxs Class "C" cement.

7. Spot from 100' to surface.

7. ND BOP. Cut off well head. RD WSU. Cut off anchors.

7. Installed dry hole marker

8. Clean up location. Dispose fluids from steel work pit.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Penros. www.cenrd.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Agent

DATE

1/26/2017

Type or print name M.Y. MerchantE-mail address: mymerch@penrocoil.comPHONE: 575-492-1236

For State Use Only

APPROVED BY:

TITLE

COMPLIANCE OFFICER

DATE

1/30/17

Conditions of Approval (if any):