Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

RECEIVED

FEB 1 0 2006

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS QUU-MITTEDIA NMNM97855

Do not use this form for proposals to drill or to re-enter an

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side					CA/Agreement, Name and/or N	
1. Type of Well Oil Well X Gas Well Other					8. Well Name and No. McKittrick 24 #3	
2. Name of Operator OXY USA WTP Limited Partnership		192	2463	Federal 9. API Well I	V.	
3a. Address P.O. Box 50250, Midland, TX 79710-	3b. Phone No. (include area code) 432 - 685 - 5717		30-015-34322 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey I SL - 290 FNL 1500 FEL NWNE(B) BHL - 1980 FSL 660 FEL NESE(I) Sec 24 T22S R24E 12. CHECK APPROPRIATE		DICATE NATURE OF N	NOTICE, REF	11. County of	r Parish, State NM HER DATA	
TYPE OF SUBMISSION		1				
Notice of Intent X Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injecti	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Reclamate Recompt	ete rily Abandon	Water Shut-Off Well Integrity X Other Spud. set Casing & cement	

Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

See other side

14. I hereby certify that the foregoing is true and correct Name (Printed Typed) David Stewart	Title	Sr. Regulatory Analyst					
On St	Date	2/9/06					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved by	Title		Date				
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject to which would entitle the applicant to conduct operations thereon.	t or Office	e					

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Well:

MCKITTRICK 24 FEDERAL #3

Date: 12/20/2005

Daily Operations Report

BUILD SLIDES FOR SOLIDS EQUIP, FILL TANKS WITH H20 RIG REPAIRS DUE TO ROUGH MOVE

Date: 12/21/2005

Daily Operations Report

FINISH RU OF SOLIDS EQUIP, FILL EXTRA WAQTER TANKS, FINISH RU OF AIR EQUIP.

DRI G FROM 40' TO 158'

WLS @ 114' (.5")

DRLG 14 3/4" HOLE FROM 158' TO 175'

Date: 12/22/2005

Daily Operations Report

DRLG 14 3/4" HOLE FROM 175' TO 340"

WLS@ 290" (.25")

DRLG 340' TO 500'

Date: 12/23/2005

Daily Operations Report

DRLG 14 3/4" HOLE FROM 500' TO 540' TRIP FOR PLUGGED JETS ON BIT DRLG 14 3/4" HOLE FROM 540' TO 605'

WLS @ 561' (.25")

WORK STUCK PIPE FOR 1.15 HOURS TRIP FOR PLUGGED JETS

DRLG 14 3/4" HOLE FROM 605' TO 1052"

Date: 12/23/2005

Daily Operations Report

DRLG 14 3/4" HOLE FROM 1052' TO 1122' TOOH, KNOCK JETS OUT OF BIT

JET PITS

TIH CHANGE ROTATING HEAD RUBBER DRLG 14 3/4" HOLE FROM 1122' TO 1340'

Date: 12/24/2005

Daily Operations Report

DRLG 14 3/4" HOLE FROM 1340' TO 1412'

WLS @ 1360' (3.5")

DRLG 14 3/4" HOLE FROM 1412' TO 1740' TOOH, LD 6" AND 8" DC'S LD REAMER AND BIT

RU CASING CREW AND LD MACHINE, RUN 40 JTS 9 5/8" 36# J-55 CSG

Date: 12/25/2005

Daily Operations Report

FINISH RUNNING 9 5/8" CASING SET @ 1726'

RU HES, CEMENT 9 5/8" CASING W/ 600 SKS HLPP 2% CACL2 @ 12.4 PPG, 2.03 FT3/SK, & 250 SKS PREM PLUS 2% cCACL2 @ 14.8 PPG 1.34 FT3/SK FOR 1ST STAGE HAD ECP AND DV TOOL SET @ 481' LANDED PLUG INFLATED PACKER, OPEN DV TOOL CIRCULATED 66 SKS OFF DV TOOL, CEMENTED 2ND STAGE W/ 340 SKS HLPP 2% CACL2 AND 100 SKS PREM PLUS 2% CACL2 CIRCULATED 20 SKS GOOD CEMENT LANDED PLUG, RD HES

JET CEMENT TO CRI BINS

shut down for xmas

Date: 12/26/2005

Daily Operations Report

CUT-OFF COND AND 9 5/8" CSG, WELD ON WELL HEAD

NU BOPE

TEST BOPE, DURING TEST BOPE STARTED LEAKING HYD OIL FROM PIPE RAM DOORS, SHUT DOWN FIX BOPE, ACCUM ALSO WAS NOT WORKING PROPERLY EITHER. HAVE IT FIXED ALSO.

WAIT ON MECHANIC, START FIXING ACCUM AND BOPE

Date: 12/27/2005

Daily Operations Report

FINISH BOPE AND ACCUM REPAIRS

TEST BOPE, ALL EQUIP TESTED OK AND CASING TEATED OK

REPLACE ROTATRY TABLE, WHILE REPLACEING ROTARY TABLE, DUMP 7.5 YARDS REDI-MIX DOWN BACKSIDE TO TOPP OFF AFTER CEMENT FELL BACK

PU HWDP AND DRLG DV TOOL

Date: 12/29/2005

Daily Operations Report

FINISH DRUG DV TOOL AND ECP

TIH W/ HWDP AND DP TAG CEMENT @ 1663' 1100 DRLG FC SJ AND FS, DRLG 100' OF FORMATION

RUN GYRO

TOOH TO PU DIRECTIONAL TOOLS

MU DIRECTIONAL TOOLS

CUT DRUG LINE

TIH W/ DIRECTIONAL TOOLS