District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. 1220 S. St. Francis Dr., Santa Fennesone CONSERVATION Santa Fe, NM 87505

Date: <u>0 - 23 - 2017</u>	MAR I	3 201/GAS CA	PTURE PL	AN			
	REC	EIVED Operator	& OGRID 1	vo.: Camb	orian Mar	nagement, Ltd - 19	1868
☐ Amended - Reason	n for Amendment:		·			7	
This Gas Capture Planew completion (new		=	•	o reduce we	ll/production	facility flaring/venting	ıg foı
Note: Form C-129 must	be submitted and app	proved prior to excee	ding 60 days a	llowed by Rul	e (Subsection A	of 19.15.18.12 NMAC).	
Well(s)/Production I	Facility – Name of	facility					
The well(s) that will b	e located at the pr	oduction facility a	re shown in	the table bel	ow.		
Well Name		Well Location	,		Flared or	Comments	7

		(ULSTR)		MCF/D	Vented	
R.C. Graves	30-005-61865	K 15 85 28E	1980 FSL 1980 FWL	۷.	۷.۱	

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Gas Transporter and will be connected to Gas Transporter low/high pressure gathering system located in Chaves County, New Mexico. It will require _____ of pipeline to connect the facility to low/high pressure gathering system. Operator provides (periodically) to Gas Transporter a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Operator and Gas Transporter have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Gas Transporter Processing Plant located in Sec. , Twn. , Rng. County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Transporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines