Form 3160-5	UNITEDSTATES	OFFICM PH	CONSE	RVATION	FORM APPROVED	
(1	PARTMENT OF THE INTE	RIOR	ESIADIS	TRICT	OMB No. 1004-0137 Expires: July 31, 2010	
	REAU OF LAND MANAGE	ment M/	AR 31	Migase Serial No.		
SUNDRY	NOTICES AND REPORTS	ON WELLS	H	6. If Indian, Allotte	MNM29234	
	form for proposals to dri		FCEIV	0. 11 Indian, Anone 20	cor intervance	
albandoned well.	Use Form 3160-3 (APD) :	for such proposals	$\mathbf{S}$	-12		
SUBM	IT IN TRIPLICATE - Olher instru	ictions on page 2		7. If Unit of CA/Ag	reement, Name and/o	r No.
I. Type of Well						
	Well Other			8. Well Name and 1 LOTO	No. S 8 FEDERAL #803	}
2. Name of Operator CHEVRON U.S.	A. INC.	•		9. API Well No. 3	0-015-32758	
3a. Address		hone No. (include area coo	le)	10. Field and Pool	or Exploratory Area	
6301 DEAUVILLE BLVD. RM#N3002 MIDLAND, TX. 79705	432-6	687-7279 LEE ROAK		SAN	D DUNES	
4. Location of Well (Footage, Sec., T.	, R., M., or Survey Description)			11. Country or Pari	sh, State	······································
1,880' FNL & 1,880' FWL, SEC- 8, T- 24S, R-	31E, LAT. 32.23354 LONG -103.80152				EDDY COUNTY, N	м.
12. CHE	CK THE APPROPRIATE BOX(ES)	) TO INDICATE NATURE	OF NOTIC	E, REPORT OR O	THER DATA	
TYPE OF SUBMISSION		TY	PE OF ACTI	ION	······································	
· · · · · · · · · · · · · · · · · · ·	Acidize	Deepen		iction (Start/Resume	Water Shul	-017
Notice of Intent	Alter Casing	Fracture Treat		mation	Well Integr	
Subsequent Report	Casing Repair	New Construction		mplete	Other	-
Y Subsequent Report	Change Plans	Plug and Abandon	Temp	orarily Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Wate	r Disposal		
Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready for	nally or recomplete horizontally, giv work will be performed or provide t lved operations. If the operation rest I Abandonment Notices must be file or final inspection.)	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement	measured an LM/BIA. R n or recomp s, including	d true vertical depti equired subsequent letion in a new inter reclamation, have b	ns of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and th	kers and zones. within 30 days ust be filed once e operator has
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready f 03/13-14/17 MI & RU P & A EQUIS 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'-	nally or recomplete horizontally, giv work will be performed or provide t lyed operations. If the operation rest l Abandonment Notices must be filed or final inspection.) P, NOTIFIED BLM YOLANDA JO 00', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8".	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T	measured an LM/BIA. R n or recompi s, including S, NDWH, N 25 SX CL "( LL BLM CH AG @ 1,48	d true vertical deptil equired subsequent letion in a new inter reclamation, have b NU BOP"S, TEST. C" CMT FROM 7,6 HASE MESSER C 12', PERF @ 1,039	ns of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, P', MIX & CIR	kers and zones. within 30 days ust be filed once e operator has
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready fr 03/13-14/17 MI & RU P & A EQUIR 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX &	nally or recomplete horizontally, giv work will be performed or provide t lyed operations. If the operation rest l Abandonment Notices must be filed or final inspection.) P, NOTIFIED BLM YOLANDA JO 00', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. & CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8". © 250', MIX & CIR 70 SX CL "C STALL REQUIRED DRY HOLE M	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA'S RECLAMAT	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LL BLM CH AG @ 1,48 SURFACE SURFACE	d true vertical deptil equired subsequent letion in a new inter reclamation, have b NU BOP"S, TEST. C" CMT FROM 7,4 HASE MESSER C 12', PERF @ 1,039 ON BOTH STRIN /ER TO RECLAM Áccep Liabili	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, D', MIX & CIR GS. ATION. Ped as to pidepert by under both is or	kers and zones. within 30 days ust be filed once to operator has & BHA. & BHA.
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready f 03/13-14/17 MI & RU P & A EQUIR 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /17 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329	nally or recomplete horizontally, giv work will be performed or provide t lyed operations. If the operation rest l Abandonment Notices must be file or final inspection.) P, NOTIFIED BLM YOLANDA JO 00', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL *C* CMT FROM 839' W/ RETURNS UP 8 5/8". © 250', MIX & CIR 70 SX CL *C STALL REQUIRED DRY HOLE M DSED LOOP SYSTEM.	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA'S RECLAMAT	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LL BLM CH AG @ 1,48 SURFACE SURFACE	d true vertical deptil equired subsequent letion in a new inter reclamation, have b NU BOP"S, TEST. C" CMT FROM 7,4 HASE MESSER C 12', PERF @ 1,039 ON BOTH STRIN /ER TO RECLAM Áccep Liabili	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, D', MIX & CIR GS. ATION. Ped as to pidepert by under both is or	kers and zones. within 30 days ust be filed once to operator has & BHA. & BHA.
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready f 03/13-14/17 MI & RU P & A EQUIR 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /17 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329	nally or recomplete horizontally, giv work will be performed or provide t lyed operations. If the operation rest l Abandonment Notices must be file or final inspection.) P, NOTIFIED BLM YOLANDA JO 00', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL *C* CMT FROM 839' W/ RETURNS UP 8 5/8". © 250', MIX & CIR 70 SX CL *C STALL REQUIRED DRY HOLE M DSED LOOP SYSTEM.	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA'S RECLAMAT	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LL BLM CH AG @ 1,48 SURFACE SURFACE	d true vertical deptil equired subsequent letion in a new inter reclamation, have b NU BOP"S, TEST. C" CMT FROM 7,4 HASE MESSER C 12', PERF @ 1,039 ON BOTH STRIN /ER TO RECLAM Áccep Liabili	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, D', MIX & CIR GS. ATION. Ped as to pidepert by under both is or	kers and zones. within 30 days ust be filed once to operator has & BHA. & BHA.
the proposal is to deepen direction Attach the Bond under which the following completion of the invoi testing has been completed. Fina determined that the site is ready f 03/13-14/17 MI & RU P & A EQUIS 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /10 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329	nally or recomplete horizontally, giv work will be performed or provide t lyed operations. If the operation rest l Abandonment Notices must be file or final inspection.) P, NOTIFIED BLM YOLANDA JO 00', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL *C* CMT FROM 839' W/ RETURNS UP 8 5/8". © 250', MIX & CIR 70 SX CL *C STALL REQUIRED DRY HOLE M DSED LOOP SYSTEM.	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA'S RECLAMAT	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LL BLM CH AG @ 1,48 SURFACE SURFACE	d true vertical deptil equired subsequent letion in a new inter reclamation, have b NU BOP"S, TEST. C" CMT FROM 7,4 HASE MESSER C 12', PERF @ 1,039 ON BOTH STRIN /ER TO RECLAM Áccep Liabili	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, D', MIX & CIR GS. ATION. Ped as to pidepert by under both is or	kers and zones. within 30 days ust be filed once to operator has & BHA. & BHA.
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready fr 03/13-14/17 MI & RU P & A EQUIS 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /10 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329 14. I hereby certify that the foregoing is Monty L. McCarver	nally or recomplete horizontally, giv work will be performed or provide t lved operations. If the operation rest l Abandonment Notices must be filed or final inspection.) P, NOTIFIED BLM YOLANDA JO 00', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8". CIR 55 SX CL "C" CMT FROM 840 CIR 55 SX CL "C" CMT FROM 840 CIR 55 SX CL "C" CHA 55 SX CL "C" CMT FROM 840 CIR 55 SX CL "C" CIR 55 SX CL "C" CMT FROM 840 CIR 55 SX CL "C" CI	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA'S RECLAMAT	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LLL BLM CH AG @ 1,48 SURFACE SURFACE TURN ON SURFACE	Id true vertical deptil equired subsequent letion in a new inter reclamation, have b JU BOP"S, TEST. C" CMT FROM 7,4 HASE MESSER C 12', PERF @ 1,038 ON BOTH STRIN /ER TO RECLAM Áccep Ljabili Gur fac	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, D', MIX & CIR GS. ATION. Ped as to pidepert by under both is or	kers and zones. within 30 days ust be filed once e operator has & BHA. & BHA.
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready fr 03/13-14/17 MI & RU P & A EQUIS 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /19 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329 14. I hereby certify that the foregoing is Monty L. McCarver	nally or recomplete horizontally, giv work will be performed or provide t lved operations. If the operation rest l Abandonment Notices must be filed or final inspection.) P, NOTIFIED BLM YOLANDA JO 10', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8". CIR 55 SX CL "C" CMT FROM 840' CIR 55 SX CL "C" CMT FROM 95 SY CL 55 SX CL 55 SX CL "C" CMT FROM 95 SY CL 55 SX CL "C" CM	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement IRDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA's RECLAMAT DUE	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LLL BLM CH AG @ 1,48 SURFACE SURFACE TURN ON SURFACE	Id true vertical deptil equired subsequent letion in a new inter reclamation, have b JU BOP"S, TEST. C" CMT FROM 7,4 HASE MESSER C 12', PERF @ 1,038 ON BOTH STRIN /ER TO RECLAM Áccep Ljabili Gur fac	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, W TUBING 500'- 7,547'. K TO SPOT, W TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SO	kers and zones. within 30 days ust be filed once e operator has & BHA. & BHA. A
the proposal is to deepen direction Attach the Bond under which the following completion of the invol- testing has been completed. Final determined that the site is ready fr 03/13-14/17 MI & RU P & A EQUIR 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /10 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329 14. 1 hereby certify that the foregoing is Monty L. McCarver Signature	nally or recomplete horizontally, giv. work will be performed or provide t lved operations. If the operation rest l Abandonment Notices must be filer or final inspection.) P, NOTIFIED BLM YOLANDA JO 10', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8". CIR 55 SX CL "C" CMT FROM 840 CH 50 CH	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement PRDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA's RECLAMAT DUE	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LL BLM CH AG @ 1,48 SURFACE S, TURN ON SURFACE TON SURFACE TON SURFACE	In the constraint of the const	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, W TUBING 500'- 7,547'. K TO SPOT, W TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SOC'- 7,547'. K TUBING SO	kers and zones. within 30 days ust be filed once to operator has & BHA. & BHA.
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready fr 03/13-14/17 MI & RU P & A EQUIS 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /10 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329 14. I hereby certify that the foregoing is Monty L. McCarver	nally or recomplete horizontally, giv work will be performed or provide t lved operations. If the operation rest l Abandonment Notices must be filer or final inspection.) P, NOTIFIED BLM YOLANDA JO DO, CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. A CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8". E @ 250', MIX & CIR 70 SX CL "C STALL REQUIRED DRY HOLE N DSED LOOP SYSTEM. True and correct. Name ( <i>Printed/Type</i> CTHIS SPACE FOR CALL ADD DRY HOLE FOR	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement RDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA's RECLAMAT DUE	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LLL BLM CH AG @ 1,48 SURFACE SURFACE TURN ON SURFACE	In the constraint of the const	is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, WIX & CIR GS. ATION. Ved as to place for by under bond it o restorction is co	kers and zones. within 30 days ust be filed once e operator has & BHA. & BHA. A
the proposal is to deepen direction Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready fi 03/13-14/17 MI & RU P & A EQUIF 03/15 /17 RIH & SET CIBP @ 7,80 03 /16 /17 MIX & SPOT 25 SX "C" MIX & SPOT 45 SX CL "C" CMT F 03 / 17 / 17 PERF @ 1,705', MIX & 55 SX CL "C" CMT FROM 1,039'- 03/ 18 /10 RIH TAG @ 797', PERF CUT OFF WELL HEAD 3' BGL,INS CLASS "C" CEMENT USED & CLO BOND COVERAGE: CA 0329 14. I hereby certify that the foregoing is Monty L. McCarver	nally or recomplete horizontally, giv. work will be performed or provide t lved operations. If the operation rest l Abandonment Notices must be filer or final inspection.) P, NOTIFIED BLM YOLANDA JO 10', CIR W/ MLF, TEST CSG 500 CMT FROM 5,809'-5,556', PERF ROM 4,424'- 3,969'. CIR 55 SX CL "C" CMT FROM 839' W/ RETURNS UP 8 5/8". CIR 55 SX CL "C" CMT FROM 9 5/8". CIR 55 SX CL "C" CAT FROM 9 5/8". CIR 55 SX CL "C" CAT FROM 9 5/8". CIR 55 SX CL "C" CIR 55 SX CL "C" CMT FROM 9 5/8". CIR 55 SX CL "C" CIR 55 SX CL "C" CMT FROM 9 5/8". CIR 55 SX CL "C" CIR 55 SX CL "C" CMT FROM 9 5/8". CIR 55 SX CL "C" CIR 55 SX C	e subsurface locations and the Bond No. on file with B ults in a multiple completio d only after all requirement PRDAN, POOH W/ RODS # GOOD, MIX & SPOT 2 F @ 4,377', NO SQZ, CA 1,705'- 1,505'. WOC & T C" CMT FROM 250' TO MARKER AS PER COA's RECLAMAT DUE	measured an LM/BIA. R n or recomp s, including S, NDWH, N 25 SX CL "( LLL BLM CH AG @ 1,48 SURFACE , TURN ON SURFACE , TURN ON	In the control of the	Is of all pertinent mar reports must be filed val, a Form 3160-4 m een completed and the POOH W/ TUBING 500'- 7,547'. K TO SPOT, K TO SPOT, W MIX & CIR GS. ATION. Inder Sond it o restorraint is co	kers and zones. within 30 days ust be filed once to operator has a BHA. A

.