NM OIL CONSERVATION

ARTESIA DISTRICT

JUN 26 2017

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department RECEIVED Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Dat	e: <u>6-26-17</u>		GAS CA	PTURE PL	AN			
	Original Amended - Reason for	Amendment:	~	& OGRID N	No.: <u>Mewbo</u>	urne Oil Com	pany - 14744	
new Note	completion (new drill c: Form C-129 must be su	, recomplete to	o new zone, re-fra	ac) activity.		•	facility flaring/venting for of 19.15.18.12 NMAC).	r
	well(s) that will be loc	ated at the pro	oduction facility a	T		7		
	Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
	Payo Macho 31 B2Ll Fed Com#1H	30-015-44066	L-31-18S-29E	1980' FSL & 185' FW	. 0	0	ONLINE AFTER FRAC	
		30-015 44	1066					

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Enterprise Field Services and will be connected to Enterprise Field Services low/high pressure gathering system located in Eddy County, New Mexico. It will require 1279 of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides (periodically) to Enterprise Field Services a drilling, completion and estimated first production deterprise Field Services have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Enterprise Field Services Processing Plant located in Sec. 17, Twn. 195, Rng. 31E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Enterprise Field Swc system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines