

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-20541
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator COG Operating, LLC		6. State Oil & Gas Lease No. B-8838
3. Address of Operator 600 W. Illinois Ave., Midland, TX 79701		7. Lease Name or Unit Agreement Name ETZ State Unit
4. Well Location Unit Letter G : 1980 feet from the N line and 1980 feet from the E line Section 16 Township 17S Range 30E NMPM County Eddy		8. Well Number 105
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6379' GR		9. OGRID Number 229137
		10. Pool name or Wildcat GRBG-Jackson, SR-Q-GRGB-SA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☒
 CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/10/17 MIRU Plugging Equipment, dug out cellar. 07/11/17 Pump'd 35 bbls mud laden fluid down tbg @ 1400 psi. Sqz'd 50 sx class C cmt @ 2500-2449 (displaced w/ 15.5 mud @ 2500' w/ a shot of 1000 psi.) (Per Bob Byrd w/ BLM's request). WOC. 07/12/17 Tagged plug @ 330' inside 2 3/8 tbg. ND well head, NU BOP. POH w/ 78 jts of 2 3/8 tbg. RIH & Tagged out @ 2365'. Set 5 1/2" CIBP @ 2030. Circulated hole w/ mud laden fluid. Pressure tested csg, held 500 psi. Spotted 25 sx class C cmt w/ 2% CACL @ 2030-1930'. WOC. Tagged plug @ 1660'. Perf'd csg @ 1095'. Sqz'd 50 sx class C cmt @ 1095-990'. 07/13/17 Perf'd csg @ 532'. No circulation in hole. Sqz'd 25 sx class C cmt w/ 2% CACL @ 532 & displaced to 100'. WOC. Tagged plug @ 100'. Spotted 20 sx class C cmt @ 100' & circulated to surface. Rigged down and moved off. 07/14/17 Moved in backhoe and welder. Dug out cellar. Cut off well head. Welded on "Above Ground Dry Hole Marker". Backfilled cellar. Cut off deadmen. Cleaned location, moved off.

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
 Liability under bond is retained pending receipt
 of C-103 (Subsequent Report of Well Plugging)
 which may be found at OCD Web Page under
 Forms, www.cmr.state.nm.us/oed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Lead Regulatory Analyst

DATE

7/24/17

Type or print name

Kanicia Castillo

E-mail address:

Kcastillo@concho.com

PHONE:

432-685-4332

For State Use Only

APPROVED BY:

TITLE

COMPLIANCE OFFICER

DATE

7/27/2017

Conditions of Approval (if any):