

NM OIL CONSERVATION

AUG 09 2017

ARTESIA DISTRICT CONSERVATION DIVISION

1220 South St. Francis Dr.

RECEIVED

Santa Fe, NM 87505

Revised July 18, 2013

WELL API NO.

30-015-26303

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

E-2781

7. Lease Name or Unit Agreement Name

Huisache AHI State

8. Well Number

1

9. OGRID Number

025575

10. Pool name or Wildcat

N. Seven Rivers; Glorieta-Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

EOG Y Resources, Inc.

3. Address of Operator

104 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter H : 1980 feet from the North line and 660 feet from the East lineSection 2 Township 20S Range 24E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3624'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/20/17 - MIRU. ND wellhead and NU BOP. Set a 7" CIBP at 2160'.

7/21/17 - Tagged CIBP. Ran gyro survey from 2100' to surface. Displaced hole with 80 bbls brine mud gel. Pressure tested to 500 psi, held good. Spotted 35 sx Class "C" cement on top of CIBP to 1945' calc TOC.

7/24/17 - Tagged TOC 1939'. Perforated at 1254'. Established pumping rate, did not squeeze. Spotted 50 sx Class "C" cement from 1304'-997' calc TOC. WOC. Tagged TOC 1019'. ND BOP. Spotted 26 sx Class "C" cement from 160' up to surface. Topped off casing with cement.

7/31/17 - Dug up cellar and cut off wellhead. Installed dry hole marker. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms. www.enr.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE August 1, 2017Type or print name Tina Huerta E-mail address: tina_huerta@eogresources.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Robert L Byrd TITLE COMPLIANCE OFFICER DATE 8/13/2017
Conditions of Approval (if any):