

30-015-43482

WELL NAME: HUMMINGBIRD FEDERAL COM #17-
API: 30-015-43482
SPUD DATE: 5/2/2017
PRODUCING FORMATION: GLORIETA-YESO
FIELD: CEDAR LAKE (BP)
COUNTY: EDDY
STATE: NEW MEXICO
WORKING INTEREST: 100.00%

SURFACE LOC: 430 FNL & 100 FWL
SECTION: 1
TOWNSHIP: 17S
RANGE: 31-E
SURVEY: Ronald J Eidson
BOTTOM HOLE LOC: 430 FNL & 340 8 FEL
SECTION: 1
TOWNSHIP: 17-S
RANGE: 31 E
SURVEY: Ronald J Eidson

DRILL RIG: Trinidad 436
RIG RELEASE: 5/20/2017

KB (ft): 4,054.50
GL (ft): 4,038.00
KB/GL DIFF (ft): 16.50
TMD (ft): 10,429.00
TD OF PILOT HOLE (ft): 10,429.00
FC DEPTH (ft): 3725
PBMD (ft): 5,311.00
RDV DEPTH (ft): 0.00
ORIO VALVE (ft): 0.00
DEEPEST TVD (ft): 4,653.00

TAPERED CASING STRING

7" 29# L-80 TO X-OVER @ 5314'
TAPERING TO 5.5" 20# L-80
DV Tool @ 5311'

SURFACE CASING - 13-3/8" H-40, STC, 48#, SET AT 820
CEMENT SURFACE CASING WITH 730 SY OF CEMENT TOC AT SURFACE.

HOLE SIZE
17-1/2"

INTERMEDIATE CASING - 9-5/8" J-55, LTC, 40#, SET AT 3772
CEMENT INTERMEDIATE CASING WITH 1300 SY OF CEMENT TOC AT SURFACE. CIRC 257 SX TO SURF

PRODUCTION CASING - 7" L-80, LTC, 29#, SET AT 10429
DV TOOL SET AT 5311'
STAGE 1: 500 CEMENT SY, TOC AT SURFACE, CIRC 250 SX TO SURF
STAGE 2: DID NOT DO 2ND STAGE

HOLE SIZE
12-1/4"

PRODUCTION Tubing - ESP - 2 875 J-55, 6.5 SET AT 5596.3

KOP (ft): 5,312
LATERAL LENGTH (ft): 4,025
TD OF PILOT HOLE (ft): 10,429

Packers and Sleeve Assembly
TOP PERF (MD): 6,404
BOTTOM PERF (MD): 10,429

TMD (ft): 10,429
FC DEPTH (ft): 3725
PBMD (ft): 5,311
RDV DEPTH (ft): 0
ORIO VALVE (ft): 0

COMPLETION:

STIMULATON

STATUS:

COMMENTS:

PACKERS & SLEEVES - 16 STAGES				
TOTAL ACID (bbl)	TOTAL LTR (bbl)	TOTAL PROPPANT (lbs)	MAX WH RATE (bpm)	MAX WH PRESSURE (psi)
2.911	84 859	4 275 540	94.00	5 451
PRODUCTION METHOD	LIFT TYPE	SETTING DEPTH		
Pumping	ESP	5562		
Crossover sub at 5314				

LAST UPDATED BY: MISTI HATHCOCK

LAST UPDATED: 8/3/2017