NM OIL CONSERVATION

ARTESIA DISTRICT

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico SEP **0 8 2017**Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

RECEIVED

Date: 08/08/2017		GAS	CAPTURE PLA	AN		
✓ Original Reason for Amendment	:	Operator & OGRID No.: RKI Exploration and Production, LLC #246289				
This Gas Capture Plan of facility flaring/venting f						reduce well/production
Note: Form C-129 must be	submitted and	approved prior to ex	ecceding 60 days al	lowed by Rule (Subsection A of	19.15.18.12 NM.1C).
Well(s)/Production Fac	cility – Name	of facility				
				1 1 1 1 1 1 1		
The well(s) that will be Well Name	API API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
RDX FEDERAL COM 17-44H	30- 44409_	Sec 17 T26S R30E	SHL: 75' FNL 2460' FWL	4,000 MCF/D	FLARE 3% 90 MCF/D	
Gathering System and						
Well(s) will be connected	l to a producti	on facility after fl				
system is in place. The						
connected to Delaware Ba	sin Midstream, L	low/hig	th pressure gathe	ring system I	ocated in Reeve	S County, Texas
It will require 50 of p Production, LLC provide						
production date for wells						
LLC and Delaware Basin M						ng and completion
schedules. Gas from thes		processed at Delay	ware Basin Midstrea	m, LLC	Processing Plan	nt located: See Below.
The actual flow of the gas	will be based	on compression of	perating paramete	ers and gatheri	ng system press	sures.
Flowback Strategy After the fracture treatmer flared or vented. During sand, the wells will be turn production facilities, unless than the strategy of the str	flowback, the ned to produc ss there are op	e fluids and sand c tion facilities. Gas perational issues or	ontent will be mo s sales should star n Delaware Basin Mi	onitored. When t as soon as the distream, LLC	en the produced ne wells start flo system at	fluids contain minimal owing through the that time. Based on
current information, it is I well(s). Safety requirements during	·			•		•

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines