District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division OIL CONSERVATION 1220 South St. Francis Dr. ARTESIA DISTRICT

Santa Ee NIM 87505

			anta Fe, INI	AT 91202	SEP 2	<u> 2017 </u>	
Date: 6-30-17		GAS CA	GAS CAPTURE PLAN			RECEIVED	
☑ Original☐ Amended - Reason for	Amendment:_	Operator	& OGRID N	No.: <u>Mewbo</u> ı	ırne Oil Com	pany - 14744	
new completion (new dril	l, recomplete to	new zone, re-fra	c) activity.			facility flaring/venting for	
Note: Form C-129 must be st Well(s)/Production Facil The well(s) that will be lo	lity – Name of	facility		·		of 19.15.18.12 NMAC).	
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
FULLER 14/11 WIED FED #111	015-44448	E-14-26S-29E	2600 FNL & 500 FEI	0	NA	ONLINE AFTER FRAC	
place. The gas produced Western low/ 1300 of pipeline to (periodically) to Western be drilled in the foreseea conference calls to discussed Western of the gas will be based on	to a production of from product thigh pressure connect the farea to ble future. In the second of the processing P.	n facility after flotion facility is de gathering system cility to low/high drilling, completio addition, Mewbo drilling and com lant located in Sec	edicated to _n located in pressure gan and estimate ourne Oil Completion scheungen _ 36 _ , Blk	thering syst ted first produles. Gas 58 T1S , (EDDY (Company and dules)	County, New em. Mewbor uction date for western from these	Mexico. It will require arne Oil Company provides r wells that are scheduled to	
flared or vented. During f sand, the wells will be tur	lowback, the flowed to product to the state of the state	uids and sand contion facilities. Gastional issues on	tent will be r s sales should Western	nonitored. V d start as so system at	When the prodon as the wel	action tanks and gas will be luced fluids contain minimal ls start flowing through the ed on current information, it	

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that

- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines