<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
<u>District II</u>
811 S. First St., Artesia, NM 88210
<u>District III</u>
1000 Rio Brazos Road, Aztec, NM 87410
<u>District IV</u>
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

NM OIL CONSERVATION of Office
ARTESIA DISTRICT

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NOV **06** 2017

Submit Original

to Appropriate

GAS CAPTURE PLAN RECEIVED

Date: 10/31/2017									
	Original Amended - Reason for Amendment:	Operator & OGRID No.: <u>OXY USA WTP LP - 192463</u>							

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Turkey Track 4-3 State 32H	30-015- 44537	Lot 4, Sec. 4, T19S, R29E	1107 FNL, 110 FWL	1427	0	
Turkey Track 4-3	30-015-	Unit L, Sec. 4,	1160 FSL,	1427	0	
State 33H Turkey Track 4-3	44 617 30-015-	T19S, R29E Unit L, Sec. 4,	360 FWL 1625 FSL	1427	0	
State 34H	44518	T19S, R29E	360 FWL		1	

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, where a gas transporter system is in place. The gas produced from production facility is dedicated to Enterprise-Field Services, LLC ("Enterprise") and will be connected to Enterprise-Field Services, LLC ("Enterprise") and will be connected to Enterprise-Field Services, LLC ("Enterprise") and will be connected to <a href="Enterprise-Field Services, LLC ("Enterprise") and will require <a href="Enterprise-Field Services, LLC ("Enterprise") and will be derived in Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Enterprise's</u> system at that time. Based on current information, it is <u>OXY's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines