Form 3160-5 (June 2015)

#### **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No. NMNM97117


SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

		-,				
SUBMIT IN 1	TRIPLICATE - Other inst	ructions on	page 2		7. If Unit or CA/Agreer NMNM111779	nent, Name and/or No.
1. Type of Well ☐ Oil Well ☑ Gas Well ☐ Oth	ner				8. Well Name and No. ROUNDY ROUND	FEDERAL COM 2
Name of Operator     COG OPERATING LLC	NTGOMERY es.com		9. API Well No. 30-015-33965-00	)-S1		
3a. Address 600 W ILLINOIS AVENUE MIDLAND, TX 79701	. (include area code) 0-7161		10. Field and Pool or Exploratory Area HAPPY VALLEY- MORROW			
4. Location of Well (Footage, Sec., T.	11. County or Parish, State					
Sec 32 T21S R26E NENE 660FNL 990FEL					EDDY COUNTY, NM	
12. CHECK THE AF	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE OF	NOTICE,	REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION			ТҮРЕ ОГ	ACTION		
Notice of Intent     ■     Notice of Intent     Notice of	☐ Acidize	☐ Dee	pen	☐ Product	ion (Start/Resume)	■ Water Shut-Off
Notice of filent	☐ Alter Casing	☐ Hyd	lraulic Fracturing	☐ Reclam	ation	□ Well Integrity
☐ Subsequent Report	☐ Casing Repair	☐ Nev	v Construction	☐ Recomp	olete	☐ Other
☐ Final Abandonment Notice	☐ Change Plans	🛭 Plug	g and Abandon	□ Tempor	☐ Temporarily Abandon	
	☐ Convert to Injection	Plug	g Back	☐ Water I	Disposal	
following completion of the involved testing has been completed. Final At determined that the site is ready for final states of the states of	bandonment Notices must be file inal inspection.  '. Circulate hole w/ MLF. F. F	Pressure test  Volfcamp)  Pressure test  Volfcamp)  Pressure test  Pressure test  Pressure test	requirements, including csg. Spot 25 sx	ng reclamatio cmt @  ATION		OCEDURE OR
	true and correct.  Electronic Submission #3 For COG O ommitted to AFMSS for pro MONTGOMERY	385494 verifie PERATING L pcessing by J	d by the BLANWER C, Some to the Ca AMES AMOS on 0 Title AGENT	Information rlsbad 9/14/2017 (1	n System 7JA0167SE)	
Signature (Electronic S	<del></del>		Date 08/21/20			
	THIS SPACE FO	R FEDERA	AL OR STATE (	OFFICE U	SE	
Approved By  Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conduction.	iitable title to those rights in the	not warrant or subject lease	Title See	1v. F	ET	//-/5-/7 Date

•			
Author:	MRM (8/2017)		
Well Name	Roundy Round I	Fe Well No.	#2
Field	Happy Valley	API#:	30-015-33965
County	Eddy	Prop #:	
State	New Mexico	Zone:	Bone Spring
Spud Date	4/9/2005		660 FNL & 990 FEL
GL	3.260		Sec 32 T21S R26E
кв			

Description	O.D.	Grade	Weight	Depth	Cmt Sx	тос
Surface Csg	20"	K-55	94	366'	750	surface
Inter Csg	9.625"	J-55	36	2,008'	1,250	surface
Prod Csg	7"	N-80	23	8,450'	1,375	??
Liner	4.5"	P-110	11.6	11,320'	300	??




Youtes Copien Rect Formation Tops 7241 2,094' Delaware 4,551' ~ Bone Spring 3rd Bone Spring 7,836 Wolfcamp 8,291' ---9,728' Strawn 10,085 197 Atoka 10,840' Morrow

Originally drilled and completed by Marbob Er COG took over operations 10/2010

3701

Author:	MRM (8/2017)		
Well Name	Roundy Round Fe V	Vell No.	#2
Field	Happy Valley A	\PI#:	30-015-33965
County	Eddy F	rop #:	
State	New Mexico Z	one:	Bone Spring
Spud Date	4/9/2005		660 FNL & 990 FEL
GL	3,260'		Sec 32 T21S R26E
KB			

Description	O.D.	Grade	Weight	Depth	Cmt Sx	тос
Surface Csg	20"	K- <b>5</b> 5	94	366'	750	surface
Inter Csg	9.625"	J-55	36	2,008'	1,250	surface
Prod Csg	7"	N-80	23	8,450'	1,375	Sup. F.
Liner	4.5"	P-110	11.6	11,320'	300	??



26" hole

20" (94#) @ 366' with 750 sks, circ with 143 sks TOC @ surface

7. Spot ∷sx cmt @ 416'-Surface.

6. Spot 40 sx cmt @ 800-700'.

12-1/4" hole

9-5/8" (36#) @ 2,008' with 1,250 sks

TOC @ surface

1st stage - 800 sks, circ 183 sks 2nd stage - 450 sks, circ 98 sks

5. Spot 55 sx cmt @ 2100-1958'. WOC & Tag (Delaware, Shoe)

#### Formation Tops

 Delaware
 2,094'

 Bone Spring
 4,551'

 3rd Bone Spring
 7,836'

 Wolfcamp
 8,291'

 Strawn
 9,728'

 Atoka
 10,085'

 Morrow
 10,840'

Originally drilled and completed by Marbob Er

COG took over operations 10/2010

4. Spot 40 sx cmt @ 4600-4500'. (Bone Springs)

3. Spot 40 sx cmt @ 6500-6400'.

8-3/4" hol€

7" (23#) @ 8,450" with 1,375 sks

TOC @ surface??

1st stage - 575 sks, circ 90 sks

2nd stage - 800 sks, circ 135 sks

2. Spot 30 sx cmt @ 8500-8250'. WOC & Tag (Shoe, Wolfcamp)

1. Spot 4 1/2" CIBP @ 10,950'. Circulate hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 10950-10850'.

11,002'-11.154' (Morrow) 84 holes - 06/09/2005 acidized with 1,500 gai 6-1/8" hole

4-1/2" (11.6#) @ 11,320" with 300 sks, arc 80 sks TOL @ 8,450"?? TOC @ 8,450"??

# BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

# Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



# **United States Department of the Interior**

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

## **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612