District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Divisial OIL CONSERVATION 1220 South St. Francis Dr. ARTESIA DISTRICT

1220 S. St. Hallels Dr., Santa Fe.	1401 87303	Santa Fe, NM 87505						
Date:	GAS CA	GAS CAPTURE PLAN			EIVED			
☑ Original ☐ Amended - Reason fo	r Amendment	-	Operator & OGRID No.: Mewbourne Oil Company - 14744					
This Gas Capture Plan onew completion (new dri		•	-	reduce we	ll/production	facility flaring/vent	ing for	
Note: Form C-129 must be s	ubmitted and ap	oproved prior to excee	eding 60 days a	llowed by Rul	e (Subsection A	1 of 19.15.18.12 NMAC,).	
Well(s)/Production Faci	<u>lity – Name o</u>	of facility						
The well(s) that will be lo	ocated at the p	production facility :	are shown in	the table bel	ow.			
Well Name	API	Well Location	Footages	Expected	Flared or	Comments		
		(ULSTR)		MCF/D	Vented			
FNR 17/20 B2IP FED COM #1H	015-4457	J-23S-30E	2340 FSL & 1368 FE	L 0	NA NA	ONLINE AFTER FRAC		

Gathering System and Pipeline Notification

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Frontier Field Svc system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits Would you like to utilize Lined Pit PWD options? NO Produced Water Disposal (PWD) Location: PWD surface owner: PWD disturbance (acres): Lined pit PWD on or off channel: Lined pit PWD discharge volume (bbl/day): Lined pit specifications: Pit liner description: Pit liner manufacturers information: Precipitated solids disposal: Decribe precipitated solids disposal: Precipitated solids disposal permit: Lined pit precipitated solids disposal schedule: Lined pit precipitated solids disposal schedule attachment: Lined pit reclamation description: Lined pit reclamation attachment: Leak detection system description: Leak detection system attachment:

Lined pit Monitor attachment:
Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit Monitor description:

Lined pit bond amount:

Additional bond information attachment: