NM OIL CONSERVATION

ARTESIA DISTRICT

DEC 06 2017

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

nent Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

| Dat | e: | | GAS CA | PTURE PL | AN | | |
|---|---|---|--|--|--|---|--|
| | Original Amended - Reason for | Amendment: | - | & OGRID N | No.: <u>Mewbor</u> | arne Oil Com | pany - 14744 |
| nev Note | v completion (new drill, e: Form C-129 must be sub | , recomplete t | o new zone, re-fra | ac) activity. | | • | facility flaring/venting for of 19.15.18.12 NMAC). |
| | ll(s)/Production Facili | | | | | | |
| The | well(s) that will be loc Well Name | ated at the pr | oduction facility a Well Location (ULSTR) | Footages | the table bel Expected MCF/D | ow. Flared or Vented | Comments |
| | HOSS 2/11 W2BO FED COM 1R | 30-015-44153 | B 2-25S-28E | 185 FNL & 1700 FEL | o | NA NA | ONLINE AFTER FRAC |
| We place 150 (per be con | ce. The gas produced low/home | o a production from production pressure connect the factor of a le future. In s changes to Processing I | on facility after floation facility is de gathering system acility to low/high drilling, completion addition, Mewbo drilling and completed in Se | edicated to not located in pressure gar and estimate our coll Completion scheme. | Crestweethering system (Crestweethering system) credit produmpany and dules. Gas n. 245, Rng | Cood County, New em. Mewbor uction date fo Crestwood from these 3. 28E, Edo | gas transporter system is in and will be connected to Mexico. It will require urne Oil Company provides or wells that are scheduled to have periodic wells will be processed at the County, New Mexico. pressures. |
| Aft flar san | ed or vented. During flo | owback, the flued to product | luids and sand contion facilities. Gas | tent will be research | nonitored. V d start as so | When the prodon as the wel | action tanks and gas will be luced fluids contain minimal ils start flowing through the ed on current information, it |

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines