r	UNITED STATE EPARTMENT OF THE I BUREAU OF LAND MANA	NTERIOR	OCD-AR7	TESIA	OMB N Expires	APPROVED IO. 1004-0135 : July 31, 2010	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side.				5. Lease Serial No. NMNM89049			
				6. If Indian, Allottee or Tribe Name			
				7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well Ø Oil Well Gas Well Other					8. Well Name and No. NUCLEUS BGN FEDERAL 1H		
2. Name of Operator Contact: LAURA WATTS YATES PETROLEUM CORPORATIONE-Mail: laura@yatespetroleum.com					9. API Well No. 30-015-39241-00-X1		
3a. Address 105 SOUTH FOURTH STREET ARTESIA, NM 88210		3b. Phone No. (include area code) Ph: 575-748-4272 Fx: 575-748-4585)	10. Field and Pool, or Exploratory WILDCAT		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, and State		
Sec 31 T19S R30E SWSW 1750FNL 330FWL					EDDY COUNTY, NM		
12. CHECK APP	PROPRIATE BOX(ES) TO	O INDICATE	E NATURE OF I	NOTICE, R	l EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
T Notice of Intent	☐ Acidize	🗖 Dee	epen	D Produc	tion (Start/Resume)	□ Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat		Reclamation		Well Integrity	
🛛 Subsequent Report	Casing Repair	New Construction		🗖 Recom	plete	⊠ Other	
Final Abandonment Notice	Change Plans	🗖 Plug	Plug and Abandon		Temporarily Abandon Drillin		
	Convert to Injection	🗖 Plu	g Back	Water Disposal			
following completion of the involve testing has been completed Final A	d operations. If the operation re bandonment Notices shall be fil-	sults in a multip	le completion or reco	ompletion in a	new interval, a Form 316	0-4 shall be filed once	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft K	final inspection.) OP and continued drilling	directional.				-	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F	final inspection.) OP and continued drilling a duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12.8	directional. and continued ment 5-1/2 ind 832 ft. Stage	l drilling. ch production ca tool at 6,131 ft a	sing at 10:0	Accepted for recon	-\$-/7 d - NMOCD	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02	final inspection.) OP and continued drilling of educed hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,6 d stage 1 with 410 sacks P 0 + 5 lb/sx D42 + 0.5 perc	directional. and continued ment 5-1/2 ind 832 ft. Stage PVL + 0.125 lt cent D201 + 0	d drilling. ch production ca: tool at 6,131 ft a o/sx D130 + 5 pe 3 percent D65 +	sing at 10:0 and float ercent D44 + - 0.4 percen	Accepted for recon	-\$-/7 d - NMOCD	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Kr 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t	final inspection.) OP and continued drilling of duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,8 d stage 1 with 410 sacks P 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 - 0.5 percent D201 + 0.2 p to surface. Cemented stat	directional. and continued ment 5-1/2 ind 832 ft. Stage VL + 0.125 ll cent D201 + 0 0.125 lb/sx D1 ercent D65 + ge 2 with 660	d drilling. ch production cas b/sx D130 + 5 pe 0.3 percent D65 + 130 + 0.2 percent 0.4 percent D16 sacks PVL + 0.1	sing at 10:0 and float freent D44 + - 0.4 percen t D46 + 4 57 (yld 1.38, 125 lb/sx D1	Accepted for recono 0 10.2 10.2 10.167 A wt 30 +	-S -J-> d - NMOCD L CONSERVATION	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Kr 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 +	final inspection.) OP and continued drilling of duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,8 d stage 1 with 410 sacks P 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 - 0.5 percent D201 + 0.2 p to surface. Cemented stat	directional. and continued ment 5-1/2 ind 832 ft. Stage VL + 0.125 ll cent D201 + 0 0.125 lb/sx D1 ercent D65 + ge 2 with 660	d drilling. ch production cas b/sx D130 + 5 pe 0.3 percent D65 + 130 + 0.2 percent 0.4 percent D16 sacks PVL + 0.1	sing at 10:0 and float freent D44 + - 0.4 percen t D46 + 4 57 (yld 1.38, 125 lb/sx D1	Accepted for recono 0 10.2 10.2 10.167 A wt 30 +	L CONSERVATION	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t 5 percent D44 + 0.2 percent 1	final inspection.) OP and continued drilling a duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12, d stage 1 with 410 sacks F 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 0.5 percent D201 + 0.2 p to surface. Cemented stag D46 + 1 percent D020 + 3 is true and correct. Electronic Submission # For YATES PETRO	directional. and continued ment 5-1/2 ind VL + 0.125 lk vent D201 + 0 0.125 lb/sx D1 vercent D65 + ge 2 with 660 lb/sx D42 + (245260 verifie DLEUM CORP	d drilling. ch production case b/sx D130 + 5 per .3 percent D65 + 30 + 0.2 percent 0.4 percent D16 sacks PVL + 0.1 0.5 percent D201 by the BLM We ORATION, sent to	sing at 10:00 and float ercent D44 + - 0.4 percen t D46 + 4 57 (yld 1.38, 125 lb/sx D1 + 0.4 perce 	Accepted for record 0.2 t D167 wt 30 + ent D65 n System ad	L CONSERVATION RTESIA DISTRICT DEC 0 4 2017	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t 5 percent D44 + 0.2 percent 1	final inspection.) OP and continued drilling d duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,8 d stage 1 with 410 sacks P 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 0.5 percent D201 + 0.2 p to surface. Cemented stag D46 + 1 percent D020 + 3 strue and correct. Electronic Submission # For YATES PETRO ommitted to AFMSS for pro	directional. and continued ment 5-1/2 ind VL + 0.125 lk vent D201 + 0 0.125 lb/sx D1 vercent D65 + ge 2 with 660 lb/sx D42 + (245260 verifie DLEUM CORP	d drilling. tool at 6,131 ft a b/sx D130 + 5 per 3 percent D65 + 30 + 0.2 percent 0.4 percent D16 9.5 percent D201 b sacks PVL + 0.1 0.5 percent D201 d by the BLM We ORATION, sent to ATHY QUEEN on	sing at 10:0 and float ercent D44 + - 0.4 percen t D46 + 4 57 (yld 1.38, 125 lb/sx D1 + 0.4 perce 11 Information o the Carlsba 06/09/2014 (1	Accepted for record 0.2 t D167 wt 30 + ent D65 n System ad	L CONSERVATION RTESIA DISTRICT DEC 0 4 2017	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft K/ 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with BI am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t 5 percent D44 + 0.2 percent 1 14. I hereby certify that the foregoing i Name(Printed/Typed) LAURA V	final inspection.) OP and continued drilling d duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,8 d stage 1 with 410 sacks P 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 0.5 percent D201 + 0.2 p to surface. Cemented stag D46 + 1 percent D020 + 3 strue and correct. Electronic Submission # For YATES PETRO ommitted to AFMSS for pro	directional. and continued ment 5-1/2 ind VL + 0.125 lk vent D201 + 0 0.125 lb/sx D1 vercent D65 + ge 2 with 660 lb/sx D42 + (245260 verifie DLEUM CORP	d drilling. ch production cas b/sx D130 + 5 pe .3 percent D65 + 30 + 0.2 percent 0.4 percent D16 sacks PVL + 0.1 0.5 percent D201 d by the BLM We ORATION, sent to ATHY QUEEN on Title REG RI	sing at 10:00 and float ercent D44 + - 0.4 percen t D46 + 4 67 (yld 1.38, 125 lb/sx D1 + 0.4 perce 11 Information o the Carlsb 06/09/2014 (1 EPORTING	Accepted for reconor 0 0.2 t D167 wt 30 + ent D65 n System ad 4CQ0286SE)	L CONSERVATION RTESIA DISTRICT DEU 0 4 2017 RECEIVED	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t 5 percent D44 + 0.2 percent 1 14. I hereby certify that the foregoing i Ca Name (Printed/Typed) LAURA V	final inspection.) OP and continued drilling a duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,4 d stage 1 with 410 sacks F 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 - 0.5 percent D201 + 0.2 p to surface. Cemented stag D46 + 1 percent D020 + 3 is true and correct. Electronic Submission # For VATES PETRO ommitted to AFMSS for pro VATTS	directional. and continued ment 5-1/2 ind 832 ft. Stage VL + 0.125 lk ent D201 + 0 0.125 lb/sx D1 ercent D65 + ge 2 with 660 lb/sx D42 + 0 245260 verifie DLEUM CORP icessing by C/	d drilling. ch production case by the BLM We of by the BLM We ORATION, sent to Title REG RI Date 05/12/2	sing at 10:00 and float ercent D44 + - 0.4 percen t D46 + 4 57 (yld 1.38, 125 lb/sx D1 + 0.4 perce 11 Information o the Carlsb 06/09/2014 (1 EPORTING	Accepted for record 0.2 t D167 wt 30 + ent D65 Accepted for record NM OI Accepted for record Accepted for	L CONSERVATION RTESIA DISTRICT DEU 0 4 2017 RECEIVED	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t 5 percent D44 + 0.2 percent l 14. I hereby certify that the foregoing i Cr Name(Printed/Typed) LAURA V Signature (Electronic	final inspection.) OP and continued drilling a duced hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12, d stage 1 with 410 sacks F 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 0.5 percent D201 + 0.2 p to surface. Cemented stag D46 + 1 percent D020 + 3 is true and correct. Electronic Submission # For YATES PETRO ommitted to AFMSS for pro VATTS	directional. and continued ment 5-1/2 ind 832 ft. Stage VL + 0.125 lk ent D201 + 0 0.125 lb/sx D1 ercent D65 + ge 2 with 660 lb/sx D42 + 0 245260 verifie DLEUM CORP icessing by C/	d drilling. ch production case by the BLM We of by the BLM We ORATION, sent to Title REG RI Date 05/12/2	sing at 10:00 and float ercent D44 + - 0.4 percen t D46 + 4 57 (yld 1.38, 125 lb/sx D1 + 0.4 perce 11 Information o the Carlsb 06/09/2014 (1 EPORTING	Accepted for record 0.2 t D167 wt 30 + ent D65 Accepted for record NM OI Accepted for record Accepted for	L CONSERVATION RTESIA DISTRICT DEU 0 4 2017 RECEIVED	
determined that the site is ready for 4/23/14 - Drilled to 7,776 ft Ki 4/25/14 - Drilled to 8,617 ft re 4/30/14 - Reached TD 8-1/2 i 5/1/14 - Notified Terry with Bl am. 5/2/14 - Set 5-1/2 inch 17 lb F collar at 12,783 ft. Cemented percent D46 + 4 percent D02 (yld 2.00, wt 12.00). Tailed ir percent D020 + 3 lb/sx D42 + 13.20). Circulated 83 sacks t 5 percent D44 + 0.2 percent 1 14. I hereby certify that the foregoing i Ca Name (Printed/Typed) LAURA V	final inspection.) OP and continued drilling of educed hole to 8-1/2 inch a inch hole to 12,837 ft. LM of intent to run and cer P-110 BT&C casing at 12,8 d stage 1 with 410 sacks P 0 + 5 lb/sx D42 + 0.5 perc n with 1010 sacks PVL + 0 - 0.5 percent D201 + 0.2 p to surface. Cemented stage D46 + 1 percent D020 + 3 is true and correct. Electronic Submission # For YATES PETRO ommitted to AFMSS for pro VATTS Submission) THIS SPACE FO ed. Approval of this notice does uitable title to those rights in the uct operations thereon.	directional. and continued ment 5-1/2 ind 832 ft. Stage VL + 0.125 ll sent D201 + 0 0.125 lb/sx D1 ercent D65 + ge 2 with 660 lb/sx D42 + (245260 verifie DLEUM CORP ideessing by C/ DR FEDERA	d drilling. ch production case box D130 + 5 per 3 percent D65 + 30 + 0.2 percent 0.4 percent D16 sacks PVL + 0.1 0.5 percent D201 d by the BLM We ORATION, sent the THY QUEEN on Title REG RI Date 05/12/2 AL OR STATE Title	sing at 10:00 and float ercent D44 + 0.4 percent D46 + 4 37 (yld 1.38, 125 lb/sx D1 + 0.4 percent U Information o the Carlsb 06/09/2014 (1 EPORTING 014 ACC 0 FICE 0	Accepted for record 0.2 10.2 10.2 10167 Wt 30 + 20 1065 NM OI A WT 30 + 20 1065 NM OI A 10 10 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 A 107 107 A 107 107 107 107 107 107 107 107	L CONSERVATION RTESIA DISTRICT DEU 0 4 2017 RECEIVED	

BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED

Additional data for EC transaction #245260 that would not fit on the form

32. Additional remarks, continued

+ 0.4 percent D167 (yld 1.96, wt 12.00). Tailed in with 100 sacks PVL + 0.125 lb/sx D130 + 0.2 percent D46 + 3 lb/sx D42 + 0.1 percent D13 + 0.1 percent D65 (yld 1.38, wt 13.20). 5/3/14 - Rig released at 12:00 am.