District 1/2 1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Fo ap Fo of

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Is pit or bel	ow-grade tan	k covered by a "ger	eral plan"? Yes \[\] No Closure of a pit or below-gr	$\overline{\boxtimes}$		
Operator: COG Operating LLC	•	e: 432-685-4372	e-mail address: dk	uykendall@concho	resources.com	1
Address: Fasken Center Tower II, 550 W. Texas Ave., St Facility or well name: Mosley Canyon 32 State #1 County: Eddy	na, 12 /9/01 30-015-34250 N 32°15' 55"	U/L or Qtr/Qtr: D Longitude: W 104°		T: 23S D: 1927 🔲 19	R: 25E 983 🔲	
Surface Owner: Federal ☐ State ☒ Private ☐ Indian ☐ Pit]	Below-grade tank				
Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thickness: 12 mil Clay Pit Volume: 25,000 bbl	Volume:bbl Type of fluid: RECEIV Construction material: Double-walled, with leak detection? Yes If not, explain why not. APR 0 5 2					
epth to ground water (vertical distance from bottom of pit to seasonal gh water elevation of ground water.) 500°		Less than 50 feet 50 feet or more, but le 100 feet or more - X	(20 points) (10 points) (0 points)	0		
Wellhead protection area: (Less than 200 feet from a priva water source, or less than 1000 feet from all other water so		Yes No - X		(20 points) (0 points)	0	
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)		Less than 200 feet 200 feet or more, but 1 1000 feet or more - X	ess than 1000 feet	(20 points) (10 points) (0 points)	0	
		Ranking Score (Tota	0 points			
Ithis is a pit closure: (1) Attach a diagram of the facility sour are burying in place) onsite offsite If offsite, na	• .	s relationship to other eq	ripment and tanks. (2) India . (3) Attach a general	•	`	

Additional Comments: Pit Closure Plan attached	
I hereby certify that the information above is true and complete to the best of	my knowledge and belief. I further certify that the above-described pit or below-grade tank

remediation start date and end date. (4) Groundwater encountered: No 🗌 Yes 🔲 If yes, show depth below ground surface ft. and attach sample results.

has been/will be constructed or closed according to NMOCD guidelines \(\text{\tinte\text{\tinitett{\texict{\texictex{\text{\texi{\tet{\texi}\text{\text{\text{\text{\text{\texi}\tiext{\text{\texit{\

Printed Name/Title <u>Diane Kuykendall, Regulatory Analyst</u> Signature <u>Jaw</u> Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval: USGS information
Printed Name/Title - shows this area to 1

shows this area to be water sensitive.

(5) Attach soil sample results and a diagram of sample locations and excavations.

Please submit a plan that can be signature approved for a sensitive area or schedule a meeting where other water data can be reviewed.

Pit Closure Plan – Drilling Pit

Operator: COG Operating LLC
Well Name: Mosley Canyon 32 State #1

Location: Unit D, Section 32, Township 23 S, Range 25 E, Eddy County, NM

The drilling pit associated with this well will be closed as per New Mexico OCD "Pit and Below-Grade Tank Guidelines" dated November 1, 2004. The visual inspection of the pit indicated that the pit liner has maintained its integrity.

- 1. Any remaining liquids will be removed from the pit.
- 2. Remaining solid wastes (i.e. buckets, cans, miscellaneous trash, debris, contaminated solids, etc.) will be removed from the pit, except for dried mud and cuttings, cement, and frac materials in drilling and reserve pits which have been approved by the OCD for encapsulation.
- 3. This well did not penetrate a salt section and was drilled with less than 9.5 lb/gal brine. Therefore, the drilling pit will be closed by encapsulation:

Encapsulation will be accomplished by mixing earthen materials with the pit contents to stiffen the pit contents, as necessary, folding the edges of the liner over the stiffened mud and cuttings and covering the encapsulated wastes and liner with a minimum of 3 feet of clean soil that is capable of supporting native plant growth.

4. Upon closure of the pit, the surface where the pit was located will be contoured to prevent erosion and ponding of rainwater over the site.

New Mexico Office of the State Engineer POD Reports and Downloads

Township: 23S Range: 25E Sections:						
NAD27 X: Y: Zone: Search Radius:						
County: Basin: Number: Suffix:						
Owner Name: (First) (Last) O Non-Domestic O Domestic						
ROD://Surface/Data/Report: AvgiDepth to Water Report Water Column: Report						
Clear-Form						

AVERAGE DEPTH OF WATER REPORT 03/24/2006

								(Depth	Water in	Feet)
Bsn	Tws	Rng	Sec	Zone	x	Y	Wells	Min	Max	Avg
С	238	25E	06				1	485	485	485
C	238	25E	09				1	593	593	593
С	23S	25E	12				1	90	90	90
С	238	25E	1.6				1			
С	238	25E	35				1	511	511	511

Record Count: 5

Mosley Caryon 32 State #1