1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410

## State of New Mexico Energy, Minerals and Natural Resources Department

**Submit Original** to Appropriate District Office

Oil Conservation Division 1000 Candle C4 E-

NM OIL CONSERVATION

District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505			Santa Fe, NM 87505			ARTESIA DISTRICT	
			DTHD P	A NI		JAN 1 1 2018	
Date: 1-11-18		GAS CA	APTURE PL	AIN		DECEN (De	
						RECEIVED	
<ul><li>☑ Original</li><li>☐ Amended - Reason for</li></ul>	A mandman	_	r & OGRID 1	No.: <u>Mewbo</u>	urne Oil Con	npany - 14744	
Amended - Reason for	Amendmen	IL.					
new completion (new drill	, recomplete	e to new zone, re-fr	ac) activity.		-	facility flaring/venting for	
Note: Form C-129 must be su	bmitted and $lpha$	pproved prior to exce	eding 60 days a	illowed by Ru	le (Subsection 2	A of 19.15.18.12 NMAC).	
Well(s)/Production Facili	ty – Name	of facility					
The well(s) that will be loc	eated at the	production facility	are shown in	the table be	low.		
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
FORTY NINER RIDGE UNIT #105H	30-015-44219	P-22-23S-30E	25 FSL & 445 FEL	0	NA NA	ONLINE AFTER FRAC	
ORTY NINER RIDGE UNIT #106H	30-015-44204	P-22-238 30E	525 FSL & 496 FEL	o	NA	ONLINE AFTER FRAC	
Gathering System and Pi			1 1 1 1		1-4- :6		
						gas transporter system is in and will be connected to	
DCP Midstream low/h	nigh pressur	re gathering syster	m located in	EDDY	County, New	v Mexico. It will require	
						ourne Oil Company provides	
						or wells that are scheduled to	
be drilled in the foreseeab	ole future.	In addition, Mewber	ourne Oil Co	<u>mpany</u> and dules Gos	DCP Mids	wells will be processed at	
DCP Midstream	Processing	Plant located in Se	ec. 3 . Tw	n. 225 . Rn	р. 371г. т.е.	a County, New Mexico.	
The actual flow of the gas w							
Flowback Strategy							

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP Midstream system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines