District 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

NM OIL CONSERVATION State of New Mexico Energy, Minerals and Natural Resources Department

> **Oil Conservation Division** 1220 South St. Francis Dr. Santa Fe, NM 87505

to Appropriate District Office FEB 1 4 2018

RECEIVED

GAS CAPTURE PLAN

Date: 8-10-2017

 \boxtimes Original Operator & OGRID No.: OXY USA Inc - 16696 □ Amended - Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Corral Fly 35-26 Federal Com #21H	Pending	Lot 4, Sec. 2, T25S, R29E	694 FNL 1248 FWL	3,238	0	
Corral Fly 35-26 Federal Com #22H	Pending	Lot 4, Sec. 2, T25S, R29E	694 FNL 1278 FWL	3,238	0	
Corral Fly 35-26 Federal Com #23H	Pending	Lot 4, Sec. 2, T25S, R29E	694 FNL 1308 FWL	3,238	0	
Corral Fly 35-26 Federal Com #24H	Pending	Lot 1, Sec. 2, T25S, R29E	314 FNL 1307 FEL	3,238	0	
Corral Fly 35-26 Federal Com #25H	Pending	Lot 1, Sec. 2, T25S, R29E	314 FNL 1277 FEL	3,238	0	
Corral Fly 35-26 Federal Com #26H	Pending	Lot 1, Sec. 2, T25S, R29E	314 FNL 1247 FEL	3,238	0	

The well(s) that will be located at the production facility are shown in the table below.

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, where a gas transporter system is expected be in place. OXY USA WTP Limited Partnership ("OXY") has begun discussion with third-party gas processors and currently has two (2) potential gas gathering pipeline options. The gas produced from the production facility will be connected to a low/high pressure gathering system and processed at a processing plant. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gatherer system at that time. Based on current information, it is OXY's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease •
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
 - Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

