<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210	State of New Mexic Energy, Minerals and Natural Resour	Submit Original to Appropriate District Office	
<u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	Oil Conservation Divis 1220 South St. Francis		
1220 S. St. Flancis DI., Santa Fe, NWI 67505	Santa Fe, NM 8750:		
		ARTESIA DISTRI	61
Date: 5/2/17	GAS CAPTURE PLAN	FEB 2 6 201	3
 Original Amended - Reason for Amendment: 	Operator & OGRID No.:	OXY USA RECEIVED	

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

	n(s) that will be located	i di ille proc	action facinity are	Shown in the				_
W	ell Name	API	Well Location	Footages	Expected	Flared or	Comments	
			(ULSTR)		MCF/D	Vented		
Co	orral Draw 14-13	Pending	Unit B, Sec 14,	473 FNL	3200	0	20100	
Fe	ederal 21H		T25S R29E	2540 FEL			30-015-44-	777
Co	orral Draw 14-13	Pending	Unit B, Sec 14,	503 FNL	3200	0		
Fe	ederal 22H		T25S R29E	2540 FEL				
Co	orral Draw 14-13	Pending	Unit J, Sec 14,	2143 FSL	3200	0		
Fe	ederal 23H		T25S R29E	2540 FEL				
Co	orral Draw 14-13	Pending	Unit J, Sec 14,	2113 FSL	3200	0		
Fe	ederal 24H		T25S R29E	2540 FEL				

The well(s) that will be located at the production facility are shown in the table below.

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>ETC Texas Pipeline, LTD ("ETC")</u> and will be connected to <u>ETC's</u> low pressure gathering system located in Eddy County, New Mexico. It will require 60,000' of pipeline to connect the facility to the low pressure gathering system. <u>OXY USA WTP Limited Partnership</u> ("OXY") provides (periodically) to <u>ETC</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>OXY</u> and <u>ETC</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>ETC's Orla</u> Processing Plant located in <u>Reeves</u> County, Texas. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>Operator's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
 - Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines