□ Original

Operator & OGRID No.: OXY USA Inc. - 16696

□ Amended - Reason for Amendment:_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

ne wen(s) that will	be located at the pro-	auction facinity are	5110 will fill the	tuble below.		
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Corral Draw 14 Federal 21H	-13 Pending	Unit B, Sec 14, T25S R29E	473 FNL 2540 FEL	3200	0	
Corral Draw 14 Federal 22H	-13 Pending	Unit B, Sec 14, T25S R29E	503 FNL 2540 FEL	3200	0	
Corral Draw 14 Federal 23H	-13 Pending	Unit J, Sec 14, T25S R29E	2143 FSL 2540 FEL	3200	0 30-0	15.44779
Corral Draw 14 Federal 24H	-13 Pending	Unit J, Sec 14, T25S R29E	2113 FSL 2540 FEL	3200	0	

The well(s) that will be located at the production facility are shown in the table below.

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>ETC Texas Pipeline, LTD ("ETC"</u>) and will be connected to <u>ETC's</u> low pressure gathering system located in Eddy County, New Mexico. It will require 60,000' of pipeline to connect the facility to the low pressure gathering system. <u>OXY USA WTP Limited Partnership</u> ("OXY") provides (periodically) to <u>ETC</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>OXY</u> and <u>ETC</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>ETC's Orla</u> Processing Plant located in <u>Reeves</u> County, Texas. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>Operator's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines