

**NM OIL CONSERVATION
ARTESIA DISTRICT**

**NM OIL CONSERVATION
ARTESIA DISTRICT**

Form 3160-3
(March 2012)

FEB 26 2018

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

RECEIVED UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

APPLICATION FOR PERMIT TO DRILL OR REENTER

| | | |
|--|--|---|
| 1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER | | 5. Lease Serial No. NMNM89057 |
| 1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone | | 6. If Indian, Allottee or Tribe Name |
| 2. Name of Operator DEVON ENERGY PRODUCTION COMPANY LP | | 7. If Unit or CA Agreement, Name and No. |
| 3a. Address 333 West Sheridan Avenue Oklahoma City OK | 3b. Phone No. (include area code) (405)552-6571 | 8. Lease Name and Well No. SNAPPING 12-1 FED 523H 3208001 |
| 4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface SENW / 2325 FNL / 1880 FWL / LAT 32.0584866 / LONG -103.7342229 At proposed prod. zone NENW / 330 FNL / 2310 FWL / LAT 32.0786162 / LONG -103.7327979 | | 9. API Well No. 30-015-44758 |
| 14. Distance in miles and direction from nearest town or post office* | | 10. Field and Pool, or Exploratory JENNINGS, WEST / BONE SPRING |
| 15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 330 feet | | 11. Sec., T. R. M. or Blk. and Survey or Area SEC 12 / T26S / R31E / NMP |
| 16. No. of acres in lease 2160 | 17. Spacing Unit dedicated to this well 240 | 12. County or Parish EDDY |
| 18. Distance from proposed location* to nearest well, drilling, completed, 2500 feet applied for, on this lease, ft. 2500 feet | 19. Proposed Depth 8773 feet / 16198 feet | 13. State NM |
| 20. BLM/BIA Bond No. on file FED: CO1104 | 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3237 feet | 22. Approximate date work will start* 04/21/2018 |
| 23. Estimated duration 30 days | | |

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

| | | |
|--|--|--------------------|
| 25. Signature (Electronic Submission) | Name (Printed/Typed) Erin Workman / Ph: (405)552-7970 | Date 10/02/2017 |
| Title Regulatory Compliance Professional | | |
| Approved by (Signature) (Electronic Submission) | Name (Printed/Typed) Cody Layton / Ph: (575)234-5959 | Date 02/08/2018 |
| Title Supervisor Multiple Resources | | |
| Office CARLSBAD | | |

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

APPROVED WITH CONDITIONS
Approval Date: 02/08/2018

RWP 2-28-18

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications.

Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

1. SHL: SENW / 2325 FNL / 1880 FWL / TWSP: 26S / RANGE: 31E / SECTION: 12 / LAT: 32.0584866 / LONG: -103.7342229 (TVD: **0** feet, MD: **0** feet)
PPP: SENW / 2128 FNL / 2310 FWL / TWSP: 26S / RANGE: 31E / SECTION: 12 / LAT: 32.0584866 / LONG: -103.7342229 (TVD: 8773 feet, MD: 9070 feet)
BHL: NENW / 330 FNL / 2310 FWL / TWSP: 26S / RANGE: 31E / SECTION: 1 / LAT: 32.0786162 / LONG: -103.7327979 (TVD: **8773** feet, MD: 16198 feet)

BLM Point of Contact

Name: Sipra Dahal

Title: Legal Instruments Examiner

Phone: 5752345983

Email: sdahal@blm.gov

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). **Contact the above listed Bureau of Land Management office for further information.**

FEB 26 2018

DRILLING CONDITIONS OF APPROVAL

RECEIVED

| | |
|-----------------------|--|
| OPERATOR'S NAME: | Devon Energy Production, L.P. |
| LEASE NO.: | NMNM-89057 |
| WELL NAME & NO.: | Snapping 12-1 Fed 523H |
| SURFACE HOLE FOOTAGE: | 2325' FNL & 1880' FWL |
| BOTTOM HOLE FOOTAGE: | 0330' FNL & 2310' FWL Sec. 01, T. 26 S., R 31 E. |
| LOCATION: | Section 12, T. 26 S., R 31 E., NMPM |
| COUNTY: | County, New Mexico |

I. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- Spudding well (minimum of 24 hours)
- Setting and/or Cementing of all casing strings (minimum of 4 hours)
- BOPE tests (minimum of 4 hours)

☐ **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

1. A Hydrogen Sulfide (H₂S) Drilling Plan shall be activated 500 feet prior to drilling into the **Delaware** formation. **As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
3. Option – Setting surface casing with Spudder Rig
 - a. Notify the BLM when removing the Spudder Rig.
 - b. Notify the BLM when moving in the H&P Flex Rig. Rig to be moved in within 60 days of notification that Ashton Oilfield Services Rig has left the location. Failure to notify or have rig on location within 60 days will result in an Incident of Non-Compliance.

- c. Once the H&P Flex Rig is on location, it shall not be removed from over the hole without prior approval unless the production casing has been run and cemented or the well has been properly plugged. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
 - d. BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as H&P Flex Rig is rigged up on well. CIT for the surface casing shall be performed and results recorded on subsequent sundry – pressure to be 1200 psi.
- 4. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
 - 5. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.**

B. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) for Water Basin:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

High Cave/Karst

Possibility of water flows in the Salado and Castile.

Possibility of lost circulation in the Rustler, Red Beds, and Delaware.

Abnormal pressures may be encountered upon penetrating the 3rd Bone Spring Sandstone and all subsequent formations.

A MINIMUM OF TWO CASING STRINGS CEMENTED TO SURFACE IS REQUIRED IN HIGH CAVE/KARST AREAS. THE CEMENT MUST BE IN A SOLID SHEATH. THEREFORE, ONE INCH OPERATIONS ARE NOT SUFFICIENT TO PROTECT CAVE KARST RESOURCES. A CASING DESIGN THAT HAS A ONE INCH JOB PERFORMED DOES NOT COUNT AS A SOLID SHEATH. IF THE PRIMARY CEMENT JOB ON THE SURFACE CASING DOES NOT CIRCULATE, THEN THE NEXT TWO CASING STRINGS MUST BE CEMENTED TO SURFACE.

1. The 13-3/8 inch surface casing shall be set at approximately **1070** feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. **If salt is encountered, set casing at least 25 feet above the salt.**
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

- ☐ Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst. Excess calculates to 22% - Additional cement may be required.**

Centralizers required on horizontal leg, must be type for horizontal service and a minimum of one every other joint.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- ☐ Cement should tie-back at least 200 feet into previous casing string. Operator shall provide method of verification. .

4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API 53.
2. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. **Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.** If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).

3. **Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be psi.**
 - a. **Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.**
 - b. **If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.**
 - c. **Manufacturer representative shall install the test plug for the initial BOP test.**
 - d. **Operator shall perform the intermediate casing integrity test to 70% of the casing burst. This will test the multi-bowl seals.**
 - e. **If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.**
4. **The appropriate BLM office shall be notified a minimum of hours in advance for a representative to witness the tests.**
 - a. **In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).**
 - a. **The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**.**
 - b. **The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.**
 - c. **The results of the test shall be reported to the appropriate BLM office.**
 - d. **All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**

- e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

E. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

JAM 020218

FEB 26 2018

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

RECEIVED

| | |
|-----------------------|---------------------------------|
| OPERATOR'S NAME: | Devon Energy Production |
| LEASE NO.: | NMNM 089057 |
| WELL NAME & NO.: | 523H-Snapping 12-1 FED |
| SURFACE HOLE FOOTAGE: | 2325'/N & 1880'/W |
| BOTTOM HOLE FOOTAGE: | 330'/N & 2310'/W |
| LOCATION: | Section 12, R. 31E, T 26S, NMPM |
| COUNTY: | Eddy County, New Mexico. |

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Cave/Karst
 - Watershed
 - Range
 - Wildlife
- ☐ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

These Pads are build as you go no grading whole area.

Surface disturbance will not be allowed within up to 200 meters of active heronries or by delaying activity for up to 120 days, or a combination of both.

Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db. measured at 30 ft. from the source of the noise.

Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

Trenches-Escape Ramps

Devon would need to construct and maintain escape ramps according to the following criteria:

- Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30-degree slope and spaced no more than 500 feet apart.
- If trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled, Devon would inspect the trench for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.

Cave and Karst Conditions of Approval for APDs

**** Depending on location, additional Drilling, Casing, and Cementing procedures may be required by engineering to protect critical karst groundwater recharge areas.**

Cave/Karst Surface Mitigation

The following stipulations will be applied to minimize impacts during construction, drilling and production.

Construction:

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

No Blasting:

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

Pad Berming:

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g., caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)
- Following a rain event, all fluids will vacuumed off of the pad and hauled off-site and disposed at a proper disposal facility.

Tank Battery Liners and Berms:

Tank battery locations and all facilities will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing, or equivalent, to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

Leak Detection System:

A method of detecting leaks is required. The method could incorporate gauges to measure loss, siting valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

Automatic Shut-off Systems:

Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Cave/Karst Subsurface Mitigation

The following stipulations will be applied to protect cave/karst and ground water concerns:

Rotary Drilling with Fresh Water:

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

Directional Drilling:

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

Lost Circulation:

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

Abandonment Cementing:

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Pressure Testing:

Annual pressure monitoring will be performed by the operator on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. Devon shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

During construction, Devon shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. Devon is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/allottee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out sloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
- Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- | | |
|--|--|
| <input checked="" type="checkbox"/> seed mixture 1 | <input type="checkbox"/> seed mixture 3 |
| <input type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4 |
| <input type="checkbox"/> seed mixture 2/LPC | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant

cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 1 for Loamy Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed shall be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed shall be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture shall be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed shall be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre shall be doubled. The seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

| <u>Species</u> | <u>lb/acre</u> |
|---|----------------|
| Plains lovegrass (<i>Eragrostis intermedia</i>) | 0.5 |
| Sand dropseed (<i>Sporobolus cryptandrus</i>) | 1.0 |
| Sideoats grama (<i>Bouteloua curtipendula</i>) | 5.0 |
| Plains bristlegrass (<i>Setaria macrostachya</i>) | 2.0 |

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

PECOS DISTRICT SURFACE USE CONDITIONS OF APPROVAL

| | |
|-----------------------|---------------------------------|
| OPERATOR'S NAME: | Devon Energy Production |
| LEASE NO.: | NMNM 089057 |
| WELL NAME & NO.: | 523H-Snapping 12-1 FED |
| SURFACE HOLE FOOTAGE: | 2325'/N & 1880'/W |
| BOTTOM HOLE FOOTAGE: | 330'/N & 2310'/W |
| LOCATION: | Section 12, R. 31E, T 26S, NMPM |
| COUNTY: | Eddy County, New Mexico. |

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Cave/Karst
 - Watershed
 - Range
 - Wildlife
- ☐ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

These Pads are build as you go no grading whole area.

Surface disturbance will not be allowed within up to 200 meters of active heronries or by delaying activity for up to 120 days, or a combination of both.

Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db. measured at 30 ft. from the source of the noise.

Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

Trenches-Escape Ramps

Devon would need to construct and maintain escape ramps according to the following criteria:

- Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30-degree slope and spaced no more than 500 feet apart.
- If trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled, Devon would inspect the trench for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.

Cave and Karst Conditions of Approval for APDs

****** Depending on location, additional Drilling, Casing, and Cementing procedures may be required by engineering to protect critical karst groundwater recharge areas.

Cave/Karst Surface Mitigation

The following stipulations will be applied to minimize impacts during construction, drilling and production.

Construction:

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

No Blasting:

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

Pad Berming:

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g., caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)
- Following a rain event, all fluids will be vacuumed off of the pad and hauled off-site and disposed at a proper disposal facility.

Tank Battery Liners and Berms:

Tank battery locations and all facilities will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing, or equivalent, to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

Leak Detection System:

A method of detecting leaks is required. The method could incorporate gauges to measure loss, siting valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

Automatic Shut-off Systems:

Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Cave/Karst Subsurface Mitigation

The following stipulations will be applied to protect cave/karst and ground water concerns:

Rotary Drilling with Fresh Water:

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

Directional Drilling:

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

Lost Circulation:

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

Abandonment Cementing:

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Pressure Testing:

Annual pressure monitoring will be performed by the operator on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. Devon shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

During construction, Devon shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. Devon is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/allottee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.

- Any water erosion that may occur due to the construction of the well pad during the life of the well will be corrected within two weeks and proper measures will be taken to prevent future erosion.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 *et seq.* (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, *et seq.* or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, *et seq.*) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
- Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- | | |
|--|--|
| <input checked="" type="checkbox"/> seed mixture 1 | <input type="checkbox"/> seed mixture 3 |
| <input type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4 |
| <input type="checkbox"/> seed mixture 2/LPC | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant

cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 1 for Loamy Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed shall be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed shall be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture shall be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed shall be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre shall be doubled. The seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

| <u>Species</u> | <u>lb/acre</u> |
|---|----------------|
| Plains lovegrass (<i>Eragrostis intermedia</i>) | 0.5 |
| Sand dropseed (<i>Sporobolus cryptandrus</i>) | 1.0 |
| Sideoats grama (<i>Bouteloua curtipendula</i>) | 5.0 |
| Plains bristlegrass (<i>Setaria macrostachya</i>) | 2.0 |

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator Certification Data Report

02/09/2018

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Erin Workman

Signed on: 10/02/2017

Title: Regulatory Compliance Professional

Street Address: 333 West Sheridan Avenue

City: Oklahoma City

State: OK

Zip: 73102

Phone: (405)552-7970

Email address: Erin.Workman@dvn.com

Field Representative

Representative Name: Ray Vaz

Street Address: 6488 Seven Rivers Hwy

City: Artesia

State: NM

Zip: 88210

Phone: (575)748-1871

Email address: ray.vaz@dvn.com



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data Report

02/09/2018

APD ID: 10400022571

Submission Date: 10/02/2017

Highlighted data
reflects the most
recent changes

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400022571

Tie to previous NOS? 10400017085

Submission Date: 10/02/2017

BLM Office: CARLSBAD

User: Erin Workman

Title: Regulatory Compliance
Professional

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM89057

Lease Acres: 2160

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: DEVON ENERGY PRODUCTION COMPANY LP

Operator letter of designation:

Operator Info

Operator Organization Name: DEVON ENERGY PRODUCTION COMPANY LP

Operator Address: 333 West Sheridan Avenue

Zip: 73102

Operator PO Box:

Operator City: Oklahoma City

State: OK

Operator Phone: (405)552-6571

Operator Internet Address: aletha.dewbre@dvn.com

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: JENNINGS, WEST Pool Name: BONE SPRING

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL,POTASH

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Describe other minerals:

Is the proposed well in a Helium production area? N

Use Existing Well Pad? NO

New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:

Number: 2

Well Class: HORIZONTAL

SNAPPING 12 WELLPAD

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: OTHER

Describe sub-type: DEVELOPMENT

Distance to town:

Distance to nearest well: 2500 FT

Distance to lease line: 330 FT

Reservoir well spacing assigned acres Measurement: 240 Acres

Well plat: Snapping_12_1_Fed_523H_C_102_signed_20170927063835.pdf

Well work start Date: 04/21/2018

Duration: 30 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number: 5440B

| | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude | Longitude | County | State | Meridian | Lease Type | Lease Number | Elevation | MD | TVD |
|------------------|----------|--------------|----------|--------------|------|-------|---------|-------------------|----------------|----------------------|----------|-------------------|-------------------|------------|---------------|---------------|----------|----------|
| SHL Leg #1 | 232 5 | FNL | 188 0 | FWL | 26S | 31E | 12 | Aliquot SENW | 32.05848 66 | - 103.7342 229 | EDD Y | NEW MEXI CO | NEW MEXI CO | F | NMNM 89057 | 323 7 | 0 | 0 |
| KOP Leg #1 | 260 5 | FNL | 228 1 | FWL | 26S | 31E | 12 | Aliquot SENW | 32.05848 66 | - 103.7342 229 | EDD Y | NEW MEXI CO | NEW MEXI CO | F | NMNM 89057 | - 505 8 | 832 0 | 829 5 |
| PPP Leg #1 | 212 8 | FNL | 231 0 | FWL | 26S | 31E | 12 | Aliquot SENW | 32.05848 66 | - 103.7342 229 | EDD Y | NEW MEXI CO | NEW MEXI CO | F | NMNM 89057 | - 553 6 | 907 0 | 877 3 |

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

| | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude | Longitude | County | State | Meridian | Lease Type | Lease Number | Elevation | MD | TVD |
|-------------------|---------|--------------|----------|--------------|------|-------|---------|-------------------|----------------|----------------------|----------|-------------------|-------------------|------------|---------------|---------------|-----------|----------|
| EXIT Leg #1 | 330 | FNL | 231 0 | FWL | 26S | 31E | 1 | Aliquot NENW | 32.07861 62 | - 103.7327 979 | EDD Y | NEW MEXI CO | NEW MEXI CO | F | NMNM 89057 | - 553 6 | 161 98 | 877 3 |
| BHL Leg #1 | 330 | FNL | 231 0 | FWL | 26S | 31E | 1 | Aliquot NENW | 32.07861 62 | - 103.7327 979 | EDD Y | NEW MEXI CO | NEW MEXI CO | F | NMNM 89057 | - 553 6 | 161 98 | 877 3 |

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Pressure Rating (PSI): 5M

Rating Depth: 4150

Equipment: BOP/BOPE will be installed per Onshore Oil & Gas Order #2 requirements prior to drilling below 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the wellhead system. BOP/BOPE will be tested by an independent service company per Onshore Oil & Gas Order #2 requirements and MASP (Maximum Anticipated Surface Pressure) calculations. If the system is upgraded, all the components installed will be functional and tested.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP stack to the choke manifold. See attached for specs for hydrostatic test chart.

Testing Procedure: A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Choke Diagram Attachment:

Snapping_12_1_Fed_533H_5M_BOPE__Ck_20171002133507.pdf

BOP Diagram Attachment:

Snapping_12_1_Fed_533H_5M_BOPE__Ck_20171002133539.pdf

Section 3 - Casing

| Casing ID | String Type | Hole Size | Csg Size | Condition | Standard | Tapered String | Top Set MD | Bottom Set MD | Top Set TVD | Bottom Set TVD | Top Set MSL | Bottom Set MSL | Calculated casing length MD | Grade | Weight | Joint Type | Collapse SF | Burst SF | Joint SF Type | Joint SF | Body SF Type | Body SF |
|-----------|--------------|-----------|----------|-----------|----------|----------------|------------|---------------|-------------|----------------|-------------|----------------|-----------------------------|-------|--------|------------|-------------|----------|---------------|----------|--------------|---------|
| 1 | SURFACE | 17.5 | 13.375 | NEW | API | N | 0 | 960 | 0 | 960 | | | 960 | H-40 | 48 | STC | 1.74 | 2.45 | DRY | 4.13 | BUOY | 4.13 |
| 2 | INTERMEDIATE | 12.25 | 9.625 | NEW | API | N | 0 | 4150 | 0 | 4150 | | | 4150 | J-55 | 40 | LTC | 1.19 | 1.42 | BUOY | 3.98 | BUOY | 3.98 |
| 3 | PRODUCTION | 8.75 | 5.5 | NEW | API | N | 0 | 16198 | 0 | 8773 | | | 16198 | P-105 | 17 | BUTT | 2.18 | 2.7 | BUOY | 3.21 | BUOY | 3.21 |

Casing Attachments

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Snapping_12_1_Fed_533H_SurfCsg_Ass_20171002133918.pdf

Casing ID: 2 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Snapping_12_1_Fed_533H_Int_Csg_Ass_20171002134038.pdf

Casing ID: 3 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Snapping_12_1_Fed_533H_ProdCasing_Ass_20171002134158.pdf

Section 4 - Cement

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

| String Type | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives |
|-------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|---------------------|
| SURFACE | Lead | | 0 | 960 | 747 | 1.34 | 14.8 | 1000 | 50 | C | 1% Calcium Chloride |

| | | | | | | | | | | | |
|--------------|------|--|------|-----------|------|------|------|------|----|-------|--|
| INTERMEDIATE | Lead | | 0 | 3150 | 694 | 1.85 | 12.9 | 1283 | 30 | C | Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sks Poly-E-Flake |
| INTERMEDIATE | Tail | | 3150 | 4150 | 306 | 1.33 | 14.8 | 407 | 30 | C | 0.125 lbs/sks Poly-R- Flake |
| PRODUCTION | Lead | | 3950 | 8700 | 459 | 3.27 | 9 | 1500 | 25 | TUNED | N/A |
| PRODUCTION | Tail | | 8700 | 1619 8 | 1972 | 1.2 | 14.5 | 2633 | 25 | H | Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite |

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

| Top Depth | Bottom Depth | Mud Type | Min Weight (lbs/gal) | Max Weight (lbs/gal) | Density (lbs/cu ft) | Gel Strength (lbs/100 sqft) | PH | Viscosity (CP) | Salinity (ppm) | Filtration (cc) | Additional Characteristics |
|-----------|--------------|----------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|
|-----------|--------------|----------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

| Top Depth | Bottom Depth | Mud Type | Min Weight (lbs/gal) | Max Weight (lbs/gal) | Density (lbs/cu ft) | Gel Strength (lbs/100 sqft) | PH | Viscosity (CP) | Salinity (ppm) | Filtration (cc) | Additional Characteristics |
|-----------|--------------|-----------------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|
| 960 | 4150 | SALT SATURATED | 10 | 11 | | | | | | | |
| 4150 | 16198 | WATER-BASED MUD | 8.5 | 9.3 | | | | | | | |
| 0 | 960 | WATER-BASED MUD | 8.5 | 9 | | | | | | | |

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.

List of open and cased hole logs run in the well:

CBL,DS,GR,MUDLOG

Coring operation description for the well:

N/A

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 3948

Anticipated Surface Pressure: 2017.94

Anticipated Bottom Hole Temperature(F): 149

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Snapping_12_1_Fed_523H_H2S_Plan_20170927064217.pdf

Opefator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Snapping_12_1_Fed_533H_AC_Rpt_20171002140514.pdf

Snapping_12_1_Fed_533H_Dir_Plan_20171002140526.pdf

Other proposed operations facets description:

CLOSED LOOP DESIGN

MULTI-BOWL VERBIAGE

MULTI-BOWL WELLHEAD

DRILLING PLAN

Other proposed operations facets attachment:

Snapping_12_1_Fed_523H_Clsd_Loop_20170927064401.pdf

Snapping_12_1_Fed_523H_MB_Verb_20170927064707.pdf

Snapping_12_1_Fed_523H_MB_Wellhd_20170927064720.pdf


Snapping_12_1_Fed_533H_Drilling_Plan_20171002140537.pdf

Other Variance attachment:


Snapping_12_1_Fed_523H_Co_flex_20170927064734.pdf

Snapping_12_1_Fed_523H_Spudder_Rig_20170927064752.pdf


13-5/8" 5M BOPE & Closed Loop Equipment Schematic




13-5/8" 5M BOPE & Closed Loop Equipment Schematic



13-5/8" 5M BOPE & Closed Loop Equipment Schematic



13-5/8" 5M BOPE & Closed Loop Equipment Schematic



Casing Assumptions and Load Cases

Surface

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.

| Surface Casing Burst Design | | |
|-----------------------------|-------------------------|---|
| Load Case | External Pressure | Internal Pressure |
| Pressure Test | Formation Pore Pressure | Max mud weight of next hole-section plus Test psi |
| Drill Ahead | Formation Pore Pressure | Max mud weight of next hole section |
| Displace to Gas | Formation Pore Pressure | Dry gas from next casing point |

| Surface Casing Collapse Design | | |
|--------------------------------|---|-------------------|
| Load Case | External Pressure | Internal Pressure |
| Full Evacuation | Water gradient in cement, mud above TOC | None |
| Cementing | Wet cement weight | Water (8.33ppg) |

| Surface Casing Tension Design | |
|-------------------------------|-------------|
| Load Case | Assumptions |
| Overpull | 100kips |
| Runing in hole | 3 ft/s |
| Service Loads | N/A |

Casing Assumptions and Load Cases

Intermediate

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.

| Intermediate Casing Burst Design | | |
|----------------------------------|-------------------------|---|
| Load Case | External Pressure | Internal Pressure |
| Pressure Test | Formation Pore Pressure | Max mud weight of next hole-section plus Test psi |
| Drill Ahead | Formation Pore Pressure | Max mud weight of next hole section |
| Fracture @ Shoe | Formation Pore Pressure | Dry gas |

| Intermediate Casing Collapse Design | | |
|-------------------------------------|---|-------------------|
| Load Case | External Pressure | Internal Pressure |
| Full Evacuation | Water gradient in cement, mud above TOC | None |
| Cementing | Wet cement weight | Water (8.33ppg) |

| Intermediate Casing Tension Design | |
|------------------------------------|-------------|
| Load Case | Assumptions |
| Overpull | 100kips |
| Runing in hole | 2 ft/s |
| Service Loads | N/A |

Casing Assumptions and Load Cases

Production

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.

| Production Casing Burst Design | | |
|--------------------------------|-------------------------|---|
| Load Case | External Pressure | Internal Pressure |
| Pressure Test | Formation Pore Pressure | Fluid in hole (water or produced water) + test psi |
| Tubing Leak | Formation Pore Pressure | Packer @ KOP, leak below surface 8.6 ppg packer fluid |
| Stimulation | Formation Pore Pressure | Max frac pressure with heaviest frac fluid |

| Production Casing Collapse Design | | |
|-----------------------------------|--|-------------------|
| Load Case | External Pressure | Internal Pressure |
| Full Evacuation | Water gradient in cement, mud above TOC. | None |
| Cementing | Wet cement weight | Water (8.33ppg) |

| Production Casing Tension Design | |
|----------------------------------|-------------|
| Load Case | Assumptions |
| Overpull | 100kips |
| Runing in hole | 2 ft/s |
| Service Loads | N/A |



**Devon Energy Center
333 West Sheridan Avenue
Oklahoma City, Oklahoma 73102-5015**

Hydrogen Sulfide (H₂S) Contingency Plan

For


Snapping 12-1 Fed 523H

**Sec-12 T-26S R-31E
2325 FNL & 1880' FWL
LAT. = 32.0584866' N (NAD83)
LONG = 103.7342229' W**

Eddy County NM


Snapping 12-1 Fed 523H

This is an open drilling site. H₂S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H₂S, including warning signs, wind indicators and H₂S monitor.



Snapping 12-1 Fed 523H

11



Location Road

ROE = Radius of Exposure

Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

Assumed 100 ppm ROE = 3000'

100 ppm H₂S concentration shall trigger activation of this plan.

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must

- **Isolate the area and prevent entry by other persons into the 100 ppm ROE.**
- **Evacuate any public places encompassed by the 100 ppm ROE.**
- **Be equipped with H₂S monitors and air packs in order to control the release.**
- **Use the “buddy system” to ensure no injuries occur during the response**
- **Take precautions to avoid personal injury during this operation.**
- **Contact operator and/or local officials to aid in operation. See list of phone numbers attached.**
- **Have received training in the**
 - **Detection of H₂S, and**
 - **Measures for protection against the gas,**
 - **Equipment used for protection and emergency response.**

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

Characteristics of H₂S and SO₂

| Common Name | Chemical Formula | Specific Gravity | Threshold Limit | Hazardous Limit | Lethal Concentration |
|-------------------------|-------------------------|--------------------------|------------------------|------------------------|-----------------------------|
| Hydrogen Sulfide | H₂S | 1.189 Air = 1 | 10 ppm | 100 ppm/hr | 600 ppm |
| Sulfur Dioxide | SO₂ | 2.21 Air = 1 | 2 ppm | N/A | 1000 ppm |

Contacting Authorities

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with

Hydrogen Sulfide Drilling Operation Plan

I. HYDROGEN SULFIDE (H₂S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H₂S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H₂S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H₂S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan.

II. HYDROGEN SULFIDE TRAINING

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S.

1. Well Control Equipment

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

2. Protective equipment for essential personnel:

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with one escape unit available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

3. H₂S detection and monitoring equipment:

Portable H₂S monitors positioned on location for best coverage and response. These units have warning lights which activate when H₂S levels reach 10 ppm and audible sirens which activate at 10 ppm. Sensor locations:

- Bell nipple
- Shale shaker
- Trip tank
- Suction pit
- Rig floor
- Cellar
- Choke manifold
- Living Quarters (usually the company man's trailer stairs.)

Visual warning systems:

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

4. Mud program:

The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight, safe drilling practices and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.

5. Metallurgy:

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H₂S trim.
- B. All elastomers used for packing and seals shall be H₂S trim.

6. Communication:

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

7. Well testing:

- A. There will be no drill stem testing.

| Devon Energy Corp. Company Call List | | |
|---|---|-------------------------------|
| Drilling Supervisor – Basin – Mark Kramer | | 405-823-4796 |
| Jerry Matthews – Day: 575-748-0161 Cell: 575-748-5234 | | |
| EHS Professional – Jason Robison | | 405-541-2841 |
| Agency Call List | | |
| Lea County (575) | Hobbs | |
| | Lea County Communication Authority | 393-3981 |
| | State Police | 392-5588 |
| | City Police | 397-9265 |
| | Sheriff's Office | 393-2515 |
| | Ambulance | 911 |
| | Fire Department | 397-9308 |
| | LEPC (Local Emergency Planning Committee) | 393-2870 |
| | NMOCD | 393-6161 |
| | US Bureau of Land Management | 393-3612 |
| | | |
| Eddy County (575) | Carlsbad | |
| | State Police | 885-3137 |
| | City Police | 885-2111 |
| | Sheriff's Office | 887-7551 |
| | Ambulance | 911 |
| | Fire Department | 885-3125 |
| | LEPC (Local Emergency Planning Committee) | 887-3798 |
| | US Bureau of Land Management | 887-6544 |
| | NM Emergency Response Commission (Santa Fe) | (505) 476-9600 |
| | 24 HR | (505) 827-9126 |
| | National Emergency Response Center | (800) 424-8802 |
| | National Pollution Control Center: Direct | (703) 872-6000 |
| | For Oil Spills | (800) 280-7118 |
| | Emergency Services | |
| | Wild Well Control | (281) 784-4700 |
| | Cudd Pressure Control | (915) 699-0139 (915) 563-3356 |
| | Halliburton | (575) 746-2757 |
| | B. J. Services | (575) 746-3569 |
| | Native Air – Emergency Helicopter – Hobbs | (575) 392-6429 |
| | Flight For Life - Lubbock, TX | (806) 743-9911 |
| Give GPS position: | Aerocare - Lubbock, TX | (806) 747-8923 |
| | Med Flight Air Amb - Albuquerque, NM | (575) 842-4433 |
| | Lifeguard Air Med Svc. Albuquerque, NM | (800) 222-1222 |
| | Poison Control (24/7) | (575) 272-3115 |
| | Oil & Gas Pipeline 24 Hour Service | (800) 364-4366 |
| | NOAA – Website - www.nhc.noaa.gov | |

Prepared in conjunction with
Dave Small



NM OIL CONSERVATION
ARTESIA DISTRICT
FEB 26 2018

RECEIVED

Devon Energy

Eddy County, New Mexico (NAD 83)
Snapping 12-1 FED
533H

OH
Plan 1

Anticollision Report

28 September, 2017

Anticollision Report

| | | | |
|---------------------------|----------------------------------|-------------------------------------|--------------------------------|
| Company: | Devon Energy | Local Co-ordinate Reference: | Well 533H |
| Project: | Eddy County, New Mexico (NAD 83) | TVD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Reference Site: | Snapping 12-1 FED | MD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Site Error: | 0.00 usft | North Reference: | Grid |
| Reference Well: | 533H | Survey Calculation Method: | Minimum Curvature |
| Well Error: | 0.00 usft | Output errors are at | 2.00 sigma |
| Reference Wellbore | OH | Database: | EDM 5000.14 Single User Db |
| Reference Design: | Plan 1 | Offset TVD Reference: | Offset Datum |

| | |
|-------------------------------------|---|
| Reference | Plan 1 |
| Filter type: | NO GLOBAL FILTER: Using user defined selection & filtering criteria |
| Interpolation Method: | MD Interval 100.00usft |
| Depth Range: | Unlimited |
| Results Limited by: | Maximum center-center distance of 1,834.38 usft |
| Warning Levels Evaluated at: | 2.00 Sigma |
| Error Model: | ISCWSA |
| Scan Method: | Closest Approach 3D |
| Error Surface: | Pedal Curve |
| Casing Method: | Not applied |

| | | |
|----------------------------|------------------|--------------------------|
| Survey Tool Program | Date | 9/28/2017 |
| From (usft) | To (usft) | Survey (Wellbore) |
| 0.00 | 16,378.88 | Plan 1 (OH) |
| | | Tool Name |
| | | MWD |
| | | Description |
| | | OWSG MWD - Standard |

| Summary | | | | | | |
|---------------------------------|---------------------------------|------------------------------|---------------------------------|----------------------------------|-------------------|-----------------|
| Site Name | Reference Measured Depth (usft) | Offset Measured Depth (usft) | Distance Between Centres (usft) | Distance Between Ellipses (usft) | Separation Factor | Warning |
| Offset Well - Wellbore - Design | | | | | | |
| Snapping 12-1 FED | | | | | | |
| 522H - OH - Plan 1 | 1,200.00 | 1,200.00 | 59.95 | 51.79 | 7.345 | CC, ES |
| 522H - OH - Plan 1 | 16,379.26 | 16,170.10 | 755.98 | 516.51 | 3.157 | SF |
| 523H - OH - Plan 1 | 1,000.00 | 1,000.00 | 30.02 | 23.29 | 4.462 | CC, ES |
| 523H - OH - Plan 1 | 16,379.26 | 16,196.45 | 294.09 | 116.15 | 1.653 | SF |
| 623H - OH - Plan 1 | 1,471.76 | 1,472.75 | 24.26 | 14.29 | 2.433 | CC |
| 623H - OH - Plan 1 | 8,501.95 | 8,503.08 | 70.83 | 10.56 | 1.175 | Level 2, ES, SF |

| | | | | | | | | | | | | | |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|------------------------|-----------------------|-------------------------------------|-------------------------------------|---------------------------------|----------------------------------|---------------------------|-------------------|
| Offset Design Snapping 12-1 FED - 522H - OH - Plan 1 | | | | | | | | | | | | | |
| Survey Program: 0-MWD | | | | | | | | | | | | | |
| Reference | | | | | | | | | | | | | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Semi Major Axis (usft) | Highside Toolface (°) | Offset Wellbore Centre +N/-S (usft) | Offset Wellbore Centre +E/-W (usft) | Distance Between Centres (usft) | Distance Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor |
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | -90.28 | -0.29 | -59.95 | 59.95 | | | |
| 100.00 | 100.00 | 100.00 | 100.00 | 0.14 | 0.14 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 59.67 | 0.28 | 217.194 |
| 200.00 | 200.00 | 200.00 | 200.00 | 0.50 | 0.50 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 58.96 | 0.99 | 60.375 |
| 300.00 | 300.00 | 300.00 | 300.00 | 0.85 | 0.85 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 58.24 | 1.71 | 35.061 |
| 400.00 | 400.00 | 400.00 | 400.00 | 1.21 | 1.21 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 57.52 | 2.43 | 24.703 |
| 500.00 | 500.00 | 500.00 | 500.00 | 1.57 | 1.57 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 56.81 | 3.14 | 19.070 |
| 600.00 | 600.00 | 600.00 | 600.00 | 1.93 | 1.93 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 56.09 | 3.86 | 15.528 |
| 700.00 | 700.00 | 700.00 | 700.00 | 2.29 | 2.29 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 55.37 | 4.58 | 13.096 |
| 800.00 | 800.00 | 800.00 | 800.00 | 2.65 | 2.65 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 54.66 | 5.29 | 11.323 |
| 900.00 | 900.00 | 900.00 | 900.00 | 3.01 | 3.01 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 53.94 | 6.01 | 9.973 |
| 1,000.00 | 1,000.00 | 1,000.00 | 1,000.00 | 3.36 | 3.36 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 53.22 | 6.73 | 8.910 |
| 1,100.00 | 1,100.00 | 1,100.00 | 1,100.00 | 3.72 | 3.72 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 52.51 | 7.45 | 8.052 |
| 1,200.00 | 1,200.00 | 1,200.00 | 1,200.00 | 4.08 | 4.08 | -90.28 | -90.28 | -0.29 | -59.95 | 59.95 | 51.79 | 8.16 | 7.345 CC, ES |
| 1,300.00 | 1,299.99 | 1,299.99 | 1,299.99 | 4.42 | 4.44 | 138.96 | -90.28 | -0.29 | -59.95 | 60.70 | 51.84 | 8.86 | 6.848 |
| 1,400.00 | 1,399.95 | 1,399.95 | 1,399.95 | 4.76 | 4.80 | 140.74 | -90.28 | -0.29 | -59.95 | 63.01 | 53.45 | 9.55 | 6.594 |
| 1,500.00 | 1,499.82 | 1,499.82 | 1,499.82 | 5.10 | 5.16 | 143.43 | -90.28 | -0.29 | -59.95 | 66.97 | 56.72 | 10.25 | 6.534 |
| 1,600.00 | 1,599.57 | 1,598.52 | 1,598.51 | 5.44 | 5.50 | 146.12 | -90.28 | -0.86 | -60.74 | 73.44 | 62.51 | 10.93 | 6.720 |
| 1,700.00 | 1,699.16 | 1,696.91 | 1,696.86 | 5.79 | 5.82 | 148.10 | -90.28 | -2.56 | -63.11 | 83.14 | 71.54 | 11.60 | 7.170 |
| 1,800.00 | 1,798.62 | 1,794.91 | 1,794.74 | 6.14 | 6.15 | 149.27 | -90.28 | -5.39 | -67.03 | 95.46 | 83.19 | 12.26 | 7.783 |
| 1,900.00 | 1,898.07 | 1,892.59 | 1,892.19 | 6.50 | 6.49 | 149.44 | -90.28 | -9.32 | -72.50 | 109.17 | 96.24 | 12.94 | 8.440 |
| 2,000.00 | 1,997.52 | 1,989.88 | 1,989.09 | 6.87 | 6.82 | 148.93 | -90.28 | -14.35 | -79.48 | 124.22 | 110.62 | 13.61 | 9.129 |

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 522H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: 0.00 usft | |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|-----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|------------------------------|--|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: 0.00 usft | |
| Reference | | Offset | | Semi Major Axis | | Distance | | | | | | | Warning | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Toolface (°) | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | |
| 2,100.00 | 2,096.97 | 2,087.99 | 2,086.67 | 7.23 | 7.17 | 148.08 | -20.28 | -87.73 | 140.33 | 126.03 | 14.29 | 9.817 | | |
| 2,200.00 | 2,196.42 | 2,186.65 | 2,184.79 | 7.60 | 7.52 | 147.37 | -26.31 | -96.10 | 156.53 | 141.54 | 14.99 | 10.441 | | |
| 2,300.00 | 2,295.87 | 2,285.31 | 2,282.91 | 7.98 | 7.88 | 146.80 | -32.34 | -104.48 | 172.75 | 157.05 | 15.69 | 11.007 | | |
| 2,400.00 | 2,395.33 | 2,383.98 | 2,381.04 | 8.35 | 8.23 | 146.33 | -38.37 | -112.85 | 188.98 | 172.58 | 16.40 | 11.522 | | |
| 2,500.00 | 2,494.78 | 2,482.64 | 2,479.16 | 8.73 | 8.60 | 145.93 | -44.40 | -121.23 | 205.23 | 188.12 | 17.11 | 11.993 | | |
| 2,600.00 | 2,594.23 | 2,581.30 | 2,577.28 | 9.11 | 8.96 | 145.58 | -50.42 | -129.60 | 221.48 | 203.66 | 17.83 | 12.425 | | |
| 2,700.00 | 2,693.68 | 2,679.96 | 2,675.40 | 9.49 | 9.33 | 145.29 | -56.45 | -137.98 | 237.74 | 219.20 | 18.54 | 12.821 | | |
| 2,800.00 | 2,793.13 | 2,778.62 | 2,773.52 | 9.87 | 9.69 | 145.03 | -62.48 | -146.35 | 254.01 | 234.75 | 19.26 | 13.187 | | |
| 2,900.00 | 2,892.58 | 2,877.29 | 2,871.64 | 10.25 | 10.06 | 144.81 | -68.51 | -154.73 | 270.28 | 250.29 | 19.98 | 13.525 | | |
| 3,000.00 | 2,992.03 | 2,975.95 | 2,969.76 | 10.64 | 10.44 | 144.61 | -74.54 | -163.10 | 286.55 | 265.84 | 20.71 | 13.838 | | |
| 3,100.00 | 3,091.49 | 3,074.61 | 3,067.88 | 11.02 | 10.81 | 144.43 | -80.57 | -171.48 | 302.83 | 281.39 | 21.43 | 14.129 | | |
| 3,200.00 | 3,190.94 | 3,173.27 | 3,166.01 | 11.41 | 11.18 | 144.27 | -86.59 | -179.85 | 319.11 | 296.95 | 22.16 | 14.400 | | |
| 3,300.00 | 3,290.39 | 3,271.94 | 3,264.13 | 11.79 | 11.56 | 144.12 | -92.62 | -188.23 | 335.39 | 312.50 | 22.89 | 14.653 | | |
| 3,400.00 | 3,389.84 | 3,370.60 | 3,362.25 | 12.18 | 11.94 | 143.99 | -98.65 | -196.60 | 351.67 | 328.05 | 23.62 | 14.889 | | |
| 3,500.00 | 3,489.29 | 3,469.26 | 3,460.37 | 12.57 | 12.31 | 143.87 | -104.68 | -204.98 | 367.96 | 343.61 | 24.35 | 15.111 | | |
| 3,600.00 | 3,588.74 | 3,567.92 | 3,558.49 | 12.96 | 12.69 | 143.76 | -110.71 | -213.35 | 384.24 | 359.16 | 25.08 | 15.319 | | |
| 3,700.00 | 3,688.19 | 3,666.59 | 3,656.61 | 13.35 | 13.07 | 143.66 | -116.74 | -221.73 | 400.53 | 374.71 | 25.82 | 15.515 | | |
| 3,800.00 | 3,787.65 | 3,765.25 | 3,754.73 | 13.74 | 13.45 | 143.57 | -122.76 | -230.10 | 416.82 | 390.27 | 26.55 | 15.699 | | |
| 3,900.00 | 3,887.10 | 3,863.91 | 3,852.85 | 14.13 | 13.83 | 143.48 | -128.79 | -238.48 | 433.11 | 405.82 | 27.29 | 15.873 | | |
| 4,000.00 | 3,986.55 | 3,962.57 | 3,950.97 | 14.52 | 14.21 | 143.40 | -134.82 | -246.85 | 449.40 | 421.38 | 28.02 | 16.037 | | |
| 4,100.00 | 4,086.00 | 4,061.23 | 4,049.10 | 14.91 | 14.59 | 143.33 | -140.85 | -255.23 | 465.69 | 436.93 | 28.76 | 16.193 | | |
| 4,200.00 | 4,185.45 | 4,159.90 | 4,147.22 | 15.30 | 14.98 | 143.26 | -146.88 | -263.60 | 481.98 | 452.49 | 29.50 | 16.340 | | |
| 4,300.00 | 4,284.90 | 4,258.56 | 4,245.34 | 15.69 | 15.36 | 143.19 | -152.91 | -271.98 | 498.28 | 468.04 | 30.23 | 16.480 | | |
| 4,400.00 | 4,384.35 | 4,357.22 | 4,343.46 | 16.08 | 15.74 | 143.13 | -158.93 | -280.35 | 514.57 | 483.60 | 30.97 | 16.613 | | |
| 4,500.00 | 4,483.80 | 4,455.88 | 4,441.58 | 16.47 | 16.13 | 143.08 | -164.96 | -288.73 | 530.86 | 499.15 | 31.71 | 16.740 | | |
| 4,600.00 | 4,583.31 | 4,554.62 | 4,539.77 | 16.86 | 16.51 | 143.07 | -170.99 | -297.11 | 546.71 | 514.26 | 32.45 | 16.847 | | |
| 4,700.00 | 4,682.99 | 4,653.56 | 4,638.18 | 17.24 | 16.90 | 142.96 | -177.04 | -305.51 | 561.03 | 527.85 | 33.19 | 16.905 | | |
| 4,800.00 | 4,782.81 | 4,752.70 | 4,736.77 | 17.61 | 17.28 | 142.74 | -183.10 | -313.92 | 573.78 | 539.86 | 33.92 | 16.916 | | |
| 4,900.00 | 4,882.73 | 4,851.98 | 4,835.50 | 17.97 | 17.67 | 142.39 | -189.16 | -322.35 | 584.96 | 550.31 | 34.65 | 16.883 | | |
| 5,000.00 | 4,982.71 | 4,951.36 | 4,934.34 | 18.32 | 18.06 | 141.93 | -195.24 | -330.79 | 594.60 | 559.23 | 35.37 | 16.811 | | |
| 5,100.00 | 5,082.71 | 5,050.81 | 5,033.24 | 18.64 | 18.45 | -87.26 | -201.31 | -339.23 | 602.95 | 566.87 | 36.08 | 16.713 | | |
| 5,200.00 | 5,182.71 | 5,150.26 | 5,132.15 | 18.97 | 18.84 | -87.87 | -207.39 | -347.67 | 611.18 | 574.41 | 36.78 | 16.618 | | |
| 5,300.00 | 5,282.71 | 5,249.71 | 5,231.05 | 19.30 | 19.22 | -88.47 | -213.47 | -356.11 | 619.49 | 582.01 | 37.48 | 16.528 | | |
| 5,400.00 | 5,382.71 | 5,349.16 | 5,329.96 | 19.62 | 19.61 | -89.04 | -219.54 | -364.55 | 627.86 | 589.68 | 38.18 | 16.443 | | |
| 5,500.00 | 5,482.71 | 5,448.61 | 5,428.87 | 19.95 | 20.00 | -89.60 | -225.62 | -373.00 | 636.29 | 597.41 | 38.89 | 16.363 | | |
| 5,600.00 | 5,582.71 | 5,548.07 | 5,527.77 | 20.28 | 20.39 | -90.15 | -231.70 | -381.44 | 644.78 | 605.20 | 39.59 | 16.287 | | |
| 5,700.00 | 5,682.71 | 5,647.52 | 5,626.68 | 20.61 | 20.78 | -90.68 | -237.77 | -389.88 | 653.33 | 613.04 | 40.29 | 16.214 | | |
| 5,800.00 | 5,782.71 | 5,746.97 | 5,725.58 | 20.94 | 21.17 | -91.20 | -243.85 | -398.32 | 661.94 | 620.94 | 41.00 | 16.146 | | |
| 5,900.00 | 5,882.71 | 5,846.42 | 5,824.49 | 21.27 | 21.56 | -91.71 | -249.92 | -406.76 | 670.59 | 628.89 | 41.70 | 16.081 | | |
| 6,000.00 | 5,982.71 | 5,945.87 | 5,923.40 | 21.61 | 21.95 | -92.20 | -256.00 | -415.21 | 679.30 | 636.89 | 42.41 | 16.019 | | |
| 6,100.00 | 6,082.71 | 6,045.32 | 6,022.30 | 21.94 | 22.34 | -92.68 | -262.08 | -423.65 | 688.06 | 644.94 | 43.11 | 15.960 | | |
| 6,200.00 | 6,182.71 | 6,153.15 | 6,129.59 | 22.28 | 22.76 | -93.17 | -268.37 | -432.39 | 696.48 | 652.60 | 43.88 | 15.873 | | |
| 6,300.00 | 6,282.71 | 6,266.27 | 6,242.35 | 22.61 | 23.19 | -93.56 | -273.60 | -439.65 | 703.17 | 658.50 | 44.67 | 15.742 | | |
| 6,400.00 | 6,382.71 | 6,379.74 | 6,355.64 | 22.95 | 23.61 | -93.84 | -277.34 | -444.85 | 707.95 | 662.51 | 45.44 | 15.579 | | |
| 6,500.00 | 6,482.71 | 6,493.45 | 6,469.28 | 23.28 | 24.02 | -94.00 | -279.57 | -447.95 | 710.81 | 664.61 | 46.20 | 15.386 | | |
| 6,600.00 | 6,582.71 | 6,607.26 | 6,583.09 | 23.62 | 24.40 | -94.05 | -280.29 | -448.95 | 711.73 | 664.80 | 46.93 | 15.167 | | |
| 6,603.60 | 6,586.32 | 6,611.37 | 6,587.19 | 23.63 | 24.41 | -94.05 | -280.29 | -448.95 | 711.73 | 664.77 | 46.95 | 15.159 | | |
| 6,700.00 | 6,682.71 | 6,706.89 | 6,682.71 | 23.96 | 24.72 | -94.05 | -280.29 | -448.95 | 711.73 | 664.13 | 47.60 | 14.953 | | |
| 6,800.00 | 6,782.71 | 6,806.89 | 6,782.71 | 24.30 | 25.05 | -94.05 | -280.29 | -448.95 | 711.73 | 663.46 | 48.27 | 14.745 | | |
| 6,900.00 | 6,882.71 | 6,906.89 | 6,882.71 | 24.64 | 25.37 | -94.05 | -280.29 | -448.95 | 711.73 | 662.78 | 48.94 | 14.542 | | |
| 7,000.00 | 6,982.71 | 7,006.89 | 6,982.71 | 24.98 | 25.70 | -94.05 | -280.29 | -448.95 | 711.73 | 662.11 | 49.62 | 14.344 | | |
| 7,100.00 | 7,082.71 | 7,106.89 | 7,082.71 | 25.32 | 26.02 | -94.05 | -280.29 | -448.95 | 711.73 | 661.43 | 50.30 | 14.150 | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 522H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------------|-----------------------------|-----------------------------|---------------------|------------------|-----------------------------|---|-----------------|------------------------------|-------------------------------|---------------------------------|----------------------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | Highside Toolface (°) | Distance | | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | Warning | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | | | | | | |
| 7,200.00 | 7,182.71 | 7,206.89 | 7,182.71 | 25.66 | 26.35 | -94.05 | -280.29 | -448.95 | 711.73 | 660.75 | 50.98 | 13.962 | | |
| 7,300.00 | 7,282.71 | 7,306.89 | 7,282.71 | 26.00 | 26.68 | -94.05 | -280.29 | -448.95 | 711.73 | 660.07 | 51.65 | 13.779 | | |
| 7,400.00 | 7,382.71 | 7,406.89 | 7,382.71 | 26.34 | 27.01 | -94.05 | -280.29 | -448.95 | 711.73 | 659.39 | 52.33 | 13.600 | | |
| 7,500.00 | 7,482.71 | 7,506.89 | 7,482.71 | 26.68 | 27.34 | -94.05 | -280.29 | -448.95 | 711.73 | 658.71 | 53.02 | 13.425 | | |
| 7,600.00 | 7,582.71 | 7,606.89 | 7,582.71 | 27.02 | 27.67 | -94.05 | -280.29 | -448.95 | 711.73 | 658.03 | 53.70 | 13.254 | | |
| 7,700.00 | 7,682.71 | 7,706.89 | 7,682.71 | 27.37 | 28.00 | -94.05 | -280.29 | -448.95 | 711.73 | 657.35 | 54.38 | 13.088 | | |
| 7,800.00 | 7,782.71 | 7,806.89 | 7,782.71 | 27.71 | 28.33 | -94.05 | -280.29 | -448.95 | 711.73 | 656.66 | 55.06 | 12.925 | | |
| 7,900.00 | 7,882.71 | 7,906.89 | 7,882.71 | 28.05 | 28.66 | -94.05 | -280.29 | -448.95 | 711.73 | 655.98 | 55.75 | 12.767 | | |
| 8,000.00 | 7,982.71 | 8,006.89 | 7,982.71 | 28.40 | 28.99 | -94.05 | -280.29 | -448.95 | 711.73 | 655.29 | 56.43 | 12.612 | | |
| 8,100.00 | 8,082.71 | 8,106.89 | 8,082.71 | 28.74 | 29.33 | -94.05 | -280.29 | -448.95 | 711.73 | 654.61 | 57.12 | 12.460 | | |
| 8,200.00 | 8,182.71 | 8,206.89 | 8,182.71 | 29.09 | 29.66 | -94.05 | -280.29 | -448.95 | 711.73 | 653.92 | 57.81 | 12.312 | | |
| 8,300.00 | 8,282.71 | 8,307.73 | 8,283.55 | 29.43 | 30.00 | -94.05 | -280.22 | -448.95 | 711.72 | 653.23 | 58.50 | 12.167 | | |
| 8,400.00 | 8,382.71 | 8,417.08 | 8,391.73 | 29.78 | 30.34 | -92.90 | -265.94 | -448.95 | 710.92 | 651.73 | 59.19 | 12.012 | | |
| 8,500.00 | 8,482.71 | 8,515.32 | 8,483.89 | 30.12 | 30.59 | -90.20 | -232.43 | -448.95 | 709.96 | 650.14 | 59.82 | 11.869 | | |
| 8,506.14 | 8,488.85 | 8,520.85 | 8,488.85 | 30.14 | 30.60 | -90.00 | -229.99 | -448.95 | 709.95 | 650.10 | 59.85 | 11.862 | | |
| 8,600.00 | 8,582.64 | 8,598.55 | 8,555.24 | 30.46 | 30.75 | -86.74 | -189.78 | -448.95 | 711.49 | 651.15 | 60.34 | 11.791 | | |
| 8,700.00 | 8,680.39 | 8,675.00 | 8,613.36 | 30.78 | 30.86 | -83.22 | -140.24 | -448.95 | 716.27 | 655.61 | 60.66 | 11.808 | | |
| 8,800.00 | 8,771.82 | 8,747.17 | 8,660.31 | 31.04 | 30.93 | -79.91 | -85.52 | -448.95 | 723.31 | 662.57 | 60.74 | 11.909 | | |
| 8,900.00 | 8,852.92 | 8,816.75 | 8,697.28 | 31.24 | 30.97 | -76.90 | -26.66 | -448.95 | 731.49 | 670.87 | 60.62 | 12.068 | | |
| 9,000.00 | 8,920.15 | 8,884.34 | 8,724.65 | 31.38 | 30.98 | -74.32 | 35.09 | -448.95 | 739.75 | 679.35 | 60.40 | 12.248 | | |
| 9,100.00 | 8,970.57 | 8,950.00 | 8,742.63 | 31.49 | 30.97 | -72.25 | 98.19 | -448.96 | 747.15 | 686.95 | 60.20 | 12.410 | | |
| 9,200.00 | 9,001.97 | 9,015.76 | 8,751.79 | 31.65 | 31.00 | -70.73 | 163.25 | -448.96 | 752.95 | 692.79 | 60.16 | 12.516 | | |
| 9,300.00 | 9,012.99 | 9,097.17 | 8,753.00 | 31.90 | 31.23 | -69.89 | 244.63 | -448.96 | 756.05 | 695.65 | 60.40 | 12.517 | | |
| 9,400.00 | 9,013.00 | 9,197.17 | 8,753.00 | 32.20 | 31.58 | -69.89 | 344.63 | -448.96 | 756.05 | 695.07 | 60.99 | 12.397 | | |
| 9,500.00 | 9,013.00 | 9,297.17 | 8,753.00 | 32.59 | 32.01 | -69.89 | 444.63 | -448.96 | 756.05 | 694.32 | 61.73 | 12.248 | | |
| 9,600.00 | 9,013.00 | 9,397.17 | 8,753.00 | 33.05 | 32.50 | -69.89 | 544.63 | -448.96 | 756.05 | 693.43 | 62.62 | 12.074 | | |
| 9,700.00 | 9,013.00 | 9,497.17 | 8,753.00 | 33.58 | 33.07 | -69.89 | 644.63 | -448.96 | 756.05 | 692.40 | 63.65 | 11.878 | | |
| 9,800.00 | 9,013.00 | 9,597.17 | 8,753.00 | 34.19 | 33.70 | -69.89 | 744.63 | -448.96 | 756.05 | 691.23 | 64.82 | 11.663 | | |
| 9,900.00 | 9,013.00 | 9,697.17 | 8,753.00 | 34.85 | 34.40 | -69.89 | 844.63 | -448.97 | 756.05 | 689.93 | 66.12 | 11.434 | | |
| 10,000.00 | 9,013.00 | 9,797.17 | 8,753.00 | 35.59 | 35.17 | -69.89 | 944.63 | -448.97 | 756.05 | 688.51 | 67.54 | 11.194 | | |
| 10,100.00 | 9,013.00 | 9,897.17 | 8,753.00 | 36.38 | 35.99 | -69.89 | 1,044.63 | -448.97 | 756.04 | 686.97 | 69.07 | 10.945 | | |
| 10,200.00 | 9,013.00 | 9,997.17 | 8,753.00 | 37.23 | 36.86 | -69.89 | 1,144.63 | -448.97 | 756.04 | 685.33 | 70.71 | 10.691 | | |
| 10,300.00 | 9,013.00 | 10,097.17 | 8,753.00 | 38.12 | 37.79 | -69.89 | 1,244.63 | -448.97 | 756.04 | 683.59 | 72.45 | 10.435 | | |
| 10,400.00 | 9,013.00 | 10,197.17 | 8,753.00 | 39.07 | 38.76 | -69.89 | 1,344.63 | -448.97 | 756.04 | 681.75 | 74.29 | 10.177 | | |
| 10,500.00 | 9,013.00 | 10,297.17 | 8,753.00 | 40.07 | 39.77 | -69.89 | 1,444.63 | -448.97 | 756.04 | 679.83 | 76.20 | 9.921 | | |
| 10,600.00 | 9,013.00 | 10,397.17 | 8,753.00 | 41.10 | 40.83 | -69.89 | 1,544.63 | -448.98 | 756.04 | 677.84 | 78.20 | 9.668 | | |
| 10,700.00 | 9,013.00 | 10,497.17 | 8,753.00 | 42.17 | 41.93 | -69.89 | 1,644.63 | -448.98 | 756.04 | 675.76 | 80.27 | 9.418 | | |
| 10,800.00 | 9,013.00 | 10,597.17 | 8,753.00 | 43.29 | 43.06 | -69.89 | 1,744.63 | -448.98 | 756.04 | 673.62 | 82.41 | 9.174 | | |
| 10,900.00 | 9,013.00 | 10,697.17 | 8,753.00 | 44.43 | 44.22 | -69.89 | 1,844.63 | -448.98 | 756.03 | 671.42 | 84.61 | 8.935 | | |
| 11,000.00 | 9,013.00 | 10,797.17 | 8,753.00 | 45.60 | 45.41 | -69.89 | 1,944.63 | -448.98 | 756.03 | 669.16 | 86.87 | 8.703 | | |
| 11,100.00 | 9,013.00 | 10,897.17 | 8,753.00 | 46.81 | 46.63 | -69.89 | 2,044.63 | -448.98 | 756.03 | 666.85 | 89.19 | 8.477 | | |
| 11,200.00 | 9,013.00 | 10,997.17 | 8,753.00 | 48.04 | 47.88 | -69.89 | 2,144.63 | -448.99 | 756.03 | 664.48 | 91.55 | 8.258 | | |
| 11,300.00 | 9,013.00 | 11,097.17 | 8,753.00 | 49.29 | 49.15 | -69.89 | 2,244.63 | -448.99 | 756.03 | 662.07 | 93.96 | 8.047 | | |
| 11,400.00 | 9,013.00 | 11,197.17 | 8,753.00 | 50.57 | 50.44 | -69.89 | 2,344.63 | -448.99 | 756.03 | 659.62 | 96.41 | 7.842 | | |
| 11,500.00 | 9,013.00 | 11,297.17 | 8,753.00 | 51.86 | 51.75 | -69.89 | 2,444.63 | -448.99 | 756.03 | 657.13 | 98.90 | 7.644 | | |
| 11,600.00 | 9,013.00 | 11,397.17 | 8,753.00 | 53.18 | 53.08 | -69.89 | 2,544.63 | -448.99 | 756.02 | 654.60 | 101.42 | 7.454 | | |
| 11,700.00 | 9,013.00 | 11,497.17 | 8,753.00 | 54.52 | 54.43 | -69.89 | 2,644.63 | -448.99 | 756.02 | 652.04 | 103.98 | 7.271 | | |
| 11,800.00 | 9,013.00 | 11,597.17 | 8,753.00 | 55.87 | 55.80 | -69.88 | 2,744.63 | -448.99 | 756.02 | 649.45 | 106.58 | 7.094 | | |
| 11,900.00 | 9,013.00 | 11,697.17 | 8,753.00 | 57.24 | 57.17 | -69.88 | 2,844.63 | -449.00 | 756.02 | 646.82 | 109.20 | 6.923 | | |
| 12,000.00 | 9,013.00 | 11,797.17 | 8,753.00 | 58.62 | 58.57 | -69.88 | 2,944.63 | -449.00 | 756.02 | 644.17 | 111.84 | 6.760 | | |
| 12,100.00 | 9,013.00 | 11,897.17 | 8,753.00 | 60.01 | 59.97 | -69.88 | 3,044.63 | -449.00 | 756.02 | 641.50 | 114.52 | 6.602 | | |
| 12,200.00 | 9,013.00 | 11,997.17 | 8,753.00 | 61.42 | 61.39 | -69.88 | 3,144.63 | -449.00 | 756.02 | 638.80 | 117.21 | 6.450 | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 522H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: 0.00 usft | |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|-----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|------------------------------|--|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: 0.00 usft | |
| Reference | | Offset | | Semi Major Axis | | | Distance | | | | | | Warning | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Toolface (°) | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | |
| 12,300.00 | 9,013.00 | 12,097.17 | 8,753.00 | 62.84 | 62.82 | -69.88 | 3,244.63 | -449.00 | 756.01 | 636.08 | 119.93 | 6.304 | | |
| 12,400.00 | 9,013.00 | 12,197.17 | 8,753.00 | 64.27 | 64.26 | -69.88 | 3,344.63 | -449.00 | 756.01 | 633.34 | 122.67 | 6.163 | | |
| 12,500.00 | 9,013.00 | 12,297.17 | 8,753.00 | 65.71 | 65.71 | -69.88 | 3,444.63 | -449.00 | 756.01 | 630.59 | 125.43 | 6.028 | | |
| 12,600.00 | 9,013.00 | 12,397.17 | 8,753.00 | 67.16 | 67.17 | -69.88 | 3,544.63 | -449.01 | 756.01 | 627.81 | 128.20 | 5.897 | | |
| 12,700.00 | 9,013.00 | 12,497.17 | 8,753.00 | 68.62 | 68.64 | -69.88 | 3,644.63 | -449.01 | 756.01 | 625.02 | 130.99 | 5.771 | | |
| 12,800.00 | 9,013.00 | 12,597.17 | 8,753.00 | 70.09 | 70.11 | -69.88 | 3,744.63 | -449.01 | 756.01 | 622.21 | 133.80 | 5.650 | | |
| 12,900.00 | 9,013.00 | 12,697.17 | 8,753.00 | 71.57 | 71.60 | -69.88 | 3,844.63 | -449.01 | 756.01 | 619.38 | 136.62 | 5.534 | | |
| 13,000.00 | 9,013.00 | 12,797.17 | 8,753.00 | 73.05 | 73.09 | -69.88 | 3,944.63 | -449.01 | 756.00 | 616.55 | 139.46 | 5.421 | | |
| 13,100.00 | 9,013.00 | 12,897.17 | 8,753.00 | 74.54 | 74.58 | -69.88 | 4,044.63 | -449.01 | 756.00 | 613.70 | 142.31 | 5.312 | | |
| 13,200.00 | 9,013.00 | 12,997.17 | 8,753.00 | 76.04 | 76.09 | -69.88 | 4,144.63 | -449.01 | 756.00 | 610.83 | 145.17 | 5.208 | | |
| 13,300.00 | 9,013.00 | 13,097.17 | 8,753.00 | 77.54 | 77.60 | -69.88 | 4,244.63 | -449.02 | 756.00 | 607.96 | 148.04 | 5.107 | | |
| 13,400.00 | 9,013.00 | 13,197.17 | 8,753.00 | 79.05 | 79.11 | -69.88 | 4,344.63 | -449.02 | 756.00 | 605.08 | 150.92 | 5.009 | | |
| 13,500.00 | 9,013.00 | 13,297.17 | 8,753.00 | 80.56 | 80.63 | -69.88 | 4,444.63 | -449.02 | 756.00 | 602.18 | 153.82 | 4.915 | | |
| 13,600.00 | 9,013.00 | 13,397.17 | 8,753.00 | 82.08 | 82.16 | -69.88 | 4,544.63 | -449.02 | 756.00 | 599.28 | 156.72 | 4.824 | | |
| 13,700.00 | 9,013.00 | 13,497.17 | 8,753.00 | 83.61 | 83.69 | -69.88 | 4,644.63 | -449.02 | 756.00 | 596.36 | 159.63 | 4.736 | | |
| 13,800.00 | 9,013.00 | 13,597.17 | 8,753.00 | 85.14 | 85.22 | -69.88 | 4,744.63 | -449.02 | 755.99 | 593.44 | 162.55 | 4.651 | | |
| 13,900.00 | 9,013.00 | 13,697.17 | 8,753.00 | 86.67 | 86.76 | -69.88 | 4,844.63 | -449.02 | 755.99 | 590.51 | 165.48 | 4.568 | | |
| 14,000.00 | 9,013.00 | 13,797.17 | 8,753.00 | 88.21 | 88.30 | -69.88 | 4,944.63 | -449.03 | 755.99 | 587.57 | 168.42 | 4.489 | | |
| 14,100.00 | 9,013.00 | 13,897.17 | 8,753.00 | 89.75 | 89.85 | -69.88 | 5,044.63 | -449.03 | 755.99 | 584.63 | 171.36 | 4.412 | | |
| 14,200.00 | 9,013.00 | 13,997.17 | 8,753.00 | 91.30 | 91.40 | -69.88 | 5,144.63 | -449.03 | 755.99 | 581.67 | 174.32 | 4.337 | | |
| 14,300.00 | 9,013.00 | 14,097.17 | 8,753.00 | 92.85 | 92.95 | -69.88 | 5,244.63 | -449.03 | 755.99 | 578.71 | 177.27 | 4.265 | | |
| 14,400.00 | 9,013.00 | 14,197.17 | 8,753.00 | 94.40 | 94.51 | -69.88 | 5,344.63 | -449.03 | 755.99 | 575.75 | 180.24 | 4.194 | | |
| 14,500.00 | 9,013.00 | 14,297.17 | 8,753.00 | 95.95 | 96.07 | -69.88 | 5,444.63 | -449.03 | 755.98 | 572.78 | 183.21 | 4.126 | | |
| 14,600.00 | 9,013.00 | 14,397.17 | 8,753.00 | 97.51 | 97.63 | -69.88 | 5,544.63 | -449.03 | 755.98 | 569.80 | 186.18 | 4.060 | | |
| 14,700.00 | 9,013.00 | 14,497.17 | 8,753.00 | 99.07 | 99.19 | -69.88 | 5,644.63 | -449.04 | 755.98 | 566.82 | 189.16 | 3.996 | | |
| 14,800.00 | 9,013.00 | 14,597.17 | 8,753.00 | 100.64 | 100.76 | -69.88 | 5,744.63 | -449.04 | 755.98 | 563.83 | 192.15 | 3.934 | | |
| 14,900.00 | 9,013.00 | 14,697.17 | 8,753.00 | 102.21 | 102.33 | -69.88 | 5,844.63 | -449.04 | 755.98 | 560.84 | 195.14 | 3.874 | | |
| 15,000.00 | 9,013.00 | 14,797.17 | 8,753.00 | 103.78 | 103.91 | -69.88 | 5,944.63 | -449.04 | 755.98 | 557.84 | 198.14 | 3.815 | | |
| 15,100.00 | 9,013.00 | 14,897.17 | 8,753.00 | 105.35 | 105.48 | -69.88 | 6,044.63 | -449.04 | 755.98 | 554.84 | 201.14 | 3.758 | | |
| 15,200.00 | 9,013.00 | 14,997.17 | 8,753.00 | 106.92 | 107.06 | -69.88 | 6,144.63 | -449.04 | 755.97 | 551.83 | 204.14 | 3.703 | | |
| 15,300.00 | 9,013.00 | 15,097.17 | 8,753.00 | 108.50 | 108.64 | -69.88 | 6,244.63 | -449.04 | 755.97 | 548.82 | 207.15 | 3.649 | | |
| 15,400.00 | 9,013.00 | 15,197.17 | 8,753.00 | 110.08 | 110.22 | -69.88 | 6,344.63 | -449.05 | 755.97 | 545.81 | 210.17 | 3.597 | | |
| 15,500.00 | 9,013.00 | 15,297.17 | 8,753.00 | 111.66 | 111.80 | -69.88 | 6,444.63 | -449.05 | 755.97 | 542.79 | 213.18 | 3.546 | | |
| 15,600.00 | 9,013.00 | 15,397.17 | 8,753.00 | 113.24 | 113.39 | -69.88 | 6,544.63 | -449.05 | 755.97 | 539.77 | 216.20 | 3.497 | | |
| 15,700.00 | 9,013.00 | 15,497.17 | 8,753.00 | 114.83 | 114.98 | -69.88 | 6,644.63 | -449.05 | 755.97 | 536.74 | 219.23 | 3.448 | | |
| 15,800.00 | 9,013.00 | 15,597.17 | 8,753.00 | 116.41 | 116.57 | -69.88 | 6,744.63 | -449.05 | 755.97 | 533.71 | 222.25 | 3.401 | | |
| 15,900.00 | 9,013.00 | 15,697.17 | 8,753.00 | 118.00 | 118.16 | -69.88 | 6,844.63 | -449.05 | 755.96 | 530.68 | 225.29 | 3.356 | | |
| 16,000.00 | 9,013.00 | 15,797.17 | 8,753.00 | 119.59 | 119.75 | -69.88 | 6,944.63 | -449.05 | 755.96 | 527.64 | 228.32 | 3.311 | | |
| 16,100.00 | 9,013.00 | 15,897.17 | 8,753.00 | 121.18 | 121.34 | -69.88 | 7,044.63 | -449.06 | 755.96 | 524.61 | 231.36 | 3.268 | | |
| 16,200.00 | 9,013.00 | 15,997.17 | 8,753.00 | 122.78 | 122.94 | -69.88 | 7,144.63 | -449.06 | 755.96 | 521.57 | 234.39 | 3.225 | | |
| 16,300.00 | 9,013.00 | 16,097.17 | 8,753.00 | 124.37 | 124.54 | -69.88 | 7,244.63 | -449.06 | 755.96 | 518.52 | 237.44 | 3.184 | | |
| 16,370.47 | 9,013.00 | 16,167.64 | 8,753.00 | 125.37 | 125.54 | -69.88 | 7,315.11 | -449.06 | 755.96 | 516.64 | 239.32 | 3.159 | | |
| 16,379.26 | 9,013.00 | 16,170.10 | 8,753.00 | 125.49 | 125.58 | -69.88 | 7,317.56 | -449.06 | 755.98 | 516.51 | 239.47 | 3.157 SF | | |

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 523H - OH - Plan 1 | | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------------|-----------------------------|-----------------------------|---------------------|------------------|-----------------------------|---|-----------------|------------------------------|-------------------------------|---------------------------------|----------------------|---------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | Highside Toolface (°) | Distance | | | | | | Warning | | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | | |
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 89.60 | 0.21 | 30.02 | 30.02 | | | | | | |
| 100.00 | 100.00 | 100.00 | 100.00 | 0.14 | 0.14 | 89.60 | 0.21 | 30.02 | 30.02 | 29.74 | 0.28 | 108.762 | | | |
| 200.00 | 200.00 | 200.00 | 200.00 | 0.50 | 0.50 | 89.60 | 0.21 | 30.02 | 30.02 | 29.03 | 0.99 | 30.233 | | | |
| 300.00 | 300.00 | 300.00 | 300.00 | 0.85 | 0.85 | 89.60 | 0.21 | 30.02 | 30.02 | 28.31 | 1.71 | 17.557 | | | |
| 400.00 | 400.00 | 400.00 | 400.00 | 1.21 | 1.21 | 89.60 | 0.21 | 30.02 | 30.02 | 27.59 | 2.43 | 12.370 | | | |
| 500.00 | 500.00 | 500.00 | 500.00 | 1.57 | 1.57 | 89.60 | 0.21 | 30.02 | 30.02 | 26.88 | 3.14 | 9.549 | | | |
| 600.00 | 600.00 | 600.00 | 600.00 | 1.93 | 1.93 | 89.60 | 0.21 | 30.02 | 30.02 | 26.16 | 3.86 | 7.776 | | | |
| 700.00 | 700.00 | 700.00 | 700.00 | 2.29 | 2.29 | 89.60 | 0.21 | 30.02 | 30.02 | 25.44 | 4.58 | 6.558 | | | |
| 800.00 | 800.00 | 800.00 | 800.00 | 2.65 | 2.65 | 89.60 | 0.21 | 30.02 | 30.02 | 24.73 | 5.29 | 5.670 | | | |
| 900.00 | 900.00 | 900.00 | 900.00 | 3.01 | 3.01 | 89.60 | 0.21 | 30.02 | 30.02 | 24.01 | 6.01 | 4.994 | | | |
| 1,000.00 | 1,000.00 | 1,000.00 | 1,000.00 | 3.36 | 3.36 | 89.60 | 0.21 | 30.02 | 30.02 | 23.29 | 6.73 | 4.462 CC, ES | | | |
| 1,100.00 | 1,100.00 | 1,099.50 | 1,099.49 | 3.72 | 3.71 | 90.67 | -0.36 | 30.83 | 30.84 | 23.41 | 7.43 | 4.151 | | | |
| 1,200.00 | 1,200.00 | 1,198.92 | 1,198.86 | 4.08 | 4.04 | 93.55 | -2.06 | 33.28 | 33.36 | 25.24 | 8.12 | 4.109 | | | |
| 1,300.00 | 1,299.99 | 1,298.23 | 1,298.05 | 4.42 | 4.38 | -34.75 | -4.90 | 37.34 | 36.88 | 28.09 | 8.79 | 4.195 | | | |
| 1,400.00 | 1,399.95 | 1,397.46 | 1,397.04 | 4.76 | 4.72 | -32.50 | -8.86 | 43.01 | 40.58 | 31.13 | 9.45 | 4.293 | | | |
| 1,500.00 | 1,499.82 | 1,496.62 | 1,495.79 | 5.10 | 5.07 | -30.88 | -13.95 | 50.30 | 44.43 | 34.31 | 10.12 | 4.390 | | | |
| 1,600.00 | 1,599.57 | 1,596.35 | 1,594.98 | 5.44 | 5.43 | -30.03 | -19.88 | 58.79 | 47.88 | 37.08 | 10.80 | 4.433 | | | |
| 1,700.00 | 1,699.16 | 1,696.33 | 1,694.42 | 5.79 | 5.79 | -30.40 | -25.86 | 67.36 | 49.66 | 38.17 | 11.50 | 4.320 | | | |
| 1,800.00 | 1,798.62 | 1,796.32 | 1,793.86 | 6.14 | 6.16 | -31.57 | -31.85 | 75.93 | 50.25 | 38.05 | 12.20 | 4.119 | | | |
| 1,900.00 | 1,898.07 | 1,896.31 | 1,893.31 | 6.50 | 6.53 | -32.74 | -37.83 | 84.50 | 50.81 | 37.91 | 12.91 | 3.936 | | | |
| 2,000.00 | 1,997.52 | 1,996.31 | 1,992.75 | 6.87 | 6.91 | -33.89 | -43.82 | 93.07 | 51.40 | 37.78 | 13.62 | 3.773 | | | |
| 2,100.00 | 2,096.97 | 2,096.30 | 2,092.20 | 7.23 | 7.28 | -35.01 | -49.80 | 101.65 | 52.01 | 37.66 | 14.34 | 3.626 | | | |
| 2,200.00 | 2,196.42 | 2,196.29 | 2,191.64 | 7.60 | 7.66 | -36.11 | -55.79 | 110.22 | 52.63 | 37.56 | 15.07 | 3.493 | | | |
| 2,300.00 | 2,295.87 | 2,296.29 | 2,291.09 | 7.98 | 8.04 | -37.18 | -61.77 | 118.79 | 53.27 | 37.48 | 15.80 | 3.372 | | | |
| 2,400.00 | 2,395.33 | 2,396.28 | 2,390.53 | 8.35 | 8.43 | -38.22 | -67.76 | 127.36 | 53.94 | 37.40 | 16.53 | 3.263 | | | |
| 2,500.00 | 2,494.78 | 2,496.27 | 2,489.98 | 8.73 | 8.81 | -39.23 | -73.74 | 135.93 | 54.62 | 37.35 | 17.27 | 3.163 | | | |
| 2,600.00 | 2,594.23 | 2,596.26 | 2,589.42 | 9.11 | 9.19 | -40.23 | -79.73 | 144.50 | 55.31 | 37.30 | 18.01 | 3.071 | | | |
| 2,700.00 | 2,693.68 | 2,696.26 | 2,688.87 | 9.49 | 9.58 | -41.19 | -85.71 | 153.07 | 56.03 | 37.27 | 18.76 | 2.987 | | | |
| 2,800.00 | 2,793.13 | 2,796.25 | 2,788.31 | 9.87 | 9.97 | -42.13 | -91.70 | 161.64 | 56.75 | 37.25 | 19.50 | 2.910 | | | |
| 2,900.00 | 2,892.58 | 2,896.24 | 2,887.76 | 10.25 | 10.35 | -43.05 | -97.68 | 170.21 | 57.50 | 37.24 | 20.25 | 2.839 | | | |
| 3,000.00 | 2,992.03 | 2,996.24 | 2,987.20 | 10.64 | 10.74 | -43.95 | -103.66 | 178.78 | 58.25 | 37.25 | 21.01 | 2.773 | | | |
| 3,100.00 | 3,091.49 | 3,096.23 | 3,086.65 | 11.02 | 11.13 | -44.82 | -109.65 | 187.35 | 59.03 | 37.26 | 21.76 | 2.712 | | | |
| 3,200.00 | 3,190.94 | 3,196.22 | 3,186.09 | 11.41 | 11.52 | -45.67 | -115.63 | 195.92 | 59.81 | 37.29 | 22.52 | 2.656 | | | |
| 3,300.00 | 3,290.39 | 3,296.22 | 3,285.54 | 11.79 | 11.91 | -46.49 | -121.62 | 204.50 | 60.61 | 37.33 | 23.28 | 2.603 | | | |
| 3,400.00 | 3,389.84 | 3,396.21 | 3,384.98 | 12.18 | 12.30 | -47.30 | -127.60 | 213.07 | 61.42 | 37.37 | 24.04 | 2.554 | | | |
| 3,500.00 | 3,489.29 | 3,496.20 | 3,484.43 | 12.57 | 12.69 | -48.08 | -133.59 | 221.64 | 62.24 | 37.43 | 24.81 | 2.509 | | | |
| 3,600.00 | 3,588.74 | 3,596.19 | 3,583.87 | 12.96 | 13.08 | -48.84 | -139.57 | 230.21 | 63.07 | 37.49 | 25.58 | 2.466 | | | |
| 3,700.00 | 3,688.19 | 3,696.19 | 3,683.32 | 13.35 | 13.47 | -49.59 | -145.56 | 238.78 | 63.91 | 37.57 | 26.34 | 2.426 | | | |
| 3,800.00 | 3,787.65 | 3,796.18 | 3,782.77 | 13.74 | 13.86 | -50.31 | -151.54 | 247.35 | 64.77 | 37.65 | 27.11 | 2.389 | | | |
| 3,900.00 | 3,887.10 | 3,896.17 | 3,882.21 | 14.13 | 14.25 | -51.02 | -157.53 | 255.92 | 65.63 | 37.75 | 27.89 | 2.354 | | | |
| 4,000.00 | 3,986.55 | 3,996.17 | 3,981.66 | 14.52 | 14.64 | -51.70 | -163.51 | 264.49 | 66.51 | 37.85 | 28.66 | 2.321 | | | |
| 4,100.00 | 4,086.00 | 4,096.16 | 4,081.10 | 14.91 | 15.04 | -52.37 | -169.49 | 273.06 | 67.39 | 37.95 | 29.43 | 2.289 | | | |
| 4,200.00 | 4,185.45 | 4,196.15 | 4,180.55 | 15.30 | 15.43 | -53.02 | -175.48 | 281.63 | 68.28 | 38.07 | 30.21 | 2.260 | | | |
| 4,300.00 | 4,284.90 | 4,296.15 | 4,279.99 | 15.69 | 15.82 | -53.66 | -181.46 | 290.20 | 69.18 | 38.19 | 30.99 | 2.233 | | | |
| 4,400.00 | 4,384.35 | 4,396.14 | 4,379.44 | 16.08 | 16.21 | -54.27 | -187.45 | 298.77 | 70.09 | 38.33 | 31.77 | 2.206 | | | |
| 4,500.00 | 4,483.80 | 4,496.13 | 4,478.88 | 16.47 | 16.61 | -54.88 | -193.43 | 307.34 | 71.01 | 38.46 | 32.55 | 2.182 | | | |
| 4,600.00 | 4,583.31 | 4,596.12 | 4,578.32 | 16.86 | 17.00 | -55.10 | -199.42 | 315.92 | 72.25 | 38.94 | 33.31 | 2.169 | | | |
| 4,700.00 | 4,682.99 | 4,696.08 | 4,677.74 | 17.24 | 17.39 | -54.11 | -205.40 | 324.48 | 74.62 | 40.58 | 34.04 | 2.192 | | | |
| 4,800.00 | 4,782.81 | 4,795.98 | 4,777.08 | 17.61 | 17.79 | -52.02 | -211.38 | 333.05 | 76.23 | 43.50 | 34.73 | 2.252 | | | |
| 4,900.00 | 4,882.73 | 4,895.76 | 4,876.32 | 17.97 | 18.18 | -49.06 | -217.35 | 341.60 | 83.24 | 47.85 | 35.39 | 2.352 | | | |
| 5,000.00 | 4,982.71 | 4,995.40 | 4,975.41 | 18.32 | 18.57 | -45.54 | -223.31 | 350.14 | 89.84 | 53.83 | 36.01 | 2.495 | | | |
| 5,100.00 | 5,082.71 | 5,094.87 | 5,074.34 | 18.64 | 18.96 | 89.57 | -229.27 | 358.66 | 98.03 | 61.42 | 36.61 | 2.678 | | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 523H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|-----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | | Distance | | | | | | | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Toolface (°) | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | Warning | |
| 5,200.00 | 5,182.71 | 5,194.32 | 5,173.25 | 18.97 | 19.35 | 92.81 | -235.22 | 367.19 | 106.74 | 69.52 | 37.22 | 2.868 | | |
| 5,300.00 | 5,282.71 | 5,293.77 | 5,272.15 | 19.30 | 19.75 | 95.56 | -241.17 | 375.71 | 115.74 | 77.90 | 37.84 | 3.059 | | |
| 5,400.00 | 5,382.71 | 5,393.23 | 5,371.06 | 19.62 | 20.14 | 97.91 | -247.12 | 384.24 | 124.97 | 86.49 | 38.48 | 3.248 | | |
| 5,500.00 | 5,482.71 | 5,492.68 | 5,469.97 | 19.95 | 20.53 | 99.93 | -253.08 | 392.76 | 134.37 | 95.25 | 39.13 | 3.434 | | |
| 5,600.00 | 5,582.71 | 5,592.13 | 5,568.87 | 20.28 | 20.92 | 101.69 | -259.03 | 401.29 | 143.93 | 104.14 | 39.78 | 3.618 | | |
| 5,700.00 | 5,682.71 | 5,691.99 | 5,668.19 | 20.61 | 21.32 | 103.23 | -264.99 | 409.83 | 153.58 | 113.13 | 40.45 | 3.797 | | |
| 5,800.00 | 5,782.71 | 5,794.61 | 5,770.37 | 20.94 | 21.71 | 104.46 | -270.37 | 417.53 | 162.12 | 120.97 | 41.15 | 3.940 | | |
| 5,900.00 | 5,882.71 | 5,897.57 | 5,873.07 | 21.27 | 22.10 | 105.33 | -274.55 | 423.51 | 168.78 | 126.94 | 41.84 | 4.034 | | |
| 6,000.00 | 5,982.71 | 6,000.79 | 5,976.16 | 21.61 | 22.48 | 105.90 | -277.52 | 427.77 | 173.53 | 131.00 | 42.52 | 4.081 | | |
| 6,100.00 | 6,082.71 | 6,104.18 | 6,079.51 | 21.94 | 22.84 | 106.23 | -279.27 | 430.27 | 176.32 | 133.13 | 43.20 | 4.082 | | |
| 6,200.00 | 6,182.71 | 6,207.39 | 6,182.71 | 22.28 | 23.18 | 106.32 | -279.79 | 431.02 | 177.16 | 133.31 | 43.85 | 4.040 | | |
| 6,300.00 | 6,282.71 | 6,307.39 | 6,282.71 | 22.61 | 23.50 | 106.32 | -279.79 | 431.02 | 177.16 | 132.64 | 44.52 | 3.979 | | |
| 6,400.00 | 6,382.71 | 6,407.39 | 6,382.71 | 22.95 | 23.82 | 106.32 | -279.79 | 431.02 | 177.16 | 131.96 | 45.20 | 3.920 | | |
| 6,500.00 | 6,482.71 | 6,507.39 | 6,482.71 | 23.28 | 24.14 | 106.32 | -279.79 | 431.02 | 177.16 | 131.29 | 45.87 | 3.862 | | |
| 6,600.00 | 6,582.71 | 6,607.39 | 6,582.71 | 23.62 | 24.46 | 106.32 | -279.79 | 431.02 | 177.16 | 130.61 | 46.55 | 3.806 | | |
| 6,700.00 | 6,682.71 | 6,707.39 | 6,682.71 | 23.96 | 24.78 | 106.32 | -279.79 | 431.02 | 177.16 | 129.94 | 47.22 | 3.751 | | |
| 6,800.00 | 6,782.71 | 6,807.39 | 6,782.71 | 24.30 | 25.10 | 106.32 | -279.79 | 431.02 | 177.16 | 129.26 | 47.90 | 3.698 | | |
| 6,900.00 | 6,882.71 | 6,907.39 | 6,882.71 | 24.64 | 25.43 | 106.32 | -279.79 | 431.02 | 177.16 | 128.58 | 48.58 | 3.647 | | |
| 7,000.00 | 6,982.71 | 7,007.39 | 6,982.71 | 24.98 | 25.75 | 106.32 | -279.79 | 431.02 | 177.16 | 127.90 | 49.26 | 3.596 | | |
| 7,100.00 | 7,082.71 | 7,107.39 | 7,082.71 | 25.32 | 26.08 | 106.32 | -279.79 | 431.02 | 177.16 | 127.22 | 49.94 | 3.547 | | |
| 7,200.00 | 7,182.71 | 7,207.39 | 7,182.71 | 25.66 | 26.41 | 106.32 | -279.79 | 431.02 | 177.16 | 126.53 | 50.63 | 3.499 | | |
| 7,300.00 | 7,282.71 | 7,307.39 | 7,282.71 | 26.00 | 26.73 | 106.32 | -279.79 | 431.02 | 177.16 | 125.85 | 51.31 | 3.453 | | |
| 7,400.00 | 7,382.71 | 7,407.39 | 7,382.71 | 26.34 | 27.06 | 106.32 | -279.79 | 431.02 | 177.16 | 125.17 | 51.99 | 3.407 | | |
| 7,500.00 | 7,482.71 | 7,507.39 | 7,482.71 | 26.68 | 27.39 | 106.32 | -279.79 | 431.02 | 177.16 | 124.48 | 52.68 | 3.363 | | |
| 7,600.00 | 7,582.71 | 7,607.39 | 7,582.71 | 27.02 | 27.72 | 106.32 | -279.79 | 431.02 | 177.16 | 123.79 | 53.37 | 3.320 | | |
| 7,700.00 | 7,682.71 | 7,707.39 | 7,682.71 | 27.37 | 28.05 | 106.32 | -279.79 | 431.02 | 177.16 | 123.11 | 54.05 | 3.278 | | |
| 7,800.00 | 7,782.71 | 7,807.39 | 7,782.71 | 27.71 | 28.38 | 106.32 | -279.79 | 431.02 | 177.16 | 122.42 | 54.74 | 3.236 | | |
| 7,900.00 | 7,882.71 | 7,907.39 | 7,882.71 | 28.05 | 28.72 | 106.32 | -279.79 | 431.02 | 177.16 | 121.73 | 55.43 | 3.196 | | |
| 8,000.00 | 7,982.71 | 8,007.39 | 7,982.71 | 28.40 | 29.05 | 106.32 | -279.79 | 431.02 | 177.16 | 121.04 | 56.12 | 3.157 | | |
| 8,100.00 | 8,082.71 | 8,107.39 | 8,082.71 | 28.74 | 29.38 | 106.32 | -279.79 | 431.02 | 177.16 | 120.35 | 56.81 | 3.119 | | |
| 8,200.00 | 8,182.71 | 8,207.39 | 8,182.71 | 29.09 | 29.72 | 106.32 | -279.79 | 431.02 | 177.16 | 119.66 | 57.50 | 3.081 | | |
| 8,300.00 | 8,282.71 | 8,307.39 | 8,282.71 | 29.43 | 30.05 | 106.32 | -279.79 | 431.02 | 177.16 | 118.97 | 58.19 | 3.045 | | |
| 8,400.00 | 8,382.71 | 8,416.23 | 8,390.90 | 29.78 | 30.40 | 103.29 | -270.17 | 431.02 | 174.89 | 116.09 | 58.80 | 2.974 | | |
| 8,500.00 | 8,482.71 | 8,517.19 | 8,486.97 | 30.12 | 30.66 | 93.28 | -239.73 | 431.02 | 170.35 | 110.62 | 59.73 | 2.852 | | |
| 8,525.79 | 8,508.50 | 8,540.96 | 8,508.50 | 30.21 | 30.72 | 90.00 | -229.67 | 431.02 | 170.02 | 110.00 | 60.02 | 2.833 | | |
| 8,600.00 | 8,582.64 | 8,603.71 | 8,562.66 | 30.46 | 30.85 | 79.53 | -198.07 | 431.02 | 173.73 | 113.20 | 60.53 | 2.870 | | |
| 8,700.00 | 8,680.39 | 8,682.94 | 8,624.37 | 30.78 | 30.97 | 66.71 | -148.51 | 431.02 | 188.48 | 128.84 | 59.64 | 3.160 | | |
| 8,800.00 | 8,771.82 | 8,757.94 | 8,674.47 | 31.04 | 31.05 | 56.39 | -92.81 | 431.01 | 209.64 | 152.52 | 57.12 | 3.670 | | |
| 8,900.00 | 8,852.92 | 8,829.89 | 8,713.79 | 31.24 | 31.09 | 48.63 | -32.63 | 431.01 | 232.66 | 178.78 | 53.88 | 4.318 | | |
| 9,000.00 | 8,920.15 | 8,900.00 | 8,742.98 | 31.38 | 31.10 | 43.03 | 31.04 | 431.01 | 254.39 | 203.66 | 50.73 | 5.015 | | |
| 9,100.00 | 8,970.57 | 8,967.85 | 8,762.07 | 31.49 | 31.09 | 39.17 | 96.09 | 431.01 | 272.83 | 224.65 | 48.18 | 5.662 | | |
| 9,200.00 | 9,001.97 | 9,034.98 | 8,771.70 | 31.65 | 31.11 | 36.64 | 162.47 | 431.00 | 286.74 | 240.04 | 46.70 | 6.140 | | |
| 9,300.00 | 9,012.99 | 9,117.19 | 8,773.00 | 31.90 | 31.34 | 35.31 | 244.65 | 431.00 | 294.11 | 247.63 | 46.48 | 6.328 | | |
| 9,400.00 | 9,013.00 | 9,217.19 | 8,773.00 | 32.20 | 31.69 | 35.31 | 344.65 | 431.00 | 294.12 | 247.11 | 47.00 | 6.257 | | |
| 9,500.00 | 9,013.00 | 9,317.19 | 8,773.00 | 32.59 | 32.12 | 35.31 | 444.65 | 430.99 | 294.12 | 246.48 | 47.64 | 6.174 | | |
| 9,600.00 | 9,013.00 | 9,417.19 | 8,773.00 | 33.05 | 32.61 | 35.31 | 544.65 | 430.99 | 294.12 | 245.75 | 48.37 | 6.081 | | |
| 9,700.00 | 9,013.00 | 9,517.19 | 8,773.00 | 33.58 | 33.18 | 35.31 | 644.65 | 430.99 | 294.12 | 244.92 | 49.20 | 5.978 | | |
| 9,800.00 | 9,013.00 | 9,617.19 | 8,773.00 | 34.19 | 33.81 | 35.31 | 744.65 | 430.98 | 294.11 | 244.00 | 50.12 | 5.868 | | |
| 9,900.00 | 9,013.00 | 9,717.19 | 8,773.00 | 34.85 | 34.51 | 35.31 | 844.65 | 430.98 | 294.11 | 242.99 | 51.13 | 5.753 | | |
| 10,000.00 | 9,013.00 | 9,817.19 | 8,773.00 | 35.59 | 35.27 | 35.31 | 944.65 | 430.97 | 294.11 | 241.90 | 52.21 | 5.633 | | |
| 10,100.00 | 9,013.00 | 9,917.19 | 8,773.00 | 36.38 | 36.08 | 35.31 | 1,044.65 | 430.97 | 294.11 | 240.73 | 53.38 | 5.510 | | |
| 10,200.00 | 9,013.00 | 10,017.19 | 8,773.00 | 37.23 | 36.95 | 35.31 | 1,144.65 | 430.97 | 294.11 | 239.49 | 54.62 | 5.385 | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 523H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|-----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | | Distance | | | | | | | Warning |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Toolface (°) | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | |
| 10,300.00 | 9,013.00 | 10,117.19 | 8,773.00 | 38.12 | 37.87 | 35.31 | 1,244.65 | 430.96 | 294.11 | 238.19 | 55.92 | 5.259 | | |
| 10,400.00 | 9,013.00 | 10,217.19 | 8,773.00 | 39.07 | 38.84 | 35.31 | 1,344.65 | 430.96 | 294.11 | 236.82 | 57.29 | 5.134 | | |
| 10,500.00 | 9,013.00 | 10,317.19 | 8,773.00 | 40.07 | 39.86 | 35.31 | 1,444.65 | 430.96 | 294.11 | 235.40 | 58.72 | 5.009 | | |
| 10,600.00 | 9,013.00 | 10,417.19 | 8,773.00 | 41.10 | 40.91 | 35.31 | 1,544.65 | 430.95 | 294.11 | 233.92 | 60.20 | 4.886 | | |
| 10,700.00 | 9,013.00 | 10,517.19 | 8,773.00 | 42.17 | 42.00 | 35.31 | 1,644.65 | 430.95 | 294.11 | 232.39 | 61.73 | 4.765 | | |
| 10,800.00 | 9,013.00 | 10,617.19 | 8,773.00 | 43.29 | 43.13 | 35.31 | 1,744.65 | 430.95 | 294.11 | 230.81 | 63.30 | 4.646 | | |
| 10,900.00 | 9,013.00 | 10,717.19 | 8,773.00 | 44.43 | 44.29 | 35.31 | 1,844.65 | 430.94 | 294.11 | 229.19 | 64.92 | 4.530 | | |
| 11,000.00 | 9,013.00 | 10,817.19 | 8,773.00 | 45.60 | 45.48 | 35.31 | 1,944.65 | 430.94 | 294.11 | 227.53 | 66.58 | 4.417 | | |
| 11,100.00 | 9,013.00 | 10,917.19 | 8,773.00 | 46.81 | 46.70 | 35.31 | 2,044.65 | 430.93 | 294.11 | 225.83 | 68.28 | 4.308 | | |
| 11,200.00 | 9,013.00 | 11,017.19 | 8,773.00 | 48.04 | 47.94 | 35.31 | 2,144.65 | 430.93 | 294.11 | 224.10 | 70.01 | 4.201 | | |
| 11,300.00 | 9,013.00 | 11,117.19 | 8,773.00 | 49.29 | 49.21 | 35.31 | 2,244.65 | 430.93 | 294.11 | 222.34 | 71.77 | 4.098 | | |
| 11,400.00 | 9,013.00 | 11,217.19 | 8,773.00 | 50.57 | 50.50 | 35.31 | 2,344.65 | 430.92 | 294.11 | 220.55 | 73.56 | 3.998 | | |
| 11,500.00 | 9,013.00 | 11,317.19 | 8,773.00 | 51.86 | 51.81 | 35.31 | 2,444.65 | 430.92 | 294.11 | 218.73 | 75.38 | 3.902 | | |
| 11,600.00 | 9,013.00 | 11,417.19 | 8,773.00 | 53.18 | 53.13 | 35.31 | 2,544.65 | 430.92 | 294.11 | 216.88 | 77.23 | 3.808 | | |
| 11,700.00 | 9,013.00 | 11,517.19 | 8,773.00 | 54.52 | 54.48 | 35.31 | 2,644.65 | 430.91 | 294.11 | 215.01 | 79.10 | 3.718 | | |
| 11,800.00 | 9,013.00 | 11,617.19 | 8,773.00 | 55.87 | 55.84 | 35.31 | 2,744.65 | 430.91 | 294.11 | 213.12 | 80.99 | 3.632 | | |
| 11,900.00 | 9,013.00 | 11,717.19 | 8,773.00 | 57.24 | 57.22 | 35.31 | 2,844.65 | 430.90 | 294.11 | 211.21 | 82.90 | 3.548 | | |
| 12,000.00 | 9,013.00 | 11,817.19 | 8,773.00 | 58.62 | 58.61 | 35.31 | 2,944.65 | 430.90 | 294.11 | 209.28 | 84.83 | 3.467 | | |
| 12,100.00 | 9,013.00 | 11,917.19 | 8,773.00 | 60.01 | 60.01 | 35.31 | 3,044.65 | 430.90 | 294.10 | 207.33 | 86.78 | 3.389 | | |
| 12,200.00 | 9,013.00 | 12,017.19 | 8,773.00 | 61.42 | 61.43 | 35.31 | 3,144.65 | 430.89 | 294.10 | 205.36 | 88.74 | 3.314 | | |
| 12,300.00 | 9,013.00 | 12,117.19 | 8,773.00 | 62.84 | 62.86 | 35.31 | 3,244.65 | 430.89 | 294.10 | 203.38 | 90.72 | 3.242 | | |
| 12,400.00 | 9,013.00 | 12,217.19 | 8,773.00 | 64.27 | 64.30 | 35.31 | 3,344.65 | 430.89 | 294.10 | 201.38 | 92.72 | 3.172 | | |
| 12,500.00 | 9,013.00 | 12,317.19 | 8,773.00 | 65.71 | 65.74 | 35.31 | 3,444.65 | 430.88 | 294.10 | 199.37 | 94.73 | 3.105 | | |
| 12,600.00 | 9,013.00 | 12,417.19 | 8,773.00 | 67.16 | 67.20 | 35.31 | 3,544.65 | 430.88 | 294.10 | 197.35 | 96.75 | 3.040 | | |
| 12,700.00 | 9,013.00 | 12,517.19 | 8,773.00 | 68.62 | 68.67 | 35.31 | 3,644.65 | 430.88 | 294.10 | 195.32 | 98.78 | 2.977 | | |
| 12,800.00 | 9,013.00 | 12,617.19 | 8,773.00 | 70.09 | 70.14 | 35.31 | 3,744.65 | 430.87 | 294.10 | 193.27 | 100.83 | 2.917 | | |
| 12,900.00 | 9,013.00 | 12,717.19 | 8,773.00 | 71.57 | 71.62 | 35.31 | 3,844.65 | 430.87 | 294.10 | 191.21 | 102.89 | 2.859 | | |
| 13,000.00 | 9,013.00 | 12,817.19 | 8,773.00 | 73.05 | 73.11 | 35.31 | 3,944.65 | 430.86 | 294.10 | 189.15 | 104.95 | 2.802 | | |
| 13,100.00 | 9,013.00 | 12,917.19 | 8,773.00 | 74.54 | 74.61 | 35.31 | 4,044.65 | 430.86 | 294.10 | 187.07 | 107.03 | 2.748 | | |
| 13,200.00 | 9,013.00 | 13,017.19 | 8,773.00 | 76.04 | 76.11 | 35.31 | 4,144.65 | 430.86 | 294.10 | 184.99 | 109.11 | 2.695 | | |
| 13,300.00 | 9,013.00 | 13,117.19 | 8,773.00 | 77.54 | 77.62 | 35.31 | 4,244.65 | 430.85 | 294.10 | 182.89 | 111.21 | 2.645 | | |
| 13,400.00 | 9,013.00 | 13,217.19 | 8,773.00 | 79.05 | 79.13 | 35.31 | 4,344.65 | 430.85 | 294.10 | 180.79 | 113.31 | 2.596 | | |
| 13,500.00 | 9,013.00 | 13,317.19 | 8,773.00 | 80.56 | 80.65 | 35.31 | 4,444.65 | 430.85 | 294.10 | 178.68 | 115.42 | 2.548 | | |
| 13,600.00 | 9,013.00 | 13,417.19 | 8,773.00 | 82.08 | 82.17 | 35.31 | 4,544.65 | 430.84 | 294.10 | 176.57 | 117.53 | 2.502 | | |
| 13,700.00 | 9,013.00 | 13,517.19 | 8,773.00 | 83.61 | 83.70 | 35.31 | 4,644.65 | 430.84 | 294.10 | 174.44 | 119.65 | 2.458 | | |
| 13,800.00 | 9,013.00 | 13,617.19 | 8,773.00 | 85.14 | 85.24 | 35.31 | 4,744.65 | 430.84 | 294.10 | 172.32 | 121.78 | 2.415 | | |
| 13,900.00 | 9,013.00 | 13,717.19 | 8,773.00 | 86.67 | 86.77 | 35.31 | 4,844.65 | 430.83 | 294.10 | 170.18 | 123.92 | 2.373 | | |
| 14,000.00 | 9,013.00 | 13,817.19 | 8,773.00 | 88.21 | 88.31 | 35.31 | 4,944.65 | 430.83 | 294.10 | 168.04 | 126.06 | 2.333 | | |
| 14,100.00 | 9,013.00 | 13,917.19 | 8,773.00 | 89.75 | 89.86 | 35.31 | 5,044.65 | 430.82 | 294.10 | 165.89 | 128.20 | 2.294 | | |
| 14,200.00 | 9,013.00 | 14,017.19 | 8,773.00 | 91.30 | 91.41 | 35.31 | 5,144.65 | 430.82 | 294.10 | 163.74 | 130.35 | 2.256 | | |
| 14,300.00 | 9,013.00 | 14,117.19 | 8,773.00 | 92.85 | 92.96 | 35.31 | 5,244.65 | 430.82 | 294.09 | 161.59 | 132.51 | 2.219 | | |
| 14,400.00 | 9,013.00 | 14,217.19 | 8,773.00 | 94.40 | 94.52 | 35.31 | 5,344.65 | 430.81 | 294.09 | 159.42 | 134.67 | 2.184 | | |
| 14,500.00 | 9,013.00 | 14,317.19 | 8,773.00 | 95.95 | 96.08 | 35.31 | 5,444.65 | 430.81 | 294.09 | 157.26 | 136.84 | 2.149 | | |
| 14,600.00 | 9,013.00 | 14,417.19 | 8,773.00 | 97.51 | 97.64 | 35.31 | 5,544.65 | 430.81 | 294.09 | 155.09 | 139.01 | 2.116 | | |
| 14,700.00 | 9,013.00 | 14,517.19 | 8,773.00 | 99.07 | 99.20 | 35.31 | 5,644.65 | 430.80 | 294.09 | 152.91 | 141.18 | 2.083 | | |
| 14,800.00 | 9,013.00 | 14,617.19 | 8,773.00 | 100.64 | 100.77 | 35.31 | 5,744.65 | 430.80 | 294.09 | 150.74 | 143.36 | 2.051 | | |
| 14,900.00 | 9,013.00 | 14,717.19 | 8,773.00 | 102.21 | 102.34 | 35.31 | 5,844.65 | 430.79 | 294.09 | 148.56 | 145.54 | 2.021 | | |
| 15,000.00 | 9,013.00 | 14,817.19 | 8,773.00 | 103.78 | 103.91 | 35.31 | 5,944.65 | 430.79 | 294.09 | 146.37 | 147.72 | 1.991 | | |
| 15,100.00 | 9,013.00 | 14,917.19 | 8,773.00 | 105.35 | 105.49 | 35.31 | 6,044.65 | 430.79 | 294.09 | 144.18 | 149.91 | 1.962 | | |
| 15,200.00 | 9,013.00 | 15,017.19 | 8,773.00 | 106.92 | 107.06 | 35.31 | 6,144.65 | 430.78 | 294.09 | 141.99 | 152.10 | 1.934 | | |
| 15,300.00 | 9,013.00 | 15,117.19 | 8,773.00 | 108.50 | 108.64 | 35.31 | 6,244.65 | 430.78 | 294.09 | 139.80 | 154.30 | 1.906 | | |
| 15,400.00 | 9,013.00 | 15,217.19 | 8,773.00 | 110.08 | 110.22 | 35.31 | 6,344.65 | 430.78 | 294.09 | 137.60 | 156.49 | 1.879 | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 523H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|-----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | Distance | | | | | | | | Warning |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Toolface (") | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | |
| 15,500.00 | 9,013.00 | 15,317.19 | 8,773.00 | 111.66 | 111.81 | 35.31 | 6,444.65 | 430.77 | 294.09 | 135.40 | 158.69 | 1.853 | | |
| 15,600.00 | 9,013.00 | 15,417.19 | 8,773.00 | 113.24 | 113.39 | 35.31 | 6,544.65 | 430.77 | 294.09 | 133.19 | 160.90 | 1.828 | | |
| 15,700.00 | 9,013.00 | 15,517.19 | 8,773.00 | 114.83 | 114.98 | 35.31 | 6,644.65 | 430.77 | 294.09 | 130.99 | 163.10 | 1.803 | | |
| 15,800.00 | 9,013.00 | 15,617.19 | 8,773.00 | 116.41 | 116.57 | 35.31 | 6,744.65 | 430.76 | 294.09 | 128.78 | 165.31 | 1.779 | | |
| 15,900.00 | 9,013.00 | 15,717.19 | 8,773.00 | 118.00 | 118.16 | 35.31 | 6,844.65 | 430.76 | 294.09 | 126.57 | 167.52 | 1.756 | | |
| 16,000.00 | 9,013.00 | 15,817.19 | 8,773.00 | 119.59 | 119.75 | 35.31 | 6,944.65 | 430.75 | 294.09 | 124.36 | 169.73 | 1.733 | | |
| 16,100.00 | 9,013.00 | 15,917.19 | 8,773.00 | 121.18 | 121.34 | 35.31 | 7,044.65 | 430.75 | 294.09 | 122.14 | 171.95 | 1.710 | | |
| 16,200.00 | 9,013.00 | 16,017.19 | 8,773.00 | 122.78 | 122.94 | 35.31 | 7,144.65 | 430.75 | 294.09 | 119.92 | 174.16 | 1.689 | | |
| 16,300.00 | 9,013.00 | 16,117.19 | 8,773.00 | 124.37 | 124.53 | 35.30 | 7,244.65 | 430.74 | 294.09 | 117.70 | 176.38 | 1.667 | | |
| 16,379.26 | 9,013.00 | 16,196.45 | 8,773.00 | 125.49 | 125.80 | 35.30 | 7,323.91 | 430.74 | 294.09 | 116.15 | 177.93 | 1.653 SF | | |

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 623H - OH - Plan 1 | | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------------|-----------------------------|-----------------------------|---------------------|------------------|-----------------------------|---|-----------------|---------------------------------|----------------------|---------|----------|--|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | Highside Toolface (°) | Distance | | Minimum Separation (usft) | Separation Factor | Warning | | | | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | | | | | | | |
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | -90.34 | -0.18 | -29.99 | 29.99 | | | | | | |
| 100.00 | 100.00 | 100.00 | 100.00 | 0.14 | 0.14 | -90.34 | -0.18 | -29.99 | 29.99 | 29.71 | 0.28 | 108.652 | | | |
| 200.00 | 200.00 | 200.00 | 200.00 | 0.50 | 0.50 | -90.34 | -0.18 | -29.99 | 29.99 | 29.00 | 0.99 | 30.203 | | | |
| 300.00 | 300.00 | 300.00 | 300.00 | 0.85 | 0.85 | -90.34 | -0.18 | -29.99 | 29.99 | 28.28 | 1.71 | 17.539 | | | |
| 400.00 | 400.00 | 400.00 | 400.00 | 1.21 | 1.21 | -90.34 | -0.18 | -29.99 | 29.99 | 27.56 | 2.43 | 12.358 | | | |
| 500.00 | 500.00 | 500.00 | 500.00 | 1.57 | 1.57 | -90.34 | -0.18 | -29.99 | 29.99 | 26.85 | 3.14 | 9.540 | | | |
| 600.00 | 600.00 | 600.00 | 600.00 | 1.93 | 1.93 | -90.34 | -0.18 | -29.99 | 29.99 | 26.13 | 3.86 | 7.768 | | | |
| 700.00 | 700.00 | 700.00 | 700.00 | 2.29 | 2.29 | -90.34 | -0.18 | -29.99 | 29.99 | 25.41 | 4.58 | 6.551 | | | |
| 800.00 | 800.00 | 800.00 | 800.00 | 2.65 | 2.65 | -90.34 | -0.18 | -29.99 | 29.99 | 24.70 | 5.29 | 5.664 | | | |
| 900.00 | 900.00 | 900.00 | 900.00 | 3.01 | 3.01 | -90.34 | -0.18 | -29.99 | 29.99 | 23.98 | 6.01 | 4.989 | | | |
| 1,000.00 | 1,000.00 | 1,000.00 | 1,000.00 | 3.36 | 3.36 | -90.34 | -0.18 | -29.99 | 29.99 | 23.26 | 6.73 | 4.457 | | | |
| 1,100.00 | 1,100.00 | 1,100.38 | 1,100.37 | 3.72 | 3.71 | -91.85 | -0.95 | -29.33 | 29.35 | 21.92 | 7.43 | 3.950 | | | |
| 1,200.00 | 1,200.00 | 1,200.67 | 1,200.62 | 4.08 | 4.04 | -96.76 | -3.24 | -27.35 | 27.55 | 19.43 | 8.12 | 3.393 | | | |
| 1,300.00 | 1,299.99 | 1,300.86 | 1,300.68 | 4.42 | 4.38 | 124.17 | -7.06 | -24.07 | 25.64 | 16.84 | 8.80 | 2.913 | | | |
| 1,400.00 | 1,399.95 | 1,400.97 | 1,400.53 | 4.76 | 4.72 | 115.20 | -12.40 | -19.47 | 24.51 | 15.03 | 9.48 | 2.586 | | | |
| 1,471.76 | 1,471.63 | 1,472.75 | 1,472.04 | 5.00 | 4.97 | 108.26 | -17.17 | -15.37 | 24.26 | 14.29 | 9.97 | 2.433 CC | | | |
| 1,500.00 | 1,499.82 | 1,500.99 | 1,500.14 | 5.10 | 5.07 | 105.49 | -19.25 | -13.57 | 24.30 | 14.14 | 10.17 | 2.390 | | | |
| 1,600.00 | 1,599.57 | 1,600.93 | 1,599.54 | 5.44 | 5.43 | 97.29 | -27.14 | -6.78 | 25.05 | 14.18 | 10.87 | 2.305 | | | |
| 1,700.00 | 1,699.16 | 1,700.91 | 1,698.97 | 5.79 | 5.79 | 93.97 | -35.07 | 0.04 | 26.35 | 14.77 | 11.58 | 2.276 | | | |
| 1,800.00 | 1,798.62 | 1,800.90 | 1,798.42 | 6.14 | 6.16 | 93.86 | -43.00 | 6.86 | 27.79 | 15.49 | 12.30 | 2.259 | | | |
| 1,900.00 | 1,898.07 | 1,900.89 | 1,897.86 | 6.50 | 6.53 | 93.86 | -50.93 | 13.69 | 29.23 | 16.19 | 13.03 | 2.243 | | | |
| 2,000.00 | 1,997.52 | 2,000.88 | 1,997.30 | 6.87 | 6.90 | 93.87 | -58.85 | 20.51 | 30.67 | 16.90 | 13.77 | 2.227 | | | |
| 2,100.00 | 2,096.97 | 2,100.87 | 2,096.74 | 7.23 | 7.28 | 93.87 | -66.78 | 27.33 | 32.11 | 17.59 | 14.51 | 2.212 | | | |
| 2,200.00 | 2,196.42 | 2,200.86 | 2,196.18 | 7.60 | 7.66 | 93.87 | -74.71 | 34.16 | 33.55 | 18.29 | 15.26 | 2.198 | | | |
| 2,300.00 | 2,295.87 | 2,300.85 | 2,295.62 | 7.98 | 8.04 | 93.88 | -82.63 | 40.98 | 34.99 | 18.97 | 16.01 | 2.185 | | | |
| 2,400.00 | 2,395.33 | 2,400.84 | 2,395.06 | 8.35 | 8.42 | 93.88 | -90.56 | 47.80 | 36.43 | 19.66 | 16.77 | 2.172 | | | |
| 2,500.00 | 2,494.78 | 2,500.83 | 2,494.50 | 8.73 | 8.80 | 93.88 | -98.49 | 54.63 | 37.87 | 20.34 | 17.53 | 2.160 | | | |
| 2,600.00 | 2,594.23 | 2,600.82 | 2,593.94 | 9.11 | 9.19 | 93.88 | -106.42 | 61.45 | 39.31 | 21.01 | 18.29 | 2.149 | | | |
| 2,700.00 | 2,693.68 | 2,700.81 | 2,693.39 | 9.49 | 9.57 | 93.89 | -114.34 | 68.27 | 40.75 | 21.69 | 19.06 | 2.138 | | | |
| 2,800.00 | 2,793.13 | 2,800.80 | 2,792.83 | 9.87 | 9.96 | 93.89 | -122.27 | 75.09 | 42.19 | 22.36 | 19.83 | 2.128 | | | |
| 2,900.00 | 2,892.58 | 2,900.79 | 2,892.27 | 10.25 | 10.35 | 93.89 | -130.20 | 81.92 | 43.63 | 23.03 | 20.60 | 2.118 | | | |
| 3,000.00 | 2,992.03 | 3,000.78 | 2,991.71 | 10.64 | 10.73 | 93.89 | -138.12 | 88.74 | 45.07 | 23.70 | 21.37 | 2.109 | | | |
| 3,100.00 | 3,091.49 | 3,100.77 | 3,091.15 | 11.02 | 11.12 | 93.89 | -146.05 | 95.56 | 46.51 | 24.37 | 22.14 | 2.101 | | | |
| 3,200.00 | 3,190.94 | 3,200.75 | 3,190.59 | 11.41 | 11.51 | 93.89 | -153.98 | 102.39 | 47.95 | 25.03 | 22.91 | 2.092 | | | |
| 3,300.00 | 3,290.39 | 3,300.74 | 3,290.03 | 11.79 | 11.90 | 93.89 | -161.91 | 109.21 | 49.39 | 25.70 | 23.69 | 2.085 | | | |
| 3,400.00 | 3,389.84 | 3,400.73 | 3,389.47 | 12.18 | 12.29 | 93.90 | -169.83 | 116.03 | 50.83 | 26.36 | 24.47 | 2.077 | | | |
| 3,500.00 | 3,489.29 | 3,500.72 | 3,488.91 | 12.57 | 12.68 | 93.90 | -177.76 | 122.86 | 52.27 | 27.02 | 25.24 | 2.070 | | | |
| 3,600.00 | 3,588.74 | 3,600.71 | 3,588.36 | 12.96 | 13.07 | 93.90 | -185.69 | 129.68 | 53.71 | 27.68 | 26.02 | 2.064 | | | |
| 3,700.00 | 3,688.19 | 3,700.70 | 3,687.80 | 13.35 | 13.46 | 93.90 | -193.61 | 136.50 | 55.15 | 28.34 | 26.80 | 2.058 | | | |
| 3,800.00 | 3,787.65 | 3,800.69 | 3,787.24 | 13.74 | 13.85 | 93.90 | -201.54 | 143.32 | 56.59 | 29.00 | 27.58 | 2.052 | | | |
| 3,900.00 | 3,887.10 | 3,900.68 | 3,886.68 | 14.13 | 14.25 | 93.90 | -209.47 | 150.15 | 58.03 | 29.66 | 28.36 | 2.046 | | | |
| 4,000.00 | 3,986.55 | 4,000.67 | 3,986.12 | 14.52 | 14.64 | 93.90 | -217.40 | 156.97 | 59.47 | 30.32 | 29.15 | 2.040 | | | |
| 4,100.00 | 4,086.00 | 4,100.66 | 4,085.56 | 14.91 | 15.03 | 93.90 | -225.32 | 163.79 | 60.91 | 30.98 | 29.93 | 2.035 | | | |
| 4,200.00 | 4,185.45 | 4,200.65 | 4,185.00 | 15.30 | 15.42 | 93.90 | -233.25 | 170.62 | 62.35 | 31.63 | 30.71 | 2.030 | | | |
| 4,300.00 | 4,284.90 | 4,300.64 | 4,284.44 | 15.69 | 15.82 | 93.90 | -241.18 | 177.44 | 63.79 | 32.29 | 31.49 | 2.025 | | | |
| 4,400.00 | 4,384.35 | 4,400.63 | 4,383.88 | 16.08 | 16.21 | 93.90 | -249.10 | 184.26 | 65.23 | 32.95 | 32.28 | 2.021 | | | |
| 4,500.00 | 4,483.80 | 4,500.62 | 4,483.33 | 16.47 | 16.60 | 93.91 | -257.03 | 191.09 | 66.67 | 33.60 | 33.06 | 2.016 | | | |
| 4,600.00 | 4,583.31 | 4,600.68 | 4,582.88 | 16.86 | 16.99 | 93.85 | -264.60 | 197.60 | 68.03 | 34.19 | 33.84 | 2.010 | | | |
| 4,700.00 | 4,682.99 | 4,700.77 | 4,682.64 | 17.24 | 17.37 | 93.77 | -270.72 | 202.87 | 69.14 | 34.54 | 34.60 | 1.998 | | | |
| 4,800.00 | 4,782.81 | 4,800.86 | 4,782.55 | 17.61 | 17.74 | 93.70 | -275.33 | 206.84 | 69.97 | 34.62 | 35.34 | 1.980 | | | |
| 4,900.00 | 4,882.73 | 4,900.97 | 4,882.57 | 17.97 | 18.10 | 93.62 | -278.41 | 209.49 | 70.52 | 34.46 | 36.06 | 1.956 | | | |
| 5,000.00 | 4,982.71 | 5,001.07 | 4,982.66 | 18.32 | 18.45 | 93.54 | -279.97 | 210.83 | 70.80 | 34.04 | 36.76 | 1.926 | | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

| Offset Design Snapping 12-1 FED - 623H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|--|-----------------------|-----------------------|-----------------------|------------------|---------------|-----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | | Distance | | | | | | | Warning |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Toolface (°) | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | |
| 5,100.00 | 5,082.71 | 5,101.13 | 5,082.71 | 18.64 | 18.78 | -135.11 | -280.18 | 211.01 | 70.83 | 33.42 | 37.41 | 1.893 | | |
| 5,200.00 | 5,182.71 | 5,201.13 | 5,182.71 | 18.97 | 19.10 | -135.11 | -280.18 | 211.01 | 70.83 | 32.77 | 38.06 | 1.861 | | |
| 5,300.00 | 5,282.71 | 5,301.13 | 5,282.71 | 19.30 | 19.42 | -135.11 | -280.18 | 211.01 | 70.83 | 32.13 | 38.71 | 1.830 | | |
| 5,400.00 | 5,382.71 | 5,401.13 | 5,382.71 | 19.62 | 19.74 | -135.11 | -280.18 | 211.01 | 70.83 | 31.48 | 39.36 | 1.800 | | |
| 5,500.00 | 5,482.71 | 5,501.13 | 5,482.71 | 19.95 | 20.06 | -135.11 | -280.18 | 211.01 | 70.83 | 30.82 | 40.01 | 1.770 | | |
| 5,600.00 | 5,582.71 | 5,601.13 | 5,582.71 | 20.28 | 20.39 | -135.11 | -280.18 | 211.01 | 70.83 | 30.17 | 40.66 | 1.742 | | |
| 5,700.00 | 5,682.71 | 5,701.13 | 5,682.71 | 20.61 | 20.71 | -135.11 | -280.18 | 211.01 | 70.83 | 29.51 | 41.32 | 1.714 | | |
| 5,800.00 | 5,782.71 | 5,801.13 | 5,782.71 | 20.94 | 21.04 | -135.11 | -280.18 | 211.01 | 70.83 | 28.86 | 41.98 | 1.687 | | |
| 5,900.00 | 5,882.71 | 5,901.13 | 5,882.71 | 21.27 | 21.37 | -135.11 | -280.18 | 211.01 | 70.83 | 28.20 | 42.64 | 1.661 | | |
| 6,000.00 | 5,982.71 | 6,001.13 | 5,982.71 | 21.61 | 21.70 | -135.11 | -280.18 | 211.01 | 70.83 | 27.53 | 43.30 | 1.636 | | |
| 6,100.00 | 6,082.71 | 6,101.13 | 6,082.71 | 21.94 | 22.03 | -135.11 | -280.18 | 211.01 | 70.83 | 26.87 | 43.96 | 1.611 | | |
| 6,200.00 | 6,182.71 | 6,201.13 | 6,182.71 | 22.28 | 22.36 | -135.11 | -280.18 | 211.01 | 70.83 | 26.20 | 44.63 | 1.587 | | |
| 6,300.00 | 6,282.71 | 6,301.13 | 6,282.71 | 22.61 | 22.69 | -135.11 | -280.18 | 211.01 | 70.83 | 25.54 | 45.29 | 1.564 | | |
| 6,400.00 | 6,382.71 | 6,401.13 | 6,382.71 | 22.95 | 23.02 | -135.11 | -280.18 | 211.01 | 70.83 | 24.87 | 45.96 | 1.541 | | |
| 6,500.00 | 6,482.71 | 6,501.13 | 6,482.71 | 23.28 | 23.36 | -135.11 | -280.18 | 211.01 | 70.83 | 24.20 | 46.63 | 1.519 | | |
| 6,600.00 | 6,582.71 | 6,601.13 | 6,582.71 | 23.62 | 23.69 | -135.11 | -280.18 | 211.01 | 70.83 | 23.53 | 47.30 | 1.497 | Level 3 | |
| 6,700.00 | 6,682.71 | 6,701.13 | 6,682.71 | 23.96 | 24.02 | -135.11 | -280.18 | 211.01 | 70.83 | 22.86 | 47.98 | 1.476 | Level 3 | |
| 6,800.00 | 6,782.71 | 6,801.13 | 6,782.71 | 24.30 | 24.36 | -135.11 | -280.18 | 211.01 | 70.83 | 22.18 | 48.65 | 1.456 | Level 3 | |
| 6,900.00 | 6,882.71 | 6,901.13 | 6,882.71 | 24.64 | 24.69 | -135.11 | -280.18 | 211.01 | 70.83 | 21.51 | 49.32 | 1.436 | Level 3 | |
| 7,000.00 | 6,982.71 | 7,001.13 | 6,982.71 | 24.98 | 25.03 | -135.11 | -280.18 | 211.01 | 70.83 | 20.83 | 50.00 | 1.417 | Level 3 | |
| 7,100.00 | 7,082.71 | 7,101.13 | 7,082.71 | 25.32 | 25.37 | -135.11 | -280.18 | 211.01 | 70.83 | 20.15 | 50.68 | 1.398 | Level 3 | |
| 7,200.00 | 7,182.71 | 7,201.13 | 7,182.71 | 25.66 | 25.71 | -135.11 | -280.18 | 211.01 | 70.83 | 19.48 | 51.36 | 1.379 | Level 3 | |
| 7,300.00 | 7,282.71 | 7,301.13 | 7,282.71 | 26.00 | 26.04 | -135.11 | -280.18 | 211.01 | 70.83 | 18.80 | 52.03 | 1.361 | Level 3 | |
| 7,400.00 | 7,382.71 | 7,401.13 | 7,382.71 | 26.34 | 26.38 | -135.11 | -280.18 | 211.01 | 70.83 | 18.12 | 52.72 | 1.344 | Level 3 | |
| 7,500.00 | 7,482.71 | 7,501.13 | 7,482.71 | 26.68 | 26.72 | -135.11 | -280.18 | 211.01 | 70.83 | 17.43 | 53.40 | 1.327 | Level 3 | |
| 7,600.00 | 7,582.71 | 7,601.13 | 7,582.71 | 27.02 | 27.06 | -135.11 | -280.18 | 211.01 | 70.83 | 16.75 | 54.08 | 1.310 | Level 3 | |
| 7,700.00 | 7,682.71 | 7,701.13 | 7,682.71 | 27.37 | 27.40 | -135.11 | -280.18 | 211.01 | 70.83 | 16.07 | 54.76 | 1.293 | Level 3 | |
| 7,800.00 | 7,782.71 | 7,801.13 | 7,782.71 | 27.71 | 27.74 | -135.11 | -280.18 | 211.01 | 70.83 | 15.38 | 55.45 | 1.277 | Level 3 | |
| 7,900.00 | 7,882.71 | 7,901.13 | 7,882.71 | 28.05 | 28.08 | -135.11 | -280.18 | 211.01 | 70.83 | 14.70 | 56.13 | 1.262 | Level 3 | |
| 8,000.00 | 7,982.71 | 8,001.13 | 7,982.71 | 28.40 | 28.42 | -135.11 | -280.18 | 211.01 | 70.83 | 14.01 | 56.82 | 1.247 | Level 2 | |
| 8,100.00 | 8,082.71 | 8,101.13 | 8,082.71 | 28.74 | 28.77 | -135.11 | -280.18 | 211.01 | 70.83 | 13.33 | 57.50 | 1.232 | Level 2 | |
| 8,200.00 | 8,182.71 | 8,201.13 | 8,182.71 | 29.09 | 29.11 | -135.11 | -280.18 | 211.01 | 70.83 | 12.64 | 58.19 | 1.217 | Level 2 | |
| 8,300.00 | 8,282.71 | 8,301.13 | 8,282.71 | 29.43 | 29.45 | -135.11 | -280.18 | 211.01 | 70.83 | 11.95 | 58.88 | 1.203 | Level 2 | |
| 8,400.00 | 8,382.71 | 8,401.13 | 8,382.71 | 29.78 | 29.80 | -135.11 | -280.18 | 211.01 | 70.83 | 11.26 | 59.57 | 1.189 | Level 2 | |
| 8,500.00 | 8,482.71 | 8,501.13 | 8,482.71 | 30.12 | 30.14 | -135.11 | -280.18 | 211.01 | 70.83 | 10.58 | 60.26 | 1.176 | Level 2 | |
| 8,501.95 | 8,484.66 | 8,503.08 | 8,484.66 | 30.13 | 30.15 | -135.11 | -280.18 | 211.01 | 70.83 | 10.56 | 60.27 | 1.175 | Level 2, ES, SF | |
| 8,600.00 | 8,582.64 | 8,601.05 | 8,582.64 | 30.46 | 30.48 | -136.27 | -280.18 | 211.01 | 72.50 | 11.56 | 60.94 | 1.190 | Level 2 | |
| 8,700.00 | 8,680.39 | 8,698.81 | 8,680.39 | 30.78 | 30.82 | -144.18 | -280.18 | 211.01 | 88.22 | 26.65 | 61.56 | 1.433 | Level 3 | |
| 8,800.00 | 8,771.82 | 8,790.24 | 8,771.82 | 31.04 | 31.13 | -152.97 | -280.18 | 211.01 | 123.33 | 61.27 | 62.06 | 1.987 | | |
| 8,900.00 | 8,852.92 | 8,871.34 | 8,852.92 | 31.24 | 31.41 | -158.62 | -280.18 | 211.01 | 178.09 | 115.63 | 62.46 | 2.851 | | |
| 9,000.00 | 8,920.15 | 8,938.56 | 8,920.15 | 31.38 | 31.65 | -160.98 | -280.18 | 211.01 | 249.77 | 186.98 | 62.79 | 3.978 | | |
| 9,100.00 | 8,970.57 | 8,988.98 | 8,970.57 | 31.49 | 31.82 | -159.87 | -280.18 | 211.01 | 334.62 | 271.61 | 63.01 | 5.310 | | |
| 9,200.00 | 9,001.97 | 9,020.39 | 9,001.97 | 31.65 | 31.93 | -151.20 | -280.18 | 211.01 | 428.54 | 365.40 | 63.14 | 6.787 | | |
| 9,300.00 | 9,012.99 | 9,031.41 | 9,012.99 | 31.90 | 31.97 | -93.55 | -280.18 | 211.01 | 527.20 | 464.03 | 63.17 | 8.346 | | |
| 9,400.00 | 9,013.00 | 9,031.42 | 9,013.00 | 32.20 | 31.97 | -90.00 | -280.18 | 211.01 | 626.82 | 563.66 | 63.15 | 9.925 | | |
| 9,500.00 | 9,013.00 | 9,031.42 | 9,013.00 | 32.59 | 31.97 | -90.00 | -280.18 | 211.01 | 726.54 | 663.40 | 63.15 | 11.506 | | |
| 9,600.00 | 9,013.00 | 9,031.42 | 9,013.00 | 33.05 | 31.97 | -90.00 | -280.18 | 211.01 | 826.33 | 763.19 | 63.14 | 13.087 | | |
| 9,700.00 | 9,013.00 | 9,031.42 | 9,013.00 | 33.58 | 31.97 | -90.00 | -280.18 | 211.01 | 926.17 | 863.03 | 63.14 | 14.668 | | |
| 9,800.00 | 9,013.00 | 9,031.42 | 9,013.00 | 34.19 | 31.97 | -90.00 | -280.18 | 211.01 | 1,026.04 | 962.89 | 63.15 | 16.249 | | |
| 9,900.00 | 9,013.00 | 9,031.42 | 9,013.00 | 34.85 | 31.97 | -90.00 | -280.18 | 211.01 | 1,125.93 | 1,062.78 | 63.15 | 17.829 | | |
| 10,000.00 | 9,013.00 | 9,031.42 | 9,013.00 | 35.59 | 31.97 | -90.00 | -280.18 | 211.01 | 1,225.84 | 1,162.68 | 63.16 | 19.409 | | |
| 10,100.00 | 9,013.00 | 9,031.42 | 9,013.00 | 36.38 | 31.97 | -90.00 | -280.18 | 211.01 | 1,325.76 | 1,262.60 | 63.17 | 20.989 | | |

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Anticollision Report

| | | | |
|---------------------------|----------------------------------|-------------------------------------|--------------------------------|
| Company: | Devon Energy | Local Co-ordinate Reference: | Well 533H |
| Project: | Eddy County, New Mexico (NAD 83) | TVD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Reference Site: | Snapping 12-1 FED | MD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Site Error: | 0.00 usft | North Reference: | Grid |
| Reference Well: | 533H | Survey Calculation Method: | Minimum Curvature |
| Well Error: | 0.00 usft | Output errors are at | 2.00 sigma |
| Reference Wellbore | OH | Database: | EDM 5000.14 Single User Db |
| Reference Design: | Plan 1 | Offset TVD Reference: | Offset Datum |

| Offset Design Snapping 12-1 FED - 623H - OH - Plan 1 | | | | | | | | | | | | | Offset Site Error: | 0.00 usft |
|---|-----------------------|-----------------------|-----------------------|------------------|---------------|----------------------|-------------------------------------|--------------|------------------------|-------------------------|---------------------------|-------------------|--------------------|-----------|
| Survey Program: 0-MWD | | | | | | | | | | | | | Offset Well Error: | 0.00 usft |
| Reference | | Offset | | Semi Major Axis | | | Distance | | | | | | Warning | |
| Measured Depth (usft) | Vertical Depth (usft) | Measured Depth (usft) | Vertical Depth (usft) | Reference (usft) | Offset (usft) | Highside Tooface (") | Offset Wellbore Centre +N/-S (usft) | +E/-W (usft) | Between Centres (usft) | Between Ellipses (usft) | Minimum Separation (usft) | Separation Factor | | |
| 10,200.00 | 9,013.00 | 9,031.42 | 9,013.00 | 37.23 | 31.97 | -90.00 | -280.18 | 211.01 | 1,425.70 | 1,362.52 | 63.17 | 22.567 | | |
| 10,300.00 | 9,013.00 | 9,031.42 | 9,013.00 | 38.12 | 31.97 | -90.00 | -280.18 | 211.01 | 1,525.64 | 1,462.45 | 63.19 | 24.145 | | |
| 10,400.00 | 9,013.00 | 9,031.42 | 9,013.00 | 39.07 | 31.97 | -90.00 | -280.18 | 211.01 | 1,625.59 | 1,562.39 | 63.20 | 25.722 | | |
| 10,500.00 | 9,013.00 | 9,031.42 | 9,013.00 | 40.07 | 31.97 | -90.00 | -280.18 | 211.01 | 1,725.54 | 1,662.33 | 63.21 | 27.298 | | |
| 10,600.00 | 9,013.00 | 9,031.42 | 9,013.00 | 41.10 | 31.97 | -90.00 | -280.18 | 211.01 | 1,825.50 | 1,762.28 | 63.23 | 28.872 | | |

Anticollision Report


Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Reference Site: Snapping 12-1 FED
Site Error: 0.00 usft
Reference Well: 533H
Well Error: 0.00 usft
Reference Wellbore: OH
Reference Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: EDM 5000.14 Single User Db
Offset TVD Reference: Offset Datum

Reference Depths are relative to GL 3280 + 23' KB @ 3303.00usft
Offset Depths are relative to Offset Datum
Central Meridian is -104.333334

Coordinates are relative to: 533H
Coordinate System is US State Plane 1983, New Mexico Eastern Zone
Grid Convergence at Surface is: 0.32°

Ladder Plot



LEGEND

—■— 523H OH, Plan 1 V0 —●— 522H OH, Plan 1 V0 —◆— 623H OH, Plan 1 V0


Anticollision Report

| | | | |
|---------------------------|----------------------------------|-------------------------------------|--------------------------------|
| Company: | Devon Energy | Local Co-ordinate Reference: | Well 533H |
| Project: | Eddy County, New Mexico (NAD 83) | TVD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Reference Site: | Snapping 12-1 FED | MD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Site Error: | 0.00 usft | North Reference: | Grid |
| Reference Well: | 533H | Survey Calculation Method: | Minimum Curvature |
| Well Error: | 0.00 usft | Output errors are at | 2.00 sigma |
| Reference Wellbore | OH | Database: | EDM 5000.14 Single User Db |
| Reference Design: | Plan 1 | Offset TVD Reference: | Offset Datum |

Reference Depths are relative to GL 3280 + 23' KB @ 3303.00usft
 Offset Depths are relative to Offset Datum
 Central Meridian is -104.333334

Coordinates are relative to: 533H
 Coordinate System is US State Plane 1983, New Mexico Eastern Zone
 Grid Convergence at Surface is: 0.32°

Separation Factor Plot




LEGEND

523H, OH, Plan 1 V0 522H, OH, Plan 1 V0 523H, OH, Plan 1 V0



Company: Devon Energy
Field: Eddy County, New Mexico (NAD 83)
Location: Snapping 12-1 FED
Well: 533H

Plan: Plan 1
GL 3280 + 23' KB @ 3303.00usft



Azimuths to Grid North
True North: -0.32°
Magnetic North: 6.67°
Magnetic Field
Strength: 47794.8snT
Dip Angle: 59.88°
Date: 9/27/2017
Model: IGRF2015

To convert a Magnetic Direction to a Grid Direction, Add 6.67°

PROJECT DETAILS: Eddy County, New Mexico (NAD 83)

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone

System Datum: Mean Sea Level

WELL DETAILS: 533H



| | | | | | |
|-------|-------|-----------|-----------|-----------|-------------|
| +N/-S | +E/-W | Nothing | Easting | Latitude | Longitude |
| 0.00 | 0.00 | 385530.04 | 726908.07 | 32.058486 | -103.734320 |

SECTION DETAILS

| Sec | MD | Inc | Azi | TVD | +N/-S | +E/-W | Dleg | TFace | VSecl | Annotation |
|-----|----------|-------|--------|---------|---------|--------|-------|--------|---------|------------------------|
| 1 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 2 | 1200.00 | 0.00 | 0.00 | 1200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | Start Nudge Build 1.15 |
| 3 | 1722.13 | 6.00 | 131.39 | 1721.17 | -18.07 | 20.51 | 1.15 | 131.39 | -18.07 | EOB 6° at 1722.13 MD |
| 4 | 4525.16 | 0.00 | 0.00 | 4508.83 | -211.93 | 240.49 | 0.00 | 0.00 | -211.93 | Start Drop -1.15 |
| 5 | 5047.29 | 0.00 | 0.00 | 5030.00 | -230.00 | 261.00 | 1.15 | 180.00 | -230.00 | Vertical at 5047.29 MD |
| 6 | 8552.82 | 0.00 | 0.00 | 8535.54 | -230.00 | 261.00 | 0.00 | 0.00 | -230.00 | Start Build 12.00 |
| 7 | 9302.82 | 90.00 | 360.00 | 9013.00 | 247.46 | 260.99 | 12.00 | 360.00 | 247.46 | LP 90° at 9302.82 MD |
| 8 | 16379.26 | 90.00 | 360.00 | 9013.00 | 7323.90 | 260.78 | 0.00 | 0.00 | 7323.90 | TD at 16379.26 |


FORMATION TOP DETAILS

| TVDPath | MDPath | Formation | DipAngle | DipDir |
|---------|---------|---------------|----------|--------|
| 903.00 | 903.00 | Rustler | 0.00 | 0.00 |
| 1253.00 | 1253.00 | Salado | 0.00 | 0.00 |
| 3998.00 | 4011.52 | Base of Salt | 0.00 | 0.00 |
| 4218.00 | 4232.73 | Delaware | 0.00 | 0.00 |
| 4248.00 | 4262.89 | Bell Canyon | 0.00 | 0.00 |
| 5233.00 | 5250.29 | Cherry Canyon | 0.00 | 0.00 |
| 6573.00 | 6590.29 | Brushy Canyon | 0.00 | 0.00 |
| 8248.00 | 8265.29 | 1st BSGP Lime | 0.00 | 0.00 |
| 8993.00 | 9164.14 | Leonard C | 0.00 | 0.00 |






Company: Devon Energy
Field: Eddy County, New Mexico (NAD 83)
Location: Snapping 12-1 FED
Well: 533H
OH
Plan: Plan 1
GL 3280 + 23' KB @ 3303.00usft



Azimuths to Grid North
True North: -0.32°
Magnetic North: 6.67°
Magnetic Field
Strength: 47794.8snT
Dip Angle: 59.88°
Date: 9/27/2017
Model: IGRF2015



NM OIL CONSERVATION
ARTESIA DISTRICT

FEB 28 2017

RECEIVED

Devon Energy

Eddy County, New Mexico (NAD 83)

Snapping 12-1 FED

533H

OH

Plan: Plan 1

Standard Planning Report

28 September, 2017

Planning Report

Database: EDM 5000.14 Single User Db
Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Site: Snapping 12-1 FED
Well: 533H
Wellbore: OH
Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

| | | | |
|--------------------|----------------------------------|----------------------|----------------|
| Project | Eddy County, New Mexico (NAD 83) | | |
| Map System: | US State Plane 1983 | System Datum: | Mean Sea Level |
| Geo Datum: | North American Datum 1983 | | |
| Map Zone: | New Mexico Eastern Zone | | |

| | | | | | |
|-----------------------|-----------|-------------------|-----------------|-------------------|-------------|
| Site | | Snapping 12-1 FED | | | |
| Site Position: | | Northing: | 385,529.86 usft | Latitude: | 32.058487 |
| From: | Map | Easting: | 726,878.08 usft | Longitude: | -103.734417 |
| Position Uncertainty: | 0.00 usft | Slot Radius: | 13-3/16 " | Grid Convergence: | 0.32 ° |

| | | | | | | |
|----------------------|-------|------------|---------------------|-----------------|---------------|---------------|
| Well | 533H | | | | | |
| Well Position | +N/-S | 0.18 usft | Northing: | 385,530.04 usft | Latitude: | 32.058487 |
| | +E/-W | 29.99 usft | Easting: | 726,908.07 usft | Longitude: | -103.734320 |
| Position Uncertainty | | 0.00 usft | Wellhead Elevation: | | Ground Level: | 3,280.00 usft |

| | | | | | |
|-----------------|----|--|--|--|--|
| Wellbore | OH | | | | |
|-----------------|----|--|--|--|--|

| Magnetics | Model Name | Sample Date | Declination (°) | Dip Angle (°) | Field Strength (nT) |
|-----------|------------|-------------|-----------------|---------------|---------------------|
| | IGRF2015 | 9/27/2017 | 6.99 | 59.88 | 47,794.81446663 |

| | | | | | |
|---------------|--------|--|--|--|--|
| Design | Plan 1 | | | | |
|---------------|--------|--|--|--|--|

Audit Notes:

| | | | | | |
|-----------------|--|---------------|------|----------------------|------|
| Version: | | Phase: | PLAN | Tie On Depth: | 0.00 |
|-----------------|--|---------------|------|----------------------|------|

| Vertical Section: | Depth From (TVD) (usft) | +N/-S (usft) | +E/-W (usft) | Direction (°) |
|-------------------|----------------------------|-----------------|-----------------|------------------|
| | 0.00 | 0.00 | 0.00 | 0.00 |

| Plan Survey Tool Program | | Date | 9/28/2017 | | |
|--------------------------|--------------------|-----------------------|-----------|---------------------|--|
| Depth From (usft) | Depth To (usft) | Survey (Wellbore) | Tool Name | Remarks | |
| 1 | 0.00 | 16,378.88 Plan 1 (OH) | MWD | OWSG MWD - Standard | |

| Plan Sections | | | | | | | | | | |
|-----------------------------|--------------------|----------------|-----------------------------|-----------------|-----------------|-------------------------------|------------------------------|-----------------------------|------------|------------|
| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) | TFO (°) | Target |
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 1,200.00 | 0.00 | 0.00 | 1,200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 1,722.13 | 6.00 | 131.39 | 1,721.17 | -18.07 | 20.51 | 1.15 | 1.15 | 0.00 | 131.39 | |
| 4,525.16 | 6.00 | 131.39 | 4,508.83 | -211.93 | 240.49 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 5,047.29 | 0.00 | 0.00 | 5,030.00 | -230.00 | 261.00 | 1.15 | -1.15 | 0.00 | 180.00 | |
| 8,552.82 | 0.00 | 0.00 | 8,535.54 | -230.00 | 261.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 9,302.82 | 90.00 | 360.00 | 9,013.00 | 247.46 | 260.99 | 12.00 | 12.00 | 0.00 | 360.00 | |
| 16,379.26 | 90.00 | 360.00 | 9,013.00 | 7,323.90 | 260.78 | 0.00 | 0.00 | 0.00 | 0.00 | BHL - 533H |

Planning Report

Database: EDM 5000.14 Single User Db
Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Site: Snapping 12-1 FED
Well: 533H
Wellbore: OH
Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
|-----------------------------|--------------------|----------------|-----------------------------|-----------------|-----------------|-------------------------------|-------------------------------|------------------------------|-----------------------------|
| 1,200.00 | 0.00 | 0.00 | 1,200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,300.00 | 1.15 | 131.39 | 1,299.99 | -0.66 | 0.75 | -0.66 | 1.15 | 1.15 | 0.00 |
| 1,400.00 | 2.30 | 131.39 | 1,399.95 | -2.65 | 3.01 | -2.65 | 1.15 | 1.15 | 0.00 |
| 1,500.00 | 3.45 | 131.39 | 1,499.82 | -5.97 | 6.77 | -5.97 | 1.15 | 1.15 | 0.00 |
| 1,600.00 | 4.60 | 131.39 | 1,599.57 | -10.61 | 12.04 | -10.61 | 1.15 | 1.15 | 0.00 |
| 1,700.00 | 5.75 | 131.39 | 1,699.16 | -16.57 | 18.81 | -16.57 | 1.15 | 1.15 | 0.00 |
| 1,722.13 | 6.00 | 131.39 | 1,721.17 | -18.07 | 20.51 | -18.07 | 1.15 | 1.15 | 0.00 |
| 1,800.00 | 6.00 | 131.39 | 1,798.62 | -23.46 | 26.62 | -23.46 | 0.00 | 0.00 | 0.00 |
| 1,900.00 | 6.00 | 131.39 | 1,898.07 | -30.37 | 34.47 | -30.37 | 0.00 | 0.00 | 0.00 |
| 2,000.00 | 6.00 | 131.39 | 1,997.52 | -37.29 | 42.32 | -37.29 | 0.00 | 0.00 | 0.00 |
| 2,100.00 | 6.00 | 131.39 | 2,096.97 | -44.21 | 50.16 | -44.21 | 0.00 | 0.00 | 0.00 |
| 2,200.00 | 6.00 | 131.39 | 2,196.42 | -51.12 | 58.01 | -51.12 | 0.00 | 0.00 | 0.00 |
| 2,300.00 | 6.00 | 131.39 | 2,295.87 | -58.04 | 65.86 | -58.04 | 0.00 | 0.00 | 0.00 |
| 2,400.00 | 6.00 | 131.39 | 2,395.33 | -64.95 | 73.71 | -64.95 | 0.00 | 0.00 | 0.00 |
| 2,500.00 | 6.00 | 131.39 | 2,494.78 | -71.87 | 81.56 | -71.87 | 0.00 | 0.00 | 0.00 |
| 2,600.00 | 6.00 | 131.39 | 2,594.23 | -78.78 | 89.40 | -78.78 | 0.00 | 0.00 | 0.00 |
| 2,700.00 | 6.00 | 131.39 | 2,693.68 | -85.70 | 97.25 | -85.70 | 0.00 | 0.00 | 0.00 |
| 2,800.00 | 6.00 | 131.39 | 2,793.13 | -92.62 | 105.10 | -92.62 | 0.00 | 0.00 | 0.00 |
| 2,900.00 | 6.00 | 131.39 | 2,892.58 | -99.53 | 112.95 | -99.53 | 0.00 | 0.00 | 0.00 |
| 3,000.00 | 6.00 | 131.39 | 2,992.03 | -106.45 | 120.80 | -106.45 | 0.00 | 0.00 | 0.00 |
| 3,100.00 | 6.00 | 131.39 | 3,091.49 | -113.36 | 128.64 | -113.36 | 0.00 | 0.00 | 0.00 |
| 3,200.00 | 6.00 | 131.39 | 3,190.94 | -120.28 | 136.49 | -120.28 | 0.00 | 0.00 | 0.00 |
| 3,300.00 | 6.00 | 131.39 | 3,290.39 | -127.20 | 144.34 | -127.20 | 0.00 | 0.00 | 0.00 |
| 3,400.00 | 6.00 | 131.39 | 3,389.84 | -134.11 | 152.19 | -134.11 | 0.00 | 0.00 | 0.00 |
| 3,500.00 | 6.00 | 131.39 | 3,489.29 | -141.03 | 160.04 | -141.03 | 0.00 | 0.00 | 0.00 |
| 3,600.00 | 6.00 | 131.39 | 3,588.74 | -147.94 | 167.88 | -147.94 | 0.00 | 0.00 | 0.00 |
| 3,700.00 | 6.00 | 131.39 | 3,688.19 | -154.86 | 175.73 | -154.86 | 0.00 | 0.00 | 0.00 |
| 3,800.00 | 6.00 | 131.39 | 3,787.65 | -161.78 | 183.58 | -161.78 | 0.00 | 0.00 | 0.00 |
| 3,900.00 | 6.00 | 131.39 | 3,887.10 | -168.69 | 191.43 | -168.69 | 0.00 | 0.00 | 0.00 |
| 4,000.00 | 6.00 | 131.39 | 3,986.55 | -175.61 | 199.28 | -175.61 | 0.00 | 0.00 | 0.00 |
| 4,100.00 | 6.00 | 131.39 | 4,086.00 | -182.52 | 207.13 | -182.52 | 0.00 | 0.00 | 0.00 |
| 4,200.00 | 6.00 | 131.39 | 4,185.45 | -189.44 | 214.97 | -189.44 | 0.00 | 0.00 | 0.00 |
| 4,300.00 | 6.00 | 131.39 | 4,284.90 | -196.36 | 222.82 | -196.36 | 0.00 | 0.00 | 0.00 |
| 4,400.00 | 6.00 | 131.39 | 4,384.35 | -203.27 | 230.67 | -203.27 | 0.00 | 0.00 | 0.00 |
| 4,500.00 | 6.00 | 131.39 | 4,483.80 | -210.19 | 238.52 | -210.19 | 0.00 | 0.00 | 0.00 |
| 4,525.16 | 6.00 | 131.39 | 4,508.83 | -211.93 | 240.49 | -211.93 | 0.00 | 0.00 | 0.00 |
| 4,600.00 | 5.14 | 131.39 | 4,583.31 | -216.73 | 245.95 | -216.73 | 1.15 | -1.15 | 0.00 |
| 4,700.00 | 3.99 | 131.39 | 4,682.99 | -222.00 | 251.92 | -222.00 | 1.15 | -1.15 | 0.00 |
| 4,800.00 | 2.84 | 131.39 | 4,782.81 | -225.94 | 256.40 | -225.94 | 1.15 | -1.15 | 0.00 |
| 4,900.00 | 1.69 | 131.39 | 4,882.73 | -228.56 | 259.37 | -228.56 | 1.15 | -1.15 | 0.00 |
| 5,000.00 | 0.54 | 131.39 | 4,982.71 | -229.85 | 260.83 | -229.85 | 1.15 | -1.15 | 0.00 |
| 5,047.29 | 0.00 | 0.00 | 5,030.00 | -230.00 | 261.00 | -230.00 | 1.15 | -1.15 | 0.00 |
| 5,100.00 | 0.00 | 0.00 | 5,082.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,200.00 | 0.00 | 0.00 | 5,182.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,300.00 | 0.00 | 0.00 | 5,282.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,400.00 | 0.00 | 0.00 | 5,382.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,500.00 | 0.00 | 0.00 | 5,482.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,600.00 | 0.00 | 0.00 | 5,582.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,700.00 | 0.00 | 0.00 | 5,682.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,800.00 | 0.00 | 0.00 | 5,782.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 5,900.00 | 0.00 | 0.00 | 5,882.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,000.00 | 0.00 | 0.00 | 5,982.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,100.00 | 0.00 | 0.00 | 6,082.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |

Planning Report

Database: EDM 5000.14 Single User Db
Company: Devon Energy
Project: Eddy County, New Mexico (NAD 83)
Site: Snapping 12-1 FED
Well: 533H
Wellbore: OH
Design: Plan 1

Local Co-ordinate Reference: Well 533H
TVD Reference: GL 3280 + 23' KB @ 3303.00usft
MD Reference: GL 3280 + 23' KB @ 3303.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
|-----------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| 6,200.00 | 0.00 | 0.00 | 6,182.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,300.00 | 0.00 | 0.00 | 6,282.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,400.00 | 0.00 | 0.00 | 6,382.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,500.00 | 0.00 | 0.00 | 6,482.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,600.00 | 0.00 | 0.00 | 6,582.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,700.00 | 0.00 | 0.00 | 6,682.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,800.00 | 0.00 | 0.00 | 6,782.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 6,900.00 | 0.00 | 0.00 | 6,882.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,000.00 | 0.00 | 0.00 | 6,982.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,100.00 | 0.00 | 0.00 | 7,082.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,200.00 | 0.00 | 0.00 | 7,182.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,300.00 | 0.00 | 0.00 | 7,282.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,400.00 | 0.00 | 0.00 | 7,382.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,500.00 | 0.00 | 0.00 | 7,482.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,600.00 | 0.00 | 0.00 | 7,582.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,700.00 | 0.00 | 0.00 | 7,682.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,800.00 | 0.00 | 0.00 | 7,782.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 7,900.00 | 0.00 | 0.00 | 7,882.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,000.00 | 0.00 | 0.00 | 7,982.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,100.00 | 0.00 | 0.00 | 8,082.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,200.00 | 0.00 | 0.00 | 8,182.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,300.00 | 0.00 | 0.00 | 8,282.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,400.00 | 0.00 | 0.00 | 8,382.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,500.00 | 0.00 | 0.00 | 8,482.71 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,552.82 | 0.00 | 0.00 | 8,535.54 | -230.00 | 261.00 | -230.00 | 0.00 | 0.00 | 0.00 |
| 8,600.00 | 5.66 | 360.00 | 8,582.64 | -227.67 | 261.00 | -227.67 | 12.00 | 12.00 | 0.00 |
| 8,700.00 | 17.66 | 360.00 | 8,680.39 | -207.50 | 261.00 | -207.50 | 12.00 | 12.00 | 0.00 |
| 8,800.00 | 29.66 | 360.00 | 8,771.82 | -167.44 | 261.00 | -167.44 | 12.00 | 12.00 | 0.00 |
| 8,900.00 | 41.66 | 360.00 | 8,852.92 | -109.24 | 261.00 | -109.24 | 12.00 | 12.00 | 0.00 |
| 9,000.00 | 53.66 | 360.00 | 8,920.15 | -35.46 | 260.99 | -35.46 | 12.00 | 12.00 | 0.00 |
| 9,100.00 | 65.66 | 360.00 | 8,970.57 | 50.69 | 260.99 | 50.69 | 12.00 | 12.00 | 0.00 |
| 9,200.00 | 77.66 | 360.00 | 9,001.97 | 145.43 | 260.99 | 145.43 | 12.00 | 12.00 | 0.00 |
| 9,300.00 | 89.66 | 360.00 | 9,012.99 | 244.64 | 260.99 | 244.64 | 12.00 | 12.00 | 0.00 |
| 9,302.82 | 90.00 | 360.00 | 9,013.00 | 247.46 | 260.99 | 247.46 | 12.00 | 12.00 | 0.00 |
| 9,400.00 | 90.00 | 360.00 | 9,013.00 | 344.64 | 260.98 | 344.64 | 0.00 | 0.00 | 0.00 |
| 9,500.00 | 90.00 | 360.00 | 9,013.00 | 444.64 | 260.98 | 444.64 | 0.00 | 0.00 | 0.00 |
| 9,600.00 | 90.00 | 360.00 | 9,013.00 | 544.64 | 260.98 | 544.64 | 0.00 | 0.00 | 0.00 |
| 9,700.00 | 90.00 | 360.00 | 9,013.00 | 644.64 | 260.97 | 644.64 | 0.00 | 0.00 | 0.00 |
| 9,800.00 | 90.00 | 360.00 | 9,013.00 | 744.64 | 260.97 | 744.64 | 0.00 | 0.00 | 0.00 |
| 9,900.00 | 90.00 | 360.00 | 9,013.00 | 844.64 | 260.97 | 844.64 | 0.00 | 0.00 | 0.00 |
| 10,000.00 | 90.00 | 360.00 | 9,013.00 | 944.64 | 260.97 | 944.64 | 0.00 | 0.00 | 0.00 |
| 10,100.00 | 90.00 | 360.00 | 9,013.00 | 1,044.64 | 260.96 | 1,044.64 | 0.00 | 0.00 | 0.00 |
| 10,200.00 | 90.00 | 360.00 | 9,013.00 | 1,144.64 | 260.96 | 1,144.64 | 0.00 | 0.00 | 0.00 |
| 10,300.00 | 90.00 | 360.00 | 9,013.00 | 1,244.64 | 260.96 | 1,244.64 | 0.00 | 0.00 | 0.00 |
| 10,400.00 | 90.00 | 360.00 | 9,013.00 | 1,344.64 | 260.95 | 1,344.64 | 0.00 | 0.00 | 0.00 |
| 10,500.00 | 90.00 | 360.00 | 9,013.00 | 1,444.64 | 260.95 | 1,444.64 | 0.00 | 0.00 | 0.00 |
| 10,600.00 | 90.00 | 360.00 | 9,013.00 | 1,544.64 | 260.95 | 1,544.64 | 0.00 | 0.00 | 0.00 |
| 10,700.00 | 90.00 | 360.00 | 9,013.00 | 1,644.64 | 260.95 | 1,644.64 | 0.00 | 0.00 | 0.00 |
| 10,800.00 | 90.00 | 360.00 | 9,013.00 | 1,744.64 | 260.94 | 1,744.64 | 0.00 | 0.00 | 0.00 |
| 10,900.00 | 90.00 | 360.00 | 9,013.00 | 1,844.64 | 260.94 | 1,844.64 | 0.00 | 0.00 | 0.00 |
| 11,000.00 | 90.00 | 360.00 | 9,013.00 | 1,944.64 | 260.94 | 1,944.64 | 0.00 | 0.00 | 0.00 |
| 11,100.00 | 90.00 | 360.00 | 9,013.00 | 2,044.64 | 260.93 | 2,044.64 | 0.00 | 0.00 | 0.00 |
| 11,200.00 | 90.00 | 360.00 | 9,013.00 | 2,144.64 | 260.93 | 2,144.64 | 0.00 | 0.00 | 0.00 |
| 11,300.00 | 90.00 | 360.00 | 9,013.00 | 2,244.64 | 260.93 | 2,244.64 | 0.00 | 0.00 | 0.00 |

Planning Report

| | | | |
|------------------|----------------------------------|-------------------------------------|--------------------------------|
| Database: | EDM 5000.14 Single User Db | Local Co-ordinate Reference: | Well 533H |
| Company: | Devon Energy | TVD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Project: | Eddy County, New Mexico (NAD 83) | MD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Site: | Snapping 12-1 FED | North Reference: | Grid |
| Well: | 533H | Survey Calculation Method: | Minimum Curvature |
| Wellbore: | OH | | |
| Design: | Plan 1 | | |

Planned Survey

| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
|-----------------------------|--------------------|----------------|-----------------------------|-----------------|-----------------|-------------------------------|-------------------------------|------------------------------|-----------------------------|
| 11,400.00 | 90.00 | 360.00 | 9,013.00 | 2,344.64 | 260.93 | 2,344.64 | 0.00 | 0.00 | 0.00 |
| 11,500.00 | 90.00 | 360.00 | 9,013.00 | 2,444.64 | 260.92 | 2,444.64 | 0.00 | 0.00 | 0.00 |
| 11,600.00 | 90.00 | 360.00 | 9,013.00 | 2,544.64 | 260.92 | 2,544.64 | 0.00 | 0.00 | 0.00 |
| 11,700.00 | 90.00 | 360.00 | 9,013.00 | 2,644.64 | 260.92 | 2,644.64 | 0.00 | 0.00 | 0.00 |
| 11,800.00 | 90.00 | 360.00 | 9,013.00 | 2,744.64 | 260.91 | 2,744.64 | 0.00 | 0.00 | 0.00 |
| 11,900.00 | 90.00 | 360.00 | 9,013.00 | 2,844.64 | 260.91 | 2,844.64 | 0.00 | 0.00 | 0.00 |
| 12,000.00 | 90.00 | 360.00 | 9,013.00 | 2,944.64 | 260.91 | 2,944.64 | 0.00 | 0.00 | 0.00 |
| 12,100.00 | 90.00 | 360.00 | 9,013.00 | 3,044.64 | 260.90 | 3,044.64 | 0.00 | 0.00 | 0.00 |
| 12,200.00 | 90.00 | 360.00 | 9,013.00 | 3,144.64 | 260.90 | 3,144.64 | 0.00 | 0.00 | 0.00 |
| 12,300.00 | 90.00 | 360.00 | 9,013.00 | 3,244.64 | 260.90 | 3,244.64 | 0.00 | 0.00 | 0.00 |
| 12,400.00 | 90.00 | 360.00 | 9,013.00 | 3,344.64 | 260.90 | 3,344.64 | 0.00 | 0.00 | 0.00 |
| 12,500.00 | 90.00 | 360.00 | 9,013.00 | 3,444.64 | 260.89 | 3,444.64 | 0.00 | 0.00 | 0.00 |
| 12,600.00 | 90.00 | 360.00 | 9,013.00 | 3,544.64 | 260.89 | 3,544.64 | 0.00 | 0.00 | 0.00 |
| 12,700.00 | 90.00 | 360.00 | 9,013.00 | 3,644.64 | 260.89 | 3,644.64 | 0.00 | 0.00 | 0.00 |
| 12,800.00 | 90.00 | 360.00 | 9,013.00 | 3,744.64 | 260.88 | 3,744.64 | 0.00 | 0.00 | 0.00 |
| 12,900.00 | 90.00 | 360.00 | 9,013.00 | 3,844.64 | 260.88 | 3,844.64 | 0.00 | 0.00 | 0.00 |
| 13,000.00 | 90.00 | 360.00 | 9,013.00 | 3,944.64 | 260.88 | 3,944.64 | 0.00 | 0.00 | 0.00 |
| 13,100.00 | 90.00 | 360.00 | 9,013.00 | 4,044.64 | 260.88 | 4,044.64 | 0.00 | 0.00 | 0.00 |
| 13,200.00 | 90.00 | 360.00 | 9,013.00 | 4,144.64 | 260.87 | 4,144.64 | 0.00 | 0.00 | 0.00 |
| 13,300.00 | 90.00 | 360.00 | 9,013.00 | 4,244.64 | 260.87 | 4,244.64 | 0.00 | 0.00 | 0.00 |
| 13,400.00 | 90.00 | 360.00 | 9,013.00 | 4,344.64 | 260.87 | 4,344.64 | 0.00 | 0.00 | 0.00 |
| 13,500.00 | 90.00 | 360.00 | 9,013.00 | 4,444.64 | 260.86 | 4,444.64 | 0.00 | 0.00 | 0.00 |
| 13,600.00 | 90.00 | 360.00 | 9,013.00 | 4,544.64 | 260.86 | 4,544.64 | 0.00 | 0.00 | 0.00 |
| 13,700.00 | 90.00 | 360.00 | 9,013.00 | 4,644.64 | 260.86 | 4,644.64 | 0.00 | 0.00 | 0.00 |
| 13,800.00 | 90.00 | 360.00 | 9,013.00 | 4,744.64 | 260.86 | 4,744.64 | 0.00 | 0.00 | 0.00 |
| 13,900.00 | 90.00 | 360.00 | 9,013.00 | 4,844.64 | 260.85 | 4,844.64 | 0.00 | 0.00 | 0.00 |
| 14,000.00 | 90.00 | 360.00 | 9,013.00 | 4,944.64 | 260.85 | 4,944.64 | 0.00 | 0.00 | 0.00 |
| 14,100.00 | 90.00 | 360.00 | 9,013.00 | 5,044.64 | 260.85 | 5,044.64 | 0.00 | 0.00 | 0.00 |
| 14,200.00 | 90.00 | 360.00 | 9,013.00 | 5,144.64 | 260.84 | 5,144.64 | 0.00 | 0.00 | 0.00 |
| 14,300.00 | 90.00 | 360.00 | 9,013.00 | 5,244.64 | 260.84 | 5,244.64 | 0.00 | 0.00 | 0.00 |
| 14,400.00 | 90.00 | 360.00 | 9,013.00 | 5,344.64 | 260.84 | 5,344.64 | 0.00 | 0.00 | 0.00 |
| 14,500.00 | 90.00 | 360.00 | 9,013.00 | 5,444.64 | 260.83 | 5,444.64 | 0.00 | 0.00 | 0.00 |
| 14,600.00 | 90.00 | 360.00 | 9,013.00 | 5,544.64 | 260.83 | 5,544.64 | 0.00 | 0.00 | 0.00 |
| 14,700.00 | 90.00 | 360.00 | 9,013.00 | 5,644.64 | 260.83 | 5,644.64 | 0.00 | 0.00 | 0.00 |
| 14,800.00 | 90.00 | 360.00 | 9,013.00 | 5,744.64 | 260.83 | 5,744.64 | 0.00 | 0.00 | 0.00 |
| 14,900.00 | 90.00 | 360.00 | 9,013.00 | 5,844.64 | 260.82 | 5,844.64 | 0.00 | 0.00 | 0.00 |
| 15,000.00 | 90.00 | 360.00 | 9,013.00 | 5,944.64 | 260.82 | 5,944.64 | 0.00 | 0.00 | 0.00 |
| 15,100.00 | 90.00 | 360.00 | 9,013.00 | 6,044.64 | 260.82 | 6,044.64 | 0.00 | 0.00 | 0.00 |
| 15,200.00 | 90.00 | 360.00 | 9,013.00 | 6,144.64 | 260.81 | 6,144.64 | 0.00 | 0.00 | 0.00 |
| 15,300.00 | 90.00 | 360.00 | 9,013.00 | 6,244.64 | 260.81 | 6,244.64 | 0.00 | 0.00 | 0.00 |
| 15,400.00 | 90.00 | 360.00 | 9,013.00 | 6,344.64 | 260.81 | 6,344.64 | 0.00 | 0.00 | 0.00 |
| 15,500.00 | 90.00 | 360.00 | 9,013.00 | 6,444.64 | 260.81 | 6,444.64 | 0.00 | 0.00 | 0.00 |
| 15,600.00 | 90.00 | 360.00 | 9,013.00 | 6,544.64 | 260.80 | 6,544.64 | 0.00 | 0.00 | 0.00 |
| 15,700.00 | 90.00 | 360.00 | 9,013.00 | 6,644.64 | 260.80 | 6,644.64 | 0.00 | 0.00 | 0.00 |
| 15,800.00 | 90.00 | 360.00 | 9,013.00 | 6,744.64 | 260.80 | 6,744.64 | 0.00 | 0.00 | 0.00 |
| 15,900.00 | 90.00 | 360.00 | 9,013.00 | 6,844.64 | 260.79 | 6,844.64 | 0.00 | 0.00 | 0.00 |
| 16,000.00 | 90.00 | 360.00 | 9,013.00 | 6,944.64 | 260.79 | 6,944.64 | 0.00 | 0.00 | 0.00 |
| 16,100.00 | 90.00 | 360.00 | 9,013.00 | 7,044.64 | 260.79 | 7,044.64 | 0.00 | 0.00 | 0.00 |
| 16,200.00 | 90.00 | 360.00 | 9,013.00 | 7,144.64 | 260.79 | 7,144.64 | 0.00 | 0.00 | 0.00 |
| 16,300.00 | 90.00 | 360.00 | 9,013.00 | 7,244.64 | 260.78 | 7,244.64 | 0.00 | 0.00 | 0.00 |
| 16,379.26 | 90.00 | 360.00 | 9,013.00 | 7,323.90 | 260.78 | 7,323.90 | 0.00 | 0.00 | 0.00 |

Planning Report

| | | | |
|------------------|----------------------------------|-------------------------------------|--------------------------------|
| Database: | EDM 5000.14 Single User Db | Local Co-ordinate Reference: | Well 533H |
| Company: | Devon Energy | TVD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Project: | Eddy County, New Mexico (NAD 83) | MD Reference: | GL 3280 + 23' KB @ 3303.00usft |
| Site: | Snapping 12-1 FED | North Reference: | Grid |
| Well: | 533H | Survey Calculation Method: | Minimum Curvature |
| Wellbore: | OH | | |
| Design: | Plan 1 | | |

Design Targets

| Target Name - hit/miss target - Shape | Dip Angle (°) | Dip Dir. (°) | TVD (usft) | +N/-S (usft) | +E/-W (usft) | Northing (usft) | Easting (usft) | Latitude | Longitude |
|--|------------------|-----------------|---------------|-----------------|-----------------|--------------------|-------------------|-----------|-------------|
| BHL - 533H - plan hits target center - Point | 0.00 | 0.00 | 9,013.00 | 7,323.90 | 260.78 | 392,853.94 | 727,168.85 | 32.078615 | -103.733347 |

Formations


| Measured Depth (usft) | Vertical Depth (usft) | Name | Lithology | Dip (°) | Dip Direction (°) |
|-----------------------------|-----------------------------|---------------|-----------|------------|-------------------------|
| 903.00 | 903.00 | Rustler | | 0.00 | 0.00 |
| 1,253.00 | 1,253.00 | Salado | | 0.00 | 0.00 |
| 4,011.52 | 3,998.00 | Base of Salt | | 0.00 | 0.00 |
| 4,232.73 | 4,218.00 | Delaware | | 0.00 | 0.00 |
| 4,262.89 | 4,248.00 | Bell Canyon | | 0.00 | 0.00 |
| 5,250.29 | 5,233.00 | Cherry Canyon | | 0.00 | 0.00 |
| 6,590.29 | 6,573.00 | Brushy Canyon | | 0.00 | 0.00 |
| 8,265.29 | 8,248.00 | 1st BSPG Lime | | 0.00 | 0.00 |
| 9,164.14 | 8,993.00 | Leonard C | | 0.00 | 0.00 |

Plan Annotations

| Measured Depth (usft) | Vertical Depth (usft) | Local Coordinates | | Comment |
|-----------------------------|-----------------------------|-------------------|-----------------|------------------------|
| | | +N/-S (usft) | +E/-W (usft) | |
| 1,200.00 | 1,200.00 | 0.00 | 0.00 | Start Nudge Build 1.15 |
| 1,722.13 | 1,721.17 | -18.07 | 20.51 | EOB 6° at 1722.13 MD |
| 4,525.16 | 4,508.83 | -211.93 | 240.49 | Start Drop -1.15 |
| 5,047.29 | 5,030.00 | -230.00 | 261.00 | Vertical at 5047.29 MD |
| 8,552.82 | 8,535.54 | -230.00 | 261.00 | Start Build 12.00 |
| 9,302.82 | 9,013.00 | 247.46 | 260.99 | LP 90° at 9302.82 MD |
| 16,379.26 | 9,013.00 | 7,323.90 | 260.78 | TD at 16379.26 |



Commitment Runs Deep



Design Plan
Operation and Maintenance Plan
Closure Plan

SENM - Closed Loop Systems
June 2010

I. Design Plan

Devon uses MI SWACO closed loop system (CLS). The MI SWACO CLS is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This insures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

Prior to installing a closed-loop system on site, the topsoil, if present, will be stripped and stockpiled for use as the final cover or fill at the time of closure.

Signs will be posted on the fence surrounding the closed-loop system unless the closed-loop system is located on a site where there is an existing well, that is operated by Devon.


II. Operations and Maintenance Plan

Primary Shakers: The primary shakers make the first removal of drill solids from the drilling mud as it leaves the well bore. The shakers are sized to handle maximum drilling rate at optimal screen size. The shakers normally remove solids down to 74 microns.

Mud Cleaner: The Mud Cleaner cleans the fluid after it leaves the shakers. A set of hydrocyclones are sized to handle 1.25 to 1.5 times the maximum circulating rate. This ensures all the fluid is being processed to an average cut point of 25 microns. The wet discharged is dewatered on a shaker equipped with ultra fine mesh screens and generally cut at 40 microns.



Closed Loop Schematic



Centrifuges: The centrifuges can be one or two in number depending on the well geometry or depth of well. The centrifuges are sized to maintain low gravity solids at 5% or below. They may or may not need a dewatering system to enhance the removal rates. The centrifuges can make a cut point of 8-10 microns depending on bowl speed, feed rate, solids loading and other factors.

The centrifuge system is designed to work on the active system and be flexible to process incoming fluids from other locations. This set-up is also dependant on well factors.

Dewatering System: The dewatering system is a chemical mixing and dosing system designed to enhance the solids removal of the centrifuge. Not commonly used in shallow wells. It may contain pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing. Chemical flocculation binds ultra fine solids into a mass that is within the centrifuge operating design. The

dewatering system improves the centrifuge cut point to infinity or allows for the return of clear water or brine fluid. This ability allows for the ultimate control of low gravity solids.

Cuttings Boxes: Cuttings boxes are utilized to capture drill solids that are discarded from the solids control equipment. These boxes are set upon a rail system that allows for the removal and replacement of a full box of cuttings with an empty one. They are equipped with a cover that insures no product is spilled into the environment during the transportation phase.

Process Tank: (Optional) The process tank allows for the holding and process of fluids that are being transferred into the mud system. Additionally, during times of lost circulation the process tank may hold active fluids that are removed for additional treatment. It can further be used as a mixing tank during well control conditions.

Sump and Sump Pump: The sump is used to collect storm water and the pump is used to transfer this fluid to the active system or to the tank for to hold in reserve. It can also be used to collect fluids that may escape during spills. The location contains drainage ditches that allow the location fluids to drain to the sump.

Reserve Fluids (Tank Farm): A series of frac tanks are used to replace the reserve pit. These are steel tanks that are equipped with a manifold system and a transfer pump. These tanks can contain any number of fluids used during the drilling process. These can include fresh water, cut brine, and saturated salt fluid. The fluid can be from the active well or reclaimed fluid from other locations. A 20 ml liner and berm system is employed to ensure the fluids do not migrate to the environment during a spill.

If a leak develops, the appropriate division district office will be notified within 48 hours of the discovery and the leak will be addressed. Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and testing will be performed to determine if a release has occurred.

All trash is kept in a wire mesh enclosure and removed to an approved landfill when full. All spent motor oils are kept in separate containers and they are removed and sent to an approved recycling center. Any spilled lubricants, pipe

dope, or regulated chemicals are removed from soil and sent to landfills approved for these products.

These operations are monitored by Mi Swaco service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

A MI SWACO field supervisor manages from 3-5 wells. They are responsible for training personnel, supervising installations, and inspecting sites for compliance of MI SWACO safety and operational policy.

III. Closure Plan

A maximum 340' X 340' caliche pad is built per well. All of the trucks and steel tanks fit on this pad. All fluid cuttings go to the steel tanks to be hauled by various trucking companies to an agency approved disposal.

A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Devon proposes using a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.


- Wellhead will be installed by wellhead representatives.
- If the welding is performed by a third party, the wellhead representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- Wellhead representative will install the test plug for the initial BOP test.
- Wellhead company will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 3M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.
- If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.
- Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.
- Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.

After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the wellhead system and will undergo a 250 psi low pressure test followed by a 3,000 psi high pressure test. The 3,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.

After running the 9-5/8" intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 3M will already be installed on the wellhead.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.

Devon's proposed wellhead manufactures will be FMC Technologies, Cactus Wellhead, or Cameron.



1. Geologic Formations

| | | | |
|---------------|--------|-------------------------------|-----|
| TVD of target | 9,013 | Pilot hole depth | |
| MD at TD: | 16,379 | Deepest expected fresh water: | 400 |

Basin

[illegible]

*H₂S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program

| Hole Size | Casing Interval | | Csg. Size | Weight (lbs) | Grade | Conn. | SF Collapse | SF Burst | SF Tension |
|-----------|-----------------|---------|-----------|---------------------------|-------|-------|-------------|----------|--------------------|
| | From | To | | | | | | | |
| 17.5" | 0 | 960' | 13.375" | 48 | H-40 | STC | 1.74 | 2.45 | 4.13 |
| 12.25" | 0 | 4,150' | 9.625" | 40 | J-55 | LTC | 1.19 | 1.42 | 3.98 |
| 8.75" | 0 | 16,379' | 5.5" | 17 | P110 | BTC | 2.18 | 2.7 | 3.21 |
| | | | | BLM Minimum Safety Factor | | | 1.125 | 1 | 1.6 Dry 1.8 Wet |

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

Devon Energy Prod. Co., L.P./Snapping 12-1 Fed 533H

| | Y or N |
|--|---------------|
| Is casing new? If used, attach certification as required in Onshore Order #1 | Y |
| Does casing meet API specifications? If no, attach casing specification sheet. | Y |
| Is premium or uncommon casing planned? If yes attach casing specification sheet. | N |
| Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria). | Y |
| Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing? | Y |
| Is well located within Capitan Reef? | N |
| If yes, does production casing cement tie back a minimum of 50' above the Reef? | |
| Is well within the designated 4 string boundary. | |
| Is well located in SOPA but not in R-111-P? | N |
| If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing? | |
| Is well located in R-111-P and SOPA? | N |
| If yes, are the first three strings cemented to surface? | |
| Is 2 nd string set 100' to 600' below the base of salt? | |
| Is well located in high Cave/Karst? | N |
| If yes, are there two strings cemented to surface? | |
| (For 2 string wells) If yes, is there a contingency casing if lost circulation occurs? | |
| Is well located in critical Cave/Karst? | N |
| If yes, are there three strings cemented to surface? | |

Devon Energy Prod. Co., L.P./Snapping 12-1 Fed 533H

3. Cementing Program

| Casing | # Sks | Wt. lb/ gal | H ₂ O gal/sk | Yld ft ³ / sack | 500# Comp. Strength (hours) | Slurry Description |
|--------------------|-------|-------------------|----------------------------|----------------------------------|--------------------------------------|--|
| 13-3/8" Surface | 747 | 14.8 | 6.34 | 1.34 | 6 | Tail: Class C Cement + 1% Calcium Chloride |
| 9-5/8" Inter. | 694 | 12.9 | 9.81 | 1.85 | 14 | Lead: (65:35) Class C Cement: Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sack Poly-E-Flake |
| | 306 | 14.8 | 6.32 | 1.33 | 6 | Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake |
| 5-1/2" Prod | 478 | 9 | 13.5 | 3.27 | 21 | Lead: Tuned Light® Cement |
| | 1967 | 14.5 | 5.31 | 1.2 | 25 | Tail: (50:50) Class H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite |

| Casing String | TOC | % Excess |
|--------------------------|-------|----------|
| 13-3/8" Surface | 0' | 50% |
| 9-5/8" Intermediate | 0' | 30% |
| 5-1/2" Production Casing | 3950' | 25% |

4. Pressure Control Equipment

| | |
|--|--|
| | A variance is requested for the use of a diverter on the surface casing. See attached for schematic. |
|--|--|

| BOP installed and tested before drilling which hole? | Size? | Min. Required WP | Type | ✓ | Tested to: |
|--|---------|------------------|------------|---|-------------------------|
| 12-1/4" | 13-5/8" | 3M | Annular | x | 50% of working pressure |
| | | | Blind Ram | | 3M |
| | | | Pipe Ram | | |
| | | | Double Ram | | |
| | | | Other* | | |
| 8-3/4" | 13-5/8" | 3M | Annular | x | 50% testing pressure |
| | | | Blind Ram | x | 3M |
| | | | Pipe Ram | x | |
| | | | Double Ram | | |
| | | | Other* | | |
| | | | Annular | | |
| | | | Blind Ram | | |
| | | | Pipe Ram | | |
| | | | Double Ram | | |
| | | | Other* | | |

*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

| | |
|---|--|
| X | Formation integrity test will be performed per Onshore Order #2. |
|---|--|

Devon Energy Prod. Co., L.P./Snapping 12-1 Fed 533H

| | |
|------|---|
| | On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i. |
| | A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart. |
| Y /N | Are anchors required by manufacturer? |
| | A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. <ul style="list-style-type: none"> • Provide description here <p>See attached schematic.</p> |

5. Mud Program

| Depth | | Type | Weight (ppg) | Viscosity | Water Loss |
|-------|-------|-----------------|--------------|-----------|------------|
| From | To | | | | |
| 0 | 960 | FW Gel | 8.6-8.8 | 28-34 | N/C |
| 725 | 4150 | Saturated Brine | 10.0-10.2 | 28-34 | N/C |
| 4350 | 16379 | Cut Brine | 8.5-9.3 | 28-34 | N/C |

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

| | |
|---|-----------------------------|
| What will be used to monitor the loss or gain of fluid? | PVT/Pason/Visual Monitoring |
|---|-----------------------------|

6. Logging and Testing Procedures

| Logging, Coring and Testing. | |
|------------------------------|---|
| x | Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM. |
| | No Logs are planned based on well control or offset log information. |
| | Drill stem test? If yes, explain |
| | Coring? If yes, explain |

| Additional logs planned | Interval |
|-------------------------|-------------|
| | Resistivity |
| | Density |
| x | CBL |
| X | Mud log |

Devon Energy Prod. Co., L.P./Snapping 12-1 Fed 533H

| | | |
|--|-----|--|
| | PEX | |
|--|-----|--|

7. Drilling Conditions

| Condition | Specify what type and where? |
|----------------------------|------------------------------|
| BH Pressure at deepest TVD | 4056 psi |
| Abnormal Temperature | No |

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

| | |
|--|-------------------|
| Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM. | |
| | H2S is present |
| | H2S Plan attached |

8. Other facets of operation

Is this a walking operation? If yes, describe.

Will be pre-setting casing? If yes, describe.

Attachments

___ Directional Plan

___ Other, describe



Fluid Technology

ContiTech Beattie Corp.
Website: www.contitechbeattie.com

Monday, June 14, 2010

RE: Drilling & Production Hoses
Lifting & Safety Equipment

To Helmerich & Payne,

A Continental ContiTech hose assembly can perform as intended and suitable for the application regardless of whether the hose is secured or unsecured in its configuration. As a manufacturer of High Pressure Hose Assemblies for use in Drilling & Production, we do offer the corresponding lifting and safety equipment, this has the added benefit of easing the lifting and handling of each hose assembly whilst affording hose longevity by ensuring correct handling methods and procedures as well as securing the hose in the unlikely event of a failure; but in no way does the lifting and safety equipment affect the performance of the hoses providing the hoses have been handled and installed correctly. It is good practice to use lifting & safety equipment but not mandatory.


Should you have any questions or require any additional information/clarifications then please do not hesitate to contact us.

ContiTech Beattie is part of the Continental AG Corporation and can offer the full support resources associated with a global organization.

Best regards,

Robin Hodgson
Sales Manager
ContiTech Beattie Corp

ContiTech Beattie Corp,
11535 Brittmoore Park Drive,
Houston, TX 77041
Phone: +1 (832) 327-0141
Fax: +1 (832) 327-0148
www.contitechbeattie.com



RIG 212



QUALITY DOCUMENT

PHOENIX RUBBER
INDUSTRIAL LTD.5728 Szeged, Budapest út 10. Hungary • H-5701 Szeged, P. O. Box 152
Phone: (3662) 566-737 • Fax: (3662) 566-738SALES & MARKETING: H-1092 Budapest, Ráday u. 42-44. Hungary • H-1440 Budapest, P. O. Box 26
Phone: (361) 456-4200 • Fax: (361) 217-2872, 456-4273 • www.taurusermerge.hu

| | | | | | |
|---|-----------|--|---------|---------------------|--|
| QUALITY CONTROL INSPECTION AND TEST CERTIFICATE | | | | CERT. N°: 552 | |
| PURCHASER: Phoenix Beattie Co. | | | | P.O. N°: 1519FA-871 | |
| PHOENIX RUBBER order N°: 170466 | | HOSE TYPE: 3" ID Choke and Kill Hose | | | |
| HOSE SERIAL N°: 34128 | | NOMINAL / ACTUAL LENGTH: 11,43 m | | | |
| W.P. 68,96 MPa 10000 psi | | T.P. 103,4 MPa 15000 psi | | Duration: 60 min. | |
| Pressure test with water at ambient temperature <p style="text-align: center;">See attachment. (1 page)</p> | | | | | |
| ↑ 10 mm = 10 Min. → 10 mm = 25 MPa | | | | | |
| COUPLINGS | | | | | |
| Type | Serial N° | Quality | Heat N° | | |
| 3" coupling with 4 1/16" Flange end | 720 719 | AISI 4130 | C7626 | | |
| | | AISI 4130 | 47357 | | |
| | | | | | |
| | | | | | |
| API Spec 16 C Temperature rate: "B" | | | | | |
| All metal parts are flawless | | | | | |
| WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT. | | | | | |
| Date: | Inspector | Quality Control | | | |
| 29. April. 2002. | | PHOENIX RUBBER Industrial Ltd. Hose Inspection and VERIFIED TRUE COPY PHOENIX RUBBER G.C. | | | |

40920-0-00015 N6006

| | | | | | | |
|---|-----|--------|----|-------|----|----|
| 6 | GNL | +0.000 | PC | 14:00 | | |
| | RDL | +0.000 | PC | 14:00 | | |
| | DL | +1044 | DB | 14:00 | | |
| 7 | GNL | +0.000 | PC | 13:40 | | |
| | RDL | +0.000 | PC | 13:40 | 40 | 60 |
| | DL | +1047 | DB | 13:40 | | 80 |
| 6 | GNL | +0.000 | PC | 13:20 | | |
| | RDL | +0.000 | PC | 13:20 | | |
| | DL | +1050 | DB | 13:20 | | |
| 5 | GNL | +0.000 | PC | 13:00 | | |
| | RDL | +0.000 | PC | 13:00 | | |
| | DL | +1055 | DB | 13:00 | | |
| 4 | | | | | | |
| 3 | | | | | | |
| 2 | | | | | | |

JOHN J. RUBBER
Industrial Ltd.
Hose Inspection and
Certification Dept.

VERIFIED TRUE CO.
PHOENIX RUBBER CO.

Devon Energy
APD VARIANCE DATA

OPERATOR NAME: Devon Energy

1. SUMMARY OF Variance:

Devon Energy respectfully requests approval for the following additions to the drilling plan:

1. Potential utilization of a spudder rig to pre-set surface casing.

2. Description of Operations

1. A spudder rig contractor may move in their rig to drill the surface hole section and pre-set surface casing on this well.
 - a. After drilling the surface hole section, the rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - b. Rig will utilize fresh water based mud to drill surface hole to TD.
2. The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
3. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wingvalves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
4. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
5. Drilling operation will be performed with the big rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The BLM will be contacted / notified 24 hours before the big rig moves back on to the pad with the pre-set surface casing.
6. Devon Energy will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
7. Once the rig is removed, Devon Energy will secure the wellhead area by placing a guard rail around the cellar area.



APD ID: 10400022571

Submission Date: 10/02/2017

Highlighted data
reflects the most
recent changes

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

Snapping_12_1_Fed_523H_Ex_Access_Rd_20170927064930.pdf

Existing Road Purpose: ACCESS,FLUID TRANSPORT

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? YES

Existing Road Improvement Description: Improve road to accommodate Drilling and Completion operations.

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

Snapping_12_1_Fed_523H_Main_Access_Rd_20170927065109.pdf

Snapping_12_1_Fed_523H_ACCESS_Rd_20171222115905.pdf

New road type: COLLECTOR,RESOURCE

Length: 2843

Feet

Width (ft.): 30

Max slope (%): 6

Max grade (%): 4

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 30

New road access erosion control: Water Drainage Ditch

New road access plan or profile prepared? YES

New road access plan attachment:

Snapping_12_1_Fed_523H_ACCESS_Rd_20171222115923.pdf

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Access road engineering design? YES

Access road engineering design attachment:

Snapping_12_1_Fed_523H_ACCESS_Rd_20171222115952.pdf

Access surfacing type: GRAVEL

Access topsoil source: ONSITE

Access surfacing type description:

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: See Interim Reclamation diagram under SUPO Section 10

Access other construction information:

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: OTHER

Drainage Control comments: N/A

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

Snapping_12_1_Fed_523H_1Mile_Map_20170922082343.pdf

Existing Wells description:

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? DEFER

Estimated Production Facilities description: All Flow lines will be buried going to the Snapping 12 CTB 2, located in Sec 12-26S-31E.

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Section 5 - Location and Types of Water Supply

Water Source Table

Water source use type: STIMULATION

Water source type: RECYCLED

Describe type:

Source latitude:

Source longitude:

Source datum:

Water source permit type: OTHER

Source land ownership: FEDERAL

Water source transport method: PIPELINE,TRUCKING

Source transportation land ownership: FEDERAL

Water source volume (barrels): 135000

Source volume (acre-feet): 17.400568

Source volume (gal): 5670000

Water source and transportation map:

Snapping_12_1_Fed_523H_Wtr_Xfr_Map_01_17_18_20180118151813.pdf

Water source comments: The attached Water Transfer Map is a proposal only and the final route and documentation will be provided by a Devon contractor prior to installation. When available Devon will always follow existing disturbance.

New water well? NO

New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: Dirt fill and caliche will be used to construct well pad.

Construction Materials source location attachment:

Snapping_12_1_Fed_523H_Caliche_Pit_20170927065715.pdf

Section 7 - Methods for Handling Waste

Waste type: PRODUCED WATER

Waste content description: Produced water during production operations. This amount is a daily average during the first year of production (BWPD)

Amount of waste: 1000 barrels

Waste disposal frequency : One Time Only

Safe containment description: N/A

Safe containmant attachment:

Waste disposal type: ON-LEASE INJECTION **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: One of three company owned SWD facilities in the area: CDU 181, CDU 89, CDU 84.

Waste type: FLOWBACK

Waste content description: Produced water during flowback operations. This amount is a daily average during flowback (BWPD).

Amount of waste: 1500 barrels

Waste disposal frequency : Daily

Safe containment description: N/A

Safe containmant attachment:

Waste disposal type: ON-LEASE INJECTION **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: One of three company owned SWD facilities in the area: CDU 181, CDU 89, CDU 84.

Waste type: COMPLETIONS/STIMULATION

Waste content description: Flow back water during completion operations.

Amount of waste: 3000 barrels

Waste disposal frequency : One Time Only

Safe containment description: N/A

Safe containmant attachment:

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: All cuttings will be disposed of at R360, Sundance or Equivalent.

Waste type: DRILLING

Waste content description: Water Based Cuttings

Amount of waste: 1810 barrels

Waste disposal frequency : Daily

Safe containment description: N/A

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: All cuttings will disposed of at R360, Sundance, or equivalent.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.) **Reserve pit width (ft.)**

Reserve pit depth (ft.) **Reserve pit volume (cu. yd.)**

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? NO

Description of cuttings location

Cuttings area length (ft.) **Cuttings area width (ft.)**

Cuttings area depth (ft.) **Cuttings area volume (cu. yd.)**

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: NO

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

Snapping_12_1_Fed_523H_Rig_Layout_20170927070551.pdf

Comments:

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: SNAPPING 12 WELLPAD

Multiple Well Pad Number: 2

Recontouring attachment:

Snapping_12_1_Fed_523H_Reclamation_20170927071039.pdf

Drainage/Erosion control construction: All areas disturbed shall be reclaimed as early and as nearly as practicable to their original condition or their final land use and shall be maintained to control dust and minimize erosion to the extent practicable.

Drainage/Erosion control reclamation: Topsoils and subsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns. The disturbed area then shall be reseeded in the first favorable growing season.

Wellpad long term disturbance (acres): 2.489

Wellpad short term disturbance (acres): 4.752

Access road long term disturbance (acres): 1.958

Access road short term disturbance (acres): 1.958

Pipeline long term disturbance (acres): 0.44075757

Pipeline short term disturbance (acres): 0.44075757

Other long term disturbance (acres): 5.739

Other short term disturbance (acres): 5.739

Total long term disturbance: 10.626758

Total short term disturbance: 12.889757

Reconstruction method: Operator will use Best Management Practices "BMP" to mechanically recontour to obtain the desired outcome.

Topsoil redistribution: Topsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.

Soil treatment: Topsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.

Existing Vegetation at the well pad:

Existing Vegetation at the well pad attachment:

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Existing Vegetation Community at the road:

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline:

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances:

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? NO

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? NO

Seed harvest description:

Seed harvest description attachment:

Seed Management

Seed Table

Seed type:

Seed source:

Seed name:

Source name:

Source address:

Source phone:

Seed cultivar:

Seed use location:

PLS pounds per acre:

Proposed seeding season:

Seed Summary

Total pounds/Acre:

| Seed Type | Pounds/Acre |
|------------------|--------------------|
|------------------|--------------------|

Seed reclamation attachment:

Operator Contact/Responsible Official Contact Info

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

First Name: Jacob

Last Name: Ochoa

Phone: (575)748-9934

Email: jacob.ochoa@dvn.com

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: Maintain weeks on a as need basis.

Weed treatment plan attachment:

Monitoring plan description: Monitor as needed.

Monitoring plan attachment:

Success standards: N/A

Pit closure description: N/A

Pit closure attachment:

Section 11 - Surface Ownership

Disturbance type: NEW ACCESS ROAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Fee Owner: Baker Ranch

Fee Owner Address: P.O. Box 24

Phone: (575)746-9540

Email:

Surface use plan certification:

Surface use plan certification document:

Surface access agreement or bond:

Surface Access Agreement Need description:

Surface Access Bond BLM or Forest Service:

BLM Surface Access Bond number:

USFS Surface access bond number:

Disturbance type: EXISTING ACCESS ROAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Disturbance type: PIPELINE

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SNAPPING 12-1 FED

Well Number: 523H

Section 12 - Other Information

Right of Way needed? NO

Use APD as ROW?

ROW Type(s):

ROW Applications

SUPO Additional Information: BATTERY CONNECT CTB CTB ELECTRIC ELECTRIC FLOWLINE GAS CAPTURE PLAN GRADING & X SEC MISC PLATS

Use a previously conducted onsite? NO

Previous Onsite information:

Other SUPO Attachment

Snapping_12_1_Fed_523H_GasCapturePlan_20170927072224.pdf

Snapping_12_1_Fed_523H_Grading__X_Sec_20170927072239.pdf

Snapping_12_1_Fed_523H_Misc_Plats_20170927072254.pdf

Snapping_12_1_Fed_523H_CTB_2_Flowline_20171222120239.pdf

Snapping_12_1_Fed_523H_CTB_2_PAD_P_20171222120242.pdf

Snapping_12_1_Fed_523H_BATTERY_EL_20171222120243.pdf

Snapping_12_1_Fed_523H_CTB_2_BATTCONNWater_20171222120245.pdf

Snapping_12_1_Fed_523H_CTB_2_BATTCONNGas_20171222120244.pdf

Snapping_12_1_Fed_523H_WP_2_EL_20171222120246.PDF

SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
AERIAL ACCESS ROUTE MAP



NOT TO SCALE
AERIAL PHOTO:
GOOGLE EARTH
NOV. 2015

DEVON ENERGY PRODUCTION COMPANY, L.P.
SNAPPING 12-1 FED 523H
LOCATED 2325 FT. FROM THE NORTH LINE
AND 1880 FT. FROM THE WEST LINE OF
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO


SEPTEMBER 18, 2017

SURVEY NO. 5440B

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SEPTEMBER 18, 2017



SEE NEXT SHEET (2-4) FOR DESCRIPTION

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD, NEW MEXICO, THIS 25TH DAY OF SEPTEMBER 2017

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 1-4

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 **CARLSBAD, NEW MEXICO**

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SEPTEMBER 18, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

BEGINNING AT A POINT WITHIN THE NW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S26°10'31"W, A DISTANCE OF 2983.70 FEET;
THENCE S00°17'51"E A DISTANCE OF 2602.78 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S86°46'22"W, A DISTANCE OF 1331.78 FEET;

SAID STRIP OF LAND BEING 2602.78 FEET OR 157.74 RODS IN LENGTH, CONTAINING 1.793 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|--------------|------------|-------------|
| NW/4 NW/4 | 1330.51 L.F. | 80.64 RODS | 0.916 ACRES |
| SW/4 NW/4 | 1272.27 L.F. | 77.11 RODS | 0.876 ACRES |

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD, NEW MEXICO, THIS 25 DAY OF SEPTEMBER 2017

FILMON F. JARAMILLO PLS 12797

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.


SHEET: 2-4

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341


ACCESS ROAD PLAT

PRIMARY AND SECONDARY ACCESS ROADS FOR SNAPPING 12 WELLPAD 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SEPTEMBER 18, 2017



SEE NEXT SHEET (2-2) FOR DESCRIPTION



GENERAL NOTES

- 1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.
- 2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 1-2

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 CARLSBAD, NEW MEXICO

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,

NEW MEXICO, THIS 18 DAY OF SEPTEMBER 2017

FILMON F. JARAMILLO PLS. 12797
MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5377A

ACCESS ROAD PLAT

PRIMARY AND SECONDARY ACCESS ROADS FOR SNAPPING 12 WELLPAD 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SEPTEMBER 18, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

PRIMARY ACCESS ROAD

BEGINNING AT A POINT WITHIN THE SW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S64°04'18"W, A DISTANCE OF 1475.17 FEET;
THENCE N89°43'05"E A DISTANCE OF 99.95 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S65°39'18"W, A DISTANCE OF 1565.87 FEET;

SAID STRIP OF LAND BEING 99.95 FEET OR 6.06 RODS IN LENGTH, CONTAINING 0.069 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|------------|-----------|-------------|
| SW/4 NW/4 | 4.21 L.F. | 0.26 RODS | 0.003 ACRES |
| SE/4 NW/4 | 95.74 L.F. | 5.80 RODS | 0.066 ACRES |

SECONDARY ACCESS ROAD

BEGINNING AT A POINT WITHIN THE SW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S86°46'22"W, A DISTANCE OF 1331.78 FEET;
THENCE N89°41'44"E A DISTANCE OF 99.97 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S86°58'37"W, A DISTANCE OF 1431.64 FEET;

SAID STRIP OF LAND BEING 99.97 FEET OR 6.06 RODS IN LENGTH, CONTAINING 0.069 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|------------|-----------|-------------|
| SW/4 NW/4 | 4.32 L.F. | 0.26 RODS | 0.003 ACRES |
| SE/4 NW/4 | 95.65 L.F. | 5.80 RODS | 0.066 ACRES |

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,

NEW MEXICO, THIS 18 DAY OF SEPTEMBER, 2017

[Signature]
FILMON F. JARAMILLO PLS. 12797

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5377A

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.


2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 2-2

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS


DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SEPTEMBER 18, 2017




ACCESS ROAD PLAT

ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

**DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SEPTEMBER 18, 2017**



DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



SHEET: 1-4

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503A

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

BEGINNING AT A POINT WITHIN THE NW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S26°10'31"W, A DISTANCE OF 2983.70 FEET;
THENCE S00°17'51"E A DISTANCE OF 2602.78 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S86°46'22"W, A DISTANCE OF 1331.78 FEET;

SAID STRIP OF LAND BEING 2602.78 FEET OR 157.74 RODS IN LENGTH, CONTAINING 1.793 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|--------------|------------|-------------|
| NW/4 NW/4 | 1330.51 L.F. | 80.64 RODS | 0.916 ACRES |
| SW/4 NW/4 | 1272.27 L.F. | 77.11 RODS | 0.876 ACRES |

SURVEYOR CERTIFICATE

I, FILIMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,
NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 2-4


MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503A

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS


DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



ACCESS ROAD PLAT


ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017




ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



SEE NEXT SHEET (2-4) FOR DESCRIPTION



GENERAL NOTES

- 1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.
- 2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 1-4

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

SURVEYOR CERTIFICATE

I, FILIMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,

NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

[Signature]
FILIMON F. JARAMILLO PLS. 12797

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503A

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

BEGINNING AT A POINT WITHIN THE NW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S26°10'31"W, A DISTANCE OF 2983.70 FEET;
THENCE S00°17'51"E A DISTANCE OF 2602.78 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S86°46'22"W, A DISTANCE OF 1331.78 FEET;

SAID STRIP OF LAND BEING 2602.78 FEET OR 157.74 RODS IN LENGTH, CONTAINING 1.793 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|--------------|------------|-------------|
| NW/4 NW/4 | 1330.51 L.F. | 80.64 RODS | 0.916 ACRES |
| SW/4 NW/4 | 1272.27 L.F. | 77.11 RODS | 0.876 ACRES |

SURVEYOR CERTIFICATE

I, FILIMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,
NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 2-4


MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503A

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS


DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



ACCESS ROAD PLAT

ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

ROSS ROAD
(PIPELINE ROAD)

N89°41'55"E 2667.50 FT

S00°17'51"E 2602.78 FT

S26°10'31"W 2983.70 FT

SNAPPING 12 CTB 1

SNAPPING 12 CTB 2

SNAPPING 12 WELLPAD 1

SNAPPING 12 WELLPAD 2

(TIE) S86°46'22"W 1331.78 FT

SEC 12
T.26S., R.31E.
BLM

STA 0+00.0 B.O.R. ON SOUTH EDGE
ROSS ROAD (PIPELINE ROAD)

STA 0+07.8 2-4" POLY SURF

STA 0+71.6 ETA BPL

STA 1+10.3 EL PASO BPL

STA 1+29.5 EL PASO BPL

STA 1+68.4 2-TRACK ROAD

STA 1+77.7 WESTERN REFINING BPL

STA 2+07.9 FRONTIER BPL

STA 2+48.8 BPL NO SIGN

STA 3+02.5 B/W FENCE

STA 9+49.2 4/W POWER LINE

STA 16+67.8 4-WAY INTERSECTION

STA 20+32.7 4-WAY INTERSECTION

STA 26+02.8 E.O.R. "T" INTERSECTION

BC 1940

BC 1940

BC 1940

BC 1940

MADRON SURVEYING.

NEW YORK, N.Y. _____ JAN. _____ 1968

Samuel J. Lerner

PHILIP F. JARANTO, PLS. 12787

SURVEY NO. 5503A

CARLSBAD, NEW MEXICO

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

BEGINNING AT A POINT WITHIN THE NW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S26°10'31"W, A DISTANCE OF 2983.70 FEET;
THENCE S00°17'51"E A DISTANCE OF 2602.78 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S86°46'22"W, A DISTANCE OF 1331.78 FEET;

SAID STRIP OF LAND BEING 2602.78 FEET OR 157.74 RODS IN LENGTH, CONTAINING 1.793 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|--------------|------------|-------------|
| NW/4 NW/4 | 1330.51 L.F. | 80.64 RODS | 0.916 ACRES |
| SW/4 NW/4 | 1272.27 L.F. | 77.11 RODS | 0.876 ACRES |

SURVEYOR CERTIFICATE

I, FILIMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,
NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 2-4


MADRON SURVEYING, INC. 301 SOUTH CANAL, CARLSBAD, NEW MEXICO 88220
(575) 234-3341

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5503A

ACCESS ROAD PLAT
ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS


DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



ACCESS ROAD PLAT

ACCESS ROAD FOR SNAPPING 12 PADS AND CTBS

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



PLAT

One Mile Radius Map

devon

This map is for illustrative purposes only and is neither a legally recorded map nor a survey and is not intended to be used as one. Devon makes no warranty, representation, or guarantee of any kind regarding this map.

GCS North American 1983
Datum: North American 1983; Units: Degree
Created by: lemois
Map is current as of 9/20/2017.



0 0.3 Miles
1 inch = 0 miles

SNAPPING 12-1 FED 523H WA017056727


BIG SINKS 1 A3OB FEE 2H
Nearest wellbore to SHL:

2369 ft.

BIG SINKS 1 A3OB FEE 2H
Nearest wellbore to BHL:

747 ft.


• SHL
× BHL



Water Transfer Route
Snapping Wells - Section 12

devon


WGS 1984, Web_Mercator_Auxiliary_Sphere
Prepared by: Ray Vaz
Map is current as of: 17-Jun-2018




Total 10,165.99 ft

Snapping 12-1 Fed 521H, 522H, 523H, 531H, 532H, 533H, 623H


- State pit 616 and 617 32- 23S- 32E





- Fed pit 25- 23S- 31E



- Private pit 26- 23S- 31E




Devon Energy - Well Pad Rig Location Layout Safety Equipment Location




CROSS-SECTIONS


SECTION A-A'



SECTION B-B'



SECTION C-C'



0+12 60 120 240
SCALE 1" = 120' - 1" = 20' VER

DEVON ENERGY PRODUCTION COMPANY, L.P.
PAD GRADING AND CROSS SECTIONS
FOR SNAPPING 12-1 FED 523H
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO




| CUT | FILL | NET |
|-------------|--------------|--------------------|
| 1267 CU. YD | 15342 CU. YD | 3275 CU. YD (FILL) |

EARTHWORK QUANTITIES ARE ESTIMATED

SEPTEMBER 18, 2017
MADRON SURVEYING, INC. 301 SOUTH CANAL
(505) 234-3341 CARLSBAD, NEW MEXICO

SHEET 2-2
SURVEY NO. 6440B

CROSS-SECTIONS



012 60 120 240
SCALE 1" = 120' - 1" = 20' VER

DEVON ENERGY PRODUCTION COMPANY, L.P.
PAD GRADING AND CROSS SECTIONS
FOR SNAPPING 12-1 FED 529H
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

| CUT | FILL | NET |
|--------------|--------------|--------------------|
| 12067 CU. YD | 15342 CU. YD | 3275 CU. YD (FILL) |

EARTHWORK QUANTITIES ARE ESTIMATED

AUGUST 30, 2017

301 SOUTH CANAL

(575) 234-3341


MADRON SURVEYING, INC.

CARLSBAD, NEW MEXICO

SHEET 2-2

SURVEY NO. 5440

**SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
SITE MAP**



010 50 100 200

SCALE 1" = 100'

DIRECTIONS TO LOCATION

FROM STATE ROAD 128 AND CR. 1 (ORLA ROAD) GO SOUTH ON CR. 1 10.4 MILES, TURN RIGHT ON CALICHE PIPELINE ROAD (ROSS ROAD) AND GO WEST 3.5 MILES TO A PROPOSED ROAD SURVEY AND FOLLOW FLAGS SOUTH 0.5 MILE TO A PROPOSED ROAD "T" AND GO EAST 100' TO THE SOUTHWEST PAD CORNER FOR SNAPPING TRANSITIONAL PAD 2, FOLLOW ROAD FLAGS EAST 140' THE SOUTHWEST PAD CORNER FOR THIS LOCATION.

**DEVON ENERGY PRODUCTION COMPANY, L.P.
SNAPPING 12-1 FED 523H
LOCATED 2325 FT. FROM THE NORTH LINE
AND 1880 FT. FROM THE WEST LINE OF
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO**

SEPTEMBER 18, 2017

SURVEY NO. 5440B

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341

CARLSBAD, NEW MEXICO

329.

2

1

Rosa Place

Sweetwater Windmill

327

HM

3254

Gravel Pit

SNAPPING 12-1
FED 523H

PROPOSED 140 LF. ACCESS ROAD

Drill Hole

3200

3204

3267

HM 3254

Drill Hole

Gravel Pit

3252

3/52


NOT TO SCALE

LOCATED 2325 FT. FROM THE NORTH LINE
AND 1880 FT. FROM THE WEST LINE OF
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

SURVEY NO. 5440B

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO
(575) 234-3341

SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
VICINITY MAP



DISTANCES IN MILES

NOT TO SCALE

DIRECTIONS TO LOCATION

FROM STATE ROAD 128 AND CR. 1 (ORLA ROAD) GO SOUTH ON CR. 1 10.4 MILES, TURN RIGHT ON CALICHE PIPELINE ROAD (ROSS ROAD) AND GO WEST 3.5 MILES TO A PROPOSED ROAD SURVEY AND FOLLOW FLAGS SOUTH 0.5 MILE TO A PROPOSED ROAD "T" AND GO EAST 100' TO THE SOUTHWEST PAD CORNER FOR SNAPPING TRANSITIONAL PAD 2, FOLLOW ROAD FLAGS EAST 140' THE SOUTHWEST PAD CORNER FOR THIS LOCATION.

**DEVON ENERGY PRODUCTION COMPANY, L.P.
SNAPPING 12-1 FED 523H**


LOCATED 2325 FT. FROM THE NORTH LINE
AND 1880 FT. FROM THE WEST LINE OF
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

SEPTEMBER 18, 2017

SURVEY NO. 5440B

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 CARLSBAD, NEW MEXICO

SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
AERIAL PHOTO



NOT TO SCALE
AERIAL PHOTO:
GOOGLE EARTH
NOV. 2015

*DEVON ENERGY PRODUCTION COMPANY, L.P.
SNAPPING 12-1 FED 523H*

*LOCATED 2325 FT. FROM THE NORTH LINE
AND 1880 FT. FROM THE WEST LINE OF
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO*

SEPTEMBER 18, 2017


SURVEY NO. 5440B

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3341 *CARLSBAD, NEW MEXICO*


FLOWLINE PLAT

THREE-4" POLY FLOWLINES AND ONE-6" GAS LIFT LINE BURIED IN THE SAME DITCH FROM SNAPPING 12 WELLPAD 2 (SNAPPING 12-1 FED 522H, 523H, & 533H) TO SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF A PIPELINE CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



SEE NEXT SHEET (2-4) FOR DESCRIPTION



GENERAL NOTES

- 1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.
- 2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 1-4

MADRON SURVEYING, INC.

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD, NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

[Signature]
 FILMON F. JARAMILLO PLS: 12797

MADRON SURVEYING, INC.
 301 SOUTH CANAL
 CARLSBAD, NEW MEXICO 88220
 Phone (575) 234-3341

SURVEY NO. 5570B

CARLSBAD, NEW MEXICO

FLOWLINE PLAT

THREE-4" POLY FLOWLINES AND ONE-6" GAS LIFT LINE BURIED IN THE SAME DITCH FROM SNAPPING
12 WELLPAD 2 (SNAPPING 12-1 FED 522H, 523H, & 533H) TO SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF A PIPELINE CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

BEGINNING AT A POINT WITHIN THE SE/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S75°31'00"W, A DISTANCE OF 2052.69 FEET;
THENCE N00°18'14"W A DISTANCE OF 579.98 FEET TO AN ANGLE POINT OF THE LINE HEREIN DESCRIBED;
THENCE S89°42'42"W A DISTANCE OF 60.00 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S60°24'13"W, A DISTANCE OF 2213.14 FEET;

SAID STRIP OF LAND BEING 639.98 FEET OR 38.79 RODS IN LENGTH, CONTAINING 0.441 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

SE/4 NW/4 639.98 L.F. 38.79 RODS 0.441 ACRES

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,
NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 2-4

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO

FILMON F. JARAMILLO PLS. 12797


MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5570B

FLOWLINE PLAT

THREE-4" POLY FLOWLINES AND ONE-6" GAS LIFT LINE BURIED IN THE SAME DITCH FROM SNAPPING
12 WELLPAD 2 (SNAPPING 12-1 FED 522H, 523H, & 533H) TO SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF A PIPELINE CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 7, 2017



FLOWLINE PLAT

THREE-4" POLY FLOWLINES AND ONE-6" GAS LIFT LINE BURIED IN THE SAME DITCH FROM SNAPPING
12 WELLPAD 2 (SNAPPING 12-1 FED 522H, 523H, & 533H) TO SNAPPING 12 CTB 2


DEVON ENERGY PRODUCTION COMPANY, L.P.

CENTERLINE SURVEY OF A PIPELINE CROSSING

SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.

EDDY COUNTY, STATE OF NEW MEXICO

DECEMBER 7, 2017



SHEET: 4-4

MADRON SURVEYING, INC.

301 SOUTH CANAL
(575) 234-3341


CARLSBAD, NEW MEXICO

SURVEY NO. 5570B

SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
IN THE N/2 SE/4 NW/4 OF
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

DECEMBER 8, 2017



DESCRIPTION

A CERTAIN PIECE OR PARCEL OF LAND AND REAL ESTATE LYING IN BUREAU OF LAND MANAGEMENT LAND IN THE N/2 SE/4 NW/4 OF SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO.

BEGINNING AT THE SOUTHWEST CORNER OF THE PARCEL, WHENCE THE WEST QUARTER CORNER OF SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S61°55'58"E, A DISTANCE OF 1616.19 FEET;
THENCE N00°17'51"W A DISTANCE OF 500.05 FEET TO THE NORTHWEST CORNER OF THE PARCEL;
THENCE N89°42'00"E A DISTANCE OF 499.96 FEET TO THE NORTHEAST CORNER OF THE PARCEL;
THENCE S00°18'02"E A DISTANCE OF 500.06 FEET TO THE SOUTHEAST CORNER OF THE PARCEL;
THENCE S89°42'05"W A DISTANCE OF 499.98 FEET TO THE SOUTHWEST CORNER OF THE PARCEL, THE POINT OF BEGINNING;
CONTAINING 5.739 ACRES MORE OR LESS.

GENERAL NOTES

- 1.) THE INTENT OF THIS SURVEY IS TO ACQUIRE A BUSINESS LEASE FOR THE PURPOSE OF BUILDING A CENTRAL TANK BATTERY
- 2.) BASIS OF BEARING IS NEW MEXICO STATE PLANE EAST ZONE MODIFIED TO THE SURFACE (NAD83), COORDINATES ARE NAD 83, ELEVATIONS ARE NAVD 88

DRIVING DIRECTIONS: FROM STATE ROAD 128 AND CR. 1 (ORLA ROAD) GO SOUTH ON CR. 1 10.4 MILES, TURN RIGHT ON CALICHE PIPELINE ROAD (ROSS ROAD) AND GO WEST 3.5 MILES TO A PROPOSED ROAD SURVEY AND FOLLOW FLAGS SOUTH 1644' SOUTH TO A PROPOSED ROAD "T" AND GO EAST 100' TO THE WEST EDGE OF PAD FOR THIS LOCATION.

SHEET: 1-3

MADRON SURVEYING, INC.

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAN MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,

NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

FILMON F. JARAMILLO PLS. 12797
MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5380C

CARLSBAD, NEW MEXICO


SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
IN THE N/2 SE/4 NW/4 OF
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

DECEMBER 8, 2017

QUAD MAP

Place:



Drill
Hole

3217

SECTION 12
T. 26 S., R. 31 E.
BUREAU OF LAND
MANAGEMENT LAND 3232



0 500 1000 2000
SCALE 1" = 1000'

3187

SHEET: 2-3

SURVEY NO. 5380C

MADRON SURVEYING, INC.

301 SOUTH CANAL
(575) 234-3341


CARLSBAD, NEW MEXICO

SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
IN THE N/2 SE/4 NW/4 OF
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

DECEMBER 8, 2017

AERIAL PHOTO



SNAPPING 12
WELLPAD 1

SNAPPING
12 CTB 2

SNAPPING 12
WELLPAD 2

12


SECTION 12
T. 26 S., R. 31 E.
BUREAU OF LAND
MANAGEMENT LAND

SHEET: 3-3

SURVEY NO. 5380C

MADRON SURVEYING, INC. 301 SOUTH CANAL (575) 234-3541 CARLSBAD, NEW MEXICO

PLAN VIEW



DEVON ENERGY PRODUCTION COMPANY, L.P.
PAD ELEVATIONS AND CROSS SECTIONS
FOR SNAPPING 12 CTB 2
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

DECEMBER 8, 2017

MADRON SURVEYING, INC. 301 SOUTH CANAL (505) 234-3341 MADRON SURVEYING, INC. CARLSBAD, NEW MEXICO


SHEET 1-2 SURVEY NO. 6380C

| CUT | FILL | NET |
|--------------|--------------|-------------------|
| 14155 CU. YD | 11584 CU. YD | 2571 CU. YD (CUT) |


EARTHWORK QUANTITIES ARE ESTIMATED

CROSS-SECTIONS


SECTION A-A'



SECTION B-B'



SECTION C-C'



012 60 120 240
SCALE 1" = 120' - 1" = 20' VER

DEVON ENERGY PRODUCTION COMPANY, L.P.
PAD ELEVATIONS AND CROSS SECTIONS
FOR SNAPPING 12 CTB 2
SECTION 12, TOWNSHIP 26 SOUTH,
RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

DECEMBER 8, 2017

MADRON SURVEYING, INC. 301 SOUTH CANAL CARLSBAD, NEW MEXICO

SURVEY NO. 5380C

| CUT | FILL | NET |
|--------------|--------------|-------------------|
| 14155 CU. YD | 11584 CU. YD | 2571 CU. YD (CUT) |


EARTHWORK QUANTITIES ARE ESTIMATED

SHEET 2-2


ACCESS ROAD PLAT

PRIMARY ACCESS ROAD FOR SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 8, 2017



SEE NEXT SHEET (2-2) FOR DESCRIPTION



GENERAL NOTES

- 1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.
- 2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 1-2

MADRON SURVEYING, INC.

SURVEYOR CERTIFICATE

I, FILIMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD, NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

Filimon F. Jaramillo
FILIMON F. JARAMILLO, PLS. 12797

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

SURVEY NO. 5380C

CARLSBAD, NEW MEXICO

ACCESS ROAD PLAT
PRIMARY ACCESS ROAD FOR SNAPPING 12 CTB 2

DEVON ENERGY PRODUCTION COMPANY, L.P.
CENTERLINE SURVEY OF AN ACCESS ROAD CROSSING
SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO
DECEMBER 8, 2017

DESCRIPTION

A STRIP OF LAND 30 FEET WIDE CROSSING BUREAU OF LAND MANAGEMENT LAND IN SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., EDDY COUNTY, STATE OF NEW MEXICO AND BEING 15 FEET EACH SIDE OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

PRIMARY ACCESS ROAD

BEGINNING AT A POINT WITHIN THE SW/4 NW/4 OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M., WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S52°40'56"W, A DISTANCE OF 1665.84 FEET;
THENCE N89°42'09"E A DISTANCE OF 100.00 FEET THE TERMINUS OF THIS CENTERLINE SURVEY, WHENCE THE WEST QUARTER CORNER OF SAID SECTION 12, TOWNSHIP 26 SOUTH, RANGE 31 EAST, N.M.P.M. BEARS S54°39'27"W, A DISTANCE OF 1746.72 FEET;

SAID STRIP OF LAND BEING 100.00 FEET OR 6.06 RODS IN LENGTH, CONTAINING 0.069 ACRES MORE OR LESS AND BEING ALLOCATED BY FORTIES AS FOLLOWS:

| | | | |
|-----------|------------|-----------|-------------|
| SW/4 NW/4 | 4.09 L.F. | 0.25 RODS | 0.003 ACRES |
| SE/4 NW/4 | 95.91 L.F. | 5.81 RODS | 0.066 ACRES |

SURVEYOR CERTIFICATE

I, FILMON F. JARAMILLO, A NEW MEXICO PROFESSIONAL SURVEYOR NO. 12797, HEREBY CERTIFY THAT I HAVE CONDUCTED AND AM RESPONSIBLE FOR THIS SURVEY, THAT THIS SURVEY IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT THIS SURVEY AND PLAT MEET THE MINIMUM STANDARDS FOR LAND SURVEYING IN THE STATE OF NEW MEXICO.

IN WITNESS WHEREOF, THIS CERTIFICATE IS EXECUTED AT CARLSBAD,
NEW MEXICO, THIS 8 DAY OF DECEMBER 2017

MADRON SURVEYING, INC.
301 SOUTH CANAL
CARLSBAD, NEW MEXICO 88220
Phone (575) 234-3341

GENERAL NOTES

1.) THE INTENT OF THIS ROUTE SURVEY IS TO ACQUIRE AN EASEMENT.

2.) BASIS OF BEARING AND DISTANCE IS NMSP EAST (NAD83) MODIFIED TO SURFACE COORDINATES. NAD 83 (FEET) AND NAVD 88 (FEET) COORDINATE SYSTEMS USED IN THE SURVEY.

SHEET: 2-2

MADRON SURVEYING, INC. 301 SOUTH CANAL
(575) 234-3341 **CARLSBAD, NEW MEXICO**

FILMON F. JARAMILLO PLS. 12797

SURVEY NO. 5380C

§



**SECTION 12, T26S-R31E, N.M.P.M.,
EDDY COUNTY, NEW MEXICO**

ELECTRIC LINE PLAT

LEGAL DESCRIPTION

FOR

DEVON ENERGY PRODUCTION COMPANY, L.P.

BUREAU OF LAND MANAGEMENT

30' EASEMENT DESCRIPTION:

BEING an easement thirty (30) feet in width lying fifteen (15) feet on the right side and fifteen (15) feet on the left side of the survey centerline described below, being out of the northwest quarter (NW ¼) of Section 12, Township 26 South, Range 31 East, N.M.P.M., Eddy County, New Mexico, and being out of a parcel of land owned by the Bureau of Land Management. Said centerline of easement being more particularly described as follows:

Commencing from a 1/2" iron pin found for the northwest corner of Section 12, T26S-R31E, N.M.P.M., Eddy County, New Mexico;

Thence S 47°43'44" E a distance of 2815.54' to the **Point of Beginning** of this easement having coordinates of Northing=385956.32, Easting=727131.10 feet and continuing the following course;

Thence S 89°40'29" W a distance of 145.21' to the **Point of Ending** having coordinates of Northing=385955.50, Easting=726985.89 feet, from said point a 1" iron pipe w/BC for the west quarter corner of Section 12, T26S-R31E, bears S 67°45'12" W a distance of 2080.44', covering **145.21' or 8.80' rods** and having an area of **0.100 acre**.

NOTES:

Bearings, distances and coordinates shown herein are based on New Mexico State Plane Coordinate System, NAD 83, East Zone 3001, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect an actual survey made on the ground under my supervision. This survey meets the minimum standards for surveying in New Mexico.




B.L. Laman PLS# 22404
Date Signed: 12-19-2017
Horizon Row, LLC
P.O. Box 548, Dry Creek, La.
(903) 388-3045 70637
Employee of Horizon Row, LLC



EXHIBIT "A"

PAGE 3 of 4



QUAD MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/20/2017

Drawn for:



LINE NUMBER:
EL8078


WBS NUMBER:
CC-123117.19

SCALE:
1" = 2000'

REVISIONS:
12-18-17 CMAAS

SHEET:
3 OF 4

EXHIBIT "A"
PAGE 4 of 4



AERIAL MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/20/2017

Drawn for:



LINE NUMBER:
EL8078


WBS NUMBER:
CC-123117.19

SCALE:
1" = 2000'

REVISIONS:
12-18-17 CMAAS

SHEET:
4 OF 4

EXHIBIT "A"
PAGE 1 of 4
SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO



20' TEMPORARY WORK SPACE EASEMENT AREA = 0.513 ACRE(S)
30' EASEMENT AREA = 0.701 ACRE(S)
1018.31 FEET OR 61.72 RODS

0+00.0 P.O.B./SNAPPING TO VAN DOO DAH LATERAL GAS
0+15.0 EXIT 30' X 75' SURFACE SITE
1+45.7 P.O.I./SNAPPING 12 CTB 2 BATTERY CONNECT GAS
10+18.3 P.O.E./ENTER SNAPPING 12 CTB 2

SEE THE ATTACHED LEGAL DESCRIPTION

Note: All bearings recited herein are based on the New Mexico State Plane Coordinate System, NAD 83, New Mexico East Zone 3001, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect actual survey made on the ground under my supervision. This survey meets the minimum standards for surveying in New Mexico.

B.L. Laman
Date Signed: 12-19-2017
P.O. Box 548, Dry Creek, La.
(903) 388-3045 70637
Employee of Horizonrow, LLC

HORIZON ROW LLC

Drawn for:

devon

Drawn by:
CHRIS MAAS

Date: 09/19/2017

DEVON ENERGY PRODUCTION COMPANY, L.P.

SNAPPING 12 CTB 2
BATTERY CONNECT WATER

PROPOSED 30' EASEMENT
ON THE PROPERTY OF
BUREAU OF LAND MANAGEMENT
SECTION 12, T26S-R31E, N.M.P.M.

LINE NUMBER:

76200102

WBS NUMBER:
CC-126150.AL

SCALE:
1" = 1000'

REVISIONS:
12-18-17 CMAAS

SHEET:
1 OF 4

0 1000 2000

**SECTION 12, T26S-R31E, N.M.P.M.,
EDDY COUNTY, NEW MEXICO**

LEGAL DESCRIPTION

FOR

DEVON ENERGY PRODUCTION COMPANY, L.P.

BUREAU OF LAND MANAGEMENT

30' EASEMENT DESCRIPTION:

BEING an easement thirty (30) feet in width lying fifteen (15) feet on the right side and fifteen (15) feet on the left side of the survey centerline described below, being out of the northwest quarter (NW ¼) of Section 12, Township 26 South, Range 31 East, N.M.P.M., Eddy County, New Mexico, and being out of a parcel of land owned by the Bureau of Land Management. Said centerline of easement being more particularly described as follows:

Commencing from a 1/2" iron pin found for the northwest corner of Section 12, T26S-R31E, N.M.P.M., Eddy County, New Mexico;

Thence S 56°39'54" E a distance of 2367.09' to the **Point of Beginning** of this easement having coordinates of Northing=386549.37, Easting=727025.31 feet and continuing the following courses;

Thence S 00°00'00" E a distance of 681.15' to an angle point;

Thence N 90°00'00" W a distance of 276.97' to an angle point;

Thence N 00°00'00" W a distance of 60.19' to the **Point of Ending** having coordinates of Northing=385928.40, Easting= 726748.34 feet, from said point a 1" iron pipe w/BC for the west quarter corner of Section 12, T26S-R31E, bears S 65°44'44" W a distance of 1851.45', covering **1018.31' or 61.72' rods** and having an area of **0.701 acre**.

20' TEMPORARY WORK SPACE DESCRIPTION:

Being a temporary work space twenty (20) feet in width lying on the left side and adjoining the left side of the above described thirty (30) feet easement, having a total area of **0.513 acres**.

NOTES:

Bearings, distances and coordinates shown herein are based on New Mexico State Plane Coordinate System, NAD 83, East Zone 3001, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect an actual survey made on the ground under my supervision. This survey meets the minimum standards for surveying in New Mexico.




B.L. Laman PLS# 22404
Date Signed: 12-19-2017
Horizon Row, LLC
P.O. Box 548, Dry Creek, La.
(903) 388-3045 70637
Employee of Horizon Row, LLC



EXHIBIT "A"

PAGE 3 of 4



QUAD MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/19/2017

Drawn for:



LINE NUMBER:
7620010Z


WBS NUMBER:
CC-126150.AL

SCALE:
1" = 2000'

REVISIONS:
12-18-17 CMAAS

SHEET:
3 OF 4

EXHIBIT "A"
PAGE 1 of 4
SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO



20' TEMPORARY WORK SPACE EASEMENT AREA = 0.109 ACRE(S)
30' EASEMENT AREA = 0.129 ACRE(S)
187.49 FEET OR 11.36 RODS

0+00.0 P.O.B./SNAPPING TO VAN DOO DAH LATERAL GAS
0+15.0 EXIT 30' X 75' SURFACE SITE
1+45.7 P.O.I./SNAPPING 12 CTB 2 BATTERY CONNECT WATER
1+87.5 P.O.E./SNAPPING 12 CTB 2

SEE THE ATTACHED LEGAL DESCRIPTION

Note: All bearings recited herein are based on the New Mexico State Plane Coordinate System, NAD 83, New Mexico East Zone 3001, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect an actual survey made on the ground under my supervision. This survey meets the minimum standards for land surveying in New Mexico.

B.L. Laman
Date Signed: 12-19-2017
P.O. Box 548, Dry Creek, La.
(903) 388-3045 70637
Employee of Horizonrow, LLC

HORIZON ROW LLC

Drawn for:

devon

Drawn by: CHRIS MAAS Date: 09/19/2017

DEVON ENERGY PRODUCTION COMPANY, L.P.

SNAPPING 12 CTB 2
BATTERY CONNECT GAS

PROPOSED 30' EASEMENT
ON THE PROPERTY OF
BUREAU OF LAND MANAGEMENT
SECTION 12, T26S-R31E, N.M.P.M.

LINE NUMBER: 7620010X
WBS NUMBER: CC-126150.AL
SCALE: 1" = 1000'
REVISIONS: 12-18-17 CMAAS
SHEET: 1 OF 4

**SECTION 12, T26S-R31E, N.M.P.M.,
EDDY COUNTY, NEW MEXICO**

**LEGAL DESCRIPTION
FOR
DEVON ENERGY PRODUCTION COMPANY, L.P.**

BUREAU OF LAND MANAGEMENT

30' EASEMENT DESCRIPTION:

BEING an easement thirty (30) feet in width lying fifteen (15) feet on the right side and fifteen (15) feet on the left side of the survey centerline described below, being out of the northwest quarter (NW ¼) of Section 12, Township 26 South, Range 31 East, N.M.P.M., Eddy County, New Mexico, and being out of a parcel of land owned by the Bureau of Land Management. Said centerline of easement being more particularly described as follows:

Commencing from a 1/2" iron pin found for the northwest corner of Section 12, T26S-R31E, N.M.P.M., Eddy County, New Mexico;

Thence S 56°39'54" E a distance of 2367.09' to the **Point of Beginning** of this easement having coordinates of Northing=386549.37, Easting=727025.31 feet and continuing the following courses;

Thence S 00°00'00" E a distance of 145.73' to an angle point;

Thence N 90°00'00" W a distance of 41.76' to the **Point of Ending** having coordinates of Northing=386403.64, Easting=726983.55 feet, from said point a 1" iron pipe w/BC for the west quarter corner of Section 12, T26S-R31E, bears S 57°16'37" W a distance of 2286.04', covering **187.49' or 11.36' rods** and having an area of **0.129 acre**.

20' TEMPORARY WORK SPACE DESCRIPTION:

Being a temporary work space twenty (20) feet in width lying on the left side and adjoining the left side of the above described thirty (30) feet easement, having a total area of **0.109 acres**.

NOTES:

Bearings, distances and coordinates shown herein are based on New Mexico State Plane Coordinate System, NAD 83, East Zone 3001, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect an actual survey made on the ground under my supervision. This survey meets the minimum standards for surveying in New Mexico.




B.L. Laman PLS# 22404
Date Signed: 12-19-2017
Horizon Row, LLC
P.O. Box 548, Dry Creek, La.
(903) 388-3045 70637
Employee of Horizon Row, LLC



EXHIBIT "A"

PAGE 3 of 4



QUAD MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/19/2017

Drawn for:



LINE NUMBER:
7620010X

WBS NUMBER:
CC-126150.AL

SCALE:
1" = 2000'

REVISIONS:
12-18-17 CMAAS

SHEET:
3 OF 4

EXHIBIT "A" PAGE 4 of 4



AERIAL MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/19/2017

Drawn for:

devon

LINE NUMBER:
7620010X

WBS NUMBER:
CC-126150.AL

SCALE:
1" = 2000'

REVISIONS:
12-18-17 CMAAS

SHEET:
4 OF 4



**SECTION 12, T26S-R31E, N.M.P.M.,
EDDY COUNTY, NEW MEXICO**

ELECTRIC LINE PLAT

LEGAL DESCRIPTION

FOR

DEVON ENERGY PRODUCTION COMPANY, L.P.

BUREAU OF LAND MANAGEMENT

30' EASEMENT DESCRIPTION:

BEING an easement thirty (30) feet in width lying fifteen (15) feet on the right side and fifteen (15) feet on the left side of the survey centerline described below, being out of the northwest quarter (NW ¼) of Section 12, Township 26 South, Range 31 East, N.M.P.M., Eddy County, New Mexico, and being out of a parcel of land owned by the Bureau of Land Management. Said centerline of easement being more particularly described as follows:

Commencing from a 1/2" iron pin found for the northwest corner of Section 12, T26S-R31E, N.M.P.M., Eddy County, New Mexico;

Thence S 54°59'28" E a distance of 1664.75' to the **Point of Beginning** of this easement having coordinates of Northing=386895.09, Easting=726411.21 feet and continuing the following courses;

Thence S 00°17'06" E a distance of 372.84' to an angle point;

Thence N 89°42'53" E a distance of 715.20' to an angle point;

Thence S 00°17'11" E a distance of 954.55' to an angle point;

Thence S 89°37'54" W a distance of 44.96' to the **Point of Ending** having coordinates of Northing=385570.98, Easting=727088.06 feet, from said point a 1" iron pipe w/BC for the west quarter corner of Section 12, T26S-R31E, bears S 78°45'22" W a distance of 2067.41', covering **2087.55' or 126.52' rods** and having an area of **1.438 acre**.

NOTES:

Bearings, distances and coordinates shown herein are based on New Mexico State Plane Coordinate System, NAD 83, East Zone 3001, US Survey Feet, all distances are grid.

I, B.L. Laman, New Mexico PLS No. 22404, hereby certify this survey to reflect an actual survey made on the ground under my supervision. This survey meets the minimum standards for surveying in New Mexico.



B.L. Laman PLS# 22404

Date Signed: 09-21-2017

Horizon Row, LLC

924 Richardson Dr., Jasper, Tx


(903) 388-3045 75951

Employee of Horizon Row, LLC



EXHIBIT "A"

PAGE 3 of 4



QUAD MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/21/2017

Drawn for:



LINE NUMBER:
EL8080

WBS NUMBER:
CC-123117.19

SCALE:
1" = 2000'

REVISIONS:

SHEET:
3 OF 4

EXHIBIT "A"
PAGE 4 of 4



AERIAL MAP

SECTION 12, T26S-R31E, N.M.P.M.
EDDY COUNTY, NEW MEXICO

HORIZON ROW LLC

DEVON ENERGY PRODUCTION CO., L.P.

PROPOSED 30' EASEMENT

Drawn by:
CHRIS MAAS

Date: 09/21/2017

Drawn for:


devon

LINE NUMBER:

EL8080

WBS NUMBER:

CC-123117.19

SCALE:

1" = 2000'

REVISIONS:

SHEET:

4 OF 4



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

PWD Data Report

02/09/2018

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Injection well name:

Assigned injection well API number?

Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data Report

02/09/2018

Bond Information

Federal/Indian APD: FED

BLM Bond number: CO1104

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: