District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION

ARTESIA DISTRICT

Date: 02/28/18	GAS CAPTURE PLAN	FEB 2 7 2018
☐ Amended - Reason for Amendment:	Operator & OGRID No.: Mewbourne Oil Compar	^{1y} RÉCÉIVED

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Zeppelin 32 W2LI St Com #2H	30-015-43165	L, 32, 23S, 28E	335 FNL & 920	FEL 0		Online after frac
Zeppelin 32 W2PM St Com #11	30-015-43161	M, 32, 23S, R28E	450 FSL & 360	FWL 0		Online after frac
Zeppelin 32 W0LI St Com #1H	30-015-44560	L, 32, 23S, R28E	2030 FSL & 205	FWL 0		Online after frac

Catherina	System	and Pinelin	e Notification
CERTIFICATION	TVALCIE A		e municanon

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in
place. The gas produced from production facility is dedicated to Crestwood and will be connected to
Crestwood low/high pressure gathering system located in Eddy County, New Mexico. It will require
2900 'of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides
(periodically) to Crestwood a drilling, completion and estimated first production date for wells that are scheduled to
be drilled in the foreseeable future. In addition, Mewbourne Oil Company and Crestwood have periodic
conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed a
Crestwood Processing Plant located in Sec. 29, Twn. 24s, Rng. 28E, Eddy County, New Mexico
The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Crestwood system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines