District. I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District. III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION

Date: 02/28/18	GAS CAPTURE PLAN					FEB 27 2018
☑ Original	Operator & OGRID No.: Mewbourne Oil CompanyRECEIVED					
☐ Amended - Reason for A	Amendment:					
This Gas Capture Plan outl new completion (new drill,				o reduce we	ll/production	facility flaring/venting for
Note: Form C-129 must be subs Well(s)/Production Facilit The well(s) that will be loca	y – Name of	f facility	- ,	·		l of 19.15.18.12 NMAC).
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Zeppelin 32 W2LI St Com #2H Zeppelin 32 W2PM St Com #1H		L, 32, 23S, 28E M, 32, 23S, R28E	335 FNL & 920 450 FSL & 360	-		Online after frac Online after frac
Zeppelin 32 W0LI St Com #1H	30-015-44560	L, 32, 23S, R28E	2030 FSL & 205	FWL 0		Online after frac
	o a production production production pressure onnect the fare a future. In changes to	on facility after flation facility is de gathering system acility to low/high drilling, completion addition, Mewbord drilling and com	edicated to _ n located in n pressure ga on and estimate ourne Oil Co npletion sche	Eddy (thering system first produmpany and dules. Gas	County, New em. Mewbo fuction date for Crestwood from these	and will be connected Mexico. It will requi urne Oil Company provid or wells that are scheduled have period
The actual flow of the gas wi						

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Crestwood system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines