

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

**NM OIL CONSERVATION
ARTESIA DISTRICT**

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals.

MAR 27 2018

RECEIVED

5. Lease Serial No. NMNM119754
6. If Indian, Allottee or Tribe Name
7. If Unit or CA/Agreement, Name and/or No.
8. Well Name and No. RB NE 5 32 FED 13H
9. API Well No. 30-015-44639-00-X1
10. Field and Pool or Exploratory Area PURPLE SAGE-WOLFCAMP (GAS)
11. County or Parish, State EDDY COUNTY, NM

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	2. Name of Operator CHEVRON USA INCORPORATED Contact: LAURA BECERRA E-Mail: LBECCERRA@CHEVRON.COM	3a. Address 6301 DEAUVILLE BLVD MIDLAND, TX 79706	3b. Phone No. (include area code) Ph: 432-687-7665
4. Location of Well (Footage, Sec. T, R, M, or Survey Description) Sec 5 T24S R29E SESE 380FSL 1250FEL 32.240520 N Lat, 104.002106 W Lon	12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Change to Original A PD
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation. Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

We are requesting the name of the well to be changed as referenced in the certified well plat as well the TVD and MD to reflect the depths on the 9 Pt Plan. Supporting documents attached.

From: RB NE 5 32 FED 13H 320646
To: CB SE 5 32 FED COM 13H 320809

TVD: 10,234'
MD: 20,402'

Carlsbad New to
Operator Copy

14. I hereby certify that the foregoing is true and correct	
Electronic Submission #402955 verified by the BLM Well Information System For CHEVRON USA INCORPORATED, sent to the Carlsbad Committed to AFMSS for processing by PRISCILLA PEREZ on 02/01/2018 (18PP1010SE)	
Name (Printed/Typed) LAURA BECERRA	Title PERMITTING SPECIALIST
Signature (Electronic Submission)	Date 02/01/2018

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By <u>ZOTA STEVENS</u>	Title <u>PETROLEUM ENGINEER</u>	Date <u>02/07/2018</u>
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office <u>Carlsbad</u>

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2) **** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

RW 4-2-18

District I
1625 N French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
New Mexico Oil Conservation
ARTESIA DISTRICT
District Office

MAR 27 2018 UNDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT RECEIVED

¹ API Number 30-015-44639		² Pool Code 98220		³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)	
⁴ Property Code 320646		⁵ Property Name CB SE 5 32 FED COM			⁶ Well Number 13H
⁷ OGRID No. 4323		⁸ Operator Name CHEVRON U.S.A. INC.			⁹ Elevation 3028'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	5	24 SOUTH	29 EAST, N.M.P.M.		380'	SOUTH	1250'	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	32	23 SOUTH	29 EAST, N.M.P.M.		280'	NORTH	330'	EAST	EDDY

¹² Dedicated Acres 640	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

¹⁶

PROPOSED BOTTOM HOLE LOCATION	
X=	603,348 NAD 27
Y=	461,262
LAT.	32.267662
LONG.	103.998972
X=	644,532 NAD83
Y=	461,321
LAT.	32.267805
LONG.	103.999463

CORNER COORDINATES TABLE (NAD 27)

A - Y=461537.13, X=601028.36
B - Y=461542.17, X=603672.21
C - Y=456270.49, X=601137.17
D - Y=456251.69, X=603786.69
E - Y=450962.21, X=601166.20
F - Y=450947.72, X=603814.23

Mid Point
Y=456254.02, X=603456.70
First Take Point
Y=451279.54, X=603482.51
Last Take Point
Y=461211.55, X=603349.30

CB SE 5 32 FED COM 13H WELL	
X=	602,562 NAD 27
Y=	451,334
LAT.	32.240399
LONG.	104.001614
X=	643,746 NAD83
Y=	451,393
LAT.	32.240522
LONG.	104.002104
ELEVATION +3028' NAVD 88	

Proposed Last Take Point
330' FNL, 330' FEL

Proposed First Take Point
330' FSL, 330' FEL

Proposed Producing Interval
N 01°14'28" W 5,008.71'

N 00°17'50" W 4,974.55'

S 86°36'26" E
921.87'

380' 1250'

¹⁷ OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Dorian K Fuentes 1/30/18
Signature Date

Dorian K. Fuentes
Printed Name

djvo@chevron.com
E-mail Address

¹⁸ SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

11-10-2016
Date of Survey

ROBERT L. LASTRAPES
NEW MEXICO
Professional Surveyor
23006
30-2018

23006
Certificate Number

1. FORMATION TOPS

The estimated tops of important geologic markers are as follows

FORMATION	SUB-SEA TVD	KBTVD	MD
Castille		758	
Lamar		2868	
Bell		2906	
Cherry		3810	
Brushy		5024	
Bone Spring Lime		6644	
Avalon		6716	
First Bone Spring Sand		7672	
SBSG Sand		8438	
Third Bone Spring Carbonate		8826	
Third Bone Spring Sand		9558	
Wolfcamp A		9911	
Wolfcamp B		10511	
Lateral TVD Wolfcamp A		10234	20402

BOP Scher



Wellhead S



Choke Hos



2. ESTIMATED DEPTH OF WATER, OIL, GAS & OTHER MINERAL BEARING FORMATIONS

The estimated depths at which the top and bottom of the anticipated water, oil, gas, or other mineral bearing formations are expected to be encountered are as follows:

Substance	Formation	Depth
Deepest Expected Base of Fresh Water		450
Water	Castille	758
Water	Cherry Canyon	3810
Oil/Gas	Brushy Canyon	5024
Oil/Gas	First Bone Spring Sand	7672
Oil/Gas	SBSG Sand	8438
Oil/Gas	Third Bone Spring Carbonate	8826
Oil/Gas	Third Bone Spring Sand	9558
Oil/Gas	Wolfcamp A	9911

All shows of fresh water and minerals will be reported and protected

3. BOP EQUIPMENT

Will have a minimum of a 5000 psi rig stack (see proposed schematic). Stack will be tested as specified in the attached testing requirements. Batch drilling of the surface, intermediate, and production will take place. A full BOP test will be performed unless approval from BLM is received otherwise. Flex choke hose will be used for all wells on the pad (see attached specs). BOP test will be conducted by a third party.

Chevron requests a variance to use a FMC UHS Multibowl wellhead, which will be run through the rig floor on surface casing. BOPE will be nipped up and tested after cementing surface casing. Subsequent tests will be performed as needed, not to exceed 30 days. The field report from FMC and BOP test information will be provided in a subsequent report at the end of the well. Please see the attached wellhead schematic. An installation manual has been placed on file with the BLM office and remains unchanged from previous submittal.

ONSHORE ORDER NO 1
 Chevron
 Rustler Bluff 5 32 Fed 13WA
 Eddy County, NM

PAGE:

4. CASING PROGRAM

Purpose	From	To	Hole Size	Csg Size	Weight	Grade	Thread	Condition
Surface	0'	450'	17-1/2"	13-3/8"	54.5 #	J-55	STC	New
Intermediate	0'	9,000'	12-1/4"	9-5/8"	43.5#	L-80	LTC	New
Production	0'	20,402'	8-1/2"	5-1/2"	20.0 #	P-110	TXP	New

SF Calculations based on the following "Worst Case" casing design:

Surface Casing: 450'
 Intermediate Casing: 9,000 MD
 Production Casing: 20,402' MD; 10,234' TVD (10,234' VS @ 90 deg Inc)

Casing String	Min SF Burst	Min SF Collapse	Min SF Tension	Min SF Tri-Axial
Surface	1.43	5.73	3.42	1.58
Intermediate	1.29	2.42	1.9	1.4
Production	1.33	1.47	2.39	1.4

Min SF is the smallest of a group of safety factors that include the following considerations.

	Surf	Int	Prod
Burst Design			
Pressure Test- Surface, Int, Prod Csg P external: Water P internal: Test psi + next section heaviest mud in csg	X	X	X
Displace to Gas- Surf Csg P external: Water P internal: Dry Gas from Next Csg Point	X		
Frac at Shoe, Gas to Surf- Int Csg P external: Water P internal: Dry Gas, 15 ppq Frac Gradient		X	
Stimulation (Frac) Pressures- Prod Csg P external: Water P internal: Max inj pressure w/ heaviest injected fluid			X
Tubing leak- Prod Csg (packer at KOP) P external: Water P internal: Leak just below surf 8.7 ppq packer fluid			X
Collapse Design			
Full Evacuation P external: Water gradient in cement, mud above TOC P internal: none	X	X	X
Cementing- Surf, Int, Prod Csg P external: Wet cement P internal: water	X	X	X
Tension Design			

ONSHORE ORDER NO. 1
 Chevron
 Rustler Bluff 5 32 Fed 13WA
 Eddy County, NM

CONFIDENTIAL -- TIGHT HOLE
 DRILLING PLAN
 PAGE: 3

○ **CEMENTING PROGRAM**

Slurry	Type	Cement Top	Cement Bottom	Weight	Yield	%Excess	Sacks	Water
Tail	Class C	0'	450'	14.8	1.33	10	311	6.37
Intermediate								
Stage 2 Lead	Class C	0'	1,600'	11.9	2.41	10	230	2.43
Stage 2 Tail	Class C	1,600'	2,500'	14.8	1.33	10	233	1.33
DV Tool		2,500'						
Stage 1 Lead	Class C	2,500'	8,000'	11.9	2.43	10	764	13.66
	Class C							
Stage 1 Tail		8,000'	9,000'	15.6	1.21	10	310	5.34
Production								
Tail	Class C	8,000'	20,402'	15.6	1.2	10	2608	7.62

1. Final cement volumes will be determined by caliper.
2. Surface casing shall have at least one centralizer installed on each of the bottom three joints starting with the shoe

joint.

3. Production casing will have one horizontal type centralizer on every joint for the first 1000' from TD, then every other joint to EOB, and then every third joint to KOP. Bowspring type centralizers will be run from KOP to intermediate casing

ONSHORE ORDER NO. 1
Chevron
Rustler Bluff 5 32 Fed 13WA
Eddy County, NM

CONFIDENTIAL -- TIGHT HOLE
DRILLING PLAN
PAGE: 4

6. MUD PROGRAM

From	To	Type	Weight	F. Vis	Filtrate
0'	450'	Spud Mud	8.3 - 10	32 - 34	NC - NC
450'	9,000'	OBM	8.8 - 9.8	50 - 70	5.0 - 10
9,000'	20,402'	OBM	9.5 - 13	50 - 70	5.0 - 10

A closed system will be utilized consisting of above ground steel tanks. All wastes accumulated during drilling operations will be contained in a portable trash cage and removed from location and deposited in an approved sanitary landfill. Sanitary wastes will be contained in a chemical porta-toilet and then hauled to an approved sanitary landfill.

All fluids and cuttings will be disposed of in accordance with New Mexico Oil Conservation Division rules and regulations.

A mud test shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.

Visual mud monitoring equipment shall be in place to detect volume changes indicating loss or gain of circulating fluid volume. When abnormal pressures are anticipated -- a pit volume totalizer (PVT), stroke counter, and flow sensor will

A weighting agent and lost circulating material (LCM) will be onsite to mitigate pressure or lost circulation as hole

7. TESTING, LOGGING, AND CORING

The anticipated type and amount of testing, logging, and coring are as follows.

- a. Drill stem tests are not planned
- b. The logging program will be as follows.

TYPE	Logs	Interval	Timing	Vendor
Mudlogs	2 man mudlog	Int Csg to TD	Drillout of Int Csg	TBD
LWD	MWD Gamma	Int CSG & Prod	While Drilling	TBD

- c. Conventional whole core samples are not planned
- d. A Directional Survey will be run.

8. ABNORMAL PRESSURES AND HYDROGEN SULFIDE

No abnormal Pressures anticipated Reference Attached H2S Contingency Plan