

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30005 C4008
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator QUATRO OILS E&P, LLC		6. State Oil & Gas Lease No. K-2114
3. Address of Operator P.O. Box 1213;		7. Lease Name or Unit Agreement Name LE Ranch 16
4. Well Location Unit Letter A : 990 feet from the N line and 330 feet from the E line Section 16 Township 11S Range 28E NMPM Chaves County NM		8. Well Number 27
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3720 GR		9. OGRID Number 372241
		10. Pool name or Wildcat Chaves S.A., EAST

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☒	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Pumper reported no pump action. Shut well off awaiting pulling unit.
April 10, 2018 BG Well Services will arrive on location. Pull rods & pump deep standing valve & pressure up on tubing if it holds water. If not will pull tubing. Testing with pressure every 10 joints until past perforated hole in tubing. Locate bad joints & replace from stuck. Reset bottom hole assembly. Test tubing upon entries. Test full string to 100 lbs upon reaching TD. Hold for 15 minutes. If good check pump rerun or replace. Place well back on pump.

NM OIL CONSERVATION
ARTESIA DISTRICT

Spud Date:

4/19/08

Rig Release Date:

APR 10 2018

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

[Signature]

TITLE

Manager/Operator

DATE

9 April 2018

Type or print name

Perry McMin

E-mail address:

perry@2mcm.com

PHONE:

575/626-7100

For State Use Only

APPROVED BY:

[Signature]

TITLE

Staff

DATE

4-10-18

Conditions of Approval (if any):