

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-30080
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator EOG Y Resources Inc.		6. State Oil & Gas Lease No. V-4100
3. Address of Operator 105 South Fourth St, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Jacque AQJ State
4. Well Location Unit Letter M : 330 feet from the South line and 330 feet from the West line Section 34 Township 21S Range 31E NMPM County Eddy		8. Well Number 001
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3461' GR		9. OGRID Number 25575
		10. Pool name or Wildcat Lost Tank Delaware, West

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. *Notify NMOC 24 hrs before MTR*

- MIRU. ND WH, NU BOP. POOH Prod equipment
- Set 5 1/2" CIBP @ 7,408'. Circ well w/ MLF. Cap BP w/ 25 sxs @ 7,408'-7,308'. WOC-Tag
- Set 5 1/2" CIBP @ 6,845'. Cap w/ 25sxcmt @ 6,845'-6,745'. WOC-Tag
- Spot 25sxcmt @ 5,144' - 5,044'
- Spot 25sxcmt @ 4,122' - 3,794'. WOC-Tag
- Spot 25sxcmt @ 1,950' - 1,850'
- Spot 25sxcmt @ 900' - 790'. WOC-Tag
- Spot 70 sxs cmt @ 645' - 3'
- Verify cmt @ surface. Top off if necessary. RDMO. Cut off WH & anchors & install DH marker.

NM OIL CONSERVATION
ARTESIA DISTRICT

APR 11 2018

RECEIVED

A closed loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17

Spud Date:

Rig Release Date:

* See Attached COA's must be plugged by 4-13-19
I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Agent DATE 4/2/18

Type or print name Greg Bryant E-mail address: PHONE:

For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 4-13-18

Conditions of Approval (if any):

New Drilling Job

Job Category	Primary Job Type	Department	Start Date	End Date
--------------	------------------	------------	------------	----------

VERTICAL - Original Hole, 1/22/2014 6:00:00 PM

MD (ftKB)	Vertical schematic (actual)	Column list (actual) Description
-7,146.0		
-6,730.0		
0.0		
6.2		
11.2		
12.1		
36.1	Polished Rod; 1 1/2; 36.2	
38.1	Rod Sub; 1; 38.2	
40.0	Rod Sub; 1; 42.2	Conductor Casing; 20; 12.0-40.0
42.3		
51.8		
839.9		Surface Casing; 13 3/8; J-55; 12.0 -840.0 RUSTLER
852.0	Sucker Rod - N97; 1; 2,117.2	SALT
2,117.1		
3,950.1	Sucker Rod - Norris; 7/8; 4,692.2	tubing; 2 7/8; 7,191.2 Intermediate Casing; 8 5/8; J-55; 12.0-3,950.0 SALT
3,961.9		BELL CAN...
4,692.3		CHERRY...
6,776.9	Sucker Rod - Norris; 3/4; 7,242.2	
6,785.1	Perforated; 6,777.0-6,785.0; 5/6/1999	
6,944.9		BRUSHY C.
6,982.0	Perforated; 6,945.0-6,982.0; 5/4/1999	
7,191.3		
7,194.2		Anchor / Catcher; 5 1/2; 7,194.2
7,242.1		
7,492.1	Sucker Rod - N97; 1; 7,492.2	Tubing; 2 7/8; 7,516.2
7,507.9	25 - 125 - RHBC - 24 - 4; 1 1/4; 7,516.2	
7,516.1	Perforated; 7,508.0-7,518.0; 5/1/1999	
7,517.1		Pump Seating Nipple; 2 7/8; 7,517.2
7,518.0		
7,521.3		Perforated Sub; 2 7/8; 7,521.2
7,553.5		Tubing; 2 7/8; 7,553.4
7,554.1		Bull Plug; 2 7/8; 7,554.0
7,813.0		
7,887.1	Perforated; 7,813.0-7,887.0	
8,120.1		Production Casing; 5 1/2; J-55; 12.0-8,120.0 BONE SPR...

595

888

3844 ✓

4122 ✓

5144'

6867 ✓

8050 ✓

Jacque AOT State #1

Spot 645-0 w/ 65SR cut

$$\frac{13\frac{3}{8}}{840} = 0.015476$$

Spot 900-790 w/25 Sk's cont
Tag

spot 1950-1850 25 skaut
spacer

$$\begin{array}{r} 85 \\ \underline{3950} \\ \text{Circ} \end{array}$$

Spot 4122 - 3794 w/ 40-5k s/g
Tag

Spot 5144 - 5044 w/ 25 sks out

Set CID @ 6845-6745 w/ 25.5k sat
Tag

6945

Set C.B.P. of 7408-7308 w/ 25 SK
Cmt Tag

7508

57413

852
8120
Circ

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
 T. Salt 888'
 B. Salt 3844'
 T. Yates _____
 T. 7 Rivers _____
 T. Queen _____
 T. Grayburg _____
 T. San Andres _____
 T. Glorieta _____
 T. Paddock _____
 T. Blinbry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abo _____
 T. Wolfcamp _____
 T. Penn _____
 T. Cisco (Bough C) _____

T. Canyon _____
 T. Strawn _____
 T. Atoka _____
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Delaware Sand _____
 T. Bone Springs 8050'
 T. Rustler 595'
 T. Bell Canyon 4122'
 T. Cherry Canyon 5144'
 T. Brushy Canyon 6867'

Northwestern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn "A" _____

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____
 No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	226	226	Surface & redbed				
226	840	614	Redbed				
840	2730	1890	Salt & anhydrite				
2730	2911	181	Anhydrite				
2911	3268	357	Salt & anhydrite				
3268	3373	105	Anhydrite				
3373	3876	503	Salt & anhydrite				
3876	4110	234	Anhydrite				
4110	6345	2235	Anhydrite & sand				
6345	7030	685	Shale & sand				
7030	7627	597	Sand				
7627	8120	493	Sand & shale				

CONDITIONS FOR PLUGGING AND ABANDONMENT

District II / Artesia N.M.

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If the well is not plugged within 1
7. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
8. **Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.**
9. Produced water **will not** be used during any part of the plugging operation.
10. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
11. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
12. **Class 'C' cement will be used above 7500 feet.**
13. **Class 'H' cement will be used below 7500 feet.**
14. **A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged**
15. **All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing**

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. **A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.**
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, **(WOC 4 hrs and tag).**
19. **No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.**
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) **Potash---** (In the R-111-P Area (Potash Mine Area), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, **WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.**
21. **If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing**

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3.API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)