Submit 3 Copies To Appropriate District	State of New Mexico		Form C-103
Office District I	Energy, Minerals and Natural Resources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		<b>30-015-34427</b> 5. Indicate Type of Lease
District III	1220 South St. Francis Dr.		STATE STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM			
87505 SUNDRY NOTICES AND REPORTS ON WELLS			7 I North Administration
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Mara State	
PROPOSALS.)  1. Type of Well: Oil Well Gas Well Other		8. Well Number	
1. Type of Well. Oil Well			1
2. Name of Operator			9. OGRID Number
BOLD ENERGY, LP			233545
3. Address of Operator			10. Pool name or Wildcat
415 W. Wall, Suite 500 Midland, Texas 79701		Undes. Runyan Ranch; Morrow	
4. Well Location			
Unit Letter N: 770 feet from the South line and 1880 feet from the West line			
Section 6 Township 19S Range 23E NMPM County Eddy			
11. Elevation (Show whether DR, RKB, RT, GR, etc.			
Pit or Below-grade Tank Application	4058'	GR	
		watan ayali D	:
	ater Distance from nearest fresh w		
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK			<del>_</del>
TEMPORARILY ABANDON			LING OPNS. P AND A
PULL OR ALTER CASING  OTHER:		CASING/CEMENT OTHER	JOB 🔲
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
or recompletion.			
Drilled 8¾" hole directionally to 7" casing point @ 4515' MD (4336' TVD @ 73° inclination). Ran 106 jts (4512') of			
7" 23.0# L-80 LTC csg w/ FS & FC; csg set @ 4515' MD w/ FC @ 4470' MD. Schlumberger cmt'd csg w/ 200 sx PVL w/			
12% gel, 0.3% anti-foam, 0.1% FLA & 0.1 pps polyester flakes (11.0 ppg, 2.71 yield) followed by 215 sx PVL w/ .03%			
FLA, 0.2% dispersant & 0.2% anti-foam (13.0 ppg, 1.40 yield). Bumped plug w/ 988 psi @ 9:30 AM on 4/13/06 – had good circ throughout job but did not circ cmt. TS indicated TOC @ 1100'. Cut csg, installed WH & BOP equip. Tested BOPE w/			
250 psi (low) & 3000 psi (high), OK. Trip in hole w/ 6 1/8" bit and after 35 hrs WOC, tested casing w/ 1500 psi – OK. Drilled			
out shoe jt & resumed drilling formation @ 6:30 AM 4/15/06.			
	_		
		_	EOCIMED
H.			ECEIVED
		1	APR 2 1 2006
I hereby certify that the information above is true and complete to the best of my knowledge and their factories that any pit or below-			
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.			
SIGNATURE (A)			
SIGNATURE WALL !		ent for BOLD ENER	
Type or print name D. C. Doc	E-mail address: ddod	d@sierra-engineer	ing.com Telephone No. 432 / 683-8000
For State Use Only			
EVE	RECORDS ONLY		
APPROVED BY:	TITLE		DAT <b>APR 2 1 2006</b>
Conditions of Approval (if any):			N 1 2000