



7821 Will Rogers Blvd.
Fort Worth, Texas 76140
817.568.1038 (office)
817.568.1499 (fax)
www.msdir.com

MS Directional Survey Data Certification

**NM OIL CONSERVATION
ARTESIA DISTRICT**

MS Directional Job Number: DDMO-171105
Survey Type: MWD
Operating Company: RKI Exploration & Production LLC
Well Name & Number: Tucker Draw 9-4 Federal COM 6H
Location: Eddy County, NM
API Number: 30-015-44479
Tie In Depth: Surface
Surveyed Depths: 154' – 18,604' MD
Projected TD Survey: 18,649' MD
Dates Performed: 11/26/2017 – 01/13/2018

APR 26 2018

RECEIVED

30-015-44479

I certify that the data is true, correct and complete and within the limitations of the tool set forth by MS Directional; that I am authorized and qualified to make this report and that I have reviewed this report and find it conforms to the principles and procedures as set forth by MS Directional.

Digitally signed by:

Paul Royar

MWD Surveyor Name: Paul Royar

Date: 02-26-2018

Email: proyar@msdir.com

CONFIDENTIALITY NOTICE: This document contains MS Directional's proprietary and confidential information and may not be copied, published, distributed or transmitted, in whole or in part, by any medium or in any form without MS Directional's prior written consent. The information contained in this document is not to be used by or disclosed to any individuals other than those who need to know such information and who have been given notice that such information is proprietary and confidential.

V09.04.02

Company:	RKI Exploration & Production LLC
Well Name:	Tucker Draw 9-4 Federal COM 6H
Location:	Eddy County, NM
Rig:	Orion Phoenix #10
Job Number:	DDMO-171105
API #:	30-015-44479

Magnetic Declination: 6.88 REFERENCED TO GRID NORTH

Vertical Section Azimuth: 359.68 Proposed Direction: 359.68

Survey Calculation Method: Minimum Curvature

PTB:	MD	INC	AZM	TVD	N/S	E/W	VS
	18,649	88.38	358.1	10941.45	7982.89	-375.55	7984.86

#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
TIE IN	0	0.00	0.00	0.00	0.00	0.00			0.00		
1	157	0.20	257.30	157.00	-0.06	-0.27	-0.06	0.27	257.30	0.13	0.13
2	247	0.30	200.60	247.00	-0.32	-0.50	-0.31	0.59	237.94	0.28	0.11
3	338	0.40	192.40	338.00	-0.85	-0.66	-0.84	1.07	217.68	0.12	0.11
4	428	0.30	179.10	428.00	-1.39	-0.72	-1.39	1.57	207.34	0.14	-0.11
5	518	0.40	164.50	517.99	-1.93	-0.63	-1.93	2.03	198.13	0.15	0.11
6	609	0.60	186.40	608.99	-2.71	-0.60	-2.71	2.77	192.49	0.30	0.22
7	699	0.70	174.90	698.98	-3.72	-0.60	-3.72	3.77	189.20	0.18	0.11
8	789	0.40	188.10	788.98	-4.58	-0.60	-4.58	4.62	187.44	0.36	-0.33
9	879	0.40	160.40	878.98	-5.19	-0.54	-5.19	5.22	185.91	0.21	0.00
10	969	0.60	225.20	968.98	-5.82	-0.77	-5.81	5.87	187.51	0.62	0.22
11	1,063	0.90	256.40	1062.97	-6.34	-1.83	-6.33	6.60	196.13	0.53	0.32
12	1,152	0.70	147.20	1151.96	-6.96	-2.22	-6.95	7.31	197.68	1.47	-0.22
13	1,243	1.30	134.30	1242.95	-8.15	-1.18	-8.14	8.23	188.23	0.70	0.66
14	1,332	1.40	125.10	1331.92	-9.48	0.43	-9.48	9.49	177.38	0.27	0.11
15	1,423	0.40	119.30	1422.91	-10.27	1.62	-10.28	10.40	171.04	1.10	-1.10
16	1,512	0.10	129.10	1511.91	-10.47	1.95	-10.49	10.65	169.45	0.34	-0.34
17	1,601	0.40	93.50	1600.91	-10.54	2.32	-10.56	10.79	167.58	0.36	0.34
18	1,691	1.00	93.70	1690.90	-10.61	3.42	-10.63	11.15	162.14	0.67	0.67
19	1,786	0.30	164.50	1785.90	-10.91	4.31	-10.93	11.73	158.42	0.99	-0.74
20	1,881	0.50	215.60	1880.89	-11.48	4.14	-11.50	12.20	160.18	0.41	0.21
21	1,975	0.90	193.60	1974.89	-12.53	3.73	-12.55	13.08	163.44	0.51	0.43
22	2,070	1.20	255.00	2069.87	-13.52	2.59	-13.53	13.76	169.16	1.16	0.32
23	2,165	2.90	265.50	2164.81	-13.96	-0.77	-13.96	13.98	183.15	1.83	1.79
24	2,260	3.60	267.70	2259.66	-14.27	-6.14	-14.24	15.54	203.29	0.75	0.74
25	2,355	4.70	272.70	2354.41	-14.21	-13.01	-14.13	19.26	222.49	1.22	1.16
26	2,450	5.30	274.20	2449.04	-13.70	-21.28	-13.58	25.31	237.22	0.65	0.63
27	2,545	4.90	274.20	2543.67	-13.08	-29.70	-12.92	32.45	246.22	0.42	-0.42
28	2,640	4.60	273.70	2638.34	-12.54	-37.55	-12.33	39.58	251.53	0.32	-0.32
29	2,734	4.00	275.10	2732.08	-12.01	-44.57	-11.76	46.16	254.93	0.65	-0.64
30	2,829	5.10	280.40	2826.78	-10.95	-52.03	-10.66	53.17	258.12	1.24	1.16
31	2,923	5.40	283.40	2920.38	-9.17	-60.44	-8.83	61.13	261.37	0.43	0.32
32	3,019	4.00	282.20	3016.06	-7.41	-68.11	-7.03	68.51	263.79	1.46	-1.46
33	3,114	4.70	273.70	3110.78	-6.46	-75.23	-6.04	75.51	265.09	1.00	0.74

Company:	RKI Exploration & Production LLC		
Well Name:	Tucker Draw 9-4 Federal COM 6H		
Location:	Eddy County, NM		
Rig:	Orion Phoenix #10	Magnetic Declination:	6.88
Job Number:	DDMO-171105		
API #:	30-015-44479		

REFERENCED TO GRID NORTH

Vertical Section Azimuth:	359.68	Proposed Direction:	359.68
---------------------------	--------	---------------------	--------

Survey Calculation Method:	Minimum Curvature
----------------------------	-------------------

PTB:	MD	INC	AZM	TVD	N/S	E/W	VS
	18,649	88.38	358.1	10941.45	7982.89	-375.55	7984.86

#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
34	3,209	6.50	271.70	3205.33	-6.05	-84.49	-5.58	84.70	265.90	1.91	1.89
35	3,304	6.10	266.90	3299.75	-6.17	-94.90	-5.64	95.10	266.28	0.70	-0.42
36	3,398	5.90	267.90	3393.24	-6.61	-104.72	-6.03	104.93	266.39	0.24	-0.21
37	3,493	6.10	271.70	3487.72	-6.64	-114.64	-6.00	114.84	266.68	0.47	0.21
38	3,588	5.30	270.20	3582.25	-6.48	-124.08	-5.78	124.25	267.01	0.86	-0.84
39	3,700	4.11	270.92	3693.87	-6.39	-133.26	-5.65	133.42	267.25	1.06	-1.06
40	3,795	5.48	287.73	3788.54	-4.96	-140.99	-4.17	141.07	267.99	2.05	1.44
41	3,889	6.15	289.89	3882.05	-1.88	-150.00	-1.04	150.01	269.28	0.75	0.71
42	3,984	5.98	288.87	3976.52	1.45	-159.47	2.34	159.47	270.52	0.21	-0.18
43	4,079	5.87	289.60	4071.02	4.68	-168.72	5.63	168.79	271.59	0.14	-0.12
44	4,173	5.61	286.35	4164.54	7.59	-177.66	8.58	177.82	272.45	0.44	-0.28
45	4,268	5.68	287.22	4259.08	10.29	-186.61	11.33	186.89	273.16	0.12	0.07
46	4,363	5.58	286.47	4353.63	12.99	-195.53	14.08	195.96	273.80	0.13	-0.11
47	4,458	6.56	276.85	4448.09	14.95	-205.35	16.09	205.89	274.16	1.48	1.03
48	4,553	6.49	275.07	4542.48	16.07	-216.08	17.27	216.68	274.25	0.23	-0.07
49	4,648	6.51	273.83	4636.87	16.90	-226.80	18.17	227.43	274.26	0.15	0.02
50	4,743	6.50	273.11	4731.26	17.55	-237.54	18.88	238.19	274.23	0.09	-0.01
51	4,838	6.55	273.19	4825.64	18.15	-248.32	19.53	248.99	274.18	0.05	0.05
52	4,932	6.65	273.70	4919.02	18.80	-259.11	20.24	259.79	274.15	0.12	0.11
53	5,028	6.41	274.01	5014.40	19.53	-270.00	21.04	270.71	274.14	0.25	-0.25
54	5,123	6.25	274.85	5108.82	20.34	-280.44	21.90	281.18	274.15	0.19	-0.17
55	5,218	6.00	273.27	5203.27	21.06	-290.55	22.68	291.32	274.15	0.32	-0.26
56	5,313	4.09	262.92	5297.90	20.92	-298.87	22.59	299.60	274.00	2.22	-2.01
57	5,408	1.55	248.78	5392.78	20.04	-303.43	21.74	304.10	273.78	2.75	-2.67
58	5,502	1.23	234.13	5486.75	18.99	-305.44	20.69	306.03	273.56	0.51	-0.34
59	5,597	0.55	121.92	5581.75	18.15	-305.88	19.86	306.41	273.40	1.61	-0.72
60	5,692	0.61	111.37	5676.74	17.73	-305.02	19.43	305.53	273.33	0.13	0.06
61	5,787	0.59	121.94	5771.74	17.28	-304.13	18.98	304.62	273.25	0.12	-0.02
62	5,882	0.90	135.11	5866.73	16.50	-303.19	18.19	303.64	273.11	0.37	0.33
63	5,976	0.83	114.78	5960.72	15.69	-302.05	17.37	302.46	272.97	0.33	-0.07
64	6,071	1.06	129.11	6055.70	14.84	-300.74	16.52	301.11	272.83	0.35	0.24
65	6,166	0.40	5.22	6150.70	14.62	-300.03	16.30	300.39	272.79	1.40	-0.69
66	6,261	0.37	337.17	6245.70	15.23	-300.12	16.91	300.51	272.91	0.20	-0.03
67	6,356	0.41	299.83	6340.70	15.68	-300.54	17.36	300.94	272.99	0.27	0.04

Company:	RKI Exploration & Production LLC		
Well Name:	Tucker Draw 9-4 Federal COM 6H		
Location:	Eddy County, NM		
Rig:	Orion Phoenix #10	Magnetic Declination:	6.88
Job Number:	DDMO-171105	REFERENCED TO GRID NORTH	
API #:	30-015-44479		

Vertical Section Azimuth:	359.68	Proposed Direction:	359.68
---------------------------	--------	---------------------	--------

Survey Calculation Method:	Minimum Curvature
----------------------------	-------------------

PTB:	MD	INC	AZM	TVD	N/S	E/W	VS
	18,649	88.38	358.1	10941.45	7982.89	-375.55	7984.86

#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
68	6,450	0.37	303.13	6434.69	16.02	-301.08	17.70	301.51	273.05	0.05	-0.04
69	6,545	0.30	258.54	6529.69	16.14	-301.58	17.82	302.01	273.06	0.28	-0.07
70	6,639	0.27	236.08	6623.69	15.96	-302.01	17.65	302.43	273.03	0.12	-0.03
71	6,734	0.07	261.48	6718.69	15.83	-302.25	17.52	302.66	273.00	0.22	-0.21
72	6,829	0.14	188.75	6813.69	15.71	-302.33	17.39	302.73	272.97	0.14	0.07
73	6,924	0.41	194.76	6908.69	15.26	-302.43	16.95	302.81	272.89	0.29	0.28
74	7,018	0.55	178.71	7002.69	14.49	-302.50	16.18	302.85	272.74	0.21	0.15
75	7,113	0.43	210.80	7097.68	13.73	-302.68	15.42	302.99	272.60	0.31	-0.13
76	7,208	0.51	208.15	7192.68	13.05	-303.06	14.74	303.34	272.46	0.09	0.08
77	7,303	0.83	196.51	7287.67	12.01	-303.45	13.71	303.69	272.27	0.36	0.34
78	7,398	0.86	189.40	7382.66	10.65	-303.77	12.35	303.95	272.01	0.11	0.03
79	7,493	0.88	218.65	7477.65	9.38	-304.34	11.08	304.48	271.76	0.46	0.02
80	7,588	0.78	213.26	7572.64	8.27	-305.15	9.97	305.26	271.55	0.13	-0.11
81	7,683	0.77	216.52	7667.63	7.21	-305.88	8.92	305.97	271.35	0.05	-0.01
82	7,778	0.70	208.28	7762.63	6.19	-306.54	7.90	306.60	271.16	0.13	-0.07
83	7,873	0.58	195.75	7857.62	5.22	-306.94	6.93	306.99	270.97	0.19	-0.13
84	7,967	0.59	181.62	7951.61	4.27	-307.09	5.99	307.12	270.80	0.15	0.01
85	8,062	0.83	160.47	8046.61	3.14	-306.87	4.85	306.89	270.59	0.37	0.25
86	8,157	0.77	160.51	8141.60	1.89	-306.43	3.60	306.43	270.35	0.06	-0.06
87	8,252	0.75	18.92	8236.59	1.87	-306.01	3.58	306.02	270.35	1.51	-0.02
88	8,346	1.03	7.50	8330.58	3.29	-305.70	5.00	305.72	270.62	0.35	0.30
89	8,441	1.14	28.06	8425.57	4.97	-305.15	6.68	305.19	270.93	0.42	0.12
90	8,536	0.97	51.40	8520.55	6.31	-304.07	8.01	304.14	271.19	0.48	-0.18
91	8,631	0.70	53.35	8615.54	7.16	-302.98	8.85	303.06	271.35	0.29	-0.28
92	8,725	0.49	76.75	8709.54	7.59	-302.13	9.28	302.22	271.44	0.34	-0.22
93	8,820	0.16	117.19	8804.53	7.62	-301.61	9.31	301.71	271.45	0.40	-0.35
94	8,915	0.57	178.02	8899.53	7.09	-301.48	8.77	301.56	271.35	0.54	0.43
95	9,010	0.49	221.57	8994.53	6.31	-301.73	8.00	301.80	271.20	0.42	-0.08
96	9,105	0.26	288.96	9089.53	6.08	-302.21	7.77	302.27	271.15	0.48	-0.24
97	9,200	0.42	260.24	9184.53	6.09	-302.75	7.78	302.81	271.15	0.24	0.17
98	9,295	0.28	208.41	9279.52	5.83	-303.21	7.52	303.26	271.10	0.35	-0.15
99	9,390	0.04	145.67	9374.52	5.60	-303.30	7.29	303.35	271.06	0.28	-0.25
100	9,485	0.52	183.00	9469.52	5.14	-303.30	6.83	303.35	270.97	0.51	0.51
101	9,580	0.82	24.53	9564.52	5.33	-303.04	7.02	303.09	271.01	1.39	0.32

Company:	RKI Exploration & Production LLC		
Well Name:	Tucker Draw 9-4 Federal COM 6H		
Location:	Eddy County, NM		
Rig:	Orion Phoenix #10	Magnetic Declination:	6.88
Job Number:	DDMO-171105		
API #:	30-015-44479		
Vertical Section Azimuth:	359.68	Proposed Direction:	359.68
Survey Calculation Method:	Minimum Curvature		

REFERENCED TO GRID NORTH

Summary											
PTB:	MD		INC		AZM	TVD	N/S	E/W		VS	
	18,649		88.38		358.1	10941.45	7982.89	-375.55		7984.86	
#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance Azm		DLS/ 100	BUR/ 100'
102	9,675	0.42	8.41	9659.51	6.29	-302.71	7.98	302.78	271.19	0.46	-0.42
103	9,770	0.64	266.08	9754.51	6.60	-303.19	8.29	303.26	271.25	0.88	0.23
104	9,865	1.21	251.48	9849.50	6.24	-304.67	7.94	304.73	271.17	0.64	0.60
105	9,959	1.24	251.73	9943.48	5.61	-306.58	7.32	306.63	271.05	0.03	0.03
106	10,055	1.30	243.37	10039.45	4.80	-308.54	6.52	308.57	270.89	0.20	0.06
107	10,150	1.50	253.76	10134.43	3.96	-310.69	5.70	310.72	270.73	0.34	0.21
108	10,235	1.38	250.57	10219.40	3.31	-312.73	5.06	312.74	270.61	0.17	-0.14
109	10,330	4.17	354.06	10314.31	6.37	-314.16	8.12	314.23	271.16	4.93	2.94
110	10,424	11.04	1.13	10407.43	18.78	-314.34	20.54	314.90	273.42	7.36	7.31
111	10,519	19.67	2.68	10498.95	43.90	-313.41	45.65	316.47	277.97	9.09	9.08
112	10,614	28.87	2.02	10585.46	82.87	-311.85	84.61	322.67	284.88	9.69	9.68
113	10,709	38.15	1.48	10664.59	135.24	-310.28	136.97	338.47	293.55	9.77	9.77
114	10,803	45.18	2.11	10734.77	197.65	-308.30	199.37	366.22	302.66	7.49	7.48
115	10,898	52.30	4.55	10797.38	268.89	-304.07	270.58	405.91	311.49	7.74	7.49
116	10,992	60.95	5.51	10849.04	347.00	-297.17	348.66	456.86	319.42	9.24	9.20
117	11,087	68.98	3.02	10889.22	432.77	-290.83	434.38	521.41	326.10	8.78	8.45
118	11,182	77.25	359.30	10916.80	523.56	-289.06	525.16	598.05	331.10	9.48	8.71
119	11,276	92.38	359.48	10925.27	616.89	-290.05	618.50	681.68	334.82	16.10	16.10
120	11,406	95.05	358.19	10916.84	746.58	-292.68	748.20	801.90	338.59	2.28	2.05
121	11,501	90.40	356.71	10912.33	841.35	-296.91	842.99	892.20	340.56	5.14	-4.89
122	11,596	87.18	354.12	10914.33	936.00	-304.50	937.69	984.29	341.98	4.35	-3.39
123	11,690	87.56	355.03	10918.65	1029.48	-313.37	1031.22	1076.12	343.07	1.05	0.40
124	11,785	88.53	357.67	10921.89	1124.23	-319.42	1125.99	1168.72	344.14	2.96	1.02
125	11,880	90.30	358.39	10922.86	1219.16	-322.68	1220.94	1261.14	345.18	2.01	1.86
126	11,975	90.86	358.41	10921.90	1314.12	-325.34	1315.91	1353.79	346.09	0.59	0.59
127	12,069	91.73	359.59	10919.77	1408.08	-326.98	1409.88	1445.54	346.93	1.56	0.93
128	12,164	91.31	0.83	10917.25	1503.04	-326.63	1504.84	1538.12	347.74	1.38	-0.44
129	12,259	88.50	359.34	10917.41	1598.03	-326.49	1599.83	1631.04	348.45	3.35	-2.96
130	12,353	88.81	358.52	10919.62	1691.98	-328.24	1693.79	1723.53	349.02	0.93	0.33
131	12,448	88.85	357.57	10921.56	1786.91	-331.48	1788.73	1817.39	349.49	1.00	0.04
132	12,542	88.57	356.36	10923.67	1880.75	-336.46	1882.60	1910.61	349.86	1.32	-0.30
133	12,637	87.48	356.52	10926.95	1975.51	-342.35	1977.39	2004.96	350.17	1.16	-1.15
134	12,732	89.64	358.13	10929.33	2070.37	-346.78	2072.27	2099.21	350.49	2.84	2.27
135	12,827	89.78	0.14	10929.82	2165.35	-348.22	2167.26	2193.17	350.86	2.12	0.15

Page 4

Company:	RKI Exploration & Production LLC		
Well Name:	Tucker Draw 9-4 Federal COM 6H		
Location:	Eddy County, NM		
Rig:	Orion Phoenix #10	Magnetic Declination:	6.88
Job Number:	DDMO-171105	REFERENCED TO GRID NORTH	
API #:	30-015-44479		

Vertical Section Azimuth:	359.68	Proposed Direction:	359.68
---------------------------	--------	---------------------	--------

Survey Calculation Method:	Minimum Curvature
----------------------------	-------------------

PTB:	MD	INC	AZM	TVD	N/S	E/W	VS
	18,649	88.38	358.1	10941.45	7982.89	-375.55	7984.86

#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
136	12,922	90.67	359.68	10929.44	2260.35	-348.37	2262.26	2287.04	351.24	1.05	0.94
137	13,016	91.93	1.52	10927.31	2354.31	-347.38	2356.22	2379.80	351.61	2.37	1.34
138	13,111	90.99	1.64	10924.89	2449.25	-344.76	2451.13	2473.39	351.99	1.00	-0.99
139	13,206	90.01	1.83	10924.06	2544.20	-341.89	2546.07	2567.07	352.35	1.05	-1.03
140	13,301	89.38	0.88	10924.57	2639.17	-339.64	2641.02	2660.93	352.67	1.20	-0.66
141	13,396	94.91	2.32	10921.01	2734.02	-336.99	2735.86	2754.72	352.97	6.01	5.82
142	13,490	89.39	1.72	10917.49	2827.86	-333.69	2829.68	2847.48	353.27	5.91	-5.87
143	13,585	89.94	1.39	10918.04	2922.83	-331.11	2924.63	2941.52	353.54	0.68	0.58
144	13,680	91.09	1.86	10917.19	3017.78	-328.41	3019.57	3035.60	353.79	1.31	1.21
145	13,775	88.52	0.62	10917.51	3112.75	-326.36	3114.52	3129.81	354.01	3.00	-2.71
146	13,869	87.92	359.80	10920.43	3206.70	-326.01	3208.47	3223.23	354.19	1.08	-0.64
147	13,964	90.45	0.29	10921.78	3301.69	-325.94	3303.45	3317.73	354.36	2.71	2.66
148	14,059	89.90	359.59	10921.49	3396.68	-326.04	3398.45	3412.30	354.52	0.94	-0.58
149	14,153	89.74	358.75	10921.79	3490.67	-327.40	3492.45	3505.99	354.64	0.91	-0.17
150	14,248	90.26	358.30	10921.79	3585.64	-329.85	3587.43	3600.78	354.74	0.72	0.55
151	14,343	90.04	358.40	10921.54	3680.60	-332.58	3682.40	3695.60	354.84	0.25	-0.23
152	14,438	84.72	358.30	10925.88	3775.43	-335.31	3777.24	3790.29	354.92	5.60	-5.60
153	14,533	89.89	359.21	10930.34	3870.27	-337.37	3872.09	3884.94	355.02	5.53	5.44
154	14,627	89.64	358.49	10930.73	3964.25	-339.26	3966.08	3978.74	355.11	0.81	-0.27
155	14,721	94.07	0.49	10927.69	4058.17	-340.10	4060.00	4072.39	355.21	5.17	4.71
156	14,816	93.61	1.93	10921.33	4152.93	-338.09	4154.75	4166.67	355.35	1.59	-0.48
157	14,911	92.13	1.45	10916.57	4247.77	-335.30	4249.57	4260.98	355.49	1.64	-1.56
158	15,005	89.76	1.38	10915.02	4341.72	-332.98	4343.51	4354.47	355.61	2.52	-2.52
159	15,100	87.55	0.45	10917.25	4436.67	-331.46	4438.45	4449.04	355.73	2.52	-2.33
160	15,194	86.42	0.22	10922.19	4530.54	-330.91	4532.32	4542.61	355.82	1.23	-1.20
161	15,288	87.53	0.35	10927.15	4624.40	-330.44	4626.18	4636.20	355.91	1.19	1.18
162	15,382	89.02	359.89	10929.98	4718.36	-330.25	4720.13	4729.90	356.00	1.66	1.59
163	15,476	88.32	359.42	10932.16	4812.33	-330.81	4814.10	4823.69	356.07	0.90	-0.74
164	15,571	88.09	358.71	10935.14	4907.27	-332.36	4909.05	4918.51	356.13	0.79	-0.24
165	15,666	90.64	359.15	10936.19	5002.24	-334.14	5004.03	5013.39	356.18	2.72	2.68
166	15,760	89.17	359.66	10936.35	5096.23	-335.11	5098.03	5107.24	356.24	1.66	-1.56
167	15,855	90.98	359.98	10936.22	5191.23	-335.41	5193.02	5202.05	356.30	1.93	1.91
168	15,949	89.08	359.16	10936.18	5285.22	-336.12	5287.02	5295.90	356.36	2.20	-2.02
169	16,044	91.93	1.82	10935.34	5380.20	-335.30	5381.98	5390.63	356.43	4.10	3.00

V09.04.02

Company:	RKI Exploration & Production LLC		
Well Name:	Tucker Draw 9-4 Federal COM 6H		
Location:	Eddy County, NM		
Rig:	Orion Phoenix #10	Magnetic Declination:	6.88
Job Number:	DDMO-171105	REFERENCED TO GRID NORTH	
API #:	30-015-44479		

Vertical Section Azimuth:	359.68	Proposed Direction:	359.68
---------------------------	--------	---------------------	--------

Survey Calculation Method:	Minimum Curvature
----------------------------	-------------------

PTB:	MD	INC	AZM	TVD	N/S	E/W	VS
	18,649	88.38	358.1	10941.45	7982.89	-375.55	7984.86

#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
170	16,139	90.54	1.24	10933.29	5475.14	-332.77	5476.91	5485.24	356.52	1.59	-1.46
171	16,234	91.08	0.01	10931.95	5570.12	-331.73	5571.88	5579.99	356.59	1.41	0.57
172	16,329	90.62	0.72	10930.54	5665.11	-331.13	5666.87	5674.77	356.65	0.89	-0.48
173	16,424	88.09	359.85	10931.61	5760.09	-330.65	5761.85	5769.57	356.71	2.82	-2.66
174	16,518	88.63	359.57	10934.30	5854.05	-331.13	5855.81	5863.41	356.76	0.65	0.57
175	16,613	88.97	359.83	10936.29	5949.03	-331.63	5950.79	5958.26	356.81	0.45	0.36
176	16,707	90.21	0.56	10936.96	6043.02	-331.31	6044.78	6052.10	356.86	1.53	1.32
177	16,802	91.49	1.16	10935.55	6138.00	-329.88	6139.75	6146.86	356.92	1.49	1.35
178	16,904	98.32	2.90	10926.83	6239.50	-326.29	6241.22	6248.02	357.01	6.91	6.70
179	16,999	89.00	1.36	10920.78	6334.13	-322.78	6335.84	6342.35	357.08	9.94	-9.81
180	17,031	88.29	0.87	10921.53	6366.12	-322.16	6367.82	6374.26	357.10	2.70	-2.22
181	17,062	88.91	0.30	10922.29	6397.10	-321.84	6398.80	6405.20	357.12	2.72	2.00
182	17,094	88.69	358.98	10922.96	6429.10	-322.04	6430.79	6437.16	357.13	4.18	-0.69
183	17,141	88.20	358.67	10924.24	6476.07	-323.00	6477.77	6484.12	357.14	1.23	-1.04
184	17,188	87.98	358.67	10925.80	6523.03	-324.09	6524.74	6531.08	357.16	0.47	-0.47
185	17,283	88.38	358.98	10928.82	6617.96	-326.04	6619.68	6625.99	357.18	0.53	0.42
186	17,377	88.51	357.48	10931.37	6711.88	-328.94	6713.61	6719.94	357.19	1.60	0.14
187	17,471	90.28	356.78	10932.36	6805.75	-333.65	6807.51	6813.93	357.19	2.02	1.88
188	17,566	90.10	359.20	10932.05	6900.69	-336.98	6902.46	6908.91	357.20	2.55	-0.19
189	17,661	90.10	358.49	10931.88	6995.67	-338.90	6997.45	7003.87	357.23	0.75	0.00
190	17,756	89.88	358.19	10931.90	7090.63	-341.65	7092.42	7098.85	357.24	0.39	-0.23
191	17,851	89.79	358.19	10932.17	7185.58	-344.65	7187.39	7193.84	357.25	0.09	-0.09
192	17,945	89.31	357.48	10932.91	7279.51	-348.20	7281.34	7287.83	357.26	0.91	-0.51
193	18,040	88.91	356.86	10934.39	7374.38	-352.89	7376.24	7382.82	357.26	0.78	-0.42
194	18,135	89.31	357.96	10935.86	7469.27	-357.18	7471.15	7477.80	357.26	1.23	0.42
195	18,229	89.62	357.96	10936.74	7563.21	-360.53	7565.10	7571.79	357.27	0.33	0.33
196	18,324	89.70	358.27	10937.30	7658.15	-363.65	7660.06	7666.78	357.28	0.34	0.08
197	18,418	89.48	357.17	10937.98	7752.07	-367.39	7754.00	7760.77	357.29	1.19	-0.23
198	18,513	89.70	358.27	10938.66	7846.99	-371.17	7848.95	7855.77	357.29	1.18	0.23
199	18,604	88.38	358.10	10940.18	7937.93	-374.05	7939.90	7946.74	357.30	1.46	-1.45
PTB:	18,649	88.38	358.10	10941.45	7982.89	-375.55	7984.86	7991.72	357.31	0.00	0.00