Submit 1 Copy To Appropriate District	State of New Mexi		Form C-103 Revised July 18, 2013
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natura	l Resources	WELL API NO.
1625 N. French Dr., Hobbs, NM 88240			30-015-44664
istrict II         - (575) 748-1283         OIL CONSERVATION DIVISION           11 S. First St., Artesia, NM 88210         1220 South St. Francis Dr.		5. Indicate Type of Lease	
		STATE FEE	
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 875	05	6. State Oil & Gas Lease No.
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM			
87505	ES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		Gobbler 5 B2AD St	
DIFFERENT RESERVOIR. USE "APPLICA	ATION FOR PERMIT" (FORM C-101) FOR	SUCH	8. Well Number 1H
PROPOSALS.)			
1. Type of them on the	Gas Well 🗌 Other		9. OGRID Number 14744
<ol> <li>Name of Operator Mewbourne Oil Company</li> </ol>			
3. Address of Operator			10. Pool name or Wildcat
PO Box 5270, Hobbs NM 88241			Palmillo; Bone Springs East
4. Well Location			
Unit LetterA:_113	60 feet from the Northli	ne and _205	feet from theEastline
	hip 19S Range 28E	NMPM	Eddy County
Section 3 TOWIS	11. Elevation (Show whether DR, J		
	3411' GL		
PULL OR ALTER CASINGDOWNHOLE COMMINGLECLOSED-LOOP SYSTEM	MULTIPLE COMPL	CASING/CEMEN	NT JOB
of starting any proposed wo proposed completion or reco 03/25/18Spud 17 1/2" hole. TD'd I w/additives. Mixed @ 14.2 #/g w/ 1. FW. Plug down @ 6:30 P.M. 03/26/ 100'. Tag w/1" pipe @ 90'. Cmt 1 <sup>st</sup> p 1500# for 30 minutes, held OK. Dri 03/28/18TD'ed 12 1/4" hole @ 115 w/additives. Mixed @ 12.0 /g w/ 2.4 hels EW_Plug down @ 9:30 PM 03	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 24 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit	. For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m	eg. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop (@ 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls /OC 6hrs. Ran temp survey indicating TOC (@ ment to pit. At 1:00 A.M. 03/28/18, tested csg PG. Sg. Cemented with 100 sks Lite Class C fixed @ 14.8 #/g w/ 1.33 yd. Displaced w/83 handrel hanger through BOP w/60k#. At 7:00
<ul> <li>13. Describe proposed or complosed of starting any proposed wo proposed completion or reconstruction of the starting any proposed wo proposed completion or reconstruction. Spud 17 1/2" hole. TD'd I w/additives. Mixed @ 14.2 #/g w/ 1. FW. Plug down @ 6:30 P.M. 03/26/100'. Tag w/1" pipe @ 90'. Cmt 1<sup>st</sup> p1500# for 30 minutes, held OK. Dri</li> <li>03/28/18TD'ed 12 1/4" hole @ 115</li> </ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 2 blug w/100 sks Class C w/4% CaCL lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW	ertinent details, a . For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with	<ul> <li>Sg. Cemented 1<sup>st</sup> lead with 181 sks Thixotrop</li> <li>(a) 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls</li> <li>/OC 6hrs. Ran temp survey indicating TOC (e) ment to pit. At 1:00 A.M. 03/28/18, tested csg</li> <li>PG.</li> <li>PG.</li> <li>Psg. Cemented with 100 sks Lite Class C</li> <li>fixed (a) 14.8 #/g w/ 1.33 yd. Displaced w/83 nandrel hanger through BOP w/60k#. At 7:00</li> </ul>
<ul> <li>13. Describe proposed or complos of starting any proposed wo proposed completion or recompletion or recompletion. Spud 17 1/2" hole. TD'd I w/additives. Mixed @ 14.2 #/g w/ 1. FW. Plug down @ 6:30 P.M. 03/26/100'. Tag w/1" pipe @ 90'. Cmt 1<sup>st</sup> p1500# for 30 minutes, held OK. Dri</li> <li>03/28/18TD'ed 12 1/4" hole @ 115 w/additives. Mixed @ 12.0 /g w/ 2.4 hels EW. Plug down @ 9:30 PM 03</li> </ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 24 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit	ertinent details, a . For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with	<ul> <li>Seg. Cemented 1<sup>st</sup> lead with 181 sks Thixotrop</li> <li>(a) 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls</li> <li>/OC 6hrs. Ran temp survey indicating TOC (a)</li> <li>ment to pit. At 1:00 A.M. 03/28/18, tested csg</li> <li>PG.</li> <li>Seg. Cemented with 100 sks Lite Class C</li> <li>fixed (a) 14.8 #/g w/ 1.33 yd. Displaced w/83</li> <li>handrel hanger through BOP w/60k#. At 7:00</li> <li>ha 3/4" bit.</li> </ul>
<ul> <li>13. Describe proposed or complof starting any proposed wo proposed completion or recompletion or recompletion. Spud 17 1/2" hole. TD'd I w/additives. Mixed @ 14.2 #/g w/ 1. FW. Plug down @ 6:30 P.M. 03/26/100'. Tag w/1" pipe @ 90'. Cmt 1<sup>st</sup> p 1500# for 30 minutes, held OK. Dri</li> <li>03/28/18TD'ed 12 1/4" hole @ 115</li> <li>w/additives. Mixed @ 12.0 /g w/ 2.4</li> <li>bbls FW. Plug down @ 9:30 PM 03</li> <li>A.M. 03/29/18, tested csg to 1500#,</li> <li>Spud Date: 03/25/2018</li> </ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 2 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW Rig Rele	ertinent details, a For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W C. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with ase Date:	eg. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop (@ 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls /OC 6hrs. Ran temp survey indicating TOC ( ment to pit. At 1:00 A.M. 03/28/18, tested cs; PG. Sg. Cemented with 100 sks Lite Class C fixed @ 14.8 #/g w/ 1.33 yd. Displaced w/83 handrel hanger through BOP w/60k#. At 7:00 h 8 3/4" bit. RECEIVED APR 3 0 2018
<ul> <li>13. Describe proposed or complof starting any proposed wo proposed completion or recompletion or recompletion. TD'd I w/additives. Mixed @ 14.2 #/g w/ 1. FW. Plug down @ 6:30 P.M. 03/26/100'. Tag w/1" pipe @ 90'. Cmt 1<sup>st</sup> p 1500# for 30 minutes, held OK. Dri</li> <li>03/28/18TD'ed 12 1/4" hole @ 115 w/additives. Mixed @ 12.0 /g w/ 2.4 bbls FW. Plug down @ 9:30 PM 03 A.M. 03/29/18, tested csg to 1500#,</li> </ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 2 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW Rig Rele	ertinent details, a For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W C. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with ase Date:	eg. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop (@ 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls /OC 6hrs. Ran temp survey indicating TOC (@ ment to pit. At 1:00 A.M. 03/28/18, tested csg PG. Sg. Cemented with 100 sks Lite Class C fixed @ 14.8 #/g w/ 1.33 yd. Displaced w/83 handrel hanger through BOP w/60k#. At 7:00 h 8 3/4" bit. RECEIVED APR 3 0 2018
<ul> <li>13. Describe proposed or complete of starting any proposed wo proposed completion or recompletion or recomplete of the starting any proposed wo proposed completion or recomplete of the starting and proposed work and the starting any proposed work and the starting any proposed work and the starting any proposed work and the starting a</li></ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 24 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW Rig Rele	ertinent details, a For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with ase Date:	Attach wendore diagram of ag. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop (a) 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls /OC 6hrs. Ran temp survey indicating TOC (a) ment to pit. At 1:00 A.M. 03/28/18, tested csg PG. Agreen and the set of
<ul> <li>13. Describe proposed or complete of starting any proposed wo proposed completion or recompletion or recomplete of the starting any proposed wo proposed completion or recomplete of the starting and proposed work and the starting any proposed work and the starting any proposed work and the starting any proposed work and the starting a</li></ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 2 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW Rig Rele	ertinent details, a For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with ase Date:	Attach wendore diagram of ag. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop 1 @ 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls /OC 6hrs. Ran temp survey indicating TOC ( ment to pit. At 1:00 A.M. 03/28/18, tested csg PG. ag. Cemented with 100 sks Lite Class C fixed @ 14.8 #/g w/ 1.33 yd. Displaced w/83 handrel hanger through BOP w/60k#. At 7:00 h 8 3/4" bit. RECEIVED APR 3 0 2018 dge and belief. DISTRICT II-ARTESIA O.
<ul> <li>13. Describe proposed or complos of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion. Specific terms and the starting and proposed completion or recompletion or recompletion. The specific terms and the starting and proposed completion or recompletion or recompletion. The specific terms are specific to a specific terms and the starting and proposed completion or recompletion or recompletion or recompletion. The specific terms are specific terms and the specific terms are specific to a specific terms and the specific terms are specific to a specific terms and the specific terms are specific terms and terms are specific terms are specific. The specific terms are specific t</li></ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 24 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW Rig Rele above is true and complete to the be 	ertinent details, a . For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with ase Date: est of my knowled latory llero@mewbourn	Sg. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop         1 @ 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls         //OC 6hrs. Ran temp survey indicating TOC (         ment to pit. At 1:00 A.M. 03/28/18, tested csp         PG.         *sg. Cemented with 100 sks Lite Class C         fixed @ 14.8 #/g w/ 1.33 yd. Displaced w/83         handrel hanger through BOP w/60k#. At 7:00         ha 3/4" bit.         RECEIVED         APR 3 0 2018         dge and belief.         DISTRICT II-AFTESIA O         DATE04/26/2018         he.com PHONE: _575-393-5905
<ul> <li>13. Describe proposed or complos of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion. Signature and the information of the proposed completion or recompletion or recompletion. The proposed completion or recompletion or recompletion. The proposed completion or recompletion or recompletion or recompletion or recompletion. The proposed completion or recompletion or recompletion or recompletion or recompletion. The proposed completion or recompletion of the proposed completion or recompletion or recompletion. The proposed completion or recompletion or recompletion or recompletion. The proposed completion of the proposed completion of the proposed completion of the proposed completion of the proposed completion or recompletion. The proposed completion of the proposed completion of the proposed completion of the proposed completion or recompletion. The proposed completion of the proposed completion of</li></ul>	rk). SEE RULE 19.15.7.14 NMAC ompletion. hole @ 455'. Ran 445' of 13 3/8" 54 62 yd. Tail w/470 sks Class C w/0.5 18. Did not circ cmt. Lift pressure 24 olug w/100 sks Class C w/4% CaCl2 lled out with 12 1/4" bit. FIT test to 7'. Ran 1147' of 9 5/8" 36# J55 & 4 47 yd. Tail with 200 sks Class C w/ /28/18. Circ 73 sks of cmt to the pit held OK. FIT test to 9.5 PPG EMW Rig Rele above is true and complete to the be 	ertinent details, a . For Multiple Co .5# J55 ST&C cs % CaCl2. Mixed 00# @ 3 BPM. W 2. Circ 30 sks cer EMW of 10.5 Pl 0# N80 LT&C C 0.1% retarder. M s. Set Cameron m . Drilled out with ase Date: est of my knowled latory llero@mewbourn	Sg. Cemented 1 <sup>st</sup> lead with 181 sks Thixotrop         1 @ 14.8 #/g w/ 1.33 yd. Displaced w/61 bbls         //OC 6hrs. Ran temp survey indicating TOC (iment to pit. At 1:00 A.M. 03/28/18, tested csg         //PG.         *sg. Cemented with 100 sks Lite Class C         fixed @ 14.8 #/g w/ 1.33 yd. Displaced w/83         handrel hanger through BOP w/60k#. At 7:00         ha 3/4" bit.         RECEIVED         APR 3 0 2018         dge and belief.         DISTRICT II-ARTESIA O         DATE04/26/2018         he.com PHONE: _575-393-5905