

Submit 1 Copy To Appropriate District
Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-23844
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Pardue Farms 27
8. Well Number: 6
9. OGRID Number 241333
10. Pool name or Wildcat Culebra Bluff, Bone Springs South, East Loving Brushy Canyon

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Pardue Farms 27
2. Name of Operator Chevron Midcontinent, L.P.	8. Well Number: 6
3. Address of Operator 6301 Deauville Blvd., Midland, TX 79706	9. OGRID Number 241333
4. Well Location Unit Letter N : 766 feet from the SOUTH line and 1874 feet from the WEST line Section 27 Township 23S Range 28E NMPM County Lea	10. Pool name or Wildcat Culebra Bluff, Bone Springs South, East Loving Brushy Canyon
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3072' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 8 5/8" 24# @ 490': TOC @ surface; 4 1/2" 10.5 & 11.6# @ 7183': TOC @ surface

5/17/2018: MIRU, pull rods 5/18/2018: Continue pull rods, N/U BOPE, pull tubing 5/19/2018: Set CIBP @ 5850', circulate well w/ 10 ppg bring, pressure test casing t/ 600 psi – failed, spot 45 sx CL "C" cement plug f/ 5850' t/ 5185' (CIBP, DV Tool), run CBL f/ 4000' t/ surface – no cement f/ 660' t/ surface, good cement f/ 2480' t/ 660', no cement f/ 2820' t/ 2480', good cement f/ 4000' t/ 2820'. 5/21/2018: Tag TOC @ 5228', pressure test casing t/ 600 psi – lost 50 psi in 10 minutes (less than 10%), perf @ 2800', establish injection rate of 2 bpm @ 800 psi, squeeze 25 sx CL "C" cement w/ gas block, leaving ETOC @ 2700', shut in w/ 700 psi. 5/22/2018: Tag TOC @ 2625', notified Gilbert Cordero, pressure test casing t/ 600 psi – lost 50 psi in 10 minutes (less than 10%), no pressure on surface casing, performed bubble test – good, spot 40 sx CL "C" cement plug f/ 2624' t/ 2080' (B. Salt, DV Tool). WOC & tag TOC @ 2074'. Pressure test casing t/ 600 psi – lost 50 psi in 10 minutes (less than 10%). Notified Gilbert Cordero. Spot salt gel f/ 2074' t/ 1279'. Spot 26 sx CL "C" cement plug f/ 1279' t/ 935' (T. Salt). 5/23/2018: Tag TOC @ 893', notified Gilbert Cordero, perf @ 540', squeeze 320 sx CL "C" cement f/ 540' t/ surface (Shoe, Fresh Water), taking returns out of 8 5/8" surface valve. Job complete.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

5/24/2018

X Nick Glann

Nick Glann
Well Abandonment Engineer

SIGNATURE Signed by: Nick Glann

E-mail address: nglann@chevron.com PHONE: 432-687-7786

For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr. DATE 5-24-18
Conditions of Approval (if any):