Form 3160-5 (September 2001)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

O STATES

OF THE INTERIOR

FORM APPROVED
OM B No. 1004-0135
Expires: January 31, 2004

### SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

	NW1 22034		
6.	If Indian, Allottee or Tribe Name		

5. Lease Serial No.

abandoned we	ell. Use Form 3160 - 3 (	APD) for such proposi	als.	
SUBMIT IN TR	7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well Oil Well □	8. Well Name and No.			
2. Name of Operator Stephens & J	Johnson Operating Co.			Mobil "22" Federal No. 9  9. API Well No.
3a Address         3b. Phone No. (in 940-723-2166)           P O Box 2249, Wichita Falls, TX 76307         940-723-2166			code)	30-015-25588  10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., 330' FSL, 990' FWL, S			Brushy Draw, Delaware  11. County or Parish, State  Eddy County, New Mexico	
12. CHECK AI	PPROPRIATE BOX(ES) TO	INDICATE NATURE O	F NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF	FACTION	
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Sta Reclamation Recomplete Temporarily Ab Water Disposal	Well Integrity Other andon
If the proposal is to deepen dire Attach the Bond under which the following completion of the inv	ectionally or recomplete horizontal the work will be performed or prov- volved operations. If the operation and Abandonment Notices shall be	ly, give subsurface locations and ide the Bond No. on file with BI results in a multiple completion	measured and tru LM/BIA. Require or recompletion in	y proposed work and approximate duration thereof. e vertical depths of all pertinent markers and zones. It is subsequent reports shall be filed within 30 days in a new interval, a Form 3160-4 shall be filed once ation, have been completed, and the operator has
2. Shoot 4 way squeeze ho 5 1/2" csg and 8 5/8" cs	July 2, 2018. Set CIBP @ 480 bles at 600'. Circulate cement g. Leave 5 1/2" csg full of cer depth and erect P&A marker	out squeeze holes at 600' ba nent. Estimate 250 sx cemer		tween
Note: Please see attached	wellbore schematics of currer	nt well condition and "Propo	sed Plug and A	
				RECEIVED
	<u> ۵</u> د	6-14-18 record - NMOCD		JUN 1 3 2018
	DISTRICT II-ARTESIA O.C.D.			
14. I hereby certify that the fore Name (Printed/Typed)	going is true and correct	į		

Name (Printed/Typed)

William M. Kincaid

Title Petroleum Engineer

Date

06/08/2018

Title Petroleum Engineer

Title Petroleum Engineer

Title Date

Office

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

#### **GENERAL INSTRUCTIONS**

This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this

form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from the local Federal office.

#### SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13 - Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or

present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well and date well site conditioned for final inspection looking to approval of the abandonment.

#### NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

**EFFECT OF NOT PROVIDING THE INFORMATION:** Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

This information is being collected to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

#### **BURDEN HOURS STATEMENT**

Public reporting burden for this form is estimated to average 25 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0135), Bureau Information Collection Clearance Officer, (WO-630), Mail Stop 401 LS, 1849 C St., N.W., Washington D.C. 20240

lobil 22 Federal No. 4	brushy Draw, Delaware	June 8, 2018
WELL	Brushy Draw, Delaware FIELD	DATE
	SUGGESTED COMPLETION	
B ELEVATION 2896	DF ELEVATION	GLELEVATION _ 2886 '
PERMANENT WELL BORE DATA		DATA ON THIS COMPLET
85/8" 23# Csq set @365 Cemented with 225 sx circ 25 sx to surface	SAME TO SECULATION AND THE SECOND SEC	Estimated TOC@327  Perk: 4912-4968
15.50# Csq set@6120' Mented with 7155x 1 Tool@ 5215' timated TOC@3,279'		
	DRID / 291	
	PBTD - <u>6091'</u>	
	PBTD - <u>6091'</u> TD - <u>6120'</u>	

Charles of Johnson Operating	, G,
Stephens & Johnson Operative Mobil 22 Federal No. 9	Brushy Draw, Delaware
WELL	EIEL D

# Proposed Plug + Abandonment DATE

KB ELEVATION 2896	DF ELEVATION	GL ELEVATION 2886
PERMANENT WELL BORE DATA		DATA ON THIS COMPLETI
858, 23# Csq set @365'  Cemented with 225 sx  Circ 25 sx to surface  Strongled & 5015'  Estimated Toc @ 3,279'	BRID - 6091	Circulate (emerout squeeze holes at 0600' back to surface between 57 csq and 85/8" csq. Leave 572" csq Gull cement. 250 st Total holes @ 600' Derf 4 way squeeze holes @ 600' Derf 4 way squeeze holes @ 600' w/4 sx cement on top  Perfs: 4912-4968
	PBTD - <u>6091'</u> TD - <u>6/20'</u>	