NM OIL CONSERVATION ARTESIA DISTRICT

AUG 27 2018

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fc. NM 875

State of New Mexico Energy, Minerals and Natural Resources Department

RECEIVED it Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

1220 S. St. Francis Dr., Santa Fc, NM 87505 Santa Fe, NM 87505						
Date: 8-24-18		GAS CA	APTURE PL	AN		
☑ Original☐ Amended - Reason for	_	Operator & OGRID No.: Mewbourne Oil Company - 14744				
This Gas Capture Plan onew completion (new dri	ill, recomplete to	o new zone, re-fra	ac) activity.			a facility flaring/venting fo
Well(s)/Production Factor The well(s) that will be 1	ility – Name of	facility				ч ој 19.15.16.12 <i>Пии</i> нс <i>ј</i> .
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Silver Bullet 16 WIDM State #211	30.015	D - 16- 26\$ - 29E	225' FNL & 360' FWL	0	NA	ONLINE AFTER FRAC
place. The gas produce western low 3,400 ' of pipeline to (periodically) to western be drilled in the foreseen	d to a production ed from product //high pressure connect the fare a connect	n facility after fl- tion facility is de- gathering system cility to low/high drilling, completion	edicated to _ n located in n pressure ga n and estimate ourne Oil Co	Western EDDY thering system ted first produmpany and	County, New em. <u>Mewbo</u> uction date for western	 Mexico. It will require the opening of the opening of

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on western system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines