State of New Mexico Energy, Minerals and Natural Resources Department

5

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit Original to Appropriate District Office

NM OIL CONSERVATION ARTESIA DISTRICT

AUG 27 2018

GAS CAPTURE PLAN

RECEIVED

Original

Date: 8-10-2018

Operator & OGRID No.: OXY USA INC. - 16696

□ Amended - Reason for Amendment:_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	Å PI	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
Refried Beans CC 15-16 State Com 12H		H 15 24S 29E	2365'FNL 280'FEL	5,536	03	0.015-45	2/5
Refried Beans CC 15-16 State Com 13H		H 15 24S 29E	2400'FNL 280'FEL	5.536	0		
Refried Beans CC 15-16 State Com 14H		1 15 24S 29E	1330'FSL 420'FEL	5,536	0		
Whomping Willow CC 15-16 State Com 44H		I 15 24S 29E	1365'FSL 420'FEL	8,717	0		

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, where a gas transporter system is in place. The gas produced from production facility is dedicated to <u>Enterprise Field Services, LLC ("Enterprise</u>") and is connected to <u>Enterprise</u> high pressure gathering system located in Eddy County, New Mexico. <u>OXY USA INC. ("OXY")</u> provides (periodically) to <u>Enterprise</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>OXY</u> and <u>Enterprise</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Orla Plant Processing Plant located in Sec. 35, Block 57, T2, T&P RR CO, Reeves, County, Texas. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Enterprise</u> system at that time. Based on current information, it is <u>OXY's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines