NM OIL CONSERVATION ARTESIA DISTRICT

	UNITED STA DEPARTMENT OF TH	TE INTERIOR	Depy SEP 04 2018	FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018	
	BUREAU OF LAND MANAGEMENT RECEI		RECEIVED	IS nease Serial No.	
SL Do no	JNDRY NOTICES AND RE	'NOTICES AND REPORTS ON WELLS		M036191	
abando	Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.			an, Allottee or Tribe Name	
SUE	BMIT IN TRIPLICATE - Other	Instructions on page 2	7. If Unit	or CA/Agreement, Name and/or N	
I. Type of Well Image: Signal Control of Signal Control Image: Signal Con			8. Well N FEDE	ame and No. RALES BO 12	
2. Name of Operator Contact: TINA HUERTA EOG Y RESOURCES INC E-Mail: tina_huerta@eogresources.com			9. API W 30-01	ell No. 5-24289-00-S1	
3a. Address 3b. Phone No. (include area control of the second secon			code) 10. Field EAGI	and Pool or Exploratory Area E CREEK	
4. Location of Well (Foota	ge, Sec., T., R., M., or Survey Descrip	ption)	11. Coun	ty or Parish, State	
Sec 22 T17S R25E NENE 330FNL 990FEL			EDDY	COUNTY, NM	
12. CHECK	THE APPROPRIATE BOX(ES) TO INDICATE NATUR	E OF NOTICE, REPORT	, OR OTHER DATA	
TYPE OF SUBMISSIO	ON	TYPE OF ACTION			
Notice of Intent	🗖 Acidize	🗖 Deepen	Production (Start/F	Resume) 🔲 Water Shut-Of	
-	Alter Casing	🗖 Hydraulic Fractur	ing 🔲 Reclamation	🗖 Well Integrity	
Subsequent Report	🗖 Casing Repair	New Construction	n 🗖 Recomplete	Other	
🗇 Final Abandonment N	votice 📋 Change Plans	🛛 Plug and Abando	n 🛛 Temporarily Aban	don	
	Convert to Inject	ion 🛛 Plug Back	🗖 Water Disposal		
testing has been completed. determined that the site is re	e involved operations. If the operations. Final Abandonment Notices must b eady for final inspection. c. plans to plug and abandon t	e filed only after all requirements, in	icluding reclamation, have been	completed and the operator has	
 MIRU all safety equipment as needed. Pull production equipment. RIH with GR/JB to 1175 ft. Set a CIBP at 1165 ft. Load the hole with fresh water, pressure test 4-1/2 inch casing to 500 psi and circulate an 82 sx class C cement plug from 1165 ft up to surface, WOC. 				MATION PROCEDURE ATTACHED	
2. RIH with GR/JB to 1 3. Set a CIBP at 1165	ft. resh water, pressure test 4-1/2	2 inch casing to 500 psi and a			
 RIH with GR/JB to 1 Set a CIBP at 1165 Load the hole with f sx class C cement plug Back fill as needed. Cut off wellbead and 	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clea	in un location as per regulater	4		
 RIH with GR/JB to 1 Set a CIBP at 1165 Load the hole with f sx class C cement plug Back fill as needed. Cut off wellbead and 	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clea	in un location as per regulater	4	CHED FOR	
 RIH with GR/JB to 1 Set a CIBP at 1165 Load the hole with f sx class C cement plug Back fill as needed. Cut off wellbead and 	iresh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clea wathached was was decured	in up location as per regulated by OCO on 3-5-20	SEE ATTA	CHED FOR NS OF APPROVA'.	
 RIH with GR/JB to 1 Set a CIBP at 1165 Load the hole with f sx class C cement plug Back fill as needed. Cut off wellbead and 	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clear wathached lug was decuded <u>weathached network</u> regoling is true and convect. Electronic Submission For EOG	In up location as per regulated by OCO on 3-5-20 <u>MARE IF 45 WELL</u> In #403052 vertified by the BLM Y RESOURCES INC. sent to 1	d. SEE ATTA(218, CONDITIO (11) CONDITIO Well Information System be Carlsbad	NS OF APPROVA'.	
2. RIH with GR/JB to 1 3. Set a CIBP at 1165 4. Load the hole with first class C cement plug 6. Back fill as needed. 6. Cut off wellhead and Wellhere schemetric Jafut for plug but my for plug but my for plug 14. I hereby certify that the for	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clear wathached lug was decuded <u>weathached network</u> regoling is true and convect. Electronic Submission For EOG	n up location as per regulated by OLD on 3-5-20 MARC & South March & South & South March & South & South & South March & South & South & South	d. SEE ATTA(218, CONDITIO (11) CONDITIO Well Information System be Carlsbad	NS OF APPROVA'.	
2. RIH with GR/JB to 1 3. Set a CIBP at 1165 4. Load the hole with first class C cement plug 6. Back fill as needed. 6. Cut off wellhead and Wellhore share the Jafut fo plug hut hereby certify that the for Name (Printed/Typed) TIM	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clear with the check ing was decreated for the subscription of the subscription regoling is true and correct. Electronic Submission For EOG Committed to AFMSS for participation	In up location as per regulated by OCO on 3-5-20 Made A to Well on #403052 verified by the BLM or RESOURCES INC, sent to to rocessing by PRISCILLA PERE Title REC	d. SEE ATTA(CONDITIO Well Information System the Carlsbad IZ on 02/02/2018 (18PP1025	NS OF APPROVA'.	
2. RIH with GR/JB to 1 3. Set a CIBP at 1165 4. Load the hole with first class C cement plug 5. Back fill as needed. 6. Cut off wellhead and Wellhore schemetric Jafut fo plug hut hope for the formation of the formation o	iresh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clear with the check ing was decided for the check ing was decided for the correct. Electronic Submission For EOG Committed to AFMSS for pr NA HUERTA	In up location as per regulated by OCO on 3-5-20 Made A to Well on #403052 verified by the BLM or RESOURCES INC, sent to to rocessing by PRISCILLA PERE Title REC	d. SEE ATTA(218, CONDITIO Well Information System the Carlsbad IZ on 02/02/2018 (18PP1025 GULATORY SPECIALIST 11/2018	NS OF APPROVA'.	
2. RIH with GR/JB to 1 3. Set a CIBP at 1165 4. Load the hole with first class C cement plug 6. Back fill as needed. 6. Cut off wellhead and Wellhere schemetric Jaffer Schemetric Jaffer John John Mame (Printed/Typed) TIN Signature (Ele Approved By	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clear with the check line was Alcused was a correct. Electronic Submission For EOG Committed to AFMSS for pr NA HUERTA ectronic Submission) THIS SPACE	in up location as per regulated by OLO on 3-5-20 Made I to Well in #403052 verified by the BLM is YRESOURCES INC, sent to to rocessing by PRISCILLA PERE Title REC Date 02/0 FOR FEDERAL OR STA	d. SEE ATTA(218, CONDITIO Well Information System the Carlsbad IZ on 02/02/2018 (18PP1025 GULATORY SPECIALIST 11/2018	NS OF APPROVA'.	
2. RIH with GR/JB to 1 3. Set a CIBP at 1165 4. Load the hole with first class C cement plug 6. Back fill as needed. 6. Cut off wellhead and Wellhore scheme king Mathematical Control of the formation of t	resh water, pressure test 4-1/2 g from 1165 ft up to surface, V d install dry hole marker. Clear wathached lug was decused <u>water Alker w</u> regoing is true and correct. Electronic Submission For EOG Committed to AFMSS for pr NA HUERTA ectronic Submission) THIS SPACE	by OCO m 3-5-20 Made A to Well m #403052 verified by the BLM PARESOURCES NC, sent to to rocessing by PRISCILLA PERE Title REC Date 02/0 FOR FEDERAL OR STA	d. SEE ATTA(218, CONDITIO Well Information System the Carlsbad IZ on 02/02/2018 (18PP1025 GULATORY SPECIALIST 11/2018	NS OF APPROVA'.	

i


.


•

*** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Revisions to Operator-Submitted EC Data for Sundry Notice #403052

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	ABD NOI	ABD NOI
Lease:	NMNM036191	NMNM036191
Agreement:		
Operator:	EOG Y RESOURCES, INC. 104 SOUTH FOURTH STREET ARTESIA, NM 88210 Ph: 575-748-1471	EOG Y RESOURCES INC 104 S 4TH STREET ARTESIA, NM 88210 Ph: 575 748 1471
Admin Contact:	TINA HUERTA REGULATORY SPECIALIST E-Maii: tina_huerta@eogresources.com	TINA HUERTA REGULATORY SPECIALIST E-Mail: Ilna_huerta@eogresources.com
	Ph: 575-748-4168	Ph: 575-748-4168 Fx: 575-748-4585
Tech Contact:	TINA HUERTA REGULATORY SPECIALIST E-Mail: tina_huerta@eogresources.com	TINA HUERTA REGULATORY SPECIALIST E-Mail: tina_huerta@eogresources.com
	Ph: 575-748-4168	Ph: 575-748-4168 Fx: 575-748-4585
Location: State: County:	NM EDDY	NM EDDY
Field/Pool:	EAGLE CREEK; SAN ANDRES	EAGLE CREEK
Well/Facility:	FEDERALES BO 12 Sec 22 T17S R25E NENE 330FNL 990FEL	FEDERALES BO 12 Sec 22 T17S R25E NENE 330FNL 990FEL





BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement</u>: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos

Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612