

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-41806
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator COG Operating LLC		6. State Oil & Gas Lease No.
3. Address of Operator 2208 W Main St., Artesia NM 82810		7. Lease Name or Unit Agreement Name Willow 17 State SWD
4. Well Location Unit Letter P : 660 feet from the South line and 660 feet from the East line Section 17 Township 25S Range 28E NMPM Eddy County		8. Well Number #1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3016' GR		9. OGRID Number 229137
		10. Pool name or Wildcat SWD Devonian

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Workover ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

POOH & LD 204 jts 4.5" P110 buttress glassbore csg. RIH w/ bit & scraper to 14,253'. Acidize well w/ 40,000 gals of 15% of double inhibited NEFE acid & 15,000 gals. Of 2500 ppm chlorine dioxide in alternating stages avg 4313#. Avg rate 14.3 BPM, ISIP 842#, well On vac in 3 min. RIH & set top pkr @ 14,210'. Tag pkr @ 14,210' on 344 jts tbg. Release ratchet latch from pkr LD tag jt., space out W/6' & 10' pup joints. Displace hole w/ W650 bbls of fresh water containg biocides, pkr fluid, oxygen scavenger & corrosion inhibitors @ 1.5 BPM. Sting into pkr. Install tbg hangar and land in WH. Pressure csg to 540# for 30 min. Chart. Final press 535# (5# loss). NMOCD rep Gilbert Cordero on site.

RECEIVED

SEP 26 2018

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Amanda L Avery TITLE Regulatory Tech DATE 09/24/2018

Type or print name Amanda L Avery E-mail address: aavery@concho.com PHONE: 575-748-6962
For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 9-26-18
Conditions of Approval (if any):