Approved By LES BABYAR

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Lease Serial No. NMNM9194

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

Date 06/27/20

abandoned we	6. If Indian, Allottee	or Tribe Name		
SUBMIT IN TRI	7. If Unit or CA/Agr	eement, Name and/or No.		
Type of Well			8. Well Name and No SACOHUISTE K	
2. Name of Operator Contact: YATES PETROLEUM CORPORATION		- 1 St	il: tinah@ypcnm.com 442 2003 5\30-015-22857-00-S1	
3a. Address 105 S 4TH STREET ARTESIA, NM 88210		36. Phone No. (include area Editived) Ph: 505.748:4168 OCD - ARTESIA Fx: 505.748.4585		r Exploratory
4. Location of Well (Footage, Sec., T., R., M., or Survey Description Sec 34 T22S R23E SWSE 660FSL 1980FEL		920212026	EDDY COUNT	,
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE NATURE OF	I NOTICE, REPORT, OR OTHI	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	☐ Acidize ☐ Alter Casing	Deepen Fracture Treat	☐ Production (Start/Resume) ☐ Reclamation	☐ Water Shut-Off ☐ Well Integrity
☐ Subsequent Report ☐ Final Abandonment Notice	Casing Repair Change Plans	☐ New Construction ☐ Plug and Abandon	Recomplete Temporarily Abandon	Other
1	Convert to Injection	Plug Back	☐ Water Disposal	
If the proposal is to deepen directions Attach the Bond under which the wo following completion of the involved	ally or recomplete horizontally, rk will be performed or provide operations. If the operation re bandonment Notices shall be file	give subsurface locations and measure the Bond No. on file with BLM/BL sults in a multiple completion or rec	ng date of any proposed work and apprured and true vertical depths of all pert A. Required subsequent reports shall be ompletion in a new interval, a Form 3 I ding reclamation, have been completed	inent markers and zones. be filed within 30 days 60-4 shall be filed once
Yates Petroleum Corporation	plans to plug and abando	on this well as follows:		
1. ND wellhead and NU BOP. replace any bad or worn joints 2. Set cement retainer at 2092 and reverse circulate cement 3. Load the hole with plugging 8-5/8" intermediate casing shu 4. Perforate 6 holes at 350'. Fe-5/8" annulus. WOC. 5. Spot 15 sx Class "C" cement 6. Remove all surface equipment.	the street of the tubing. It is a count of the tubing. It is mud and spot 25 sx Clabe. It is a count of the tubing the surface plug.	Class "C" cement. Sting out on the sting out of the second section 1955'-205' ement down the casing and u	of the retainer 55' across the	
14. Thereby certify that the foregoing is	true and correct			
	Electronic Submission :	#23494 verified by the BLM We DLEUM CORPORATION, sent to ocessing by Linda Askwig on the control of the control	ll Information System to the Carlsbad 06/24/2003 (03LA0638SE)	
Name (Printed/Typed) TINA HUE		· ·	OMPLIANCE SUPERVISOR	
Signature (Electronic S	Supplies (Supplies Supplies Su	Date 06/20/2	2003	
	THIS SPACE FO	OR FEDERAL OR STATE	OFFICE USE	

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant solds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

TitlePETROLEUM ENGINEER

Office Carlsbad