

**NM OIL CONSERVATION
ARTESIA DISTRICT**

Intent ☒ As Drilled ☐

OCT 18 2018

API #

30-015-45358

RECEIVED

Operator Name:	Property Name:	Well Number
EOG Resources, Inc.	Badboy	1H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
N	15	19S	25E		365	S	1983	W	EDDY
Latitude					Longitude				NAD
32.6548109					-104.4747440				83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
O	15	19S	25E		330	S	2520	E	EDDY
Latitude					Longitude				NAD
32.6547189					-104.4723069				83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
N	14	19S	25E		330	S	2598	W	EDDY
Latitude					Longitude				NAD
32.6546755					-104.4556773				83

Is this well the defining well for the Horizontal Spacing Unit? ☐

Is this well an infill well? ☒

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #	
Operator Name:	Property Name:
EOG Resources, Inc.	Badboy
Well Number	2H

KZ 06/29/2018

State Permit Information:**Well Name: Badboy #1H****Location:**

SL: 365' FSL & 1983' FWL, Section 15, T-19-S, R-25-E, Eddy Co., N.M.

BHL: 330' FSL & 2598' FWL, Section 14, T-19-S, R-25-E, Eddy Co., N.M.

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
12.25"	0'-1250'	9.625"	36#	J-55	LTC	1.125	1.25	1.60
8.75"	0-2836'	7"	29#	L-80	BTC	1.125	1.25	1.60
8.75"	2836'-8334'	5 1/2"	17#	L-80	BTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. lb/gal	Yld Ft ³ /ft	Slurry Description
1250'	265	12.9	1.97	Lead: Class 'C' + 4%PF20(Bentonite Gel) + 2%PF1(Calcium Chloride) + 0.125#/skPF29(Celloflake) + 0.4#/skPF45 (Defoamer) 100% Excess (TOC @ Surface)
	200	1.34	1.34	Tail: Class 'C' + 2%PF1(Calcium Chloride)
8334'	235	11.9	2.47	Lead: Class 50/50 PozC + 5%PF44(BWOW)(Salt) + 10% PF20(Bentonite Gel) +.2%PF153(Anti Settling Agent(+ 3#/sk OF42(Kolseal) + 0.125#/sk PF29 (celloflake) + 0.4#/sk PF45 (Defoamer) (TOC @ Surface) 35% Excess
	1270	13	1.48	Tail: Class PVL + 1.3% PF44(BWOW)(Salt) + 5% PF174 (Expanding Cement) + 0.5% PF606 (Fluid Loss) + 0.1% PF153 (Anti Settling Agent) + 0.4#/sk PF45 (Defoamer) 35% Excess

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 - 1250'	Fresh Water	8.6-8.8	28-32	N/c
1,250' - 8334'	Cut Brine	8.8-9.2	28-32	N/c
Vertical/Curve/Lateral				