Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137

NMNM0555569

OMD	110. 100	- -0	13/
Expires:	January	31,	2018
Lease Serial No.			

SUNDRY NO	OTICES AND	REPORTS	ON WELLS
Do not use this	form for prope	osals to drill o	r to re-enter an
abandoned well.	Use form 316	0-3 (APD) for	such proposals.

6. If Indian, Allottee or Tribe Name

apandoned wei	II. USE IOIIII 3100-3 (AP	D) for such p	roposais.		,	
SUBMIT IN 1	TRIPLICATE OTHER INS	tructions on	page 2 SIA		7. If Unit or CA/Agreeme	ent, Name and/or No.
Type of Well ☐ Gas Well ☐ Oth	ner	V I HA VV	.		8. Well Name and No. GREEN FEDERAL 4	,
Name of Operator ROVER OPERATING LLC	Contact: E-Mail: kpreston@	KENNETH A proverpetro.com			9. API Well No. 30-015-10546-00-	S1
3a. Address 17304 PRESTON ROAD SUIT DALLAS, TX 75252	ΓE 300	3b. Phone No Ph: 214-23	(include area code) 4-9115		10. Field and Pool or Exp ARTESIA	oloratory Area
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	1)			11. County or Parish, Sta	te
Sec 31 T17S R29E SWNE 16	50FNL 2310FEL			į	EDDY COUNTY, I	NM
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE OF	NOTICE,	REPORT, OR OTHE	R DATA
TYPE OF SUBMISSION			TYPE OF	ACTION		
	☐ Acidize	☐ Dee	pen	☐ Producti	ion (Start/Resume)	■ Water Shut-Off
Notice of Intent	☐ Alter Casing	☐ Hyd	raulic Fracturing	☐ Reclama	ation	■ Well Integrity
☐ Subsequent Report	☐ Casing Repair	□ New	Construction	☐ Recomp	lete	Other
Final Abandonment Notice	☐ Change Plans	_	and Abandon	□ Tempora	arily Abandon	-
	☐ Convert to Injection	Plug	Back	□ Water D	Disposal	
testing has been completed. Final At determined that the site is ready for final At the site	inal inspection. wishes to inform you of ir This wellbore has potent	ntent to tempo tial utility for fu	rarily abandon th	e Green perations.	RECEIV	
POOH with rods, pump TOH with tubing RU WL. Set CIBP at 2450?, to	est CIRD & casing to 500:				OCT 1 2	2018
Cap with 25 sxs cmt Notify BLM official and perform	n witnessed MIT				DISTRICT II-ART	ESIA O.C.D.
14. I hereby certify that the foregoing is	Electronic Submission #	OPERATING	LC, sent to the C	arlsbad	-	
Name (Printed/Typed) BRADY W	/ILTON		Title ENGINE	ER		
Signature (Electronic S	Submission)		Date 09/14/20	18		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved By ZOTA STEVENS Conditions of approval, if any, are attache	d. Approval of this notice does	s not warrant or	TitlePETROLE!	JM ENGINE	EER	Date 10/03/2018
certify that the applicant holds legal or equivalent would entitle the applicant to condu	iitable title to those rights in th		Office Carlsbad	 	=:	
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						

Additional data for EC transaction #435349 that would not fit on the form

32. Additional remarks, continued

Clean loc, RDMO

ROVER PETROLEUM, LLC **WELLBORE DIAGRAM - CURRENT**

Lease/Well No.:

GREEN FEDERAL No. 4

ELEVATION, GL: 3640'

Location:

1,650' FNL & 2,310' FEL

UL: G, SEC: 31, T: 17-S, R:29-E

FIELD: ARTESIA: QN-GB-SA

EDDY County, NM

API No.:

30-015-10546

Spudded:

7/24/1965

Drlg Stopped:

8/23/1965

<u>Plugs</u>

Completed:

8/30/1965

10" HOLE

Surface Csg: 8-5/8" 20#

Csg Set @ 461' Cmt'd w/50 sx

TOC = 107' (CALC)

8" HOLE

Production Csg: 5-1/2" 15.5# J-55 Csg Set @ 2,690' Cmt'd w/ 165 sx

TOC = 2261' (CALC)

2,690' PBTD 2,698' TD

Tubing Count Rod Count 73 jts 2 3/8" tbg 2 x 5/8" subs 5-1/2" x 2-3/8" 23 x 5/8" rods 8 jts 2-3/8" tbg 78 x 5/8" rods SN @ 2588' 2x1.25x12 pump 15' mule shoe

FORMATIONS:

<u>TOPS</u>	DEPTH, ft
TOP OF SALT	460
BOT OF SALT	720
YATES	904
SEVEN RIVERS	1,190
QUEEN	1,855
GRAYBURG	2,304
SAN ANDRES	2,664

PERFORATIONS

DEPTHS	ZONE	SPF - # OF HOLES	DATE
2504 - 2510'	GB - Metex	6' 4 spf - 24 holes	09/09/66
2520 - 2526'	GB - Metex	6' 4 spf - 24 holes	09/09/66
2602.5 - 2603.5'	GB - Premier	1' 2 spf - 2 holes	08/26/65
2609 - 2613'	GB - Premier	4' 2 spf - 8 holes	08/26/65
2630.5 - 2631.5'	GB - Premier	1' 2 spf - 2 holes	08/26/65
2634 - 2637'	GB - Premier	3' 2 spf - 6 holes	08/26/65
2645 - 2647'	GB - Premier	2' 1 spf - 3 holes	08/26/65
2651 - 2654'	GB - Premier	3' 2 spf - 6 holes	08/26/65
	TOTALS:	26' 75 holes	_

ROVER PETROLEUM, LLC WELLBORE DIAGRAM - PROPOSED

Lease/Well No.: GREEN FEDERAL No. 4

ELEVATION, GL: 3640'

Location:

1,650' FNL & 2,310' FEL

UL: G, SEC: 31, T: 17-S, R:29-E

FIELD: ARTESIA: QN-GB-SA

EDDY County, NM

API No.:

30-015-10546

Spudded:

7/24/1965

Drlg Stopped:

8/23/1965

Completed:

Tubing Count

N/A

8/30/1965

Plugs

25 sxs plug CIBP @ 2450'

Rod Count

N/A



8-5/8" 20#

Csg Set @ 461' Cmt'd w/ 50 sx

TOC = 107' (CALC)

FORMATIONS:

TOPS	DEPTH, ft
TOP OF SALT	460
BOT OF SALT	720
YATES	904
SEVEN RIVERS	1,190
QUEEN	1,855
GRAYBURG	2,304
SAN ANDRES	2,664

8" HOLE

0 11022

PERFORATIONS

DEPTHS	ZONE	SPF - # OF HOLES	<u>DATE</u>
2504 - 2510'	GB - Metex	6' 4 spf - 24 holes	09/09/66
2520 - 2526'	GB - Metex	6' 4 spf - 24 holes	09/09/66
2602.5 - 2603.5'	GB - Premier	1' 2 spf - 2 holes	08/26/65
2609 - 2613'	GB - Premier	4' 2 spf - 8 holes	08/26/65
2630.5 - 2631.5'	GB - Premier	1' 2 spf - 2 holes	08/26/65
2634 - 2637'	GB - Premier	3' 2 spf - 6 holes	08/26/65
2645 - 2647'	GB - Premier	2' 1 spf - 3 holes	08/26/65
2651 - 2654'	GB - Premier	3' 2 spf - 6 holes	08/26/65
	TOTALS	26' 75 holes	•

Production Csg: 5-1/2" 15.5# J-55 Csg Set @ 2,690' Cmt'd w/ 165 sx TOC = 2261' (CALC)

2,690' PBTD 2,698' TD **≡**

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Temporary Abandonment of Wells on Federal Lands Conditions of Approval

A temporarily abandoned well is defined as a completion that is not capable of production in paying quantities but which may have value as a service well. Pursuant to 43 CFR 3162.3-4 (c), no well may be temporarily abandoned for more than 30 days without the prior approval of the authorized officer.

Temporary Abandonment (TA) status approval requires a successful mechanical or casing integrity test as follows:

- 1. A Notice of Intent (NOI) Sundry Notice (Form 3160-5) requesting approval to run a mechanical integrity test (MIT) or casing integrity test (CIT).
- 2. A description of the temporary abandonment procedure.

. . **. .**

- a. A bridge plug or packer must be installed as close to 50 feet above any open perforations or open hole as possible. If a cement plug is used, the top of the cement must be verified by tagging. CIBP must be capped with minimum 25 sacks cement, **placed with tubing**.
- b. The wellbore must be filled with corresion inhibited fluid and pressure tested to 500 psi. The casing shall be capable of holding this pressure for at least 30 minutes. Any leak-off will be evaluated.
- c. All downhole production/injection equipment (tubing, rods, etc.) shall be removed from the casing if they are not isolated by a packer.
- d. A bradenhead test must be conducted. If the test indicates a problem exists, a remedial plan and time frame for remediation shall be submitted within ninety (90) days of the test.
- e. Contact the appropriate BLM office at least 24 hours prior to the scheduled Casing Integrity Test. For wells in Eddy County, 575,361-2822, Lea County 575-393-3612
- 3. Provides justification why the well should be temporarily abandoned rather than permanently plugged and abandoned and an estimated date that the well will be returned to beneficial use of plugged and abandoned 43 CFR 3162.3-4 (a) The operator shall promptly plug and abandon...wells in which oil or gas is not encountered in paying quantities...

Wells that successfully pass the casing integrity test **may** be approved for Temporary Abandonment (TA) status provided that the operator:

- 1. Submits a subsequent Sundry Notice (Form 3160-5) requesting TA approval with well bore diagram with all-perforations and CIBP's and tops of cement on CIBP's.
- 2. Describes the temporary abandonment procedure.
- 3. Attaches a clear copy or the original of the pressure test chart.
- 4. Give justification to allow well to be place in TA status and plan for future use of well with time frame that well will be place back on line or plans to P&A well will be submitted.

If the well does not pass the casing integrity test, then the operator shall within 30 days submit to BLM for approval one of the following:

- 1. A procedure to repair the casing so that a TA approval can be granted.
- 2. A procedure to plug and abandon the well.

Well Name: Golden Spur Federal 001H Submit Subsequent Report and well bore diagram with all Perforations and CIBP with tops of cement. Well may be approved to be TA for a period of 6 months or until 08/01/2018 after successful MIT and subsequent report is submitted. This well has been shut-in since November 2016.