District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION ARTESIA DISTRICT

Data	10/30/2018		GAS CA	PTURE PL	AN	N	10V 01	2018	
X O	riginal mended - Reason for	Amendment:_		Operator & OGRID No.: Hadaway Consulting & Engr LLC 371985					
new	Gas Capture Plan ou completion (new drill Form C-129 must be su	, recomplete to	o new zone, re-fra	c) activity.					
The '	well(s) that will be lo	cated at the pro	duction facility a	re shown in	the table bel	ow.			
	Well Name			Footages	Expected MCF/D	Flared or Vented	Comments		
	Pinehurst 5H	3000564299	21C11S28E	104 FN 1623 FW	200	flare			
Well The press facil estim Tran proce	hering System and P (s) will be connected to gas produced from pro- sure gathering system ity to low/high pressurated first production of sporter have periodic of essed at Gas Transporter at flow of the gas will be	o a production for a production facility of a located in Cincer gathering syntate for wells the conference calls or Processing Pl	racility after flowly is dedicated to chaves County, Notem. Operator pat are scheduled to discuss change ant located in Sec.	talking w/ to back operation of the control of the	DCP Midstream ons are comp ter and will It will recodically) to go the foreseed and completing. Rng.	be connected quire Gas Transpor able future. I on schedules.	Aidland TX. Ansported To Gas T Of pipe Ter a drill The addition The Gas from Count	r system is in place. ransporter low/high line to connect the ing, completion and n, Operator and Gas n these wells will be	

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>Operator's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines