District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION ARTESIA DISTRICT

MITO 11 01

	GAS CAPTURE PLAN	140 4 2 8 2018		
Date: 07/16/18	GAS CAI TURE I DAN	RECEIVED		
☐ Original	Operator & OGRID No.:	BOPCO, LP [260737]		
☐ Amended - Reason for Amendment:	SHL moved			

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

## Well(s)/Production Facility - Name of facility: Poker Lake Unit 20 BD West CTB

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Poker Lake Unit 20 BD 703H		N-20-25S-30E	955' FSL & 1915' FWL	2900	Flared/Sold	
Poker Lake Unit 20 BD 903H		N-20-25S-30E	955' FSL & 1945' FWL	2600	Flared/Sold	
Poker Lake Unit 20 BD 123H		N-20-25S-30E	955' FSL & 1975' FWL	4500	Flared/Sold	
Poker Lake Unit 20 BD 124H		N-20-25S-30E	955' FSL & 2010' FWL	4500	Flared/Sold	
Poker Lake Unit 20 BD 104H 30 -015	45469	N-20-25S-30E	955' FSL & 2005' FWL	2800	Flared/Sold	

### **Gathering System and Pipeline Notification**

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <a href="Enlink">Enlink</a> and will be connected to <a href="Enlink">Enlink</a> low/high pressure gathering system located in <a href="Loving">Loving</a> County, Texas. It will require <a href="1505">1505</a> of pipeline to connect the facility to low/high pressure gathering system. <a href="BOPCO">BOPCO</a> provides (periodically) to <a href="Enlink">Enlink</a> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <a href="BOPCO">BOPCO</a> and <a href="Enlink">Enlink</a> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <a href="Enlink">Enlink</a> Processing Plant located in <a href="Block 27">Block 27</a>, <a href="Sec. 4">Sec. 4</a>, <a href="Loving">Loving</a> County, <a href="Texas">Texas</a>. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Enlink system at that time. Based on current information, it is BOPCO's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared

- Compressed Natural Gas On rease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - O Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines