

DISTRICT I  
P.O. Box 1980, Hobbs NM 88240

DISTRICT II  
811 South First, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd, Aztec, NM 87410

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, New Mexico 87505

WELL API NO. 30-015-10400
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-4109
7. Lease Name or Unit Agreement Name Aoudad State
8. Well No. 6
9. Pool name or Wildcat Maljamar GB SA
10. Elevation (Show whether DF, RKB, RT, GR, etc.)

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS).	
1. Type Of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Mack Energy Corporation	
3. Address of Operator P.O. Box 960, Artesia, NM 88211-0960	
4. Well Location Unit Letter <u>B</u> : <u>330</u> Feet From The <u>North</u> <u>Line</u> and <u>1980</u> Feet From The <u>East</u> <u>Line</u> Section <u>36</u> Township <u>17S</u> Range <u>31E</u> NMPM <u>Eddy</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Mack Energy Corporation proposes to plug and abandon well as follows:

1. Notify OCD 24 hours prior to starting plugging operations
  2. Set CIBP @ 3900' (+)(-) w/35' cement cap.
  3. Set 35 sx cement plug from 2045-1945', base of salt csq. 2005'-2105' - TAG
  4. Set 35 sx cement plug from 1090-990', 50' above and below 8 5/8 casing shoe. Perf csq @ 1090' Place 200' of cmt inside & outside of csq. 890'-1090' - TAG
  5. Set 10 sx cement plug from 60-0'.
  6. Install dry hole marker.
- Perf both csq. strings @ 60' - Place 60' of cmt inside & outside of both csq. strings 0'-60' - WOC-24 hrs. TAG

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 6/2/2003

TYPE OR PRINT NAME Jerry W. Sherrell TELEPHONE NO. 748-1288

(This space for State Use)

APPROVED BY [Signature] TITLE Field Rep ID DATE 6-11-03

CONDITIONS OF APPROVAL, IF ANY:

OPERATOR: Mack Energy		API# 30-015-10400	
WELL: Aoudad State # 6		LOCATION: B-36-17-31	
SURFACE CSG-HOLE SIZE "	CSG. SIZE 8 5/8"	SET @ 1041'	SX. CMT. TOC. 392'
LONG STRING- HOLE SIZE "	CSG. SIZE 4 1/2"	SET @ 4049'	SX. CMT. TOC. 3759'
OTHER-			

