District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

NM OIL CONSERVATION Energy, Minerals and Natural Resources Department ARTESIA DISTRICT to Appropriate

DEC 1'8 2018 District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

RECEIVED

GAS CAPTURE PLAN

Dat	e: 12-4-18						
	Original Amended - Reason for A	Amendment:	-	& OGRID N	No.: <u>Mewbor</u>	urne Oil Con	npany - 14744
	s Gas Capture Plan outly completion (new drill,				reduce we	11/production	facility flaring/venting for
Note	e: Form C-129 must be sub	mitted and app	roved prior to exceed	ding 60 days a	llowed by Rul	e (Subsection A	1 of 19.15.18.12 NMAC).
<u>We</u>	ll(s)/Production Facilit	y - Name of	facility				
The	well(s) that will be loca	ated at the pro	oduction facility a	re shown in	the table bel	ow.	
	Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
	Sapphire 11/12 B3LK State Com #211		L - 11- 19S - 29B	1350 FSL & 285' FW	. 0	NA	ONLINE AFTER FRAC
	30.0	15-4555	9				
We place 1 w 3,400 (per be con w of t	ce. The gas produced low/him l	o a production from production pressure connect the far and le future. In a changes to Processing P	n facility after flotion facility is de gathering system cility to low/high drilling, completio addition, Mewbo drilling and completiont located in Section 1	dicated to no located in pressure gar and estima nume Oil Completion sche	thering systed first produmpany and dules. Gas	County, New em. Mewbo luction date for Western from these CulbersonCo	gas transporter system is in and will be connected to Mexico. It will require the output of Mexico is the many provides or wells that are scheduled to have periodic wells will be processed at punty, Texas. The actual flow
Aft flar san	ed or vented. During flo d, the wells will be turn	wback, the fled to product	uids and sand contion facilities. Ga	itent will be a	nonitored. V d start as so	When the procon on as the we	uction tanks and gas will be duced fluids contain minimal ills start flowing through the sed on current information, it

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines