

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-26113

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Petco State

8. Well Number **#3**

9. OGRID Number
14774

10. Pool name or Wildcat
Parkway; Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
P.O. Box 5270, Hobbs, NM 88241

4. Well Location
Unit Letter **N** : **330** feet from the **S** line and **1980** feet from the **W** line
Section **26** Township **19S** Range **29E** NMPM County **Eddy**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3324' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/05/18 MIRU Plugging equipment to location. Unhung well, POH w/ rods & pump. Dug out cellar. ND tbq, NU BOP.
11/06/18 Set 5 1/2" CIBP 4270'. Pressure tested casing, held 500 psi. Isolated hole in casing at surface. Circulated hole w/ MLF. Pressure test casing, held 500 psi. Spotted 25 sx class C cement @ 4270-4023'. WOC. Tagged plug @ 4025'. Spotted 65 sx class C cement @ 3866-3224'. WOC. 11/07/18 Tagged plug @ 3300'. Perf'd casing @ 1600'. Established an injection rate, circulated out of 8 5/8". Squeezed 45 sx class C cement w/ 2% CACL @ 1600-1500'. WOC. Tagged plug @ 1480'. ND BOP. Flange up well head, Perf'd casing @ 408'. Squeezed 115 sx class C cement @ 408' & circulated to surface. Rigged down & moved off. 11/12/18 Moved in backhoe and welder. Dug out cellar. Cut off well head. Verified cement to surface. Welded on "Above Ground Dry Hole Marker". Backfilled cellar, cut off deadmen, cleaned location and moved off.

NM OIL CONSERVATION

Spud Date:

Rig Release Date:

ARTESIA DISTRICT
DEC 12 2018

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

RECEIVED

SIGNATURE Robin Terrell TITLE District Superintendent DATE 11/26/18

Type or print name Robin Terrell E-mail address: rterrell@mewbourne.com PHONE: 505-393-5905
For State Use Only

APPROVED BY: [Signature] TITLE S/A H DATE 12-12-18
Conditions of Approval (if any):

