



TECHNOLOGY SERVICES USA INC.

Celebrating 20 Years of Focused Solutions

3610 Elkins Road, Midland, Texas 79705 T. 432.684.0057 F. 432.686.7964 www.phxtech.com

December 26, 2018

Oil Conservation Division
State of New Mexico
811 S. First St.
Artesia, New Mexico 88210

Dear District 2 - Artesia

RECEIVED

Attention: Regulatory Department

DEC 31 2018

Re: Burnett Oil
Stevens A No. 22
Eddy County, NM
API #30-015-43437
Job No. 64010

DISTRICT II-ARTESIA O.C.D.

Enclosed please find the Survey Data Certification, and the original Plat and one copy of the Survey Report performed on the above referenced Well by Phoenix Technology Services, Inc. (P-5 No. 664171). Other information required by your office is as follows:

Name & Title of Surveyor	Drain Hole Number	Surveyed Depths		Dates Performed		Type of Survey
		From	To	Start	End	
Noe Garza	22	0	6,209	12/18/18	12/18/18	Gyro

A certified plat on which the bottom hole location is oriented both to the surface location and to the lease lines (or unit lines in case of pooling) is attached to the survey report. If any other information is required, please contact the undersigned at the letterhead address and phone number.

Best Regards,

Brittany Carley

Brittany Carley
Operations Administrator

SURVEY CERTIFICATION FORM

3610 Elkins Road Midland, TX 79705 t:432-684-0057 f: 432-686-7964



PHOENIX
TECHNOLOGY SERVICES

Company: Burnett

Job #: 64010

Well Name: Stevens A No. 22

County/State: Eddy Co., New Mexico

Survey Instrument Type: North Seek Rate Gyro

API # 30-015-43437

TIE-IN DATA

Measure Depth (ft)	Vertical Depth (ft)	Inclination (°)	Azimuth (°)	N-S Coordinates	E-W Coordinates	Data Source
0	0	0	0	0	0	Surface

First Survey

Date	Depth (ft)	Inclination (°)	Azimuth (°)
2018-12-18	0	0	0

Last Survey

Date	Depth (ft)	Inclination (°)	Azimuth (°)
2018-12-18	6209	0.58	193.89

Projected TD Survey

Date	Depth (ft)	Inclination (°)	Azimuth (°)
0	0	0	0

Grid Correction
-0.22

Gyro Operator: Phoenix Technology Services USA Ltd.

Gyro Supervisor: Angel Guebara

To the best of my knowledge I certify this survey data to be correct and true

Date: 12-18-18

Print Name: Noe Garza

Signature: _____



Company: Burnett
 Well: Stevens A No. 22
 Location: Eddy Co., New Mexico
 Rig: Pulling Unit

Job Number: 64010
 Grid Corr.: -0.22
 Lat: 32.83
 Long: -103.93

Date: 12-18-18
 Calculation Method: Minimum Curvature
 Proposed Azimuth: Ground
 RKB - MSL in feet: Ground
 Tie Into: Surface

Survey Tool Type	Survey Depth (ft)	Inclination (deg)	Azimuth (deg)	Course Length (ft)	True Vertical Depth (ft)	Vertical Section (ft)	Coordinates		Closure		Dogleg Severity (d/100')	Build Rate (d/100')	Walk Rate (d/100')
							N/S (ft)	E/W (ft)	Distance (ft)	Angle (deg)			
Enter Tie-In Survey on Line 10													
FIELD COPY, NON-DEFINITIVE													
TIE IN	0			0	0	0	0	0					
Gyro	100.00	0.48	8.34	100	100.00	0.41	0.41 N	0.06 E	0.42	8.34	0.48	0.48	8.34
	150.00	0.42	19.53	50	150.00	0.79	0.79 N	0.15 E	0.81	10.86	0.21	-0.12	22.38
	200.00	0.07	311.19	50	200.00	0.99	0.99 N	0.19 E	1.01	10.93	0.80	-0.70	583.32
	250.00	0.30	238.75	50	250.00	0.94	0.94 N	0.06 E	0.94	3.40	0.57	0.46	-144.88
	300.00	0.57	218.04	50	300.00	0.68	0.68 N	0.21 W	0.71	342.78	0.62	0.54	-41.42
	350.00	0.79	225.51	50	349.99	0.24	0.24 N	0.61 W	0.65	291.38	0.47	0.44	14.94
	400.00	1.08	237.33	50	399.98	-0.26	0.26 S	1.25 W	1.28	258.36	0.69	0.58	23.64
	450.00	1.25	235.54	50	449.97	-0.82	0.82 S	2.10 W	2.25	248.63	0.35	0.34	-3.58
	500.00	1.47	226.89	50	499.96	-1.57	1.57 S	3.02 W	3.40	242.53	0.60	0.44	-17.30
	550.00	1.62	218.25	50	549.94	-2.56	2.56 S	3.92 W	4.68	236.85	0.55	0.30	-17.28
	600.00	1.49	213.33	50	599.92	-3.66	3.66 S	4.72 W	5.97	232.19	0.37	-0.26	-9.84
	650.00	1.48	206.02	50	649.91	-4.78	4.78 S	5.36 W	7.18	228.24	0.38	-0.02	-14.62
	700.00	0.99	193.45	50	699.90	-5.78	5.78 S	5.74 W	8.15	224.79	1.11	-0.98	-25.14
	750.00	0.49	196.92	50	749.89	-6.41	6.41 S	5.90 W	8.71	222.65	1.00	-1.00	6.94
	800.00	0.56	224.60	50	799.89	-6.79	6.79 S	6.14 W	9.15	222.12	0.52	0.14	55.36
	850.00	0.74	235.05	50	849.89	-7.14	7.14 S	6.57 W	9.71	222.61	0.43	0.36	20.90
	900.00	0.98	232.03	50	899.88	-7.59	7.59 S	7.17 W	10.45	223.38	0.49	0.48	-6.04
	950.00	1.04	224.27	50	949.87	-8.18	8.18 S	7.83 W	11.32	223.74	0.30	0.12	-15.52
	1000.00	1.14	203.86	50	999.86	-8.96	8.96 S	8.35 W	12.25	222.97	0.80	0.20	-40.82
	1050.00	0.98	172.97	50	1049.86	-9.84	9.84 S	8.50 W	13.00	220.80	1.17	-0.32	-61.78
	1100.00	0.75	168.58	50	1099.85	-10.59	10.59 S	8.38 W	13.50	218.36	0.48	-0.46	-8.78
	1150.00	0.52	164.82	50	1149.85	-11.12	11.12 S	8.25 W	13.85	216.57	0.47	-0.46	-7.52
	1200.00	0.60	164.16	50	1199.84	-11.60	11.60 S	8.12 W	14.16	215.01	0.16	0.16	-1.32
	1250.00	0.51	169.24	50	1249.84	-12.07	12.07 S	8.01 W	14.48	213.58	0.20	-0.18	10.16
	1300.00	0.58	208.04	50	1299.84	-12.51	12.51 S	8.09 W	14.89	212.89	0.74	0.14	77.60
	1350.00	1.21	196.69	50	1349.83	-13.24	13.24 S	8.36 W	15.65	212.27	1.30	1.26	-22.70
	1400.00	0.81	173.09	50	1399.83	-14.09	14.09 S	8.47 W	16.44	211.00	1.14	-0.80	-47.20



Company: Burnett
Well: Stevens A No. 22
Location: Eddy Co., New Mexico
Rig: Pulling Unit

Job Number: 64010
Grid Corr.: -0.22
Lat: 32.83
Long: -103.93

Calculation Method: Minimum Curvature
Proposed Azimuth:
RKB - MSL in feet: Ground
Tie Into: Surface

Survey Tool Type	Survey Depth (ft)	Inclination (deg)	Azimuth (deg)	Course Length (ft)	True Vertical Depth (ft)	Vertical Section (ft)	Coordinates		Closure		Dogleg Severity (d/100')	Build Rate (d/100')	Walk Rate (d/100')
	1450.00	0.88	185.26	50	1449.82	-14.83	14.83 S	8.46 W	17.07	209.71	0.38	0.14	24.34
	1500.00	0.92	221.88	50	1499.81	-15.51	15.51 S	8.76 W	17.81	209.47	1.13	0.08	73.24
	1550.00	1.41	214.07	50	1549.80	-16.32	16.32 S	9.38 W	18.82	209.88	1.03	0.98	-15.62
	1600.00	1.62	211.51	50	1599.79	-17.43	17.43 S	10.09 W	20.14	210.07	0.44	0.42	-5.12
	1650.00	1.42	192.72	50	1649.77	-18.64	18.64 S	10.60 W	21.44	209.62	1.07	-0.40	-37.58
	1700.00	1.42	221.55	50	1699.75	-19.70	19.70 S	11.14 W	22.64	209.49	1.41	0.00	57.66
	1750.00	1.70	207.16	50	1749.74	-20.83	20.83 S	11.89 W	23.98	209.73	0.96	0.56	-28.78
	1800.00	1.75	199.08	50	1799.71	-22.21	22.21 S	12.48 W	25.47	209.33	0.50	0.10	-16.16
	1850.00	1.64	222.29	50	1849.69	-23.46	23.46 S	13.21 W	26.92	209.39	1.38	-0.22	46.42
	1900.00	2.07	220.94	50	1899.67	-24.67	24.67 S	14.28 W	28.51	210.07	0.86	0.86	-2.70
	1950.00	2.19	212.17	50	1949.63	-26.16	26.16 S	15.38 W	30.35	210.46	0.69	0.24	-17.54
	2000.00	1.75	218.72	50	1999.60	-27.57	27.57 S	16.37 W	32.06	210.71	0.99	-0.88	13.10
	2050.00	2.54	217.72	50	2049.57	-29.04	29.04 S	17.53 W	33.92	211.11	1.58	1.58	-2.00
	2100.00	2.20	232.25	50	2099.52	-30.50	30.50 S	18.96 W	35.92	211.87	1.38	-0.68	29.06
	2150.00	2.56	233.14	50	2149.48	-31.76	31.76 S	20.62 W	37.86	212.99	0.72	0.72	1.78
	2200.00	2.80	224.29	50	2199.43	-33.30	33.30 S	22.36 W	40.11	213.88	0.96	0.48	-17.70
	2250.00	2.33	231.67	50	2249.38	-34.81	34.81 S	24.01 W	42.29	214.60	1.15	-0.94	14.76
	2300.00	2.87	223.42	50	2299.32	-36.35	36.35 S	25.67 W	44.50	215.23	1.31	1.08	-16.50
	2350.00	2.69	229.31	50	2349.27	-38.02	38.02 S	27.42 W	46.88	215.80	0.67	-0.36	11.78
	2400.00	2.91	237.58	50	2399.21	-39.47	39.47 S	29.38 W	49.20	216.67	0.92	0.44	16.54
	2450.00	3.08	230.99	50	2449.14	-40.99	40.99 S	31.50 W	51.70	217.54	0.77	0.34	-13.18
	2500.00	2.56	240.48	50	2499.08	-42.39	42.39 S	33.51 W	54.03	218.33	1.39	-1.04	18.98
	2550.00	2.56	240.77	50	2549.03	-43.48	43.48 S	35.46 W	56.11	219.19	0.03	0.00	0.58
	2600.00	2.76	243.53	50	2598.97	-44.57	44.57 S	37.51 W	58.25	220.09	0.47	0.40	5.52
	2650.00	3.17	231.78	50	2648.91	-45.96	45.96 S	39.67 W	60.71	220.80	1.46	0.82	-23.50
	2700.00	2.86	231.73	50	2698.84	-47.59	47.59 S	41.74 W	63.30	221.25	0.62	-0.62	-0.10
	2750.00	2.68	216.95	50	2748.78	-49.29	49.29 S	43.42 W	65.69	221.38	1.47	-0.36	-29.56
	2800.00	1.87	217.44	50	2798.74	-50.87	50.87 S	44.62 W	67.67	221.25	1.62	-1.62	0.98
	2850.00	1.91	212.87	50	2848.71	-52.22	52.22 S	45.57 W	69.31	221.11	0.31	0.08	-9.14
	2900.00	1.68	205.99	50	2898.69	-53.58	53.58 S	46.34 W	70.84	220.86	0.63	-0.46	-13.76



Company:	Burnett
Well:	Stevens A No. 22
Location:	Eddy Co., New Mexico
Rig:	Pulling Unit

Job Number:	64010
Grid Corr.:	-0.22
Lat:	32.83
Long:	-103.93

Calculation Method: Minimum Curvature
Proposed Azimuth: _____
RKB - MSL in feet: Ground
Tie Into: Surface

Survey Tool Type	Survey Depth (ft)	Inclina- tion (deg)	Azimuth (deg)	Course Length (ft)	True Vertical Depth (ft)	Vertical Section (ft)	Coordinates		Closure		Dogleg Severity (d/100')	Build Rate (d/100')	Walk Rate (d/100')
							N/S (ft)	E/W (ft)	Distance (ft)	Angle (deg)			
	2950.00	1.18	205.14	50	2948.67	-54.71	54.71 S	46.88 W	72.04	220.60	1.00	-1.00	-1.70
	3000.00	1.65	211.81	50	2998.66	-55.78	55.78 S	47.48 W	73.25	220.40	0.99	0.94	13.34
	3050.00	1.22	198.45	50	3048.64	-56.90	56.90 S	48.03 W	74.46	220.17	1.08	-0.86	-26.72
	3100.00	1.72	211.22	50	3098.63	-58.05	58.05 S	48.58 W	75.70	219.93	1.19	1.00	25.54
	3150.00	1.23	199.92	50	3148.61	-59.19	59.19 S	49.16 W	76.94	219.71	1.14	-0.98	-22.60
	3200.00	1.67	214.24	50	3198.59	-60.30	60.30 S	49.75 W	78.17	219.52	1.13	0.88	28.64
	3250.00	1.28	199.87	50	3248.58	-61.43	61.43 S	50.35 W	79.42	219.34	1.07	-0.78	-28.74
	3300.00	1.62	213.80	50	3298.56	-62.54	62.54 S	50.93 W	80.65	219.16	0.97	0.68	27.86
	3350.00	1.24	193.35	50	3348.54	-63.65	63.65 S	51.45 W	81.85	218.95	1.26	-0.76	-40.90
	3400.00	1.60	217.47	50	3398.53	-64.73	64.73 S	52.00 W	83.03	218.77	1.38	0.72	48.24
	3450.00	1.12	193.02	50	3448.52	-65.76	65.76 S	52.53 W	84.17	218.62	1.49	-0.96	-48.90
	3500.00	1.67	212.10	50	3498.50	-66.86	66.86 S	53.03 W	85.34	218.42	1.43	1.10	38.16
	3550.00	1.07	201.38	50	3548.49	-67.91	67.91 S	53.59 W	86.51	218.28	1.30	-1.20	-21.44
	3600.00	1.26	221.74	50	3598.48	-68.75	68.75 S	54.12 W	87.50	218.21	0.90	0.38	40.72
	3650.00	1.46	191.73	50	3648.46	-69.79	69.79 S	54.62 W	88.62	218.05	1.46	0.40	-60.02
	3700.00	1.53	217.16	50	3698.45	-70.94	70.94 S	55.15 W	89.86	217.86	1.32	0.14	50.86
	3750.00	1.11	206.66	50	3748.43	-71.91	71.91 S	55.77 W	91.00	217.80	0.97	-0.84	-21.00
	3800.00	1.71	209.82	50	3798.42	-72.99	72.99 S	56.36 W	92.22	217.68	1.21	1.20	6.32
	3850.00	1.40	224.38	50	3848.40	-74.07	74.07 S	57.16 W	93.56	217.66	1.00	-0.62	29.12
	3900.00	1.39	195.59	50	3898.39	-75.09	75.09 S	57.75 W	94.73	217.56	1.39	-0.02	-57.58
	3950.00	1.78	214.16	50	3948.37	-76.32	76.32 S	58.35 W	96.07	217.40	1.28	0.78	37.14
	4000.00	1.35	218.20	50	3998.35	-77.43	77.43 S	59.15 W	97.43	217.38	0.89	-0.86	8.08
	4050.00	1.49	199.23	50	4048.33	-78.50	78.50 S	59.73 W	98.64	217.27	0.98	0.28	-37.94
	4100.00	1.76	212.31	50	4098.31	-79.76	79.76 S	60.35 W	100.02	217.11	0.91	0.54	26.16
	4150.00	1.34	223.38	50	4148.29	-80.84	80.84 S	61.16 W	101.37	217.11	1.03	-0.84	22.14
	4200.00	1.26	202.93	50	4198.28	-81.77	81.77 S	61.78 W	102.48	217.07	0.94	-0.16	-40.90
	4250.00	1.82	207.47	50	4248.26	-82.98	82.98 S	62.36 W	103.80	216.92	1.15	1.12	9.08
	4300.00	1.79	217.81	50	4298.24	-84.30	84.30 S	63.21 W	105.36	216.86	0.65	-0.06	20.68
	4350.00	1.52	222.70	50	4348.22	-85.41	85.41 S	64.13 W	106.81	216.90	0.61	-0.54	9.78
	4400.00	1.32	209.68	50	4398.20	-86.39	86.39 S	64.87 W	108.04	216.90	0.76	-0.40	-26.04



Company: Burnett
Well: Stevens A No. 22
Location: Eddy Co., New Mexico
Rig: Pulling Unit

Job Number: 64010
Grid Corr.: -0.22
Lat: 32.83
Long: -103.93

Calculation Method: Minimum Curvature
Proposed Azimuth:
RKB - MSL in feet: Ground
Tie Into: Surface

Survey Tool Type	Survey Depth (ft)	Inclination (deg)	Azimuth (deg)	Course Length (ft)	True Vertical Depth (ft)	Vertical Section (ft)	Coordinates		Closure		Dogleg Severity (d/100')	Build Rate (d/100')	Walk Rate (d/100')
	4450.00	1.42	196.02	50	4448.19	-87.49	87.49 S	65.32 W	109.19	216.75	0.68	0.20	-27.32
	4500.00	1.56	192.32	50	4498.17	-88.75	88.75 S	65.64 W	110.39	216.49	0.34	0.28	-7.40
	4550.00	1.84	208.25	50	4548.15	-90.12	90.12 S	66.17 W	111.80	216.29	1.09	0.56	31.86
	4600.00	1.72	197.57	50	4598.13	-91.54	91.54 S	66.77 W	113.31	216.11	0.70	-0.24	-21.36
	4650.00	1.93	199.26	50	4648.10	-93.05	93.05 S	67.28 W	114.83	215.87	0.43	0.42	3.38
	4700.00	2.00	203.95	50	4698.07	-94.65	94.65 S	67.91 W	116.49	215.66	0.35	0.14	9.38
	4750.00	1.95	204.94	50	4748.04	-96.22	96.22 S	68.62 W	118.18	215.50	0.12	-0.10	1.98
	4800.00	1.04	208.11	50	4798.02	-97.39	97.39 S	69.19 W	119.47	215.39	1.83	-1.82	6.34
	4850.00	0.69	230.37	50	4848.02	-97.98	97.98 S	69.64 W	120.21	215.40	0.96	-0.70	44.52
	4900.00	0.69	230.90	50	4898.01	-98.36	98.36 S	70.11 W	120.79	215.48	0.01	0.00	1.06
	4950.00	0.62	240.46	50	4948.01	-98.68	98.68 S	70.57 W	121.32	215.57	0.26	-0.14	19.12
	5000.00	0.55	240.73	50	4998.01	-98.94	98.94 S	71.02 W	121.79	215.67	0.14	-0.14	0.54
	5050.00	0.61	234.40	50	5048.01	-99.21	99.21 S	71.44 W	122.26	215.76	0.18	0.12	-12.66
	5100.00	0.30	216.66	50	5098.00	-99.47	99.47 S	71.74 W	122.64	215.80	0.67	-0.62	-35.48
	5150.00	0.51	245.20	50	5148.00	-99.67	99.67 S	72.02 W	122.96	215.85	0.57	0.42	57.08
	5200.00	0.59	254.69	50	5198.00	-99.83	99.83 S	72.47 W	123.36	215.98	0.24	0.16	18.98
	5250.00	0.66	259.42	50	5248.00	-99.95	99.95 S	73.00 W	123.77	216.14	0.17	0.14	9.46
	5300.00	0.76	263.37	50	5297.99	-100.04	100.04 S	73.61 W	124.20	216.35	0.22	0.20	7.90
	5350.00	0.80	259.28	50	5347.99	-100.14	100.14 S	74.29 W	124.69	216.57	0.14	0.08	-8.18
	5400.00	0.82	251.33	50	5397.98	-100.32	100.32 S	74.97 W	125.24	216.77	0.23	0.04	-15.90
	5450.00	0.89	240.05	50	5447.98	-100.63	100.63 S	75.64 W	125.89	216.93	0.36	0.14	-22.56
	5500.00	0.76	204.99	50	5497.97	-101.12	101.12 S	76.12 W	126.57	216.97	1.02	-0.26	-70.12
	5550.00	0.72	254.02	50	5547.97	-101.51	101.51 S	76.56 W	127.15	217.02	1.23	-0.08	98.06
	5600.00	0.83	202.07	50	5597.97	-101.93	101.93 S	77.00 W	127.75	217.07	1.37	0.22	-103.90
	5650.00	0.52	200.73	50	5647.96	-102.48	102.48 S	77.22 W	128.32	217.00	0.62	-0.62	-2.68
	5700.00	0.36	204.16	50	5697.96	-102.84	102.84 S	77.36 W	128.69	216.95	0.32	-0.32	6.86
	5750.00	0.58	247.56	50	5747.96	-103.08	103.08 S	77.66 W	129.06	216.99	0.81	0.44	86.80
	5800.00	0.77	203.83	50	5797.96	-103.48	103.48 S	78.03 W	129.60	217.02	1.07	0.38	-87.46
	5850.00	0.57	183.53	50	5847.95	-104.04	104.04 S	78.18 W	130.14	216.92	0.61	-0.40	-40.60
	5900.00	0.66	181.40	50	5897.95	-104.57	104.57 S	78.20 W	130.58	216.79	0.19	0.18	-4.26



Company: Burnett
 Well: Stevens A No. 22
 Location: Eddy Co., New Mexico
 Rig: Pulling Unit

Job Number: 64010
 Grid Corr.: -0.22
 Lat: 32.83
 Long: -103.93

Calculation Method: Minimum Curvature
 Proposed Azimuth:
 RKB - MSL in feet: Ground
 Tie Into: Surface

Survey Tool Type	Survey Depth (ft)	Inclina- tion (deg)	Azimuth (deg)	Course Length (ft)	True Vertical Depth (ft)	Vertical Section (ft)	Coordinates		Closure		Dogleg Severity (d/100')	Build Rate (d/100')	Walk Rate (d/100')
							N/S (ft)	E/W (ft)	Distance (ft)	Angle (deg)			
	5950.00	0.49	184.23	50	5947.95	-105.07	105.07 S	78.22 W	131.00	216.67	0.34	-0.34	5.66
	6000.00	0.41	174.85	50	5997.95	-105.47	105.47 S	78.22 W	131.31	216.56	0.22	-0.16	-18.76
	6050.00	0.17	179.83	50	6047.95	-105.72	105.72 S	78.21 W	131.50	216.49	0.48	-0.48	9.96
	6100.00	0.13	178.16	50	6097.95	-105.85	105.85 S	78.21 W	131.61	216.46	0.08	-0.08	-3.34
	6150.00	0.30	285.90	50	6147.94	-105.87	105.87 S	78.33 W	131.70	216.50	0.72	0.34	215.48
	6209.00	0.58	193.89	59	6206.94	-106.12	106.12 S	78.55 W	132.03	216.51	1.12	0.47	-155.95

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
Phone (505) 393-0161 Fax: (505) 393-0720
DISTRICT II
811 S. First St., Artesia, NM 88210
Phone (505) 740-1283 Fax: (505) 740-0720

DISTRICT III
1000 Rio Brazos Ed., Artec, NM 87410
Phone (505) 534-6178 Fax: (505) 534-6170

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone (505) 476-3400 Fax: (505) 476-3403

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised August 13, 2011

Submit one copy to appropriate
District Office

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-015-43437		Pool Code 96831	Pool Name CEDAR LAKE GLORIETA YESO
Property Code 20145	Property Name STEVENS A		Well Number 22
OGRID No. 03080	Operator Name BURNETT OIL COMPANY, INC.		Elevation 3705

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	FEET from the	SOUTH/South line	FEET from the	East/EAST line	County
L	13	17 S	30 E		2365	SOUTH	330	WEST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	FEET from the	SOUTH/South line	FEET from the	East/EAST line	County
L	13	17 S	30 E		2310	SOUTH	330	WEST	EDDY

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
40			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

N: 670128.5 E: 622808.4 NAD 27		N: 670142.4 E: 628087.3 NAD 27	
N: 667491.2 E: 622833.9 NAD 27		N: 667491.2 E: 622833.9 NAD 27	
3705.3' 3710.2'		3705.3' 3710.2'	
330' S.L. 330' B.H. 3699.2' 3704.5'		330' S.L. 330' B.H. 3699.2' 3704.5'	
SURFACE LOCATION Lat - N 32.833616" Long - W 103.932406" NMSPCE- N 667214.5 E 623147.9 (NAD-27)		BOTTOM HOLE LOCATION Lat - N 32.833467" Long - W 103.932359" NMSPCE- N 667180.1 E 623162.9 (NAD-27)	
N: 664849.3 E: 622825.6 NAD 27		N: 664851.6 E: 628104.3 NAD 27	

OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or released mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Leslie Garvis 3/4/15
Signature Date
Leslie Garvis
Printed Name
lgarvis@burnettoil.com
Email Address

SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

NOVEMBER 16, 2014
Date Surveyed
Signature of Professional Surveyor
Certification Number 7977
BRAIN SURVEYING

0' 500' 1000' 1500' 2000'
SCALE: 1" = 1000'
WO Num.: 31126