District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department 7 2019

Submit Original to Appropriate District Office

Oil Conservation Division STRICT II-ARTESIA O.C.D. 1220 South St. Francis Dr. Santa Fe, NM 87505

C	A	C	C	٩T	T	H	E	DI		N	J
	4			٩r		1 1	CP.		. A	. 11	и

Date: 08/01/2018		
☑ Original	Operator & OGRID No.: XTO Energy, Inc [005380]	
☐ Amended - Reason for Amendment:		

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility: Ross Draw 25 Northeast

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Ross Draw 25 Fed WX #22H		C-25-26S-29E	170'FNL & 2071	2500MCF/D	Flared/Sold	CTB to be Connected to P/L
30-0	015-455	85				

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>ETC</u> and will be connected to <u>ETC's</u> low/high pressure gathering system located in Lea County, New Mexico. It will require 0' of pipeline to connect the facility to low/high pressure gathering system. <u>XTO Energy, Inc.</u> provides (periodically) to <u>ETC</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>XTO Energy, Inc.</u> and <u>ETC</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>ETC</u> Processing Plant located in Sec. 33 Twn. 24S, Rng. 37E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>XTO Energy</u>, Inc.'s belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines



www.prototypewellplanning.com

Planning Report

Database: Company: EDM 5000.1 Single User Db

XTO Energy

Project:

Eddy County, NM (NAD-27)

Site:

Ross Draw 25 Fed

Well: Wellbore: WX #22H

Design:

ОН PERMIT Local Co-ordinate Reference:

TVD Reference:

Well WX #22H

RKB = 27' @ 2986.00usft RKB = 27' @ 2986.00usft

MD Reference: North Reference:

Survey Calculation Method:

Grid

Minimum Curvature

_				. 1	_	_	_
r	OI	rm	а	E I	0	n	5

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
293.00	293.00	Rustler				
914.00	914.00	Salado				
1,415.00	1,415.00	Castile				
3,141.00	3,141.00	Lamar				
3,181.00	3,181.00	Delaware				
6,906.00	6,906.00	Bone Spring				
7,876.33	7,875.00	1st Bone Spring Ss				
8,519.78	8,516.00	2nd Bone Spring Ss				
9,779.47	9,769.00	3rd Bone Spring				
10,264.08	10,125.00	Wolfcamp				
10,328.67	10,149.00	Wolfcamp X				