

Submit 1-Copy To Appropriate District Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised July 18, 2013

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. <b>30-015-10129</b>
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator <b>COG Operating, LLC</b>		6. State Oil & Gas Lease No. <b>B-2071</b>
3. Address of Operator <b>600 W. Illinois Ave, Midland, TX 79701</b>		7. Lease Name or Unit Agreement Name <b>NG Phillips State</b>
4. Well Location Unit Letter <b>H</b> : <b>2263</b> feet from the <b>N</b> line and <b>660</b> feet from the <b>E</b> line Section <b>27</b> Township <b>17S</b> Range <b>28E</b> NMPM County <b>Eddy</b>		8. Well Number # <b>9</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>3614' GR</b>		9. OGRID Number <b>229137</b>
		10. Pool name or Wildcat <b>Artesia, Red Lake</b>

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL. <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

**Notify OCD 24 hrs. prior to any work done.**

- Tag 4 1/2" CIBP @ 950' w/ 3 sx cmt cap.
- Set 4 1/2" CIBP @ 730'. Pressure test csg. Circulate hole w/ MLF. Spot 25 sx cmt @ 730-380'. - woc + Tag
- Spot 25 sx cmt @ 60' to surface.
- Cut off well head, verify cmt to surface, weld on Dry Hole Marker

RECEIVED

DEC 24 2018

DISTRICT II-ARTESIA O.C.D.

Spud Date:

Rig Release Date:

*\*See Attached COA's Must be Plugged by 12/26/19*

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Abigail Anderson TITLE Agent DATE 12/19/2018


Type or print name Abigail Anderson E-mail address: abbym@bcmadassociates.com PHONE: 432-580-7161  
 For State Use Only

APPROVED BY: [Signature] TITLE STAFF MGR DATE 12/26/18


Conditions of Approval (if any):




# NG Phillips St #9



**Csg:** 8-5/8" 24# J55 STC  
**Set @** 963'  
**Cement w/** 650 sx Class C  
**circ.** Yes



**35sx cement bridge plug**  
**Shot off 4-1/2" Casing at 1362'**




**Csg:** 4-1/2" 9.5# J55 LTC  
**Depth:** 2046'  
**Cement w/** 75 sx Class C  
**circ.** Unknown

**Seven Rivers: 1960' - 1972'**  
**Cut and pulled 4-1/2" csg from 5340'**  
**TOC @ 5500'**

**Abo: 6022' - 6160'**

**Csg:** 4-1/2" 9.5# J55 LTC  
**Depth:** 6204'  
**Cement w/** 150 sx Class C  
**circ.** No - TOC @ 5500'



### Well ID Info:

API No:	30-015-10129
Field:	Artesia; Red Lake
Spud Date:	1/19/1963
Location:	
Footage:	2263' FNL & 660' FEL
Section:	27
Township	17S
Range	28E
County:	Eddy
Elevations:	
GL:	3614
KB:	12
Pumping Unit:	
Unit Size:	
Speed:	
History	
1/19/63	Spudded
2/8/1963	4.5" 9.5# 8R J-55 casing was run and set at 6204' and set with 150 sx cement. Tested casing with 3,000 PSI, OK. Top of cement 5500'. Perforated 6128'-6160' W/2 SPF. Acidized with 5,000 gal. No oil or gas. Set BP at 6100' Perforated intervals 6022'-30', 6034'-45', 6050'-55' W/2 SPF. Acidized with 10,000 gallons. No oil. Pulled BP at 6,100'. Fraced all perforations with 100,000 gal water and 100,000# sand on 2-22-63. On 4-5-63, there were 486 barrels of load to recover.
4/3/63	Plug back lower zone, cut and pull casing
4/27/63	Ran 4-1/2" 9.5# J-55 casing to 2046', cemented with 75 sx, perf 1960-72' Frac with 42,000gals crude and 60,000# sand
5/26/79	Plugged back San Andres and completed 7 rivers formation Shot off pipe @ 1362', pumped 23sx in and out of pipe, set cement BP @ 1300' Acidized well at 1050' open hole, Perforated 912-915' 6 shots, 902-905' 6 shots, 778-782' 8 Shots Wireline set bridge plug at 950' dumped 3 sx on top of plug


32.806572

-104.1575851

# NG Phillips St #9


**Well ID Info:**

API No:	30-015-10129
Field:	Artesia; Red Lake
Spud Date:	1/19/1963
Location:	
Footage:	2263' FNL & 660' FEL
Section:	27
Township	17S
Range	28E
County:	Eddy
<b>Elevations:</b>	
GL:	3614
KB:	12
<b>Pumping Unit:</b>	
Unit Size:	
Speed:	
<b>History</b>	
1/19/63	Spudded
2/8/1963	4.5" 9.5# 8R J-55 casing was run and set at 6204' and set with 150 sx cement. Tested casing with 3,000 PSI. OK. Top of cement 5500'. Perforated 6128'-6160' W/2 SPF. Acidized with 5,000 gals. No oil or gas. Set BP at 6100' Perforated intervals 6022'-30', 6034'-45', 6050'-55' W/2 SPF. Acidized with 10,000 gallons. No oil. Pulled BP at 6,100'. Fraced all perforations with 100,000 gal water and 100,000# sand on 2-22-63. On 4-5-63, there were 488 barrels of load to recover.
4/3/63	Plug back lower zone, cut and pull casing
4/27/63	Ran 4-1/2" 9.5# J-55 casing to 2046', cemented with 75 sx, perf 1960-72' Frac with 42,000gals crude and 60,000# sand
5/26/79	Plugged back San Andres and completed 7 rivers formation Shot off pipe @ 1362', pumped 23sx in and out of pipe, set cement BP @ 1300' Acidized well at 1050' open hole, Perforated 912-915' 6 shots, 902-905' 8 shots, 778-782' 8 Shots Wireline set bridge plug at 950' dumped 3 sx on top of plug




3. Spot 25 sx cmt @ 60' to surface.
2. Set 4 1/2" CIBP @ 730'. Circ hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 730-380'.  
7Rivers: 778'-782', 902'-905', 912'-916'
1. Tag 4 1/2" CIBP @ 950' w/ 3 sx cmt cap.

Csg: 8-5/8" 24# J55 STC  
Set @ 963'  
Cement w/ 650 sx Class C  
circ. Yes



36sx cement bridge plug  
Shot off 4-1/2" Casing at 1362'




Csg: 4-1/2" 9.5# J55 LTC  
Depth: 2046'  
Cement w/ 75 sx Class C  
circ. Unknown

Seven Rivers: 1960' - 1972'  
Cut and pulled 4-1/2" csg from 5340'  
TOC @ 5500'

Abo: 6022' - 6160'

Csg: 4-1/2" 9.5# J55 LTC  
Depth: 6204'  
Cement w/ 150 sx Class C  
circ. No - TOC @ 5500'



## CONDITIONS FOR PLUGGING AND ABANDONMENT

### District II / Artesia N.M.

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If the well is not plugged within 1
7. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
8. **Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.**
9. Produced water **will not** be used during any part of the plugging operation.
10. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
11. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
12. **Class 'C' cement will be used above 7500 feet.**
13. **Class 'H' cement will be used below 7500 feet.**
14. **A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged**
15. **All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing**

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. **A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.**
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, **(WOC 4 hrs and tag).**
19. **No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.**
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
  - A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.
  - K) **Potash---** (In the R-111-P Area (Potash Mine Area), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, **WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.**
21. **If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing**

#### **DRY HOLE MARKER REQUIRMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

**1. Operator name 2. Lease and Well Number 3.API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS**

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)