

Submit 1 Copy To Appropriate District
Office
District I - (505) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (505) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

RECEIVED
State of New Mexico
Energy, Minerals and Natural Resources
DEC 20 2018
CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
DISTRICT II-ARTESIA

Form C-103
Revised July 18, 2013

WELL API NO. 30-015-24564	
5. Indicate Type of Lease STATE ☒ FEE ☐	
6. State Oil & Gas Lease No. B-2071	
7. Lease Name or Unit Agreement Name NG Phillips State	
8. Well Number #34	
9. OGRID Number 229137	
10. Pool name or Wildcat Artesia, QN-GRBG-SA	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	
2. Name of Operator COG Operating, LLC	
3. Address of Operator 600 W. Illinois Ave, Midland, TX 79701	
4. Well Location Unit Letter H : 1725 feet from the N line and 330 feet from the E line Section 27 Township 17S Range 28E NMPM County Eddy	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3595' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
CLOSED-LOOP SYSTEM ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Set 5 1/2" CIBP @ 1955'. Pressure test csg. Circ hole w/ MLF. Spot 25 sx cmt @ 1955-1755'. WOC & Tag
2. Spot 25 sx cmt @ 900-700'. WOC & Tag
3. Perf & Sqz 120 sx class C cmt @ 573' to surface.
4. Cut off well head, verify cmt to surface, weld on Dry Hole Marker.

Notify OCD 24 hrs. prior to any work done.

Spud Date:

Rig Release Date:

* See Attached COA's Must be Plugged by 12/27/19
I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Abigail Anderson TITLE Agent DATE 12/21/2018
Type or print name Abigail Anderson E-mail address abbym@bcmmandassociates.com PHONE: 432-580-7161
For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 12/27/18
Conditions of Approval (if any):

ENTERED
[Signature]

Field & Pool

Artesia Qn. Grbg. SA

G-27-17S-28E

NG Phillips St #34

Well ID Info:

API No: 30-015-24564

Spud Date: 8/11/1983

Csg: 8-5/8" 24# J55 STC
Set @ 523'
Cement w/ 325 sx
circ. 50sx

Tubing Detail Rod Detail
2-3/8" Tubing PR W/ LNR

89 JTS @2698' 1 - 4' X 3/4" SUB
106 - 3/4" RODS
2 X 1 1/2 X 12' RWTC #Y-8904

Grayburg/SA
2002'-2147'
Acidized w/ 1,000gals
NEFE 15%

SAN ANDRES
2280'-2612'
7500bbl gelled water
243,900# Sand

PBTD 2977'
TD 3020'

Csg: 5-1/2" 15.5#
Depth: 3020'
Cement w/ 850 sx

32.8080559


-104.1564941

Field & Pool

Artesia Qn. Grbg. SA
G-27-17S-28E

NG Phillips St #34

Well ID Info:	
API No:	30-015-24564
Spud Date:	8/11/1983



Csg: 8-5/8" 24# J55 STC
Set @ 523'
Cement w/ 325 sx
circ. 50sx

3. Perf & Sqz 120 sx cmt @ 573' to Surface.

2. Spot 25 sx cmt @ 900-700'. WOC & Tag

1. Set 5 1/2" CIBP @ 1955'. Pressure test csg. Circ hole w/ MLF. Spot 25 sx cmt @ 1955-1755'. WOC & Tag.

Grayburg/SA
2002'-2147'
Acidized w/ 1,000gals
NEFE 15%

SAN ANDRES
2280'-2612'
7500bbl gelled water
243,900# Sand

PBTD 2977'
TD 3020'

Csg: 5-1/2" 15.5#
Depth: 3020'
Cement w/ 850 sx