

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-63737
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. VO-5730
7. Lease Name or Unit Agreement Name Brick BPN State Com
8. Well Number 1
9. OGRID Number 7377
10. Pool name or Wildcat Foor Ranch; Pre-Permian, NE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

EOG Resources, Inc.

3. Address of Operator

104 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter D : 900 feet from the North line and 660 feet from the West line
Section 9 Township 8S Range 27E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3946'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

EOG Resources, Inc. plans to plug and abandon this well as follows:

Notary OCD 24 hrs. prior to any work done.

1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment..
2. Set a 5-1/2" CIBP at 6575' with 35' Class "A" cement on top. WOC and tag.
3. Circulate hole with plugging mud and pressure test casing.
4. Spot a 25 sx Class "A" cement plug from 5855'-6075'. **Class C**
5. Spot a 25 sx Class "C" cement plug from 5250'-5500'.
6. Spot a 25 sx Class "C" cement plug from 4540'-4790'.
7. Spot a 25 sx Class "C" cement plug from 2290'-2540'.
8. Perforate at 1420' and attempt to establish an injection rate.
9. Spot a 25 sx Class "C" cement plug from 1170'-1420'. **WOC + Tag**
10. Perforate at 400' and attempt to establish an injection rate.
11. Spot a 25 sx Class "C" cement plug from 400' up to surface.
12. Cut off wellhead, install dry hole marker and clean location.

RECEIVED

JAN 30 2019

DISTRICT II-ARTESIA O.C.D.

Wellbore schematics attached

***See Attached COAs**

Must be Plugged by 1/31/20

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tina Huerta

TITLE

Regulatory Specialist

DATE

January 29, 2019

Type or print name

Tina Huerta

E-mail address:

tina.huerta@eogresources.com

PHONE:

575-748-4168

For State Use Only

APPROVED BY:

[Signature]

TITLE

Staff Mgr

DATE

1/31/19

Conditions of Approval (if any):

ENTERED
1/31/19

Brick BPN State Com #1

Sec-TWN-RNG: 9-8S-27E API: 30-005-63737
 FOOTAGES: 900' FNL & 660' FWL GL: 3,946'
 KB:

COMMENTS

CASING DETAIL

#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC by
A	14 3/4	11 3/4	42		0	344	550	Circ	
B	11	8 5/8	24		0	1,370	600	Circ	
C	7 7/8	5 1/2	15.5		0	6827	1375	Circ	

FORMATION TOPS

FORMATION	TOP	FORMATION	TOP
Yates	288	Wolfcamp	5442
Seven Rivers	390	Cisco	6024
Queen	880	Strawn	6172
Grayburg	1082	Mississippian	6383
San Andres	1350	Devonian	6570
Glorieta	2488		
Yeso	2568		
Tubb	4000		
Abo	4734		

Perforation Detail

Formation	Top	Bottom	Treatment	Notes
	6658	6662		Squeezed
Silurian	6624	6842	250g 20% IC	

TBG Detail

#	Joint	Description	Length	OD	ID	Grade	Wt(lb/ft)	Top (ftKB)	Botm (ftKB)
		2 7/8"	6555					0	6555
		ASI 10k PKR w/ 2.25" o/o tool	5					6555	6560

Plugs

#	SX	CMT CLASS	TOP	BTM	DESCRIPTION

ADDITIONAL DETAIL

FORMATION	TOP	BTM	#	NOTES

Prepared by: JDE

1/28/2019

Perfs 6,624' - 6,642'
 Perfs 6,658' - 6,662'

PBTD: 6,827 MD
 TD: 6,827 MD

[illegible]